

Document ID
Title
Version
Date
Issuer
Status

Case notice

HLX-002

Helix technical compliance schedule

1.0

2026-08-27

Helix Test Infrastructure

submitted

Fictional training case; all people, organisations, products, rules and events are invented. This is not A
Singapore procurement law.



Row	Requirement	V60 response	
T-01	Per-run positions		60
T-02	Temperature range, °C	−40 to 125	
T-03	Load range, N	0 to 500	
T-04	Electrical bias, V	0 to 24	
T-05	Raw export	CSV and JSON, local	
T-06	Training places		8

Block locator

HLX-002 T1
HLX-002 §3
HLX-002 §3.1
HLX-002 §3.2
HLX-002 §4
HLX-002 §4.1
HLX-002 §5
HLX-002 §5.1
HLX-002 §5.2

Type

table
heading
paragraph
paragraph
heading
paragraph
heading
paragraph
paragraph

Content

Row | Requirement | V60 response
T-01 | Per run positions | 60

Configuration and measurement record
The V60 groups positions into monitored banks while retaining a single run identifier and synchronise the position count is intended to absorb repeat runs and mixed cohort scheduling without a hardware export. Each active position is associated with a channel identifier in the exported record. The controller CSV and JSON exports can be saved to the Institute's local storage without an ongoing hosted account field guide covering timestamp format, units, channel identifiers, event codes and file naming. During For the delivered V60, each specimen position is given a channel identifier before a controlled run starts. An acceptance, a representative run should exercise the installed higher capacity chamber, export a full event record can be linked back to a position and timestamp. The operator guide should show which t

Source / fact references