WORK ORDER

Customer:	Test Customer		Input Info:	11/5/2026
Reference:	Ambrish Single Door	SupplyAndFit		
Job No:	341	Page 1	Print Info:	11/5/2026

Main Options	
Colour (External)	White [SP]
Colour (Internal)	White [SP]
Frame (Standard) (Top)	SPQ-6-11252 68mm 6 Chamber
Frame (Standard) (Bottom)	SPQ-6-11252 68mm 6 Chamber
Frame (Standard) (Left)	SPQ-6-11252 68mm 6 Chamber
Frame (Standard) (Right)	SPQ-6-11252 68mm 6 Chamber
Bead	28mm
Sash Type	Door left hung
Cylinder	Brass Cylinder
Handle (Door)	White Handle Lever/Lever (Short Backplate)
Hinge (Door)	Flag Hinge
Hinge Colour (Door)	White Flag Hinge
Hinge Position (Door)	3 Hinges
Lock (Door) (Single Door)	Standard Door Lock
Glazing Method	Glazed
Glass Type	4-20-4 Clear Tuff Low E
Glass Gas Fill	Argon
Opening Direction	Open In
Component Type	Glass
Drainage	Concealed Drainage
Location	Please Specify



Sections Required:			Qty	Length	End Prep	Reinforcing	Length
Hor	Bead	28mm Bead	2	950	[-]		
Vert	Bead	28mm Bead	2	1850	[-]		
Hor	Frame	Frame 6 Chamber	2	1205	\ - /		
Vert	Frame	Frame 6 Chamber	2	2105	\ - /		
Hor	Sash	Door Sash Z	2	1125	\ - /	28 x 44.5 U Steel Reinforcement	910
Vert	Sash	Door Sash Z	2	2025	\ - /	28 x 44.5 U Steel Reinforcement	1810

Accessories Required:	Qty	Unit Of Measurement
Run Up Block	1	Unit
Gasket 01	12.559999	Metres
White Handle Lever/Lever (Short Backplate)	1	Unit
Flag Hinge White	3	Unit
L/H Keep Set	1	Unit
Standard Door Lock	1	Unit
Brass Cylinder	1	Unit
Gasket 02	5.56	Metres
Glazing Bridge Packer	8	Unit

Glass Required:	Qty	Width	Length
01 (Frame-01) 4-20-4 Clear Tuff Low E : Thermal Spacer Bar	1	940	1840

WORK ORDER

Customer:	Test Customer		Input Info:	11/5/2026
Reference:	Ambrish Single Door	SupplyAndFit		
Job No:	341	Page 2	Print Info:	11/5/2026

Main Options	
Colour (External)	White [SP]
Colour (Internal)	White [SP]
Frame (Standard) (Top)	SPQ-6-11252 68mm 6 Chamber
Frame (Standard) (Bottom)	SPQ-6-11252 68mm 6 Chamber
Frame (Standard) (Left)	SPQ-6-11252 68mm 6 Chamber
Frame (Standard) (Right)	SPQ-6-11252 68mm 6 Chamber
Bead	28mm
Sash Type	Door right hung
Cylinder	Brass Cylinder
Handle (Door)	White Handle Lever/Lever (Short Backplate)
Hinge (Door)	Flag Hinge
Hinge Colour (Door)	White Flag Hinge
Hinge Position (Door)	3 Hinges
Lock (Door) (Single Door)	Standard Door Lock
Glazing Method	Glazed
Glass Type	4-20-4 Clear Tuff Low E
Glass Gas Fill	Argon
Opening Direction	Open In
Component Type	Glass
Drainage	Concealed Drainage
Location	Please Specify



Sections Required:			Qty	Length	End Prep	Reinforcing	Length
Hor	Bead	28mm Bead	2	750	[-]		
Vert	Bead	28mm Bead	2	1650	[-]		
Hor	Frame	Frame 6 Chamber	2	1005	\ - /		
Vert	Frame	Frame 6 Chamber	2	1905	\ - /		
Hor	Sash	Door Sash Z	2	925	\ - /	28 x 44.5 U Steel Reinforcement	710
Vert	Sash	Door Sash Z	2	1825	\ - /	28 x 44.5 U Steel Reinforcement	1610

Accessories Required:	Qty	Unit Of Measurement
Run Up Block	1	Unit
Gasket 01	10.96	Metres
White Handle Lever/Lever (Short Backplate)	1	Unit
Flag Hinge White	3	Unit
R/H Keep Set	1	Unit
Standard Door Lock	1	Unit
Brass Cylinder	1	Unit
Gasket 02	4.76	Metres
Glazing Bridge Packer	8	Unit

Glass Required:	Qty	Width	Length
01 (Frame-01) 4-20-4 Clear Tuff Low E : Thermal Spacer Bar	1	740	1640

WORK ORDER

Customer:	Test Customer		Input Info:	11/5/2026
Reference:	Ambrish Single Door	SupplyAndFit		
Job No:	341	Page 3	Print Info:	11/5/2026

Main Options	
Colour (External)	White [SP]
Colour (Internal)	White [SP]
Frame (Standard) (Top)	SPQ-6-11252 68mm 6 Chamber
Frame (Standard) (Bottom)	SPQ-6-11252 68mm 6 Chamber
Frame (Standard) (Left)	SPQ-6-11252 68mm 6 Chamber
Frame (Standard) (Right)	SPQ-6-11252 68mm 6 Chamber
Transom	SPQ-5-30252 78mm
Joint (Structural T/Z) (Transo...	Welded (Standard)
Bead	28mm
Sash Type	Door left hung
Cylinder	Brass Cylinder
Handle (Door)	White Handle Lever/Lever (Short Backplate)
Hinge (Door)	Flag Hinge
Hinge Colour (Door)	White Flag Hinge
Hinge Position (Door)	3 Hinges
Lock (Door) (Single Door)	Standard Door Lock
Glazing Method	Glazed
Glass Type	4-20-4 Clear Tuff Low E
Glass Gas Fill	Argon
Opening Direction	Open In
Component Type	Glass
Drainage	Concealed Drainage
Location	Please Specify
Vertical Split Position	By Dimensions



Sections Required:			Qty	Length	End Prep	Reinforcing	Length
Hor	Bead	28mm Bead	2	904	[-]		
Vert	Bead	28mm Bead	2	283	[-]		
Hor	Bead	28mm Bead	2	750	[-]		
Vert	Bead	28mm Bead	2	1429	[-]		
Hor	Frame	Frame 6 Chamber	2	1005	\ - /		
Vert	Frame	Frame 6 Chamber	2	2005	\ - /		
Hor	Frame	T Transom/Mullion	1	1025	< - >		
Hor	Sash	Door Sash Z	2	925	\ - /	28 x 44.5 U Steel Reinforcement	710
Vert	Sash	Door Sash Z	2	1604	\ - /	28 x 44.5 U Steel Reinforcement	1389

Accessories Required:	Qty	Unit Of Measurement
Run Up Block	1	Unit
Gasket 02	6.652	Metres
Glazing Bridge Packer	13	Unit
Gasket 01	10.076	Metres
White Handle Lever/Lever (Short Backplate)	1	Unit
Flag Hinge White	3	Unit
L/H Keep Set	1	Unit
Standard Door Lock	1	Unit
Brass Cylinder	1	Unit

Glass Required:	Qty	Width	Length
01 (Frame-01) 4-20-4 Clear Tuff Low E : Thermal Spacer Bar	1	894	273
02 (Frame-01) 4-20-4 Clear Tuff Low E : Thermal Spacer Bar	1	740	1419

WORK ORDER

Customer:	Test Customer		Input Info:	11/5/2026
Reference:	Ambrish Single Door	SupplyAndFit		
Job No:	341	Page 4	Print Info:	11/5/2026

Main Options	
Colour (External)	White [SP]
Colour (Internal)	White [SP]
Frame (Standard) (Top)	SPQ-6-11252 68mm 6 Chamber
Frame (Standard) (Bottom)	SPQ-6-11252 68mm 6 Chamber
Frame (Standard) (Left)	SPQ-6-11252 68mm 6 Chamber
Frame (Standard) (Right)	SPQ-6-11252 68mm 6 Chamber
Transom	SPQ-5-30252 78mm
Joint (Structural T/Z) (Transo...	Welded (Standard)
Bead	28mm
Sash Type	Door right hung
Cylinder	Brass Cylinder
Handle (Door)	White Handle Lever/Lever (Short Backplate)
Hinge (Door)	Flag Hinge
Hinge Colour (Door)	White Flag Hinge
Hinge Position (Door)	3 Hinges
Lock (Door) (Single Door)	Standard Door Lock
Glazing Method	Glazed
Glass Type	4-20-4 Clear Tuff Low E
Glass Gas Fill	Argon
Opening Direction	Open In
Component Type	Glass
Drainage	Concealed Drainage
Location	Please Specify
Vertical Split Position	By Dimensions



Sections Required:			Qty	Length	End Prep	Reinforcing	Length
Hor	Bead	28mm Bead	2	804	[-]		
Vert	Bead	28mm Bead	2	233	[-]		
Hor	Bead	28mm Bead	2	650	[-]		
Vert	Bead	28mm Bead	2	1379	[-]		
Hor	Frame	Frame 6 Chamber	2	905	\ - /		
Vert	Frame	Frame 6 Chamber	2	1905	\ - /		
Hor	Frame	T Transom/Mullion	1	925	< - >		
Hor	Sash	Door Sash Z	2	825	\ - /	28 x 44.5 U Steel Reinforcement	610
Vert	Sash	Door Sash Z	2	1554	\ - /	28 x 44.5 U Steel Reinforcement	1339

Accessories Required:	Qty	Unit Of Measurement
Run Up Block	1	Unit
Gasket 02	6.052	Metres
Glazing Bridge Packer	13	Unit
Gasket 01	9.476	Metres
White Handle Lever/Lever (Short Backplate)	1	Unit
Flag Hinge White	3	Unit
R/H Keep Set	1	Unit
Standard Door Lock	1	Unit
Brass Cylinder	1	Unit

Glass Required:	Qty	Width	Length
01 (Frame-01) 4-20-4 Clear Tuff Low E : Thermal Spacer Bar	1	794	223
02 (Frame-01) 4-20-4 Clear Tuff Low E : Thermal Spacer Bar	1	640	1369

WORK ORDER

Customer:	Test Customer		Input Info:	11/5/2026
Reference:	Ambrish Single Door	SupplyAndFit		
Job No:	341	Page 5	Print Info:	11/5/2026

Main Options	
Colour (External)	White [SP]
Colour (Internal)	White [SP]
Frame (Standard) (Top)	SPQ-6-11252 68mm 6 Chamber
Frame (Standard) (Bottom)	SPQ-6-11252 68mm 6 Chamber
Frame (Standard) (Left)	SPQ-6-11252 68mm 6 Chamber
Frame (Standard) (Right)	SPQ-6-11252 68mm 6 Chamber
Mullion	SPQ-5-30252 78mm
Joint (Structural T/Z) (Mullion)	Welded (Standard)
Bead	28mm
Sash Type	Door left hung
Cylinder	Brass Cylinder
Handle (Door)	White Handle Lever/Lever (Short Backplate)
Hinge (Door)	Flag Hinge
Hinge Colour (Door)	White Flag Hinge
Hinge Position (Door)	3 Hinges
Lock (Door) (Single Door)	Standard Door Lock
Glazing Method	Glazed
Glass Type	4-20-4 Clear Tuff Low E
Glass Gas Fill	Argon
Opening Direction	Open In
Component Type	Glass
Drainage	Concealed Drainage
Location	Please Specify
Horizontal Split Position	By Dimensions



Sections Required:			Qty	Length	End Prep	Reinforcing	Length
Vert	Bead	28mm Bead	2	1904	[-]		
Hor	Bead	28mm Bead	2	333	[-]		
Vert	Bead	28mm Bead	2	1750	[-]		
Hor	Bead	28mm Bead	2	779	[-]		
Hor	Frame	Frame 6 Chamber	2	1405	\ - /		
Vert	Frame	Frame 6 Chamber	2	2005	\ - /		
Hor	Frame	T Transom/Mullion	1	2025	< - >	26 x 26 U Steel Reinforcement	1864
Vert	Sash	Door Sash Z	2	1925	\ - /	28 x 44.5 U Steel Reinforcement	1710
Hor	Sash	Door Sash Z	2	954	\ - /	28 x 44.5 U Steel Reinforcement	739

Accessories Required:	Qty	Unit Of Measurement
Run Up Block	1	Unit
Gasket 02	9.452	Metres
Glazing Bridge Packer	13	Unit
Gasket 01	11.476	Metres
White Handle Lever/Lever (Short Backplate)	1	Unit
Flag Hinge White	3	Unit
L/H Keep Set	1	Unit
Standard Door Lock	1	Unit
Brass Cylinder	1	Unit

Glass Required:	Qty	Width	Length
01 (Frame-01) 4-20-4 Clear Tuff Low E : Thermal Spacer Bar	1	769	1740
02 (Frame-01) 4-20-4 Clear Tuff Low E : Thermal Spacer Bar	1	323	1894

WORK ORDER

Customer:	Test Customer		Input Info:	11/5/2026
Reference:	Ambrish Single Door	SupplyAndFit		
Job No:	341	Page 6	Print Info:	11/5/2026

Main Options	
Colour (External)	White [SP]
Colour (Internal)	White [SP]
Frame (Standard) (Top)	SPQ-6-11252 68mm 6 Chamber
Frame (Standard) (Bottom)	SPQ-6-11252 68mm 6 Chamber
Frame (Standard) (Left)	SPQ-6-11252 68mm 6 Chamber
Frame (Standard) (Right)	SPQ-6-11252 68mm 6 Chamber
Mullion	SPQ-5-30252 78mm
Joint (Structural T/Z) (Mullion)	Welded (Standard)
Bead	28mm
Sash Type	Door right hung
Cylinder	Brass Cylinder
Handle (Door)	White Handle Lever/Lever (Short Backplate)
Hinge (Door)	Flag Hinge
Hinge Colour (Door)	White Flag Hinge
Hinge Position (Door)	3 Hinges
Lock (Door) (Single Door)	Standard Door Lock
Glazing Method	Glazed
Glass Type	4-20-4 Clear Tuff Low E
Glass Gas Fill	Argon
Opening Direction	Open In
Component Type	Glass
Drainage	Concealed Drainage
Location	Please Specify
Horizontal Split Position	By Dimensions



Sections Required:			Qty	Length	End Prep	Reinforcing	Length
Vert	Bead	28mm Bead	2	2004	[-]		
Hor	Bead	28mm Bead	2	333	[-]		
Vert	Bead	28mm Bead	2	1850	[-]		
Hor	Bead	28mm Bead	2	779	[-]		
Hor	Frame	Frame 6 Chamber	2	1405	\ - /		
Vert	Frame	Frame 6 Chamber	2	2105	\ - /		
Hor	Frame	T Transom/Mullion	1	2125	< - >	26 x 26 U Steel Reinforcement	1964
Vert	Sash	Door Sash Z	2	2025	\ - /	28 x 44.5 U Steel Reinforcement	1810
Hor	Sash	Door Sash Z	2	954	\ - /	28 x 44.5 U Steel Reinforcement	739

Accessories Required:	Qty	Unit Of Measurement
Run Up Block	1	Unit
Gasket 02	9.852	Metres
Glazing Bridge Packer	13	Unit
Gasket 01	11.875999	Metres
White Handle Lever/Lever (Short Backplate)	1	Unit
Flag Hinge White	3	Unit
R/H Keep Set	1	Unit
Standard Door Lock	1	Unit
Brass Cylinder	1	Unit

Glass Required:	Qty	Width	Length
01 (Frame-01) 4-20-4 Clear Tuff Low E : Thermal Spacer Bar	1	323	1994
02 (Frame-01) 4-20-4 Clear Tuff Low E : Thermal Spacer Bar	1	769	1840

WORK ORDER

Customer:	Test Customer		Input Info:	11/5/2026
Reference:	Ambrish Single Door	SupplyAndFit		
Job No:	341	Page 7	Print Info:	11/5/2026

Main Options	
Colour (External)	White [SP]
Colour (Internal)	White [SP]
Frame (Standard) (Top)	SPQ-6-11252 68mm 6 Chamber
Frame (Standard) (Bottom)	SPQ-6-11252 68mm 6 Chamber
Frame (Standard) (Left)	SPQ-6-11252 68mm 6 Chamber
Frame (Standard) (Right)	SPQ-6-11252 68mm 6 Chamber
Mullion	SPQ-5-30252 78mm
Joint (Structural T/Z) (Mullion)	Welded (Standard)
Bead	28mm
Sash Type	Door right hung
Cylinder	Brass Cylinder
Handle (Door)	White Handle Lever/Lever (Short Backplate)
Hinge (Door)	Flag Hinge
Hinge Colour (Door)	White Flag Hinge
Hinge Position (Door)	3 Hinges
Lock (Door) (Single Door)	Standard Door Lock
Glazing Method	Glazed
Glass Type	4-20-4 Clear Tuff Low E
Glass Gas Fill	Argon
Opening Direction	Open In
Component Type	Glass
Drainage	Concealed Drainage
Location	Please Specify
Horizontal Split Position	By Dimensions



Sections Required:			Qty	Length	End Prep	Reinforcing	Length
Vert	Bead	28mm Bead	2	1904	[-]		
Hor	Bead	28mm Bead	2	383	[-]		
Vert	Bead	28mm Bead	2	1750	[-]		
Hor	Bead	28mm Bead	2	729	[-]		
Hor	Frame	Frame 6 Chamber	2	1405	\ - /		
Vert	Frame	Frame 6 Chamber	2	2005	\ - /		
Hor	Frame	T Transom/Mullion	1	2025	< - >	26 x 26 U Steel Reinforcement	1864
Vert	Sash	Door Sash Z	2	1925	\ - /	28 x 44.5 U Steel Reinforcement	1710
Hor	Sash	Door Sash Z	2	904	\ - /	28 x 44.5 U Steel Reinforcement	689

Accessories Required:	Qty	Unit Of Measurement
Run Up Block	1	Unit
Gasket 02	9.452	Metres
Glazing Bridge Packer	13	Unit
Gasket 01	11.276	Metres
White Handle Lever/Lever (Short Backplate)	1	Unit
Flag Hinge White	3	Unit
R/H Keep Set	1	Unit
Standard Door Lock	1	Unit
Brass Cylinder	1	Unit

Glass Required:	Qty	Width	Length
01 (Frame-01) 4-20-4 Clear Tuff Low E : Thermal Spacer Bar	1	719	1740
02 (Frame-01) 4-20-4 Clear Tuff Low E : Thermal Spacer Bar	1	373	1894

WORK ORDER

Customer:	Test Customer		Input Info:	11/5/2026
Reference:	Ambrish Single Door	SupplyAndFit		
Job No:	341	Page 8	Print Info:	11/5/2026

Main Options	
Colour (External)	White [SP]
Colour (Internal)	White [SP]
Frame (Standard) (Top)	SPQ-6-11252 68mm 6 Chamber
Frame (Standard) (Bottom)	SPQ-6-11252 68mm 6 Chamber
Frame (Standard) (Left)	SPQ-6-11252 68mm 6 Chamber
Frame (Standard) (Right)	SPQ-6-11252 68mm 6 Chamber
Mullion	SPQ-5-30252 78mm
Joint (Structural T/Z) (Mullion)	Welded (Standard)
Bead	28mm
Sash Type	Door left hung
Cylinder	Brass Cylinder
Handle (Door)	White Handle Lever/Lever (Short Backplate)
Hinge (Door)	Flag Hinge
Hinge Colour (Door)	White Flag Hinge
Hinge Position (Door)	3 Hinges
Lock (Door) (Single Door)	Standard Door Lock
Glazing Method	Glazed
Glass Type	4-20-4 Clear Tuff Low E
Glass Gas Fill	Argon
Opening Direction	Open In
Component Type	Glass
Drainage	Concealed Drainage
Location	Please Specify
Horizontal Split Position	By Dimensions



Sections Required:			Qty	Length	End Prep	Reinforcing	Length
Vert	Bead	28mm Bead	2	2004	[-]		
Hor	Bead	28mm Bead	2	383	[-]		
Vert	Bead	28mm Bead	2	1850	[-]		
Hor	Bead	28mm Bead	2	829	[-]		
Hor	Frame	Frame 6 Chamber	2	1505	\ - /		
Vert	Frame	Frame 6 Chamber	2	2105	\ - /		
Hor	Frame	T Transom/Mullion	1	2125	< - >	26 x 26 U Steel Reinforcement	1964
Vert	Sash	Door Sash Z	2	2025	\ - /	28 x 44.5 U Steel Reinforcement	1810
Hor	Sash	Door Sash Z	2	1004	\ - /	28 x 44.5 U Steel Reinforcement	789

Accessories Required:	Qty	Unit Of Measurement
Run Up Block	1	Unit
Gasket 02	10.052	Metres
Glazing Bridge Packer	13	Unit
Gasket 01	12.076	Metres
White Handle Lever/Lever (Short Backplate)	1	Unit
Flag Hinge White	3	Unit
L/H Keep Set	1	Unit
Standard Door Lock	1	Unit
Brass Cylinder	1	Unit

Glass Required:	Qty	Width	Length
01 (Frame-01) 4-20-4 Clear Tuff Low E : Thermal Spacer Bar	1	373	1994
02 (Frame-01) 4-20-4 Clear Tuff Low E : Thermal Spacer Bar	1	819	1840

WORK ORDER

Customer:	Test Customer		Input Info:	11/5/2026
Reference:	Ambrish Single Door	SupplyAndFit		
Job No:	341	Page 9	Print Info:	11/5/2026

Main Options	
Colour (External)	White [SP]
Colour (Internal)	White [SP]
Frame (Standard) (Top)	SPQ-6-11252 68mm 6 Chamber
Frame (Standard) (Bottom)	SPQ-6-11252 68mm 6 Chamber
Frame (Standard) (Left)	SPQ-6-11252 68mm 6 Chamber
Frame (Standard) (Right)	SPQ-6-11252 68mm 6 Chamber
Transom	SPQ-5-30252 78mm
Mullion	SPQ-5-30252 78mm
Joint (Structural T/Z) (Transo...	Welded (Standard)
Joint (Structural T/Z) (Mullion)	Welded (Standard)
Bead	28mm
Sash Type	Door left hung
Cylinder	Brass Cylinder
Handle (Door)	White Handle Lever/Lever (Short Backplate)
Hinge (Door)	Flag Hinge
Hinge Colour (Door)	White Flag Hinge
Hinge Position (Door)	3 Hinges
Lock (Door) (Single Door)	Standard Door Lock
Glazing Method	Glazed
Glass Type	4-20-4 Clear Tuff Low E
Glass Gas Fill	Argon
Opening Direction	Open In
Component Type	Glass
Drainage	Concealed Drainage
Location	Please Specify
Horizontal Split Position	By Dimensions
Vertical Split Position	By Dimensions



Sections Required:			Qty	Length	End Prep	Reinforcing	Length
Hor	Bead	28mm Bead	2	933	[-]		
Vert	Bead	28mm Bead	4	333	[-]		
Hor	Bead	28mm Bead	4	333	[-]		
Vert	Bead	28mm Bead	2	1633	[-]		
Hor	Bead	28mm Bead	2	779	[-]		
Vert	Bead	28mm Bead	2	1479	[-]		
Hor	Frame	Frame 6 Chamber	2	1405	\ - /		
Vert	Frame	Frame 6 Chamber	2	2105	\ - /		
Hor	Frame	T Transom/Mullion	1	2125	< - >	26 x 26 U Steel Reinforcement	1964
Hor	Frame	T Transom/Mullion	1	1054	< - >		
Hor	Frame	T Transom/Mullion	1	454	< - >		
Hor	Sash	Door Sash Z	2	954	\ - /	28 x 44.5 U Steel Reinforcement	739
Vert	Sash	Door Sash Z	2	1654	\ - /	28 x 44.5 U Steel Reinforcement	1439

Accessories Required:	Qty	Unit Of Measurement
Run Up Block	1	Unit
Gasket 02	12.152	Metres
Glazing Bridge Packer	23	Unit
Gasket 01	10.392	Metres
White Handle Lever/Lever (Short Backplate)	1	Unit
Flag Hinge White	3	Unit
L/H Keep Set	1	Unit
Standard Door Lock	1	Unit
Brass Cylinder	1	Unit

Glass Required:	Qty	Width	Length
01 (Frame-01) 4-20-4 Clear Tuff Low E : Thermal Spacer Bar	1	923	323

WORK ORDER

Customer:	Test Customer		Input Info:	11/5/2026
Reference:	Ambrish Single Door	SupplyAndFit		
Job No:	341	Page 10	Print Info:	11/5/2026

Glass Required:	**Qty**	**Width**	**Length**
02 (Frame-01) 4-20-4 Clear Tuff Low E : Thermal Spacer Bar	1	769	1469
03 (Frame-01) 4-20-4 Clear Tuff Low E : Thermal Spacer Bar	1	323	323
04 (Frame-01) 4-20-4 Clear Tuff Low E : Thermal Spacer Bar	1	323	1623

WORK ORDER

Customer:	Test Customer		Input Info:	11/5/2026
Reference:	Ambrish Single Door	SupplyAndFit		
Job No:	341	Page 11	Print Info:	11/5/2026

Main Options	
Colour (External)	White [SP]
Colour (Internal)	White [SP]
Frame (Standard) (Top)	SPQ-6-11252 68mm 6 Chamber
Frame (Standard) (Bottom)	SPQ-6-11252 68mm 6 Chamber
Frame (Standard) (Left)	SPQ-6-11252 68mm 6 Chamber
Frame (Standard) (Right)	SPQ-6-11252 68mm 6 Chamber
Transom	SPQ-5-30252 78mm
Mullion	SPQ-5-30252 78mm
Joint (Structural T/Z) (Transo...	Welded (Standard)
Joint (Structural T/Z) (Mullion)	Welded (Standard)
Bead	28mm
Sash Type	Door right hung
Cylinder	Brass Cylinder
Handle (Door)	White Handle Lever/Lever (Short Backplate)
Hinge (Door)	Flag Hinge
Hinge Colour (Door)	White Flag Hinge
Hinge Position (Door)	3 Hinges
Lock (Door) (Single Door)	Standard Door Lock
Glazing Method	Glazed
Glass Type	4-20-4 Clear Tuff Low E
Glass Gas Fill	Argon
Opening Direction	Open In
Component Type	Glass
Drainage	Concealed Drainage
Location	Please Specify
Horizontal Split Position	By Dimensions
Vertical Split Position	By Dimensions



Sections Required:			Qty	Length	End Prep	Reinforcing	Length
Hor	Bead	28mm Bead	4	283	[-]		
Vert	Bead	28mm Bead	2	1483	[-]		
Vert	Bead	28mm Bead	4	283	[-]		
Hor	Bead	28mm Bead	2	983	[-]		
Hor	Bead	28mm Bead	2	829	[-]		
Vert	Bead	28mm Bead	2	1329	[-]		
Hor	Frame	Frame 6 Chamber	2	1405	\ - /		
Vert	Frame	Frame 6 Chamber	2	1905	\ - /		
Hor	Frame	T Transom/Mullion	1	1925	< - >	26 x 26 U Steel Reinforcement	1764
Hor	Frame	T Transom/Mullion	1	404	< - >		
Hor	Frame	T Transom/Mullion	1	1104	< - >	26 x 26 U Steel Reinforcement	943
Hor	Sash	Door Sash Z	2	1004	\ - /	28 x 44.5 U Steel Reinforcement	789
Vert	Sash	Door Sash Z	2	1504	\ - /	28 x 44.5 U Steel Reinforcement	1289

Accessories Required:	Qty	Unit Of Measurement
Run Up Block	1	Unit
Gasket 02	11.352	Metres
Glazing Bridge Packer	23	Unit
Gasket 01	9.992	Metres
White Handle Lever/Lever (Short Backplate)	1	Unit
Flag Hinge White	3	Unit
R/H Keep Set	1	Unit
Standard Door Lock	1	Unit
Brass Cylinder	1	Unit

Glass Required:	Qty	Width	Length
01 (Frame-01) 4-20-4 Clear Tuff Low E : Thermal Spacer Bar	1	273	273

WORK ORDER

Customer:	Test Customer		Input Info:	11/5/2026
Reference:	Ambrish Single Door	SupplyAndFit		
Job No:	341	Page 12	Print Info:	11/5/2026

Glass Required:	**Qty**	**Width**	**Length**
02 (Frame-01) 4-20-4 Clear Tuff Low E : Thermal Spacer Bar	1	273	1473
03 (Frame-01) 4-20-4 Clear Tuff Low E : Thermal Spacer Bar	1	973	273
04 (Frame-01) 4-20-4 Clear Tuff Low E : Thermal Spacer Bar	1	819	1319

WORK ORDER

Customer:	Test Customer		Input Info:	11/5/2026
Reference:	Ambrish Single Door	SupplyAndFit		
Job No:	341	Page 13	Print Info:	11/5/2026

Main Options	
Colour (External)	White [SP]
Colour (Internal)	White [SP]
Frame (Standard) (Top)	SPQ-6-11252 68mm 6 Chamber
Frame (Standard) (Bottom)	SPQ-6-11252 68mm 6 Chamber
Frame (Standard) (Left)	SPQ-6-11252 68mm 6 Chamber
Frame (Standard) (Right)	SPQ-6-11252 68mm 6 Chamber
Transom	SPQ-5-30252 78mm
Mullion	SPQ-5-30252 78mm
Joint (Structural T/Z) (Transo...	Welded (Standard)
Joint (Structural T/Z) (Mullion)	Welded (Standard)
Bead	28mm
Sash Type	Door right hung
Cylinder	Brass Cylinder
Handle (Door)	White Handle Lever/Lever (Short Backplate)
Hinge (Door)	Flag Hinge
Hinge Colour (Door)	White Flag Hinge
Hinge Position (Door)	3 Hinges
Lock (Door) (Single Door)	Standard Door Lock
Glazing Method	Glazed
Glass Type	4-20-4 Clear Tuff Low E
Glass Gas Fill	Argon
Opening Direction	Open In
Component Type	Glass
Drainage	Concealed Drainage
Location	Please Specify
Horizontal Split Position	By Dimensions
Vertical Split Position	By Dimensions



Sections Required:			Qty	Length	End Prep	Reinforcing	Length
Hor	Bead	28mm Bead	2	933	[-]		
Vert	Bead	28mm Bead	4	383	[-]		
Hor	Bead	28mm Bead	4	333	[-]		
Vert	Bead	28mm Bead	2	1483	[-]		
Hor	Bead	28mm Bead	2	779	[-]		
Vert	Bead	28mm Bead	2	1329	[-]		
Hor	Frame	Frame 6 Chamber	2	1405	\ - /		
Vert	Frame	Frame 6 Chamber	2	2005	\ - /		
Hor	Frame	T Transom/Mullion	1	2025	< - >	26 x 26 U Steel Reinforcement	1864
Hor	Frame	T Transom/Mullion	1	1054	< - >		
Hor	Frame	T Transom/Mullion	1	454	< - >		
Hor	Sash	Door Sash Z	2	954	\ - /	28 x 44.5 U Steel Reinforcement	739
Vert	Sash	Door Sash Z	2	1504	\ - /	28 x 44.5 U Steel Reinforcement	1289

Accessories Required:	Qty	Unit Of Measurement
Run Up Block	1	Unit
Gasket 02	11.752	Metres
Glazing Bridge Packer	23	Unit
Gasket 01	9.792	Metres
White Handle Lever/Lever (Short Backplate)	1	Unit
Flag Hinge White	3	Unit
R/H Keep Set	1	Unit
Standard Door Lock	1	Unit
Brass Cylinder	1	Unit

Glass Required:	Qty	Width	Length
01 (Frame-01) 4-20-4 Clear Tuff Low E : Thermal Spacer Bar	1	923	373

WORK ORDER

Customer:	Test Customer		Input Info:	11/5/2026
Reference:	Ambrish Single Door	SupplyAndFit		
Job No:	341	Page 14	Print Info:	11/5/2026

Glass Required:	**Qty**	**Width**	**Length**
02 (Frame-01) 4-20-4 Clear Tuff Low E : Thermal Spacer Bar	1	769	1319
03 (Frame-01) 4-20-4 Clear Tuff Low E : Thermal Spacer Bar	1	323	373
04 (Frame-01) 4-20-4 Clear Tuff Low E : Thermal Spacer Bar	1	323	1473

WORK ORDER

Customer:	Test Customer		Input Info:	11/5/2026
Reference:	Ambrish Single Door	SupplyAndFit		
Job No:	341	Page 15	Print Info:	11/5/2026

Main Options	
Colour (External)	White [SP]
Colour (Internal)	White [SP]
Frame (Standard) (Top)	SPQ-6-11252 68mm 6 Chamber
Frame (Standard) (Bottom)	SPQ-6-11252 68mm 6 Chamber
Frame (Standard) (Left)	SPQ-6-11252 68mm 6 Chamber
Frame (Standard) (Right)	SPQ-6-11252 68mm 6 Chamber
Transom	SPQ-5-30252 78mm
Mullion	SPQ-5-30252 78mm
Joint (Structural T/Z) (Transo...	Welded (Standard)
Joint (Structural T/Z) (Mullion)	Welded (Standard)
Bead	28mm
Sash Type	Door left hung
Cylinder	Brass Cylinder
Handle (Door)	White Handle Lever/Lever (Short Backplate)
Hinge (Door)	Flag Hinge
Hinge Colour (Door)	White Flag Hinge
Hinge Position (Door)	3 Hinges
Lock (Door) (Single Door)	Standard Door Lock
Glazing Method	Glazed
Glass Type	4-20-4 Clear Tuff Low E
Glass Gas Fill	Argon
Opening Direction	Open In
Component Type	Glass
Drainage	Concealed Drainage
Location	Please Specify
Horizontal Split Position	By Dimensions
Vertical Split Position	By Dimensions



Sections Required:			Qty	Length	End Prep	Reinforcing	Length
Hor	Bead	28mm Bead	4	233	[-]		
Vert	Bead	28mm Bead	2	1483	[-]		
Vert	Bead	28mm Bead	4	283	[-]		
Hor	Bead	28mm Bead	2	933	[-]		
Hor	Bead	28mm Bead	2	779	[-]		
Vert	Bead	28mm Bead	2	1329	[-]		
Hor	Frame	Frame 6 Chamber	2	1305	\ - /		
Vert	Frame	Frame 6 Chamber	2	1905	\ - /		
Hor	Frame	T Transom/Mullion	1	1925	< - >	26 x 26 U Steel Reinforcement	1764
Hor	Frame	T Transom/Mullion	1	354	< - >		
Hor	Frame	T Transom/Mullion	1	1054	< - >		
Hor	Sash	Door Sash Z	2	954	\ - /	28 x 44.5 U Steel Reinforcement	739
Vert	Sash	Door Sash Z	2	1504	\ - /	28 x 44.5 U Steel Reinforcement	1289

Accessories Required:	Qty	Unit Of Measurement
Run Up Block	1	Unit
Gasket 02	10.952	Metres
Glazing Bridge Packer	23	Unit
Gasket 01	9.792	Metres
White Handle Lever/Lever (Short Backplate)	1	Unit
Flag Hinge White	3	Unit
L/H Keep Set	1	Unit
Standard Door Lock	1	Unit
Brass Cylinder	1	Unit

Glass Required:	Qty	Width	Length
01 (Frame-01) 4-20-4 Clear Tuff Low E : Thermal Spacer Bar	1	223	273

WORK ORDER

Customer:	Test Customer		Input Info:	11/5/2026
Reference:	Ambrish Single Door	SupplyAndFit		
Job No:	341	Page 16	Print Info:	11/5/2026

Glass Required:	**Qty**	**Width**	**Length**
02 (Frame-01) 4-20-4 Clear Tuff Low E : Thermal Spacer Bar	1	223	1473
03 (Frame-01) 4-20-4 Clear Tuff Low E : Thermal Spacer Bar	1	923	273
04 (Frame-01) 4-20-4 Clear Tuff Low E : Thermal Spacer Bar	1	769	1319

WORK ORDER

Customer:	Test Customer		Input Info:	11/5/2026
Reference:	Ambrish Single Door	SupplyAndFit		
Job No:	341	Page 17	Print Info:	11/5/2026

Main Options	
Colour (External)	White [SP]
Colour (Internal)	White [SP]
Frame (Standard) (Top)	SPQ-6-11252 68mm 6 Chamber
Frame (Standard) (Bottom)	SPQ-6-11252 68mm 6 Chamber
Frame (Standard) (Left)	SPQ-6-11252 68mm 6 Chamber
Frame (Standard) (Right)	SPQ-6-11252 68mm 6 Chamber
Mullion	SPQ-5-30252 78mm
Joint (Structural T/Z) (Mullion)	Welded (Standard)
Bead	28mm
Sash Type	Door left hung
Cylinder	Brass Cylinder
Handle (Door)	White Handle Lever/Lever (Short Backplate)
Hinge (Door)	Flag Hinge
Hinge Colour (Door)	White Flag Hinge
Hinge Position (Door)	3 Hinges
Lock (Door) (Single Door)	Standard Door Lock
Glazing Method	Glazed
Glass Type	4-20-4 Clear Tuff Low E
Glass Gas Fill	Argon
Opening Direction	Open In
Component Type	Glass
Drainage	Concealed Drainage
Location	Please Specify
Horizontal Split Position	By Dimensions



Sections Required:			Qty	Length	End Prep	Reinforcing	Length
Vert	Bead	28mm Bead	4	2004	[-]		
Hor	Bead	28mm Bead	4	333	[-]		
Vert	Bead	28mm Bead	2	1850	[-]		
Hor	Bead	28mm Bead	2	808	[-]		
Hor	Frame	Frame 6 Chamber	2	1805	\ - /		
Vert	Frame	Frame 6 Chamber	2	2105	\ - /		
Hor	Frame	T Transom/Mullion	2	2125	< - >	26 x 26 U Steel Reinforcement	1964
Vert	Sash	Door Sash Z	2	2025	\ - /	28 x 44.5 U Steel Reinforcement	1810
Hor	Sash	Door Sash Z	2	983	\ - /	28 x 44.5 U Steel Reinforcement	768

Accessories Required:	Qty	Unit Of Measurement
Run Up Block	1	Unit
Gasket 02	14.544	Metres
Glazing Bridge Packer	18	Unit
Gasket 01	11.992	Metres
White Handle Lever/Lever (Short Backplate)	1	Unit
Flag Hinge White	3	Unit
L/H Keep Set	1	Unit
Standard Door Lock	1	Unit
Brass Cylinder	1	Unit

Glass Required:	Qty	Width	Length
01 (Frame-01) 4-20-4 Clear Tuff Low E : Thermal Spacer Bar	1	323	1994
02 (Frame-01) 4-20-4 Clear Tuff Low E : Thermal Spacer Bar	1	798	1840
03 (Frame-01) 4-20-4 Clear Tuff Low E : Thermal Spacer Bar	1	323	1994

WORK ORDER

Customer:	Test Customer		Input Info:	11/5/2026
Reference:	Ambrish Single Door	SupplyAndFit		
Job No:	341	Page 18	Print Info:	11/5/2026

Main Options	
Colour (External)	White [SP]
Colour (Internal)	White [SP]
Frame (Standard) (Top)	SPQ-6-11252 68mm 6 Chamber
Frame (Standard) (Bottom)	SPQ-6-11252 68mm 6 Chamber
Frame (Standard) (Left)	SPQ-6-11252 68mm 6 Chamber
Frame (Standard) (Right)	SPQ-6-11252 68mm 6 Chamber
Mullion	SPQ-5-30252 78mm
Joint (Structural T/Z) (Mullion)	Welded (Standard)
Bead	28mm
Sash Type	Door left hung
Cylinder	Brass Cylinder
Handle (Door)	White Handle Lever/Lever (Short Backplate)
Hinge (Door)	Flag Hinge
Hinge Colour (Door)	White Flag Hinge
Hinge Position (Door)	3 Hinges
Lock (Door) (Single Door)	Standard Door Lock
Glazing Method	Glazed
Glass Type	4-20-4 Clear Tuff Low E
Glass Gas Fill	Argon
Opening Direction	Open In
Component Type	Glass
Drainage	Concealed Drainage
Location	Please Specify
Horizontal Split Position	By Dimensions



Sections Required:			Qty	Length	End Prep	Reinforcing	Length
Vert	Bead	28mm Bead	4	2004	[-]		
Hor	Bead	28mm Bead	4	333	[-]		
Vert	Bead	28mm Bead	2	1850	[-]		
Hor	Bead	28mm Bead	2	808	[-]		
Hor	Frame	Frame 6 Chamber	2	1805	\ - /		
Vert	Frame	Frame 6 Chamber	2	2105	\ - /		
Hor	Frame	T Transom/Mullion	2	2125	< - >	26 x 26 U Steel Reinforcement	1964
Vert	Sash	Door Sash Z	2	2025	\ - /	28 x 44.5 U Steel Reinforcement	1810
Hor	Sash	Door Sash Z	2	983	\ - /	28 x 44.5 U Steel Reinforcement	768

Accessories Required:	Qty	Unit Of Measurement
Run Up Block	1	Unit
Gasket 02	14.544	Metres
Glazing Bridge Packer	18	Unit
Gasket 01	11.992	Metres
White Handle Lever/Lever (Short Backplate)	1	Unit
Flag Hinge White	3	Unit
L/H Keep Set	1	Unit
Standard Door Lock	1	Unit
Brass Cylinder	1	Unit

Glass Required:	Qty	Width	Length
01 (Frame-01) 4-20-4 Clear Tuff Low E : Thermal Spacer Bar	1	323	1994
02 (Frame-01) 4-20-4 Clear Tuff Low E : Thermal Spacer Bar	1	798	1840
03 (Frame-01) 4-20-4 Clear Tuff Low E : Thermal Spacer Bar	1	323	1994

WORK ORDER

Customer:	Test Customer		Input Info:	11/5/2026
Reference:	Ambrish Single Door	SupplyAndFit		
Job No:	341	Page 19	Print Info:	11/5/2026

Main Options	
Colour (External)	White [SP]
Colour (Internal)	White [SP]
Frame (Standard) (Top)	SPQ-6-11252 68mm 6 Chamber
Frame (Standard) (Bottom)	SPQ-6-11252 68mm 6 Chamber
Frame (Standard) (Left)	SPQ-6-11252 68mm 6 Chamber
Frame (Standard) (Right)	SPQ-6-11252 68mm 6 Chamber
Transom	SPQ-5-30252 78mm
Mullion	SPQ-5-30252 78mm
Joint (Structural T/Z) (Transo...	Welded (Standard)
Joint (Structural T/Z) (Mullion)	Welded (Standard)
Bead	28mm
Sash Type	Door left hung
Cylinder	Brass Cylinder
Handle (Door)	White Handle Lever/Lever (Short Backplate)
Hinge (Door)	Flag Hinge
Hinge Colour (Door)	White Flag Hinge
Hinge Position (Door)	3 Hinges
Lock (Door) (Single Door)	Standard Door Lock
Glazing Method	Glazed
Glass Type	4-20-4 Clear Tuff Low E
Glass Gas Fill	Argon
Opening Direction	Open In
Component Type	Glass
Drainage	Concealed Drainage
Location	Please Specify
Horizontal Split Position	By Dimensions
Vertical Split Position	By Dimensions



Sections Required:			Qty	Length	End Prep	Reinforcing	Length
Hor	Bead	28mm Bead	8	383	[-]		
Vert	Bead	28mm Bead	4	1583	[-]		
Vert	Bead	28mm Bead	6	383	[-]		
Hor	Bead	28mm Bead	2	962	[-]		
Hor	Bead	28mm Bead	2	808	[-]		
Vert	Bead	28mm Bead	2	1429	[-]		
Hor	Frame	Frame 6 Chamber	2	1905	\ - /		
Vert	Frame	Frame 6 Chamber	2	2105	\ - /		
Hor	Frame	T Transom/Mullion	2	2125	< - >	26 x 26 U Steel Reinforcement	1964
Hor	Frame	T Transom/Mullion	2	504	< - >		
Hor	Frame	T Transom/Mullion	1	1083	< - >	26 x 26 U Steel Reinforcement	922
Hor	Sash	Door Sash Z	2	983	\ - /	28 x 44.5 U Steel Reinforcement	768
Vert	Sash	Door Sash Z	2	1604	\ - /	28 x 44.5 U Steel Reinforcement	1389

Accessories Required:	Qty	Unit Of Measurement
Run Up Block	1	Unit
Gasket 02	17.852	Metres
Glazing Bridge Packer	33	Unit
Gasket 01	10.308	Metres
White Handle Lever/Lever (Short Backplate)	1	Unit
Flag Hinge White	3	Unit
L/H Keep Set	1	Unit
Standard Door Lock	1	Unit
Brass Cylinder	1	Unit

Glass Required:	Qty	Width	Length
01 (Frame-01) 4-20-4 Clear Tuff Low E : Thermal Spacer Bar	1	373	373

WORK ORDER

Customer:	Test Customer		Input Info:	11/5/2026
Reference:	Ambrish Single Door	SupplyAndFit		
Job No:	341	Page 20	Print Info:	11/5/2026

Glass Required:	**Qty**	**Width**	**Length**
02 (Frame-01) 4-20-4 Clear Tuff Low E : Thermal Spacer Bar	1	373	1573
03 (Frame-01) 4-20-4 Clear Tuff Low E : Thermal Spacer Bar	1	952	373
04 (Frame-01) 4-20-4 Clear Tuff Low E : Thermal Spacer Bar	1	798	1419
05 (Frame-01) 4-20-4 Clear Tuff Low E : Thermal Spacer Bar	1	373	373
06 (Frame-01) 4-20-4 Clear Tuff Low E : Thermal Spacer Bar	1	373	1573

WORK ORDER

Customer:	Test Customer		Input Info:	11/5/2026
Reference:	Ambrish Single Door	SupplyAndFit		
Job No:	341	Page 21	Print Info:	11/5/2026

Main Options	
Colour (External)	White [SP]
Colour (Internal)	White [SP]
Frame (Standard) (Top)	SPQ-6-11252 68mm 6 Chamber
Frame (Standard) (Bottom)	SPQ-6-11252 68mm 6 Chamber
Frame (Standard) (Left)	SPQ-6-11252 68mm 6 Chamber
Frame (Standard) (Right)	SPQ-6-11252 68mm 6 Chamber
Transom	SPQ-5-30252 78mm
Mullion	SPQ-5-30252 78mm
Joint (Structural T/Z) (Transo...	Welded (Standard)
Joint (Structural T/Z) (Mullion)	Welded (Standard)
Bead	28mm
Sash Type	Door right hung
Cylinder	Brass Cylinder
Handle (Door)	White Handle Lever/Lever (Short Backplate)
Hinge (Door)	Flag Hinge
Hinge Colour (Door)	White Flag Hinge
Hinge Position (Door)	3 Hinges
Lock (Door) (Single Door)	Standard Door Lock
Glazing Method	Glazed
Glass Type	4-20-4 Clear Tuff Low E
Glass Gas Fill	Argon
Opening Direction	Open In
Component Type	Glass
Drainage	Concealed Drainage
Location	Please Specify
Horizontal Split Position	By Dimensions
Vertical Split Position	By Dimensions



Sections Required:			Qty	Length	End Prep	Reinforcing	Length
Hor	Bead	28mm Bead	8	333	[-]		
Vert	Bead	28mm Bead	4	1483	[-]		
Vert	Bead	28mm Bead	6	383	[-]		
Hor	Bead	28mm Bead	2	962	[-]		
Hor	Bead	28mm Bead	2	808	[-]		
Vert	Bead	28mm Bead	2	1329	[-]		
Hor	Frame	Frame 6 Chamber	2	1805	\ - /		
Vert	Frame	Frame 6 Chamber	2	2005	\ - /		
Hor	Frame	T Transom/Mullion	2	2025	< - >	26 x 26 U Steel Reinforcement	1864
Hor	Frame	T Transom/Mullion	2	454	< - >		
Hor	Frame	T Transom/Mullion	1	1083	< - >	26 x 26 U Steel Reinforcement	922
Hor	Sash	Door Sash Z	2	983	\ - /	28 x 44.5 U Steel Reinforcement	768
Vert	Sash	Door Sash Z	2	1504	\ - /	28 x 44.5 U Steel Reinforcement	1289

Accessories Required:	Qty	Unit Of Measurement
Run Up Block	1	Unit
Gasket 02	16.852001	Metres
Glazing Bridge Packer	33	Unit
Gasket 01	9.908	Metres
White Handle Lever/Lever (Short Backplate)	1	Unit
Flag Hinge White	3	Unit
R/H Keep Set	1	Unit
Standard Door Lock	1	Unit
Brass Cylinder	1	Unit

Glass Required:	Qty	Width	Length
01 (Frame-01) 4-20-4 Clear Tuff Low E : Thermal Spacer Bar	1	323	373

WORK ORDER

Customer:	Test Customer		Input Info:	11/5/2026
Reference:	Ambrish Single Door	SupplyAndFit		
Job No:	341	Page 22	Print Info:	11/5/2026

Glass Required:	**Qty**	**Width**	**Length**
02 (Frame-01) 4-20-4 Clear Tuff Low E : Thermal Spacer Bar	1	323	1473
03 (Frame-01) 4-20-4 Clear Tuff Low E : Thermal Spacer Bar	1	952	373
04 (Frame-01) 4-20-4 Clear Tuff Low E : Thermal Spacer Bar	1	798	1319
05 (Frame-01) 4-20-4 Clear Tuff Low E : Thermal Spacer Bar	1	323	373
06 (Frame-01) 4-20-4 Clear Tuff Low E : Thermal Spacer Bar	1	323	1473