WORK ORDER

Customer:	Test Customer		Input Info:	10/25/2026
Reference:	French Doors	SupplyAndFit		
Job No:	318	Page 1	Print Info:	10/25/2026

Main Options	
Colour (External)	White [SP]
Colour (Internal)	White [SP]
Frame (Standard) (Top)	SPQ-6-11252 68mm 6 Chamber
Frame (Standard) (Bottom)	SPQ-6-11252 68mm 6 Chamber
Frame (Standard) (Left)	SPQ-6-11252 68mm 6 Chamber
Frame (Standard) (Right)	SPQ-6-11252 68mm 6 Chamber
Bead	28mm
Cylinder	Brass Cylinder
Handle (Door)	White Handle Lever/Lever (Short Backplate)
Hinge (Door)	Flag Hinge
Hinge Colour (Door)	White Flag Hinge
Hinge Position (Door)	3 Hinges
Lock (Door) (Double Door)	Standard Door Lock
Glazing Method	Glazed
Glass Type	4-20-4 Clear Tuff Low E
Glass Gas Fill	Argon
Opening Direction	Open Out
Master Leaf	Left
Component Type	Glass
Drainage	Concealed Drainage
Location	Please Specify
Horizontal Split Position	Equal Split



Sections Required:			Qty	Length	End Prep	Reinforcing	Length
Vert	Bead	28mm Bead	4	950	[-]		
Hor	Bead	28mm Bead	4	284	[-]		
Hor	Frame	Frame 6 Chamber	2	1005	\ - /		
Vert	Frame	Frame 6 Chamber	2	1205	\ - /		
Vert	Sash	Door Sash T	4	1125	\ - /	28 x 44.5 U Steel Reinforcement	910
Hor	Sash	Door Sash T	4	459	\ - /	28 x 44.5 U Steel Reinforcement	244
Vert	Sash group	French Mullion	1	1038	[-]	28 x 24 Steel Reinforcement	1038

Accessories Required:	Qty	Unit Of Measurement
French Door End Cap	2	Unit
Run Up Block	2	Unit
Gasket 01	12.592	Metres
White Handle Lever/Lever (Short Backplate)	2	Unit
Flag Hinge White	6	Unit
L/H Keep Set	1	Unit
Standard Door Lock	1	Unit
Brass Cylinder	2	Unit
Gasket 02	4.856	Metres
Glazing Bridge Packer	16	Unit
Double Shootbolt Keep Set	1	Unit
Standard Slave Door Lock	1	Unit

Glass Required:	Qty	Width	Length
01 (Frame-01) 4-20-4 Clear Tuff Low E : Thermal Spacer Bar	1	274	940
02 (Frame-01) 4-20-4 Clear Tuff Low E : Thermal Spacer Bar	1	274	940

WORK ORDER

Customer:	Test Customer		Input Info:	10/25/2026
Reference:	French Doors	SupplyAndFit		
Job No:	318	Page 2	Print Info:	10/25/2026

Main Options	
Colour (External)	White [SP]
Colour (Internal)	White [SP]
Frame (Standard) (Top)	SPQ-6-11252 68mm 6 Chamber
Frame (Standard) (Bottom)	SPQ-6-11252 68mm 6 Chamber
Frame (Standard) (Left)	SPQ-6-11252 68mm 6 Chamber
Frame (Standard) (Right)	SPQ-6-11252 68mm 6 Chamber
Transom	SPQ-5-30252 78mm
Joint (Structural T/Z) (Transo...	Welded (Standard)
Bead	28mm
Cylinder	Brass Cylinder
Handle (Door)	White Handle Lever/Lever (Short Backplate)
Hinge (Door)	Flag Hinge
Hinge Colour (Door)	White Flag Hinge
Hinge Position (Door)	3 Hinges
Lock (Door) (Double Door)	Standard Door Lock
Glazing Method	Glazed
Glass Type	4-20-4 Clear Tuff Low E
Glass Gas Fill	Argon
Opening Direction	Open Out
Master Leaf	Left
Component Type	Glass
Drainage	Concealed Drainage
Location	Please Specify
Horizontal Split Position	Equal Split
Vertical Split Position	By Dimensions



Sections Required:			Qty	Length	End Prep	Reinforcing	Length
Hor	Bead	28mm Bead	2	1104	[-]		
Vert	Bead	28mm Bead	2	433	[-]		
Vert	Bead	28mm Bead	4	1379	[-]		
Hor	Bead	28mm Bead	4	384	[-]		
Hor	Frame	Frame 6 Chamber	2	1205	\ - /		
Vert	Frame	Frame 6 Chamber	1	505	[Y - /		
Vert	Frame	Frame 6 Chamber	1	1605	[Y - /		
Vert	Frame	Frame 6 Chamber	1	1605	\ - Y]		
Vert	Frame	Frame 6 Chamber	1	505	\ - Y]		
Hor	Frame		1	1209	< - >		
Vert	Sash	Door Sash T	4	1554	\ - /	28 x 44.5 U Steel Reinforcement	1339
Hor	Sash	Door Sash T	4	559	\ - /	28 x 44.5 U Steel Reinforcement	344
Vert	Sash group	French Mullion	1	1471	[-]	28 x 24 Steel Reinforcement	1471

Accessories Required:	Qty	Unit Of Measurement
Gasket 02	10.006	Metres
Glazing Bridge Packer	21	Unit
French Door End Cap	2	Unit
Run Up Block	2	Unit
Gasket 01	16.824001	Metres
White Handle Lever/Lever (Short Backplate)	2	Unit
Flag Hinge White	6	Unit
L/H Keep Set	1	Unit
Standard Door Lock	1	Unit
Brass Cylinder	2	Unit
Double Shootbolt Keep Set	1	Unit
Standard Slave Door Lock	1	Unit

WORK ORDER

Customer:	Test Customer		Input Info:	10/25/2026
Reference:	French Doors	SupplyAndFit		
Job No:	318	Page 3	Print Info:	10/25/2026

Glass Required:	**Qty**	**Width**	**Length**
01 (Frame-01) 4-20-4 Clear Tuff Low E : Thermal Spacer Bar	1	1094	423
02 (Frame-01) 4-20-4 Clear Tuff Low E : Thermal Spacer Bar	1	374	1369
03 (Frame-01) 4-20-4 Clear Tuff Low E : Thermal Spacer Bar	1	374	1369

WORK ORDER

Customer:	Test Customer		Input Info:	10/25/2026
Reference:	French Doors	SupplyAndFit		
Job No:	318	Page 4	Print Info:	10/25/2026

Main Options	
Colour (External)	White [SP]
Colour (Internal)	White [SP]
Frame (Standard) (Top)	SPQ-6-11252 68mm 6 Chamber
Frame (Standard) (Bottom)	SPQ-6-11252 68mm 6 Chamber
Frame (Standard) (Left)	SPQ-6-11252 68mm 6 Chamber
Frame (Standard) (Right)	SPQ-6-11252 68mm 6 Chamber
Transom	SPQ-5-30252 78mm
Mullion	SPQ-5-30252 78mm
Joint (Structural T/Z) (Transo...	Welded (Standard)
Joint (Structural T/Z) (Mullion)	Welded (Standard)
Bead	28mm
Cylinder	Brass Cylinder
Handle (Door)	White Handle Lever/Lever (Short Backplate)
Hinge (Door)	Flag Hinge
Hinge Colour (Door)	White Flag Hinge
Hinge Position (Door)	3 Hinges
Lock (Door) (Double Door)	Standard Door Lock
Glazing Method	Glazed
Glass Type	4-20-4 Clear Tuff Low E
Glass Gas Fill	Argon
Opening Direction	Open Out
Master Leaf	Left
Component Type	Glass
Drainage	Concealed Drainage
Location	Please Specify
Horizontal Split Position	By Dimensions
Vertical Split Position	By Dimensions



Sections Required:			Qty	Length	End Prep	Reinforcing	Length
Vert	Bead	28mm Bead	4	533	[-]		
Hor	Bead	28mm Bead	4	533	[-]		
Vert	Bead	28mm Bead	4	1579	[-]		
Hor	Bead	28mm Bead	4	384	[-]		
Hor	Frame	Frame 6 Chamber	2	1205	\ - /		
Vert	Frame	Frame 6 Chamber	1	605	[Y - /		
Vert	Frame	Frame 6 Chamber	1	1805	[Y - /		
Vert	Frame	Frame 6 Chamber	1	1805	\ - Y]		
Vert	Frame	Frame 6 Chamber	1	605	\ - Y]		
Hor	Frame		1	1209	< - >		
Hor	Frame	T Transom/Mullion	1	654	< - >		
Vert	Sash	Door Sash T	4	1754	\ - /	28 x 44.5 U Steel Reinforcement	1539
Hor	Sash	Door Sash T	4	559	\ - /	28 x 44.5 U Steel Reinforcement	344
Vert	Sash group	French Mullion	1	1671	[-]	28 x 24 Steel Reinforcement	1671

Accessories Required:	Qty	Unit Of Measurement
Gasket 02	11.956	Metres
Glazing Bridge Packer	26	Unit
French Door End Cap	2	Unit
Run Up Block	2	Unit
Gasket 01	18.424	Metres
White Handle Lever/Lever (Short Backplate)	2	Unit
Flag Hinge White	6	Unit
L/H Keep Set	1	Unit
Standard Door Lock	1	Unit
Brass Cylinder	2	Unit

WORK ORDER

Customer:	Test Customer		Input Info:	10/25/2026
Reference:	French Doors	SupplyAndFit		
Job No:	318	Page 5	Print Info:	10/25/2026

Accessories Required:	Qty	Unit Of Measurement
Double Shootbolt Keep Set	1	Unit
Standard Slave Door Lock	1	Unit

Glass Required:	Qty	Width	Length
01 (Frame-01) 4-20-4 Clear Tuff Low E : Thermal Spacer Bar	1	523	523
02 (Frame-01) 4-20-4 Clear Tuff Low E : Thermal Spacer Bar	1	374	1569
03 (Frame-01) 4-20-4 Clear Tuff Low E : Thermal Spacer Bar	1	374	1569
04 (Frame-01) 4-20-4 Clear Tuff Low E : Thermal Spacer Bar	1	523	523

WORK ORDER

Customer:	Test Customer		Input Info:	10/25/2026
Reference:	French Doors	SupplyAndFit		
Job No:	318	Page 6	Print Info:	10/25/2026

Main Options	
Colour (External)	White [SP]
Colour (Internal)	White [SP]
Frame (Standard) (Top)	SPQ-6-11252 68mm 6 Chamber
Frame (Standard) (Bottom)	SPQ-6-11252 68mm 6 Chamber
Frame (Standard) (Left)	SPQ-6-11252 68mm 6 Chamber
Frame (Standard) (Right)	SPQ-6-11252 68mm 6 Chamber
Mullion	SPQ-5-30252 78mm
Joint (Structural T/Z) (Mullion)	Welded (Standard)
Bead	28mm
Cylinder	Brass Cylinder
Handle (Door)	White Handle Lever/Lever (Short Backplate)
Hinge (Door)	Flag Hinge
Hinge Colour (Door)	White Flag Hinge
Hinge Position (Door)	3 Hinges
Lock (Door) (Double Door)	Standard Door Lock
Glazing Method	Glazed
Glass Type	4-20-4 Clear Tuff Low E
Glass Gas Fill	Argon
Opening Direction	Open Out
Master Leaf	Left
Component Type	Glass
Drainage	Concealed Drainage
Location	Please Specify
Horizontal Split Position	By Dimensions



Sections Required:			Qty	Length	End Prep	Reinforcing	Length
Vert	Bead	28mm Bead	2	1404	[-]		
Hor	Bead	28mm Bead	2	433	[-]		
Vert	Bead	28mm Bead	4	1250	[-]		
Hor	Bead	28mm Bead	2	446.5	[-]		
Hor	Bead	28mm Bead	2	450.5	[-]		
Hor	Frame	Frame 6 Chamber	1	505	[Y - /		
Hor	Frame	Frame 6 Chamber	1	1305	[Y - /		
Vert	Frame	Frame 6 Chamber	2	1505	\ - /		
Hor	Frame	Frame 6 Chamber	1	1305	\ - Y]		
Hor	Frame	Frame 6 Chamber	1	505	\ - Y]		
Hor	Frame		1	1509	< - >		
Vert	Sash	Door Sash T	4	1425	\ - /	28 x 44.5 U Steel Reinforcement	1210
Hor	Sash	Door Sash T	2	621.5	\ - /	28 x 44.5 U Steel Reinforcement	406.5
Hor	Sash	Door Sash T	2	625.5	\ - /	28 x 44.5 U Steel Reinforcement	410.5
Vert	Sash group	French Mullion	1	1338	[-]	28 x 24 Steel Reinforcement	1338

Accessories Required:	Qty	Unit Of Measurement
Gasket 02	10.348001	Metres
Glazing Bridge Packer	21	Unit
French Door End Cap	2	Unit
Run Up Block	2	Unit
Gasket 01	16.308	Metres
White Handle Lever/Lever (Short Backplate)	2	Unit
Flag Hinge White	6	Unit
L/H Keep Set	1	Unit
Standard Door Lock	1	Unit
Brass Cylinder	2	Unit
Double Shootbolt Keep Set	1	Unit
Standard Slave Door Lock	1	Unit

WORK ORDER

Customer:	Test Customer		Input Info:	10/25/2026
Reference:	French Doors	SupplyAndFit		
Job No:	318	Page 7	Print Info:	10/25/2026

Glass Required:	**Qty**	**Width**	**Length**
01 (Frame-01) 4-20-4 Clear Tuff Low E : Thermal Spacer Bar	1	423	1394
02 (Frame-01) 4-20-4 Clear Tuff Low E : Thermal Spacer Bar	1	436	1240
03 (Frame-01) 4-20-4 Clear Tuff Low E : Thermal Spacer Bar	1	440	1240

WORK ORDER

Customer:	Test Customer		Input Info:	10/25/2026
Reference:	French Doors	SupplyAndFit		
Job No:	318	Page 8	Print Info:	10/25/2026

Main Options	
Colour (External)	White [SP]
Colour (Internal)	White [SP]
Frame (Standard) (Top)	SPQ-6-11252 68mm 6 Chamber
Frame (Standard) (Bottom)	SPQ-6-11252 68mm 6 Chamber
Frame (Standard) (Left)	SPQ-6-11252 68mm 6 Chamber
Frame (Standard) (Right)	SPQ-6-11252 68mm 6 Chamber
Mullion	SPQ-5-30252 78mm
Joint (Structural T/Z) (Mullion)	Welded (Standard)
Bead	28mm
Cylinder	Brass Cylinder
Handle (Door)	White Handle Lever/Lever (Short Backplate)
Hinge (Door)	Flag Hinge
Hinge Colour (Door)	White Flag Hinge
Hinge Position (Door)	3 Hinges
Lock (Door) (Double Door)	Standard Door Lock
Glazing Method	Glazed
Glass Type	4-20-4 Clear Tuff Low E
Glass Gas Fill	Argon
Opening Direction	Open Out
Master Leaf	Left
Component Type	Glass
Drainage	Concealed Drainage
Location	Please Specify
Horizontal Split Position	By Dimensions



Sections Required:			Qty	Length	End Prep	Reinforcing	Length
Vert	Bead	28mm Bead	2	1704	[-]		
Hor	Bead	28mm Bead	2	433	[-]		
Vert	Bead	28mm Bead	4	1550	[-]		
Hor	Bead	28mm Bead	2	600.5	[-]		
Hor	Bead	28mm Bead	2	596.5	[-]		
Hor	Frame	Frame 6 Chamber	1	1605	\ - Y]		
Hor	Frame	Frame 6 Chamber	1	505	\ - Y]		
Vert	Frame	Frame 6 Chamber	2	1805	\ - /		
Hor	Frame	Frame 6 Chamber	1	505	[Y - /		
Hor	Frame	Frame 6 Chamber	1	1605	[Y - /		
Hor	Frame		1	1809	< - >		
Vert	Sash	Door Sash T	4	1725	\ - /	28 x 44.5 U Steel Reinforcement	1510
Hor	Sash	Door Sash T	2	775.5	\ - /	28 x 44.5 U Steel Reinforcement	560.5
Hor	Sash	Door Sash T	2	771.5	\ - /	28 x 44.5 U Steel Reinforcement	556.5
Vert	Sash group	French Mullion	1	1638	[-]	28 x 24 Steel Reinforcement	1638

Accessories Required:	Qty	Unit Of Measurement
Gasket 02	12.748	Metres
Glazing Bridge Packer	21	Unit
French Door End Cap	2	Unit
Run Up Block	2	Unit
Gasket 01	19.908	Metres
White Handle Lever/Lever (Short Backplate)	2	Unit
Flag Hinge White	6	Unit
L/H Keep Set	1	Unit
Standard Door Lock	1	Unit
Brass Cylinder	2	Unit
Double Shootbolt Keep Set	1	Unit
Standard Slave Door Lock	1	Unit

WORK ORDER

Customer:	Test Customer		Input Info:	10/25/2026
Reference:	French Doors	SupplyAndFit		
Job No:	318	Page 9	Print Info:	10/25/2026

Glass Required:	**Qty**	**Width**	**Length**
01 (Frame-01) 4-20-4 Clear Tuff Low E : Thermal Spacer Bar	1	590	1540
02 (Frame-01) 4-20-4 Clear Tuff Low E : Thermal Spacer Bar	1	586	1540
03 (Frame-01) 4-20-4 Clear Tuff Low E : Thermal Spacer Bar	1	423	1694