

Angular Event Binding - Complete Information

Event Binding म्हणजे:

HTML Event → TypeScript Function

जेव्हा User काही action करतो (click, keypress, hover), तेव्हा Angular TypeScript मधील method execute करतो.

Syntax

```
(event)="methodName()"
```

उदा.

```
<button (click)="saveData()">
```

Save

```
</button>
```

```
saveData(){
```

```
  console.log("Data Saved");
```

```
}
```

Event Binding ची गरज का आहे?

User Interface (HTML) आणि Business Logic (TypeScript) connect करण्यासाठी.

उदा.

- Button Click
- Form Submit
- Input Typing
- Mouse Hover

Flow

User Action



HTML Event Trigger



TypeScript Function Call



Result

Event Binding मधील सर्व **events** चे **code** पाठ करण्या ऐवजी त्यामागचा **pattern** समजून घे.

Function कसा लिहायचा?

```
functionName() {  
  
}
```

उदा.

```
showMessage() {  
  alert("Hello");  
}
```

1. Click Event

HTML

```
<button (click)="showMessage()">
  Click Me
</button>
```

TS

```
showMessage() {
  alert("Button Clicked");
}
```

2. Double Click Event

HTML

```
<button (dblclick)="doubleClick()">
  Double Click
</button>
```

TS

```
doubleClick() {
  alert("Double Clicked");
}
```

3. Mouse Over

HTML

```
<h1 (mouseover)="mouseOver()">
  Hover Me
</h1>
```

TS

```
mouseOver() {
  console.log("Mouse Entered");
}
```

4. Mouse Leave

HTML

```
<h1 (mouseleave)="mouseLeave()">  
  Move Mouse Away  
</h1>
```

TS

```
mouseLeave() {  
  console.log("Mouse Left");  
}
```

5. Focus Event

Input मध्ये cursor आला की.

HTML

```
<input (focus)="inputFocus()">
```

TS

```
inputFocus() {  
  console.log("Input Focused");  
}
```

6. Blur Event

Input मधून cursor बाहेर गेला की.

HTML

```
<input (blur)="inputBlur()">
```

TS

```
inputBlur() {  
  console.log("Input Blur");  
}
```

7. Change Event

HTML

```
<select (change)="courseChange()">
  <option>Angular</option>
  <option>React</option>
</select>
```

TS

```
courseChange() {
  console.log("Course Changed");
}
```

8. Keyup Event

Key सोडल्यावर.

HTML

```
<input (keyup)="keyUp()">
```

TS

```
keyUp() {
  console.log("Key Released");
}
```

9. Keydown Event

Key दाबताच.

HTML

```
<input (keydown)="keyDown()">
```

TS

```
keyDown() {
  console.log("Key Pressed");
}
```

10. Input Event

प्रत्येक character टाईप होताना.

HTML

```
<input (input)="typing()">
```

TS

```
typing() {  
  console.log("Typing...");  
}
```

Parameter Passing

HTML

```
<button (click)="showName('Gaurav')">  
  Click  
</button>
```

TS

```
showName(name: string) {  
  alert(name);  
}
```

Using \$event

HTML

```
<input (keyup)="getValue($event)">
```

TS

```
getValue(event: any) {  
  console.log(event.target.value);  
}
```

जर user टाईप करेल:

Angular

Console:

Most Important Functions for Beginners

आधी हे 5 events पक्के कर:

1. `(click)`
2. `(keyup)`
3. `(change)`
4. `(focus)`
5. `(blur)`

हेच events 90% Angular forms आणि CRUD projects मध्ये वापरले जातात.

Practice Task

Student Management Project मध्ये:

- Add Student button → `(click)`
- Search Student → `(keyup)`
- Course Dropdown → `(change)`
- Name Input → `(focus)`
- Email Input → `(blur)`