

Review

Which of the property of **HDFS** make it impossible to have 100% availability?

Which of the properties of **HDFS** make it impossible to have 100% availability?

- Single point of failure of NameNode

Which of the following properties does Cassandra possess?

- Linearly scalable
- Free and open source
- Supports horizontal scaling
- One of the nodes has to be much powerful than the rest of the nodes

Which of the following properties does Cassandra possess?

- Linearly scalable
- Free and open source
- Supports horizontal scaling
- One of the nodes has to be much powerful than the rest of the nodes

What is the reason that Cassandra is linearly scalable while HDFS is not?

What is the reason that Cassandra is linearly scalable while HDFS is not?

- Cassandra doesn't have a single point bottleneck like HDFS.  
In HDFS, you can add more datanodes, but there still will be a single namenode which can be a bottleneck.

If you wanted to run real-time analytics queries on structured/semi-structured data, which storage would you prefer – HDFS or Cassandra?



If you wanted to run analytics queries on live structured/semi-structured data, which storage would you prefer – HDFS or Cassandra?

- Cassandra is better suited for online operations, that includes analytics on live or hot data. It has lower latency than HDFS

<http://www.datastax.com/nosql-databases/nosql-cassandra-and-hadoop>

If you wanted to achieve high throughput processing on historical data, which technology would you prefer – HDFS or Cassandra?

If you wanted to achieve high throughput processing on historical data, which technology would you prefer – HDFS or Cassandra?

- HDFS has higher throughput on historical data.

Do Peer-to-Peer (P2P) systems provide better **availability** than master/slave architecture? What about **consistency**?

Do Peer-to-Peer (P2P) systems provide better **availability** than master/slave architecture? What about **consistency**?

**Availability** – Yes, because there is no single point of failure and each node can act as the coordinator for different client requests.


**Consistency** – Not necessarily. Data has to be shared with each node, which may take place over time. They aim for eventual consistency.

What is token range in a Cassandra cluster? How is it distributed?  
What is the default token generation algorithm

What is token range in a Cassandra cluster? How is it distributed?  
What is the default token generation algorithm

Entire keyspace is represented by the token range, which is distributed in the form of a ring.

Default algorithm: Murmur3Partitioner




Each node in a Cassandra cluster is assigned a token. What does it signify?



Each node in a Cassandra cluster is assigned a token. What does it signify?


Node tokens represent the highest value in the segment owned by that node.



Where is the first replica of a write request written to in Cassandra?

Where is the first replica of a write request written to in Cassandra?

On the node owning the token's primary range



What is consistency level ? What is the most strict consistency level.  
Which level provides the best balance between consistency and availability?

What is consistency level ? What is the most strict consistency level.  
Which level provides the best balance between consistency and availability?

Consistency level – how many nodes must acknowledge a read/write  
CL of ALL provides the highest consistency.  
CL of QUORUM provides the best balance.

What is the stale read problem? When does it occur? Can it occur for a QUORUM CL?

What is the stale read problem? When does it occur? Can it occur for a QUORUM CL?

Stale read= when the data returned to the client is not the latest version.

It happens when  $(\text{read CL} + \text{write CL}) < RF$

It can not happen when  $CL = QUORUM$


Which protocol is used to spread network topology information to all the nodes in a Cassandra cluster?



Which protocol is used to spread network topology information to all the nodes in a Cassandra cluster?

### What is the Gossip protocol?

- Once per second, each node contacts 1 to 3 others, requesting and sharing updates about
  - Known node states ("heartbeats")
  - Known node locations
  - Requests and acknowledgments are timestamped, so information is continually updated and discarded



Which one of the following is true about columns in Cassandra data model?

All rows should have the same column keys

The column keys in a row are always sorted

To retrieve a column value, both the row key and column key must be known

All rows should have the same number of columns

Which one of the following is true about columns in Cassandra data model?

All rows should have the same column keys

The column keys in a row are always sorted


To retrieve a column value, both the row key and column key must be known

All rows should have the same number of columns

What is a column family in Cassandra?

What is a column family in Cassandra?

A set of rows having similar column structure



What is a partition ? What is the use of a clustering key column within a partition?

What is a partition ? What is the use of a clustering key column within a partition?

Partition – a group of rows with the same value of the partitioning columns.

Clustering key column within a partition allows for efficient retrieval of rows.

- Table with multi-row partitions

composite partition key

columns

The clustering key columns are used to cluster the data of a partition, allowing a very efficient retrieval of rows.


clustering column

rows in a partition/table

partitions

cells

album_title	year	number	track_title
Revolver	1966	I	Taxman
Revolver	1966	...	...
Revolver	1966	14	Tomorrow Never Knows
Let It Be	1970	I	Two Of Us
Let It Be	1970	...	...
Let It Be	1970	II	Get Back
Magical Mystery Tour	1967	I	Revolver:1966
Magical Mystery Tour	1967	...	...
Magical Mystery Tour	1967	II	Let It Be:1970





Why does HBase provide less availability than Cassandra?

Why does HBase provide less availability than Cassandra?

HBase runs on top of HDFS, which has a single point of failure.  
HBase has a single master called HMaster that is responsible for various RegionServers (each RegionServer manages a region, which is a group of contiguous rows)

In which of the following cases would you store data in HBase as compared to files in HDFS?

- You require low latency data access.
- You require random read access to individual data items.
- You would like higher throughput batch processing of data items.
- You are storing semi-structured data that share a number of key values that can be grouped together.

In which of the following cases would you store data in HBase as compared to files in HDFS?

- You require low latency data access.
- You require random read access to individual data items.
- You would like higher throughput batch processing of data items.
- You are storing semi-structured data that share a number of key values that can be grouped together.

Which of the following is true about HBase schema?

- Schema defines individual columns
- Schema only defines column families
- Column families are identified by their prefix
- There is only one key for retrieving values in HBase

Which of the following is true about HBase schema?

- Schema defines individual columns
- Schema only defines column families
- Column families are identified by their prefix
- There is only one key for retrieving values in HBase

A value in HBase table is indexed by 3 keys. Identify them.

A value in HBase table is indexed by 3 keys. Identify them.

- Row key
- Column key
- Timestamp



A RegionServer manages a region of the HBase table. How is region defined:

- a portion of the sorted row keyspace.
- a portion of the sorted column keyspace.
- it could be either row or column keyspace.
- it is a combination of row and column keyspace.

A RegionServer manages a region of the HBase table. How is region defined:

- a portion of the sorted row keyspace.
- a portion of the sorted column keyspace.
- it could be either row or column keyspace.
- it is a combination of row and column keyspace.

HBase master is responsible for which of the following:

- data storage
- assigning regions to region servers
- processing data
- administrative functions and recovering from region server failure

HBase master is responsible for which of the following:

- data storage
- assigning regions to region servers
- processing data
- administrative functions and recovering from region server failure

What is ZooKeeper?

## What is ZooKeeper?

- If you are building a distributed application and require fault tolerance, ability to recover from partial failures, provide synchronization, and group services, then you can use ZooKeeper.
- ZooKeeper is a centralized service that provides high performance coordination among the nodes in a distributed application