

## ASSSIGNMENT 2

NAME:

ROLL NO:

---

**PROBLEM STATEMENT:** DESIGN AND DEVELOP SQL DDL STATEMENTS WHICH DEMONSTRATE THE USE OF SQL OBJECTS SUCH AS TABLE.

\*\*\*\*\*

### A) CREATE TABLES

CLIENT\_MASTER,  
PRODUCT\_MASTER,  
SALESMAN\_MASTER,  
SALES\_ORDER,  
SALES\_ORDER\_DETAILS.

\*\*\*\*\*

```
mysql> create database ENGG;  
Query OK, 1 row affected (0.00 sec)
```

```
mysql> use ENGG;  
Database changed
```

---

```
>CREATE TABLE CLIENT_MASTER(CLIENT_NO VARCHAR (6), NAME VARCHAR  
(20), ADDRESS1 VARCHAR (30), ADDRESS2 VARCHAR (30), CITY VARCHAR (15),  
PINCODE INTEGER (8), STATE VARCHAR (15), BAL_DUE FLOAT (10,2), PRIMARY  
KEY (CLIENT_NO));  
Query OK, 0 rows affected (0.08 sec)
```

```
mysql> DESC CLIENT_MASTER;  
+-----+-----+-----+-----+-----+-----+  
| Field | Type | Null | Key | Default | Extra |  
+-----+-----+-----+-----+-----+-----+  
| CLIENT_NO | varchar(6) | NO | PRI | | |  
| NAME | varchar(20) | NO | | NULL | |  
| ADDRESS1 | varchar(30) | NO | | NULL | |  
| ADDRESS2 | varchar(30) | NO | | NULL | |  
| CITY | varchar(15) | NO | | NULL | |  
| PINCODE | int(8) | NO | | NULL | |  
| STATE | varchar(15) | NO | | NULL | |  
| BAL_DUE | float(10,2) | NO | | NULL | |  
+-----+-----+-----+-----+-----+-----+  
8 rows in set (0.00 sec)
```

---

```
mysql> CREATE TABLE PRODUCT_MASTER (PRODUCT_NO VARCHAR (6),
```

DESCRIPTION VARCHAR (15) NOT NULL, PROFIT\_PERSCENT FLOAT (4,2) NOT NULL, UNIT\_MEASURE VARCHAR (10) NOT NULL, QTY\_ON\_HAND INTEGER (8) NOT NULL, REORDER\_LVL INTEGER (8) NOT NULL, SELL\_PRICE FLOAT (8,2) NOT NULL, COST\_PRICE FLOAT (8,2) NOT NULL, PRIMARY KEY (PRODUCT\_NO));  
Query OK, 0 rows affected (0.08 sec)

```
mysql> DESC PRODUCT_MASTER;+-----+-----+-----+-----+
| Field      | Type      | Null | Key | Default | Extra |
+-----+-----+-----+-----+
| PRODUCT_NO | varchar(6) | NO   | PRI |         |       |
| DESCRIPTION | varchar(15)| NO   |     | NULL    |       |
| PROFIT_PERSCENT | float(4,2) | NO   |     | NULL    |       |
| UNIT_MEASURE | varchar(10)| NO   |     | NULL    |       |
| QTY_ON_HAND | int(8)     | NO   |     | NULL    |       |
| REORDER_LVL | int(8)     | NO   |     | NULL    |       |
| SELL_PRICE  | float(8,2) | NO   |     | NULL    |       |
| COST_PRICE  | float(8,2) | NO   |     | NULL    |       |
+-----+-----+-----+-----+
8 rows in set (0.00 sec)
```

---

```
mysql> CREATE TABLE SALESMAN_MASTER (SALESMAN_NO VARCHAR (6)
PRIMARY KEY, SALESMAN_NAME VARCHAR (20) NOT NULL, ADDRESS1 VARCHAR
(30) NOT NULL, ADDRESS2 VARCHAR (30), CITY VARCHAR (20), PINCODE FLOAT
(8,2), STATE VARCHAR (20), SAL_AMT FLOAT (8,2) NOT NULL, TGT_TO_GET FLOAT
(6,2) NOT NULL, YTD_SALES FLOAT (6,2) NOT NULL, REMARKS VARCHAR (60));
Query OK, 0 rows affected (0.06 sec)
```

```
mysql> DESC SALESMAN_MASTER;
+-----+-----+-----+-----+
| Field      | Type      | Null | Key | Default | Extra |
+-----+-----+-----+-----+
| SALESMAN_NO | varchar(6) | NO   | PRI | NULL    |       |
| SALESMAN_NAME | varchar(20)| NO   |     | NULL    |       |
| ADDRESS1     | varchar(30)| NO   |     | NULL    |       |
| ADDRESS2     | varchar(30)| YES  |     | NULL    |       |
| CITY         | varchar(20)| YES  |     | NULL    |       |
| PINCODE      | float(8,2) | YES  |     | NULL    |       |
| STATE        | varchar(20)| YES  |     | NULL    |       |
| SAL_AMT      | float(8,2) | NO   |     | NULL    |       |
| TGT_TO_GET   | float(6,2) | NO   |     | NULL    |       |
| YTD_SALES    | float(6,2) | NO   |     | NULL    |       |
| REMARKS      | varchar(60)| YES  |     | NULL    |       |
+-----+-----+-----+-----+
11 rows in set (0.00 sec)
```

---

```
mysql> CREATE TABLE SALES_ORDER (ORDER_NO VARCHAR (6) PRIMARY
KEY, CLIENT_NO VARCHAR (6), ORDER_DATE DATE NOT NULL, DELY_ADDR
VARCHAR (25), SALESMAN_NO VARCHAR (6), DELY_TYPE CHAR (1), BILLYN CHAR
```

(1), DELY\_DATE DATE, ORDER\_STATUS VARCHAR (10), FOREIGN KEY (CLIENT\_NO) REFERENCES CLIENT\_MASTER (CLIENT\_NO), FOREIGN KEY (SALESMAN\_NO) REFERENCES SALESMAN\_MASTER (SALESMAN\_NO));  
Query OK, 0 rows affected (0.14 sec)

mysql> DESC SALES\_ORDER;

Field	Type	Null	Key	Default	Extra
ORDER_NO	varchar(6)	NO	PRI	NULL	
CLIENT_NO	varchar(6)	YES	MUL	NULL	
ORDER_DATE	date	NO		NULL	
DELY_ADDR	varchar(25)	YES		NULL	
SALESMAN_NO	varchar(6)	YES	MUL	NULL	
DELY_TYPE	char(1)	YES		NULL	
BILLYN	char(1)	YES		NULL	
DELY_DATE	date	YES		NULL	
ORDER_STATUS	varchar(10)	YES		NULL	

9 rows in set (0.00 sec)

mysql> CREATE TABLE SALES\_ORDER\_DETAILS (ORDER\_NO VARCHAR (6), PRODUCT\_NO VARCHAR (6), QTY\_ORDERED INTEGER (8), QTY\_DISP INTEGER (8), PRODUCT\_RATE FLOAT (10,2), FOREIGN KEY (ORDER\_NO) REFERENCES SALES\_ORDER (ORDER\_NO), FOREIGN KEY (PRODUCT\_NO) REFERENCES PRODUCT\_MASTER (PRODUCT\_NO));  
Query OK, 0 rows affected (0.12 sec)

mysql> DESC SALES\_ORDER\_DETAILS;

Field	Type	Null	Key	Default	Extra
ORDER_NO	varchar(6)	YES	MUL	NULL	
PRODUCT_NO	varchar(6)	YES	MUL	NULL	
QTY_ORDERED	int(8)	YES		NULL	
QTY_DISP	int(8)	YES		NULL	
PRODUCT_RATE	float(10,2)	YES		NULL	

5 rows in set (0.01 sec)

\*\*\*\*\*

## B) INSERT THE DATA INTO THEIR RESPECTIVE TABLES.

\*\*\*\*\*

mysql>

INSERT INTO

CLIENT\_MASTER(CLIENT\_NO,NAME,ADDRESS1,ADDRESS2,CITY,PINCODE,STATE, BAL\_DUE)

VALUES

('C00001','IVAN

```

BAYROSS','NASHIK','YEOLA','MUMBAI','400054','MAHARASHTRA','15000'),
('C00002','MAMTA MUZUMDAR','NIMANI','CBS','MADRAS','780001','TAMIL NADU','0'),
('C00003','CHHAYA
BANKER','DWARKA','ASHOKNAGAR','MUMBAI','400057','MAHARASHTRA','5000'),
('C00004','ASHWINI
JOSHI','RK','SHALIMAR','BANGALORE','560001','KARNATAKA','0'),
('C00005','HANSEL
COLACO','KOPARGAON','LASLGAON','MUMBAI','400060','MAHARASHTRA','2000'),
('C00006','DIPAK
SHARMA','VAIJAPUR','VINCHUR','BANGALORE','560050','KARNATAKA','0');
Query OK, 6 rows affected (0.02 sec)
Records: 6 Duplicates: 0 Warnings: 0

```

```

mysql> SELECT *FROM CLIENT_MASTER;
+-----+-----+-----+-----+-----+-----+-----+
| CLIENT_NO | NAME          | ADDRESS1 | ADDRESS2 | CITY    | PINCODE | STATE |
| BALDUE   |
+-----+-----+-----+-----+-----+-----+-----+
| C00001   | IVAN BAYROSS | NASHIK   | YEOLA     | MUMBAI  | 400054 | MAHARASHTRA | 15000.00 |
| C00002   | MAMTA MUZUMDAR | NIMANI    | CBS       | MADRAS  | 780001 | TAMIL NADU | 0.00 |
| C00003   | CHHAYA BANKER | DWARKA    | ASHOKNAGAR | MUMBAI  | 400057 | MAHARASHTRA | 5000.00 |
| C00004   | ASHWINI JOSHI | RK        | SHALIMAR  | BANGALORE | 560001 | KARNATAKA | 0.00 |
| C00005   | HANSEL COLACO | KOPARGAON | LASLGAON  | MUMBAI  | 400060 | MAHARASHTRA | 2000.00 |
| C00006   | DIPAK SHARMA | VAIJAPUR | VINCHUR   | BANGALORE | 560050 | KARNATAKA | 0.00 |
+-----+-----+-----+-----+-----+-----+-----+
6 rows in set (0.00 sec)

```

```

mysql> INSERT INTO
PRODUCT_MASTER(PRODUCT_NO,DESCRIPTION,PROFIT_PERSCENT,UNIT_MEAS
URE,QTY_ON_HAND,REORDER_LVL,SELL_PRICE,COST_PRICE) VALUES
('P0001','T-SHIRTS','5','PIECE','200','50','350','250'),
('P0345','SHIRTS','6','PIECE','150','50','500','350'), ('P06734','COTTON
JEANS','5','PIECE','100','20','600','450'),
('P07865','JEANS','5','PIECE','100','20','750','500'),
('P07868','TROUSERS','2','PIECE','150','50','850','550'), ('P07885','PULL
OVERS','2.5','PIECE','80','30','700','450'), ('P07965','DEIM
SHIRTS','4','PIECE','100','40','350','250'), ('P07975','LYCRA
TOPS','5','PIECE','70','30','300','175'), ('P08865','SKIRTS','5','PIECE','75','30','450','300');
Query OK, 9 rows affected (0.02 sec)
Records: 9 Duplicates: 0 Warnings: 0

```

```

mysql> SELECT *FROM PRODUCT_MASTER;
+-----+-----+-----+-----+-----+-----+-----+

```

```

-+
| PRODUCT_NO | DESCRIPTION | PROFIT_PERSCENT | UNIT_MEASURE |
QTY_ON_HAND | REORDER_LVL | SELL_PRICE | COST_PRICE |
+-----+-----+-----+-----+-----+-----+-----+-----+
-+
| P0001 | T-SHIRTS | 5.00 | PIECE | 200 | 50 | 350.00 |
250.00 |
| P0345 | SHIRTS | 6.00 | PIECE | 150 | 50 | 500.00 |
350.00 |
| P06734 | COTTON JEANS | 5.00 | PIECE | 100 | 20 | 600.00 |
450.00 |
| P07865 | JEANS | 5.00 | PIECE | 100 | 20 | 750.00 |
500.00 |
| P07868 | TROUSERS | 2.00 | PIECE | 150 | 50 | 850.00 |
550.00 |
| P07885 | PULL OVERS | 2.50 | PIECE | 80 | 30 | 700.00 |
450.00 |
| P07965 | DEIM SHIRTS | 4.00 | PIECE | 100 | 40 | 350.00 |
250.00 |
| P07975 | LYCRA TOPS | 5.00 | PIECE | 70 | 30 | 300.00 |
175.00 |
| P08865 | SKIRTS | 5.00 | PIECE | 75 | 30 | 450.00 |
300.00 |
+-----+-----+-----+-----+-----+-----+-----+-----+
-+
9 rows in set (0.00 sec)

```

```

mysql> INSERT INTO
SALESMAN_MASTER(SALESMAN_NO,SALESMAN_NAME,ADDRESS1,ADDRESS2,CI
TY,PINCODE,STATE,SAL_AMT,TGT_TO_GET,YTD_SALES,REMARKS) VALUES
('S00001','AMAN','A/14','WORLI','MUMBAI','400002','MAHARSHTRA','3000','100','50','GO
OD'),
('S00002','OMKAR','65','NARIMAN','MUMBAI','400001','MAHARSHTRA','3000','200','100','
GOOD'), ('S00003','RAJ','P-
7','BANDRA','MUMBAI','400032','MAHARSHTRA','3000','200','100','GOOD'),
('S00004','ASHISH','A/5','JUHU','MUMBAI','400044','MAHARSHTRA','3000','200','150','GO
OD');
Query OK, 4 rows affected (0.02 sec)
Records: 4 Duplicates: 0 Warnings: 0

```

```

mysql> SELECT *FROM SALESMAN_MASTER;
+-----+-----+-----+-----+-----+-----+-----+-----+
-----+-----+
| SALESMAN_NO | SALESMAN_NAME | ADDRESS1 | ADDRESS2 | CITY | PINCODE
| STATE | SAL_AMT | TGT_TO_GET | YTD_SALES | REMARKS |
+-----+-----+-----+-----+-----+-----+-----+-----+
-----+-----+
| S00001 | AMAN | A/14 | WORLI | MUMBAI | 400002.00 | MAHARSHTRA |
3000.00 | 100.00 | 50.00 | GOOD |
| S00002 | OMKAR | 65 | NARIMAN | MUMBAI | 400001.00 | MAHARSHTRA |

```

3000.00	200.00	100.00	GOOD				
S00003	RAJ	P-7	BANDRA	MUMBAI	400032.00	MAHARSHTRA	
3000.00	200.00	100.00	GOOD				
S00004	ASHISH	A/5	JUHU	MUMBAI	400044.00	MAHARSHTRA	
3000.00	200.00	150.00	GOOD				

4 rows in set (0.00 sec)

```
mysql> insert into SALES_ORDER
(ORDER_NO,CLIENT_NO,ORDER_DATE,DELY_ADDR,SALESMAN_NO,DELY_TYPE,B
ILLYN,DELY_DATE,ORDER_STATUS)
values
('O19001','C00001','04-06-12','NASHIK','S00001','F','N','02-07-20','In Process'),
('O19002','C00002','04-06-25','NASHIK','S00002','P','N','02-06-27','Cancelled'),
('O46865','C00003','04-02-18','NASHIK','S00003','F','Y','02-02-20','Fulfilled'),
('O19003','C00001','04-04-03','NASHIK','S00001','F','Y','02-04-07','Fulfilled'),
('O46866','C00004','04-05-20','NASHIK','S00002','P','N','02-05-22','Cancelled'),
('O19008','C00005','04-05-24','NASHIK','S00004','F','N','02-07-26','In Process');
```

Query OK, 6 rows affected (0.33 sec)  
Records: 6 Duplicates: 0 Warnings: 0

```
mysql> select * from SALES_ORDER;
```

ORDERNO	CLIENTNO	ORDER_DATE	DELY_ADDR	SALESMANNO	DELYTYPE	BILLYN	DELYDATE	ORDERSTATUS
O19001	C00001	2004-06-12	NASHIK	S00001	F	N	2002-07-20	In Process
O19002	C00002	2004-06-25	NASHIK	S00002	P	N	2002-06-27	Cancelled
O19003	C00001	2004-04-03	NASHIK	S00001	F	Y	2002-04-07	Fulfilled
O19008	C00005	2004-05-24	NASHIK	S00004	F	N	2002-07-26	In Process
O46865	C00003	2004-02-18	NASHIK	S00003	F	Y	2002-02-20	Fulfilled
O46866	C00004	2004-05-20	NASHIK	S00002	P	N	2002-05-22	Cancelled

6 rows in set (0.00 sec)

```
mysql> insert into SALES_ORDER_DETAILS
(ORDER_NO,PRODUCT_NO,QTY_ORDERED,QTY_DISP,PRODUCT_RATE)
values
('O19001','P0001','4','4','525'),
('O19001','P07965','2','1','8400');
```

```
( 'O19001','P07885','2','1','5250'),
( 'O19002','P0001','10','0','525'),
( 'O46865','P07868','3','3','3150'),
( 'O46865','P07885','3','1','5250'),
( 'O46865','P0001','10','10','525'),
( 'O46865','P0345','4','4','1050'),
( 'O19003','P0345','2','2','1050'),
( 'O19003','P06734','1','1','12000'),
( 'O46866','P07965','1','0','8400'),
( 'O46866','P07975','1','0','1050'),
( 'O19008','P0001','10','5','525'),
( 'O19008','P07975','5','3','1050');
```

```
mysql> select * from SALES_ORDER_DETAILS;
```

```
+-----+-----+-----+-----+-----+
| ORDERNO | PRODUCTNO | QTYORDERED | QTYDISP | PRODUCTRATE |
+-----+-----+-----+-----+-----+
| O19001 | P0001 | 4 | 4 | 525.00 |
| O19001 | P07965 | 2 | 1 | 8400.00 |
| O19001 | P07885 | 2 | 1 | 5250.00 |
| O19002 | P0001 | 10 | 0 | 525.00 |
| O46865 | P07868 | 3 | 3 | 3150.00 |
| O46865 | P07885 | 3 | 1 | 5250.00 |
| O46865 | P0001 | 10 | 10 | 525.00 |
| O46865 | P0345 | 4 | 4 | 1050.00 |
| O19003 | P0345 | 2 | 2 | 1050.00 |
| O19003 | P06734 | 1 | 1 | 12000.00 |
| O46866 | P07965 | 1 | 0 | 8400.00 |
| O46866 | P07975 | 1 | 0 | 1050.00 |
| O19008 | P0001 | 10 | 5 | 525.00 |
| O19008 | P07975 | 5 | 3 | 1050.00 |
+-----+-----+-----+-----+-----+
```

```
14 rows in set (0.00 sec)
```

```
*****
```

### C) EXERCISE ON ALTERING THE TABLE STRUCTURE.

```
*****
```

**1) Add column called 'Telephone' of data type 'number' and size '10' to the 'CLIENT\_MASTER' table.**

```
mysql> alter table CLIENT_MASTER add TELEPHONE integer(10);
```

```
Query OK, 6 rows affected (0.58 sec)
```

```
Records: 6 Duplicates: 0 Warnings: 0
```

```
mysql> DESC CLIENT_MASTER;
```

```
+-----+-----+-----+-----+-----+
| Field | Type | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+
| CLIENT_NO | varchar(6) | NO | PRI | | |
| NAME | varchar(20) | YES | | NULL | |
| ADDRESS1 | varchar(30) | YES | | NULL | |
```

```
| ADDRESS2 | varchar(30) | YES | | NULL | |
| CITY | varchar(15) | YES | | NULL | |
| PINCODE | int(8) | YES | | NULL | |
| STATE | varchar(15) | YES | | NULL | |
| BAL_DUE | float(10,2) | YES | | NULL | |
| TELEPHONE | int(10) | YES | | NULL | |
+-----+-----+-----+-----+-----+
9 rows in set (0.01 sec)
```

---

## 2) Change the size of SellPrice column in PRODUCT\_MASTER to 10,2.

```
mysql> alter table PRODUCT_MASTER modify column SELL_PRICE float (10,2);
Query OK, 9 rows affected (0.52 sec)
Records: 9 Duplicates: 0 Warnings: 0
```

```
mysql> DESC PRODUCT_MASTER;
+-----+-----+-----+-----+-----+
| Field | Type | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+
| PRODUCT_NO | varchar(6) | NO | PRI | | |
| DESCRIPTION | varchar(15) | NO | | NULL | |
| PROFIT_PERSCENT | float(4,2) | NO | | NULL | |
| UNIT_MEASURE | varchar(10) | NO | | NULL | |
| QTY_ON_HAND | int(8) | NO | | NULL | |
| REORDER_LVL | int(8) | NO | | NULL | |
| SELL_PRICE | float(10,2) | YES | | NULL | |
| COST_PRICE | float(8,2) | NO | | NULL | |
+-----+-----+-----+-----+-----+
8 rows in set (0.00 sec)
```

---

## 3) Destroy the table CLIENT\_MASTER along with its data.

```
Mysql> DROP TABLE CLIENT_MASTER;

mysql> desc CLIENT_MASTER;
ERROR 1146 (42S02): Table 'ASS_1_to_4.CLIENT_MASTER' doesn't exist
```

---

## 4) Change the name of the SALESMAN\_MASTER to SMAN\_MAST.

```
mysql> rename table SALESMAN_MASTER to Sman_mast;
Query OK, 0 rows affected (0.04 sec)
```

```
mysql> show tables;
+-----+
```



```
| Tables_in_ASS_1_to_4 |
+-----+
| CLIENT_MASTER      |
| PRODUCT_MASTER     |
| SALES_ORDER        |
| SALES_ORDER_DETAILS |
| Sman_mast          |
+-----+
5 rows in set (0.00 sec)
```

---

#### D) Write appropriate SQL statements for the following:

---

**1) Create a simple index idx\_Prod on product cost price from the Product Master Table.**

```
mysql> CREATE INDEX idx_Prod ON PRODUCT_MASTER (COST_PRICE);
Query OK, 0 rows affected (0.17 sec)
Records: 0 Duplicates: 0 Warnings: 0
```

```
mysql> show index from PRODUCT_MASTER;
```

```
+-----+-----+-----+-----+-----+-----+-----+-----+
---+---+-----+-----+-----+
| Table      | Non_unique | Key_name | Seq_in_index | Column_name | Collation | Cardinality | Sub_part | Packed | Null | Index_type | Comment | Index_comment |
+-----+-----+-----+-----+-----+-----+-----+-----+
---+---+-----+-----+-----+
| PRODUCT_MASTER | 0 | PRIMARY | 1 | PRODUCT_NO | A | 9 |
| NULL | NULL | | BTREE | | | |
| PRODUCT_MASTER | 1 | idx_Prod | 1 | COST_PRICE | A | 9 |
| NULL | NULL | | BTREE | | | |
+-----+-----+-----+-----+-----+-----+-----+-----+
---+---+-----+-----+-----+
2 rows in set (0.00 sec)
```

---

**2) Create View on Order\_No, Order\_Date, Order\_Status of the sales\_order table and productNo. ProductRate and QTYOrdered of Sales\_Order\_Details.**

```
mysql> CREATE VIEW vw_Sal_Ord AS
-> SELECT s.ORDER_NO, s.ORDER_DATE, sod.PRODUCT_NO,
sod.PRODUCT_RATE, sod.QTY_ORDERED, s.ORDER_STATUS -> FROM
SALES_ORDER s, SALES_ORDER_DETAILS sod WHERE s.ORDER_NO =
sod.ORDER_NO;
Query OK, 0 rows affected (0.08 sec)
```

```
mysql> desc vw_Sal_Ord;
```

Field	Type	Null	Key	Default	Extra
ORDER_NO	varchar(6)	NO		NULL	
ORDER_DATE	date	NO		NULL	
PRODUCT_NO	varchar(6)	YES		NULL	
PRODUCT_RATE	float(10,2)	YES		NULL	
QTY_ORDERED	int(8)	YES		NULL	
ORDER_STATUS	varchar(10)	YES		NULL	

6 rows in set (0.00 sec)

mysql> select \* FROM vw\_Sal\_Ord;

ORDER_NO	ORDER_DATE	PRODUCT_NO	PRODUCT_RATE	QTY_ORDERED	ORDER_STATUS
O19001	2004-06-12	P0001	525.00	4	In Process
O19001	2004-06-12	P07965	8400.00	2	In Process
O19001	2004-06-12	P07885	5250.00	2	In Process
O19002	2004-06-25	P0001	525.00	10	Cancelled
O19003	2004-04-03	P0345	1050.00	2	Fulfilled
O19003	2004-04-03	P06734	12000.00	1	Fulfilled
O19008	2004-05-24	P0001	525.00	10	In Process
O19008	2004-05-24	P07975	1050.00	5	In Process
O46865	2004-02-18	P07868	3150.00	3	Fulfilled
O46865	2004-02-18	P07885	5250.00	3	Fulfilled
O46865	2004-02-18	P0001	525.00	10	Fulfilled
O46865	2004-02-18	P0345	1050.00	4	Fulfilled
O46866	2004-05-20	P07965	8400.00	1	Cancelled
O46866	2004-05-20	P07975	1050.00	1	Cancelled

14 rows in set (0.00 sec)

---

**3) Create a Sequence inv\_seq with the following parameters. Increment by 3, cache 4 and which generates the number from 1 to 9999 in ascending order.**