```
import datetime

# Simulated security event logs mirroring our VirtualBox lab traffic
# Between Kali (192.168.56.101) and Windows (192.168.56.102)
lab_telemetry_logs = [
    ("192.168.56.101", "192.168.56.102", "ICMP_PING", 14, "NORMAL"),
    ("192.168.56.101", "192.168.56.102", "ICMP_PING", 14, "NORMAL"),
    ("192.168.56.101", "192.168.56.102", "TCP_PORT_SCAN_PORT_135", 2, "SUSPICIOUS"),
    ("192.168.56.101", "192.168.56.102", "TCP_BRUTE_FORCE", 3, "HIGH_RISK"),
    ("192.168.56.101", "192.168.56.102", "TCP_BRUTE_FORCE", 3, "HIGH_RISK")
]

print("="*65)
print("   VIRTUALBOX LAB: AI-AUGMENTED THREAT MODEL & LOG ANALYZER")
print("="*65)
print(f"[*] Analyzing lab packet telemetry between Kali and Windows...\n")

total_alerts = 0

for src, dest, action, hour, baseline_status in lab_telemetry_logs:
    threat_score = 0
    indicators = []

    # Rule 1: Flag odd-hour activities (Nighttime testing)
    if hour < 6 or hour > 22:
        threat_score += 3
        indicators.append(f"Off-hours execution ({hour}:00)")

    # Rule 2: Flag aggressive scanning or brute forcing
    if action in ["TCP_PORT_SCAN_PORT_135", "TCP_BRUTE_FORCE"]:
        threat_score += 3
        indicators.append(f"Signature match: {action}")

    # Evaluate against automated threshold
    if threat_score >= 4:
        total_alerts += 1
        print(f"[!] SECURITY ALERT (Risk Score: {threat_score}) | Source: {src} -> Target: {dest}")
        print(f"    └─ Indicators: {', '.join(indicators)}")
    else:
        print(f"[-] Baseline Event Logged (Normal Traffic): {action} from {src}")

print("\n" + "="*65)
print(f"Analysis Complete. Events Processed: {len(lab_telemetry_logs)} | Critical Alerts:
{total_alerts}")
```

```
print("="*65)
```