


# Assignment 2

## Implementation Report for Shortest Path Finding Program

### Results:



Algorithm	Dijkstaras	A*	WA e=2	WA e=3	WA e=4	WA e=5
Final Cost	30.1421	30. 1421	31.7990	31.7990	31.7990	31.7990
Iteration	562	363	173	145	149	141

### Files

- **input.txt:** Contains details about the graph (number of vertices, starting and target vertices).
- **coords.txt:** Holds the coordinates of graph vertices.
- **FormattedInput.txt:** Contains organized input data.
- **output.txt:** The output file where results are stored.

### 1. Input Processing

- Reads **input.txt** to get important details like the number of vertices, starting point, and target point.

### 2. Coordinate Handling

- Takes coordinates from **coords.txt** and stores them for later use in plotting.

### 3. Graph Initialization

- Sets up the graph structure and fills it with edges from **FormattedInput.txt**.

### 4. Dijkstra's Algorithm

- The program employs this algorithm to find the shortest path from the starting point to all other points.

### 5. Weighted A\* Algorithm

- Offers an alternative algorithm that can be influenced by different weightings.

### 6. Heuristic Dictionary

- Calculates heuristic distances for the Weighted A\* algorithm.

### 7. Plotting and Visualization

- Uses **matplotlib** to create visual representations of the graph and algorithm steps.

### 8. Output File Generation

- Adds results to **output.txt**, including the path and distances.

### Running the Program

- Make sure **input.txt**, **FormattedInput.txt**, **coords.txt**, and **output.txt** are available.
- Run the program to see the algorithms in action.
- The output will be saved in **output.txt**.

### Usage Examples

- This program is great for learning about graphs and algorithms. You can experiment with different setups to see how the algorithms behave.

### Conclusion

This Python program provides an easy-to-follow demonstration of two methods for finding the shortest path in a graph. The combination of clear visuals and detailed output makes it a valuable learning tool.

### Dijkstra's Algorithm (dijkstra)

Function Signature

```
def dijkstra(self, start):
```

Description

This function implements Dijkstra's algorithm to find the shortest path from a given starting vertex to all other vertices in the graph.

#### Parameters

- **self**: Refers to the current instance of the **Graph** class.
- **start**: The starting vertex for the algorithm.

#### Returns

- **dist**: A dictionary containing the shortest distances from the starting vertex to all other vertices.
- **parent**: A dictionary containing the parent vertices that lead to the shortest path.

#### Shortest Path with Distances (`shortest_path_with_distances`)

##### Function Signature

```
def shortest_path_with_distances(self, start, end, parent):
```

##### Description

This function calculates the shortest path and distances from the starting vertex to the target vertex using the parent vertices obtained from Dijkstra's algorithm.

#### Parameters

- **self**: Refers to the current instance of the **Graph** class.
- **start**: The starting vertex.
- **end**: The target vertex.
- **parent**: A dictionary containing the parent vertices obtained from Dijkstra's algorithm.

#### Returns

- **path**: A list representing the shortest path from the starting vertex to the target vertex.
- **distances\_between**: A dictionary containing distances between vertices in the shortest path.

#### Weighted A\* Algorithm (`weighted_a_star`)

##### Function Signature

```
def weighted_a_star(self, start, weight=1):
```

##### Description

This function implements the weighted A\* algorithm to find the shortest path from a given starting vertex to all other vertices in the graph. It allows for the influence of different weights on the search process.

#### Parameters

- **self**: Refers to the current instance of the **Graph** class.
- **start**: The starting vertex for the algorithm.
- **weight**: A multiplier influencing the heuristic function (default is 1).

## Returns

- **dist:** A dictionary containing the shortest distances from the starting vertex to all other vertices.
- **parent:** A dictionary containing the parent vertices that lead to the shortest path.