

ITC LIMITED - PAPER BOARDS AND SPECIALTY PAPERS DIVISION UNIT :- BOLLARAM

SPECIFICATION SHEET

Grade Name: INDO BEV 2 PE SPEC NO: 2 BV/TXG/PSPD/BOL/PE

Grade Id: 2 BV/ 2 PV Format No: QISD/SPEC/02

SUBSTANCE (GSM)	CALIPER (µM)	BENDING RESISTANCE(L&W) mN		
		Tappi T 556		
Tappi T 410 om-98	Tappi T 411 om-97	MD	CD	GM
197	225	92	21	44
200	228	94	23	46
202	230	95	26	50
210	239	104	33	59
212	242	105	35	61
217	247	107	38	64
230	262	123	54	81
232	264	124	55	83
240	274	134	63	92
242	276	135	64	93
250	285	144	74	103
252	287	145	75	104
TOL: ±5%	± 5%		·	± 15%

PARAMETER	UNITS	VALUE
POLY SUBSTANCE	GSM	
TOP		10±1.5
		12±1.5
BACK		10±1.5
		12±1.5
		15±1.5
TAPPI T 480 om-96		
SMOOTHNESS (Bendsten)	ML/MIN	
TOP		MAX 250
BACK		MAX 500
ISO 8791-2		
SURFACE TENSION	Dynes/cm	
TOP		Min 38
TAPPI T 412 om-94		
MOISTURE	%	
Tappi T 412		5.0-6.0
STRETCH	%	
MD		2.5 MIN
CD		5.5 MIN
Tappi T 494 om-96		
EDGEWICK - LA/23	Kg/m²/Hour	1.2 MAX
TP84010		

Construction PE Coated (Gloss) Surface sized Bleached chemical pulp Bleached chemical pulp Surface sized PE Coated (Matt)

Note:

- 1.) All Properties are according to ITC Limited, PSPD Unit:BOL Measurements
- 2.) Test Climate 23°C ± 1 & 50% ± 2 RH
- 3.) Tolerances are based upon 95% Confidence limits of single mill measurements of conditioned random samples