

ITC LIMITED - PAPERBOARDS AND SPECIALTY PAPERS DIVISION UNIT :- BOLLARAM

SPECIFICATION SHEET

Grade Name : ART MAESTRO SPEC NO : AM/AMB/PSPD/BOL/SC

Grade Id: AM/AMC Format No: QISD/SPEC/02

SUBSTANCE (GSM)	CALIPER (μM)	BENDING RESISTANCE(L&W) mN		
		Tappi T556		
Tappi T 410	Tappi T 411	MD	CD	GM
200	188	49	25	35
210	197	59	29	41
220	207	69	34	48
230	216	78	39	55
250	235	108	54	76
260	244	118	59	83
270	254	137	69	97
275	259	142	71	100
280	263	147	74	104
285	268	157	78	111
300	282	177	88	125
310	291	191	98	137
320	301	226	108	156
330	310	245	123	174
350	329	294	147	208
380	357	334	167	236
400	376	353	177	250
TOL: ±5%	± 5%			-15%

PARAMETER		UNITS	VALUE
ROUGHNESS - BENDSTEN	١	ml/min	
(Avg.)	TOP		50 MAX
E	BACK		100 MAX
ISO 8791-2			
BRIGHTNESS ISO		%	
TOP & E	BACK		90 MIN
ISO 2469			
WHITENESS CIE		%	
TOP & E	BACK		110 MIN
Tappi T 560			
SURFACE STRENGTH		m/sec	
IGT PICK (MED.VISCOSITY	′)		
TOP & E	BACK		0.7 MIN
ISO 3782 & 3783			
GLOSS AT 60°		%	
(Avg.)	TOP		15 MIN
E	BACK		10 MIN
Tappi T 480			
MOISTURE		%	
Tappi T 412	1		5.0 - 8.0

CONSTRUCTION



Note:

- 1.) All Properties are according to ITC Limited, PSPD Unit:BOL Measurements
- 2.) Test Climate 23°C ± 1 & 50% ± 2 RH
- 3.) Tolerances are based upon 95% Confidence limits of single mill measurements of conditioned random samples