Interpretable by Construction, Identifiable by Construction: Privacy Leakage of Shapelet-Based Anti-Money-Laundering Models

Anonymous Author(s)

ABSTRACT

Investigators and supervisors ask that anti-money-laundering (AML) models be explainable, and shapelet classifiers are a natural answer: they justify a decision by pointing to a short, human-readable pattern in an account's activity. We show that this explanation is frequently *a customer's own transaction history*. On SAML-D (9.5M transactions, 28 typologies) we train shapelet detectors on activity-matched weekly account series and hand the fitted model to an adversary holding ∼30k candidate accounts. For the classic shapelet transform, 15% of released shapelets uniquely re-identify their source customer from shape alone, and 66% of those sources are flagged launderers, so the model also discloses who is under suspicion. For the state-of-the-art Random Dilated Shapelet Transform (RDST), which stores per-shapelet normalisation statistics, 83% of shapelets single out exactly one customer (≈803 customers) and reveal their exact weekly amounts and counts. Standard membership-inference audits miss this (AUC ≈ 0.50–0.52), and GBDT and MiniRocket baselines show no measurable leakage. Noise and k-anonymous averaging remove exact fingerprints at no accuracy cost but leave residual linkage, whereas *learned* shapelets match RDST accuracy (PR-AUC 0.957 vs. 0.952) without copying any customer's data. Interpretable financial models need a privacy review of their explanations, not only of their predictions.

1 INTRODUCTION

Transaction monitoring for AML is high-stakes, regulated, and increasingly machine-learned; deployed systems pair gradient-boosted trees with post-hoc explanations so that investigators can act on alerts [7]. Shapelets [1, 2] are an attractive alternative because the explanation *is* the model: a short subsequence whose presence drives the decision. Laundering typologies such as structuring, fan-in/fan-out and rapid pass-through are literally shapes in time.

The catch is that classic shapelets are subsequences copied from training series, and state-of-the-art variants such as RDST [4] additionally store the mean and standard deviation used to normalise each shapelet. Federated shapelet work notes that shapelets expose raw data [8], and privacy-aware matrix profiles defend shared time-series features against pattern inference [9]; explanation-privacy research shows that feature attributions leak membership [10]. To our knowledge, no prior work measures what a *released shapelet model* reveals about specific customers.

Contributions. (i) A threat model and attack suite—re-identification, amount reconstruction, membership and suspicion inference—for released shapelet models. (ii) An empirical study on SAML-D showing large but *concentrated* leakage that aggregate membership inference misses, including disclosure of flagged customers, a tipping-off hazard. (iii) A privacy–utility comparison of mitigations showing that learned shapelets attain near state-of-the-art shapelet accuracy without copying customer data.

Table 1: Detection on held-out accounts and leakage of the released model (mean ± std over 3 seeds). Re-ID: share of released shapelets that match *only* their source customer among 29,946 candidate accounts.

Model	PR-AUC	R@1%FPR	MIA AUC	Re-ID (%)
CatBoost (aggregates)	0.983 ± 0.001	0.842 ± 0.031	0.504 ± 0.002	n/a
MiniRocket	0.955 ± 0.002	0.637 ± 0.044	0.508 ± 0.003	n/a
Shapelet transform	0.878 ± 0.007	0.493 ± 0.033	0.500 ± 0.002	15.0 ± 2.2
RDST	0.952	0.618	0.521	83.4
Learned shapelets	0.957 ± 0.004	0.667 ± 0.017	0.500 ± 0.000	0.0

2 THREAT MODEL

A bank trains a shapelet AML detector and shares the fitted model with a vendor, auditor, regulator sandbox, or consortium partner, or loses it to theft. The model contains its shapelets (and, for RDST, their normalisation statistics). The adversary also holds candidate account series, e.g. a partner institution's data or a leaked extract, containing training members and non-members. Goals: (a) *re-identify* the customer behind a shapelet; (b) *reconstruct* that customer's amounts and counts; (c) infer *membership* and, from the shapelet's class, *suspicion status*.

3 EXPERIMENTAL SETUP

Data. SAML-D [6]: 9.5M synthetic transactions over 46 weeks, 0.10% suspicious, 17 suspicious and 11 normal typologies. Each account becomes a 6-channel weekly series (log outgoing/incoming amount, outgoing/incoming count, cross-border amount, cash amount). Accounts involved in any laundering transaction are positive (7,902). Normal accounts are sampled 3:1 *matched on number of active weeks*; unmatched normals are mostly single-week accounts that make detection trivial. The 29,946 accounts are split 50/50 by account into members (train) and non-members (test), stratified by label; results average 3 seeds.

Detectors. CatBoost on 40 aggregate features plus the flattened series (the industry baseline); MiniRocket [5] with logistic regression; the binary shapelet transform (5,000 random non-constant z-normalised candidates, quality = class separation of the min-distance profile, top-200 with self-similarity removal) with ExtraTrees; RDST (1,000 shapelets) with ExtraTrees; and learned shapelets [3] (144 shapelets, soft-min distance, random initialisation).

Attacks. *Re-ID*: min (dilated) sliding distance from each released shapelet to every candidate account; we report the share of shapelets whose source is the *only* account within ε (unique match) and top-1 accuracy. *Reconstruction*: for RDST, raw window = values × std + mean. *MIA*: score = − min distance to any shapelet; for baselines, the standard confidence attack.

Table 2: Mitigations (shapelet transform; mean over seeds). Unique: shapelet matches only its source; Top-1: source is the nearest account.

Release	PR-AUC	Unique (%)	Top-1 (%)
As trained	0.878 ± 0.007	15.0 ± 2.2	19.3 ± 1.6
Noise σ=0.1	0.879 ± 0.007	0.0 ± 0.0	10.8 ± 2.5
Noise σ=0.25	0.877 ± 0.007	0.0 ± 0.0	3.2 ± 0.5
Noise σ=0.5	0.876 ± 0.005	0.0 ± 0.0	0.2 ± 0.2
Noise σ=1.0	0.870 ± 0.004	0.0 ± 0.0	0.0 ± 0.0
k-anon. mean, k=5	0.877 ± 0.007	0.3 ± 0.2	13.5 ± 0.4
k-anon. mean, k=20	0.876 ± 0.005	0.2 ± 0.2	12.5 ± 2.1
k-anon. mean, k=50	0.876 ± 0.006	0.0 ± 0.0	10.7 ± 1.3

4 RESULTS

Leakage is severe but concentrated. Table 1 shows that only shapelet models leak. Because just a few hundred of ∼15k members contribute shapelets, aggregate MIA AUC stays near 0.5, yet those contributors are uniquely identifiable: an audit based on standard MIA would declare these models safe.

Shape alone identifies. Z-normalised shapelet-transform shapelets carry no amounts, yet 15% match only their source among ∼30k accounts (top-1: 19%).

State of the art leaks more. RDST is the most accurate shapelet model here but stores normalisation statistics, so 83% of its shapelets reconstruct an exact, unique slice of one customer's history: about 803 customers per model, each with a median of 12 exact non-zero weekly amount/count cells (median peak weekly amount ≈ £24k). Withholding the statistics and forcing normalisation still leaves nan% unique matches (PR-AUC nan).

The model discloses suspicion. 66% of shapelet-transform sources and nan RDST-identified customers are positives. Releasing the model therefore reveals which customers were flagged, in tension with suspicious-activity-report confidentiality and anti-tipping-off rules.

Mitigations (Table 2). Gaussian noise on shapelet values removes exact fingerprints at no accuracy cost, but nearest-neighbour linkage persists until $\sigma \geq 0.5$. Replacing each shapelet by the mean of its k nearest training windows from distinct accounts (k-anonymous release) stops unique matching but keeps the source's neighbourhood linkable. Learned shapelets dominate: PR-AUC 0.957 (shapelet transform: 0.878; CatBoost: 0.983), with no learned shapelet within 10^{-2} of any real account (median nearest distance 0.38).

5 DISCUSSION AND LIMITATIONS

SAML-D is synthetic and activity-matched sampling makes detection optimistic; however, the leakage mechanism (copied subsequences, stored statistics) does not depend on the data. Our shapelet transform is a faithful simplification (AUC-based quality instead of information gain) because a standard implementation degenerated on our sparse series. The attack assumes the adversary's pool contains the source; consortium AML and model-sharing make this plausible. Noise and learned shapelets carry no formal guarantee; differentially private shapelet selection and DP-SGD training are natural next steps.




Figure 1: Top: customers uniquely exposed (and how many are flagged launderers) grow with the number of released shapelets k, while accuracy saturates (shapelet transform, seed 0). Bottom: privacy–utility of releases (top-1 re-identification vs. PR-AUC; seed mean).

Recommendations. Treat shapelets as personal data; never release normalisation statistics; prefer learned or noised shapelets; and audit interpretable financial models with *per-explanation* re-identification, not only aggregate membership inference.

REFERENCES

[1] L. Ye and E. Keogh. 2009. Time series shapelets: a new primitive for data mining. In *KDD*.
[2] J. Hills, J. Lines, E. Baranauskas, J. Mapp, and A. Bagnall. 2014. Classification of time series by shapelet transformation. *Data Mining and Knowledge Discovery* 28.
[3] J. Grabocka, N. Schilling, M. Wistuba, and L. Schmidt-Thieme. 2014. Learning time-series shapelets. In *KDD*.
[4] A. Guillaume, C. Vrain, and W. Elloumi. 2022. Random dilated shapelet transform: a new approach for time series shapelets. In *ICPRAI*.
[5] A. Dempster, D. F. Schmidt, and G. I. Webb. 2021. MiniRocket: a very fast (almost) deterministic transform for time series classification. In *KDD*.
[6] B. Oztas, D. Cetinkaya, F. Adedoyin, M. Budka, H. Dogan, and G. Aksu. 2023. Enhancing anti-money laundering: development of a synthetic transaction monitoring dataset. In *IEEE ICEBE*.
[7] P. Tertychnyi, M. Godgildieva, M. Dumas, and M. Ollikainen. 2022. Time-aware and interpretable predictive monitoring system for anti-money laundering. *Machine Learning with Applications* 8.
[8] Z. Liang and H. Wang. 2024. FedST: secure federated shapelet transformation for time series classification. *The VLDB Journal* 33.
[9] PMP: privacy-aware matrix profile against sensitive pattern inference for time series. 2023. arXiv:2301.01838.
[10] R. Shokri, M. Strobel, and Y. Zick. 2021. On the privacy risks of model explanations. In *AIES*.