

CREATING A FORM USING HTML5

<p> Gautam Mukherjee </p>



Forms x



HTML FORMS

- An HTML form is used to collect user input. The user input is most often sent to a server for processing.





Forms x



FORM ELEMENT

- The `HTML <form> element` is used to create an HTML form for user input:
- The `<form>` element is a container for different types of input elements, such as: text fields, checkboxes, radio buttons, submit buttons, etc.






Forms

Input x

INPUT ELEMENT

- The HTML `<input>` element is the most used form element.
- An `<input>` element can be displayed in many ways, depending on the type attribute.





INPUT ELEMENT

Type	Description
<code><input type="text"></code>	Displays a single-line text input field
<code><input type="radio"></code>	Displays a radio button (for selecting one of many choices)
<code><input type="checkbox"></code>	Displays a checkbox (for selecting zero or more of many choices)
<code><input type="submit"></code>	Display a submit button (for submitting the form)
<code><input type="button"></code>	Displays a clickable button



TEXT FIELDS

- The `<input type="text">` defines a single-line input field for text input.

- Example code:

```
<form>
```

```
  <label for="fname">First name:</label><br>
```

```
    <input type="text" id="fname" name=""><br>
```

```
  <label for="lname">Last name:</label><br>
```

```
    <input type="text" id="lname" name="">
```

```
</form>
```





LABEL ELEMENT

- The `<label>` tag defines a label for many form elements.
- The `<label>` element is useful for screen-reader users, because the screen-reader will read out loud the label when the user focuses on the input element.





LABEL ELEMENT

- The `<label>` element also helps users who have difficulty clicking on very small regions (such as radio buttons or checkboxes) - because when the user clicks the text within the `<label>` element, it toggles the radio button/checkbox.
- The for attribute of the `<label>` tag should be equal to the id attribute of the `<input>` element to bind them together.





RADIO **BUTTONS**

- The `<input type="radio">` defines a radio button.
- Radio buttons let a user select ONE of a limited number of choices.





RADIO **BUTTONS**

● Example code:

```
<form>
```

```
  <input type="radio" id="boy" name="select">
```

```
  <label for="boy">Boy</label><br>
```

```
  <input type="radio" id="girl" name="select">
```

```
  <label for="girl">Girl</label><br>
```

```
</form>
```





CHECKBOXES

- The `<input type="checkbox">` defines a checkbox.
- Checkboxes let a user select ZERO or MORE options of a limited number of choices.





CHECKBOXES

- Example code:

```
<form>
```

```
<input type="checkbox" id="vehicle1" name="vehicle1">
```

```
<label for="vehicle1"> I have a bike</label><br>
```

```
<input type="checkbox" id="vehicle2" name="vehicle2">
```

```
<label for="vehicle2"> I have a car</label><br>
```

```
<input type="checkbox" id="vehicle3" name="vehicle3">
```

```
<label for="vehicle3"> I have a boat</label>
```

```
</form>
```





SUBMIT **BUTTON**

- The `<input type="submit">` defines a button for submitting the form data to a form-handler.
- The form-handler is typically a file on the server with a script for processing input data.
- The form-handler is specified in the form's action attribute.





SUBMIT **BUTTON**

● Example code:

```
<form action="">
  <label for="fname">First name:</label><br>
  <input type="text" id="fname" name=""><br>
  <label for="lname">Last name:</label><br>
  <input type="text" id="lname" name=""><br><br>
  <input type="submit" value="Submit">
</form>
```





NAME ATTRIBUTE FOR INPUT

- Notice that each input field must have a name attribute to be submitted.
- If the name attribute is omitted, the value of the input field will not be sent at all.





SELECT ELEMENT

- The `<select>` element defines a drop-down list:
- Example code:

```
<label>Choose a car:</label>
```

```
<select>
```

```
  <option>Volvo</option>
```

```
  <option>Saab</option>
```

```
  <option>Fiat</option>
```

```
  <option>Audi</option>
```

```
</select>
```





OPTION ELEMENT

- The `<option>` element defines an option that can be selected.
- By default, the first item in the drop-down list is selected.
- To define a pre-selected option, add the selected attribute to the option:
- Example code:

```
<option value="fiat" selected>Fiat</option>
```





SIZE ATTRIBUTE

- Use the size attribute to specify the number of visible values:

- Example code:

```
<label for="cars">Choose a car:</label>
<select id="cars" name="cars" size="3">
  <option value="volvo">Volvo</option>
  <option value="saab">Saab</option>
  <option value="fiat">Fiat</option>
  <option value="audi">Audi</option>
</select>
```





TEXTAREA ELEMENT

- The `<textarea>` element defines a multi-line input field (a text area):
- Example code:

```
<textarea name="" rows="10" cols="30"></textarea>
```





BUTTON ELEMENT

- The `<button>` element defines a clickable button:

- Example code:

```
<button type="button" onclick="alert('Hello World!')">Click  
Me!</button>
```





FIELDSET AND LEGEND ELEMENT

- The `<fieldset>` element is used to group related data in a form.
- The `<legend>` element defines a caption for the `<fieldset>` element.





FIELDSET AND LEGEND ELEMENT

● Example code:

```
<form action="">
  <fieldset>
    <legend>Name:</legend>
    <label for="fname">First name:</label><br>
    <input type="text" id="fname" name="fname"><br>
    <label for="lname">Last name:</label><br>
    <input type="text" id="lname" name="lname"><br>
  <br>
  <input type="submit" value="Submit">
  </fieldset>
</form>
```





DATALIST ELEMENT

- The `<datalist>` element specifies a list of pre-defined options for an `<input>` element.
- Users will see a drop-down list of the pre-defined options as they input data.
- The list attribute of the `<input>` element, must refer to the id attribute of the `<datalist>` element.





DATALIST ELEMENT

● Example code:

```
<form action="">
  <input list="Philippines">
  <datalist id="Philippines">
    <option value="Manila">
    <option value="Cebu">
    <option value="Davao">
    <option value="Palawan">
    <option value="Batanes">
  </datalist>
</form>
```





INPUT TYPE **PASSWORD**

- `<input type="password">` defines a password field:

- Example code:

```
<form>
  <label for="username">Username:</label><br>
  <input type="text" id="username" name=""><br>
  <label for="pwd">Password:</label><br>
  <input type="password" id="pwd" name="">
</form>
```





INPUT TYPE **RESET**

- `<input type="reset">` defines a reset button that will reset all form values to their default values:
- Example code:

```
<input type="reset" value="Reset">
```





INPUT TYPE **DATE**

- The `<input type="date">` is used for input fields that should contain a date.
- Depending on browser support, a date picker can show up in the input field.
- Example code:

```
<form>  
  <label for="birthday">Birthday:</label>  
  <input type="date" id="birthday" name="">  
</form>
```



INPUT TYPE EMAIL

- The `<input type="email">` is used for input fields that should contain an e-mail address.
- Depending on browser support, the e-mail address can be automatically validated when submitted.
- Some smartphones recognize the email type, and add ".com" to the keyboard to match email input.





INPUT TYPE **FILE**

- The `<input type="file">` defines a file-select field and a "Browse" button for file uploads.

- Example code:

```
<form>  
  <label for="myfile">Select a file:</label>  
  <input type="file" id="myfile" name="">  
</form>
```





INPUT TYPE **NUMBER**

- The `<input type="number">` defines a numeric input field.
- You can also set restrictions on what numbers are accepted.
- The following example displays a numeric input field, where you can enter a value from 1 to 5:





INPUT TYPE **NUMBER**

● Example code:

```
<form>  
  <label>Quantity (between 1 and 5):</label>  
  <input type="number" min="1" max="5">  
</form>
```





PLACEHOLDER **ATTRIBUTE**

- The input placeholder attribute specifies a short hint that describes the expected value of an input field (a sample value or a short description of the expected format). The short hint is displayed in the input field before the user enters a value.
- The placeholder attribute works with the following input types: text, search, url, tel, email, and password.





REQUIRED **ATTRIBUTE**

- The input required attribute specifies that an input field must be filled out before submitting the form.
- The required attribute works with the following input types: text, search, url, tel, email, password, date pickers, number, checkbox, radio, and file.





REQUIRED ATTRIBUTE

● Example code:

```
<form>
  <label for="username">Username:</label>
  <input type="text" id="username" name="" required>
</form>
```



`<p>` **THANK YOU**
FOR **WATCHING** `</p>`