

1 What will be the output of the following code snippet?

```
def func(a, b):  
    return b if a == 0 else func(b % a,  
        a)  
print(func(30, 75))
```

- a) 10
- b) 20
- c) 15
- d) 0

Answer: - C) 15

2) numbers = (4, 7, 19, 2, 89, 45, 72, 22)
sorted_numbers = sorted(numbers)
even = lambda a: a % 2 == 0
even_numbers = filter(even, sorted_numbers)
print(type(even_numbers))
a) Int
b) Filter
c) List
d) Tuple

Answer : - b) Filter

3) As what datatype are the *args stored, when passed into
a) Tuple
b) List
c) Dictionary
d) none

Answer : - a) Tuple
4) set1 = {14, 3, 55}
set2 = {82, 49, 62}
set3 = {99, 22, 17}

```
print(len(set1 + set2 + set3))
```

- a) 105
- b) 270
- c) 0
- d) Error

Answer : - d) Error

5) What keyword is used in Python to raise exceptions?
a) raise b) try c) goto d) except

Answer : - a) raise

6) Which of the following modules need to be imported to handle date time computations in Python?
a) timedate b) datec) datetimed)
time

Answer : - d) datetime

7) What will be the output of the following code snippet?
`print(4**3 + (7 + 5)**(1 + 1))`
a) 248
b) 169
c) 208
d) 233

Answer : - c) 208

8) Which of the following functions converts date to corresponding time in Python?
a) strptime
b) strftime
c) both a) and b)
d) None
Answer : - a) strptime

9) The python tuple is in nature.a) mutable
b)immutablec) unchangeabled) none

Answer : - b) immutable

10) The is a built-in function that returns a range object that consists series of integer numbers, which we can iterate using a for loop.A. range()B. set()C. dictionary{}D. None of the mentioned aboveAnswer: - A) range()

11 Amongst which of the following is a function which does not have any name?A. Del functionB. Show functionC. Lambda functionD. None of the mentioned above

Answer: - C) Lamda function

12 The module Pickle is used to .A. Serializing Python object structureB. De-serializing Python object structureC. Both A and BD. None of the mentioned above

Answer: - C) Both A and b

13 Amongst which of the following is / are the method of convert Python objects for writing data in a binary file?A. set() methodB. dump() methodC. load() method d) none of the mentioned above

Answer - b)dump()method

14. Amongst which of the following is / are the method used to unpickling data from a binary file?
A. load()
B. set() method
C. dump()
method
D. None of the mentioned above

Answer: - A) load()

15.A text file contains only textual information consisting of .
A. Alphabets
B. Numbers
C. Special symbols
D. All of the mentioned above

Answer: - D) All of the mentioned above

16Which Python code could replace the ellipsis (...) below to get the following output?
(Select all that apply.)
captains = {"Enterprise": "Picard", "Voyager": "Janeway", "Defiant": "Sisko", }
Enterprise Picard,Voyager JanewayDefiant Siskoa) for ship, captain in captains.items(): print(ship, captain)
b) for ship in captains: print(ship, captains[ship])
c) for ship in captains: print(ship, captains)
d) both a and b

Answer: - d) both a and b

17)Which of the following lines of code will create an empty dictionary named captains?
a) captains = {dict} b) type(captains)c)
captains.dict()d) captains = {}

Answer: - d) captions={}

18) Now you have your empty dictionary named captains.It's time to add some data! Specifically, you want to add the key-value pairs "Enterprise": "Picard", "Voyager": "Janeway",and "Defiant": "Sisko".Which of the following code snippets will successfully add these key-value pairs to theexisting captains dictionary?a) captains{"Enterprise" = "Picard"}captains{"Voyager" = "Janeway"}captains{"Defiant" = "Sisko"} b)
captains["Enterprise"] = "Picard"captains["Voyager"] = "Janeway"captains["Defiant"] = "Sisko"c)
captains = {"Enterprise": "Picard","Voyager": "Janeway","Defiant": "Sisko",}d) None of the above

Answer: - c)captains = {"Enterprise": "Picard","Voyager": "Janeway","Defiant": "Sisko", }

19)You're really building out the Federation Starfleet now!Here's what you have:captains = {"Enterprise": "Picard","Voyager": "Janeway","Defiant": "Sisko","Discovery": "unknown",}Now, say you want to display the ship and captain names contained in the dictionary, but you also want to provide some additional context. How could you do it?a) for item in captains.items(): print(f"The [ship] is captained by [captain].") b) for ship, captain in captains.items(): print(f"The {ship} is captained by {captain}.")c) for captain, ship in captains.items(): print(f"The {ship} is captained by {captain}.")d) All are correct
Answer: - b)for ship, captain in captains.items(): print(f"The{ship} is captained by {captain}.")

20)You've created a dictionary, added data, checked for the existence of keys, and iterated over it with a for loop. Now you're ready to delete a key from this dictionary:captains = {"Enterprise": "Picard","Voyager": "Janeway","Defiant": "Sisko","Discovery": "unknown"}

What statement will remove the entry for the key "Discovery"?
a) del captains
b)
captains.remove()
c) del
captains["Discovery"]
d)
captains["Discovery"].pop()

Answer: - c)del captains["Discovery"]

1 What will be the output of the following code snippet?

```
def func(a, b):  
    return b if a == 0 else func(b % a,  
        a)  
print(func(30, 75))
```

- a) 10
- b) 20
- c) 15
- d) 0

Answer: - C) 15

```
2) numbers = (4, 7, 19, 2, 89, 45, 72,  
22)  
sorted_numbers = sorted(numbers)  
even = lambda a: a % 2 == 0  
even_numbers = filter(even,  
sorted_numbers)  
print(type(even_numbers))
```

- a) Int
- b) Filter
- c) List
- d) Tuple

Answer : - b) Filter

```
3) As what datatype are the *args stored,  
when passed into  
a) Tuple  
b) List  
c) Dictionary  
d) none
```

Answer : - a) Tuple
4) set1 = {14, 3, 55}
set2 = {82, 49, 62}
set3 = {99, 22, 17}

```
print(len(set1 + set2 + set3))
```

- a) 105
- b) 270
- c) 0
- d) Error

Answer : - d) Error

5) What keyword is used in Python to raise exceptions?
a) raise b) try c) goto d) except

Answer : - a) raise

6) Which of the following modules need to be imported to handle date time computations in Python?
a) timedate b) datec) datetimed)
time

Answer : - d) datetime

7) What will be the output of the following code snippet?
`print(4**3 + (7 + 5)**(1 + 1))`
a) 248
b) 169
c) 208
d) 233

Answer : - c) 208

8) Which of the following functions converts date to corresponding time in Python?
a) strptime
b) strftime
c) both a) and b)
d) None
Answer : - a) strptime

9) The python tuple is in nature.a) mutable
b)immutablec) unchangeabled) none

Answer : - b) immutable

10) The is a built-in function that returns a range object that consists series of integer numbers, which we can iterate using a for loop.A. range()B. set()C. dictionary{}D. None of the mentioned aboveAnswer: - A) range()

11 Amongst which of the following is a function which does not have any name?A. Del functionB. Show functionC. Lambda functionD. None of the mentioned above

Answer: - C) Lamda function

12 The module Pickle is used to .A. Serializing Python object structureB. De-serializing Python object structureC. Both A and BD. None of the mentioned above

Answer: - C) Both A and b

13 Amongst which of the following is / are the method of convert Python objects for writing data in a binary file?A. set() methodB. dump() methodC. load() method d) none of the mentioned above

Answer - b)dump()method

14. Amongst which of the following is / are the method used to unpickling data from a binary file?
A. load()
B. set() method
C. dump()
method
D. None of the mentioned above

Answer: - A) load()

15.A text file contains only textual information consisting of .
A. Alphabets
B. Numbers
C. Special symbols
D. All of the mentioned above

Answer: - D) All of the mentioned above

16Which Python code could replace the ellipsis (...) below to get the following output?
(Select all that apply.)
captains = {"Enterprise": "Picard", "Voyager": "Janeway", "Defiant": "Sisko", }
Enterprise Picard,Voyager JanewayDefiant Siskoa) for ship, captain in captains.items(): print(ship, captain)
b) for ship in captains: print(ship, captains[ship])
c) for ship in captains: print(ship, captains)
d) both a and b

Answer: - d) both a and b

17)Which of the following lines of code will create an empty dictionary named captains?
a) captains = {dict} b) type(captains)c)
captains.dict()d) captains = {}

Answer: - d) captions={}

18) Now you have your empty dictionary named captains.It's time to add some data! Specifically, you want to add the key-value pairs "Enterprise": "Picard", "Voyager": "Janeway", and "Defiant": "Sisko".Which of the following code snippets will successfully add these key-value pairs to theexisting captains dictionary?
a) captains{"Enterprise" = "Picard"}captains{"Voyager" = "Janeway"}
captains{"Defiant" = "Sisko"} b)
captains["Enterprise"] = "Picard"captains["Voyager"] = "Janeway"captains["Defiant"] = "Sisko"
c) captains = {"Enterprise": "Picard", "Voyager": "Janeway", "Defiant": "Sisko", }d) None of the above

Answer: - c)captains = {"Enterprise": "Picard", "Voyager": "Janeway", "Defiant": "Sisko", }

19)You're really building out the Federation Starfleet now!Here's what you have:captains = {"Enterprise": "Picard","Voyager": "Janeway","Defiant": "Sisko","Discovery": "unknown",}Now, say you want to display the ship and captain names contained in the dictionary, but you also want to provide some additional context. How could you do it?a) for item in captains.items(): print(f"The [ship] is captained by [captain].") b) for ship, captain in captains.items(): print(f"The {ship} is captained by {captain}.")c) for captain, ship in captains.items(): print(f"The {ship} is captained by {captain}.")d) All are correct
Answer: - b)for ship, captain in captains.items(): print(f"The{ship} is captained by {captain}.")

20)You've created a dictionary, added data, checked for the existence of keys, and iterated over it with a for loop. Now you're ready to delete a key from this dictionary:captains = "Enterprise": "Picard","Voyager": "Janeway","Defiant": "Sisko","Discovery": "unknown"

What statement will remove the entry for the key "Discovery"?
a) del captains
b)
captains.remove()
c) del
captains["Discovery"]
d)
captains["Discovery"].pop()

Answer: - c)del captains["Discovery"]