```
#include <iostream>
#include <string>
using namespace std;

struct Node {
    int orderID;
    string customerName;
    string foodName;
    Node* prev;
    Node* next;
};

Node* HEAD = NULL;
Node* TAIL = NULL;

// Add a new order
void addOrder() {
    Node* newNode = new Node;

    cout << "Enter Order ID: ";
    cin >> newNode->orderID;

    cin.ignore();

    cout << "Enter Customer Name: ";
    getline(cin, newNode->customerName);
```

```
    cout << "Enter Food Name: ";
    getline(cin, newNode->foodName);

    newNode->prev = NULL;
    newNode->next = NULL;

    if (HEAD == NULL) {
        HEAD = TAIL = newNode;
    } else {
        TAIL->next = newNode;
        newNode->prev = TAIL;
        TAIL = newNode;
    }

    cout << "Order added successfully!\n";
}

// Display all orders
void displayOrders() {
    if (HEAD == NULL) {
        cout << "No orders available.\n";
        return;
    }

    Node* temp = HEAD;

    cout << "\n--- Food Orders ---\n";
```

```
    while (temp != NULL) {
        cout << "Order ID: " << temp->orderID << endl;
        cout << "Customer Name: "
             << temp->customerName << endl;
        cout << "Food Name: " << temp->foodName << endl;
        cout << "--------------------\n";

        temp = temp->next;
    }
}

// Complete the first order
void completeOrder() {
    if (HEAD == NULL) {
        cout << "No orders available to complete.\n";
        return;
    }

    Node* temp = HEAD;

    cout << "Completed Order ID: "
         << temp->orderID << endl;

    HEAD = HEAD->next;

    if (HEAD != NULL) {
```

```
        HEAD->prev = NULL;
    } else {
        TAIL = NULL;
    }

    delete temp;

    cout << "Order completed successfully!\n";
}

// Display orders in reverse order
void displayReverse() {
    if (TAIL == NULL) {
        cout << "No orders available.\n";
        return;
    }

    Node* temp = TAIL;

    cout << "\n--- Orders in Reverse ---\n";

    while (temp != NULL) {
        cout << "Order ID: " << temp->orderID << endl;
        cout << "Customer Name: "
             << temp->customerName << endl;
        cout << "Food Name: " << temp->foodName << endl;
        cout << "--------------------\n";
```

```
        temp = temp->prev;
    }
}

int main() {
    int choice;

    do {
        cout << "\n===== FOOD ORDER MANAGEMENT =====\n";
        cout << "1. Add New Order\n";
        cout << "2. Display Orders\n";
        cout << "3. Complete Order\n";
        cout << "4. Display Orders in Reverse\n";
        cout << "5. Exit\n";
        cout << "Enter your choice: ";
        cin >> choice;

        switch (choice) {
            case 1:
                addOrder();
                break;

            case 2:
                displayOrders();
                break;
```

```
        case 3:
            completeOrder();
            break;

        case 4:
            displayReverse();
            break;

        case 5:
            cout << "Exiting program...\n";
            break;

        default:
            cout << "Invalid choice. Try again.\n";
    }

} while (choice != 5);

// Free remaining nodes
while (HEAD != NULL) {
    Node* temp = HEAD;
    HEAD = HEAD->next;
    delete temp;
}

TAIL = NULL;
```

```
    return 0;
}
```