

Sensitivity Analysis of Biochemical Systems Using Bond Graphs: Additional Material.

Peter Gawthrop. *peter.gawthrop@unimelb.edu.au*

January 17, 2023

Contents

1	Introduction	2
1.1	Import packages	2
1.2	Transfer function properties	3
1.3	Plotting and printing	3
1.4	Steady-state by simulation	4
1.5	Stoichiometry	4
1.6	Linearisation	5
1.7	Extract subsystem from linear system	5
1.8	Plotting	7
2	Normalisation constants	7
3	Simple example $A = B = C$	8
3.1	Bond Graph	8
3.2	Parameters	9
3.3	Stoichiometry & linearisation	9
3.4	Sensitivity Bond Graph – change chemostats	11
3.4.1	Compare sensitivity with exact simulation	11
3.5	Sensitivity Bond Graph – change K_B	12
3.5.1	Stoichiometry & linearisation	13
3.5.2	Compare sensitivity with exact simulation	14
3.6	Sensitivity Bond Graph – change κ_1	14
3.6.1	Stoichiometry & linearisation	15
3.6.2	Compare sensitivity with exact simulation	16
4	Sensitivity components	17
4.1	sCe	17
4.1.1	Bond Graph	17
4.2	sRe	18
4.2.1	Bond Graph	18
4.3	Simple system revisited	19
4.3.1	Parameters	19
4.3.2	Stoichiometry & linearisation	20
4.3.3	Stoichiometric matrix	21
4.4	Sensitivity Bond Graph – change B	21
4.4.1	Compare sensitivity with exact simulation	22
4.5	Sensitivity Bond Graph – change r1	23
4.5.1	Compare sensitivity with exact simulation	24
4.6	Sensitivity Bond Graph – change r2	24

4.6.1	Compare sensitivity with exact simulation	25
5	Stoichiometric approach	26
5.1	Simple example $A = B = C$	27
5.1.1	Vary λ	32
5.1.2	Sloppy parameters	34
5.2	Example: Enzyme-catalysed reaction	38
5.2.1	Vary λ	42
5.2.2	Simulate over flow range - quasi steady-state	43
5.2.3	Simulate over flow range - quasi steady-state	45
5.3	Example: Modulated Enzyme-catalysed reaction	47
5.3.1	Vary λ	54
5.3.2	Simulate over flow range - quasi steady-state	57
5.3.3	Simulate over flow range - quasi steady-state	59
5.3.4	Simulate over flow range - quasi steady-state	61
5.3.5	Sloppy parameters	63

1 Introduction

This notebook generates the figures for the paper: Sensitivity Analysis of Biochemical Systems Using Bond Graphs

1.1 Import packages

```
[1]: ## Some useful imports
import BondGraphTools as bgt
import numpy as np
import sympy as sp
import matplotlib.pyplot as plt
import control as con
import copy
import importlib

## For reimporting: use imp.reload(module)
import importlib as imp

## Stoichiometric analysis
import stoich as st

## SVG
import svgBondGraph as sbg

## Stoichiometry to BG
import stoichBondGraph as stbg

## Modularity
# import modular as bgm

## Sloppy parameters
import sloppy as slp
```

```

## Display (eg disp.SVG(), disp.
import IPython.display as disp

##
quiet = True
Titles = False
Plotting = False

```

Warning - scikit.odes not found. Simulations are disabled.

1.2 Transfer function properties

```

[2]: def tfProps(tf,method='truncate'):

    ## Steady-state gain
    g = con.dcgain(tf)

    if not con.issiso(tf):
        g = g[0][0]

    ## Time constant
    ## Check if direct link
    direct_link = np.any(tf.D)
    ## Only set tau=0 if siso
    if direct_link and con.issiso(tf):
        ## Instant response
        tau = 0
    else:
        ## Reduce to first-order to estimate time constant
        ## Note that method='matchdc' can give a kernel crash - use 'truncate'
        tf1 = con.balred(sys,orders=1,method=method)
        poles = con.poles(tf1)
        realPoles = np.real(poles)
        tau = -1/min(realPoles)

    return g,tau

```

1.3 Plotting and printing

```

[3]: ## Optional plotting
def Savefig(name):
    if Plotting:
        plt.rcParams.update({'font.size': 14})
        plotname = 'Figs/'+name+'.pdf'
        print('Saving',plotname)
        plt.savefig(plotname)

```

```

[4]: def latex(m,name):
    lm = sp.latex(sp.Matrix(m),mat_delim="(")
    return name+ ' &= ' +lm

```

```

## Optional print latex for the paper
printing = True
def printLatex(s,sc=None):
    if printing:
        ## System properties in LaTeX
        AA = Sys.A; print(latex(AA, 'A'))
        BB = Sys.B; print(latex(BB, 'B'))
        CC = Sys.C; print(latex(CC, 'C'))
        DD = Sys.D; print(latex(DD, 'D'))

        for m in ['species', 'reaction', 'Nf', 'Nr', 'N']:
            print(st.sprintl(s,m))

        if not (sc==None):
            print('% Nc matrix')
            print(st.sprintl(sc, 'N'))

        print(st.sprintrl(s,all=True,chemformula=True))
        print(st.sprintvl(s))

```

1.4 Steady-state by simulation

```

[5]: ## Steady-state by simulation
def SteadyState(s,sc,sf=None,parameter={},X0=None,t_ss=1000):
    t = np.linspace(0,t_ss)
    dat = st.
    →sim(s,sc=sc,sf=sf,t=t,parameter=parameter,X0=X0,tol=1e-4,quiet=quiet)
    X_ss = dat['X'][-1]
    V_ss = dat['V'][-1]
    #dX_ss = sc['N']@V_ss
    dX_ss = dat['dX'][-1]
    dXc_ss = dat['dXc'][-1]
    print(f'Steady-state finder error: {np.linalg.norm(dXc_ss):.2e}')
    return X_ss,V_ss

```

1.5 Stoichiometry

```

[6]: def
    →Stoichiometry(model,chemostats=[],flowstats=[],CommonSpecies=None,sensitivity=False):
    →

    ## Stoichiometry
    s = st.stoich(model,quiet=quiet)

    ## Unify species
    if not (CommonSpecies is None):
        commonSpecies = st.merge(s,CommonSpecies=CommonSpecies)
    #
        print(commonSpecies)

```

```

        st.unify(s,commonSpecies=commonSpecies)

    ## Sensitivity
    if sensitivity:
        extra = st.stoichSensitivity(s)
    else:
        extra = []

#     print(chemostats+extra)

    ## Chemostats and flowstats
    sc = st.statify(s,chemostats=chemostats+extra)
    sf = st.statify(s,flowstats=flowstats)

    return s,sc,sf

```

1.6 Linearisation

```

[7]: def Linear(s,sc,sf=None,parameter={},X0=None, invar='X', outvar = 'V',
    ↪quiet=False):

    ## Steady state
    if X0 is None:
        X0 = np.ones(s['n_X'])
#     print(len(X0))

    X_ss,V_ss = SteadyState(s,sc,sf=sf,parameter=parameter,X0=X0)
    dX_ss = s['N']@V_ss
    print('X_ss =',X_ss)
    print('V_ss =', V_ss)
#     print('dX_ss =', dX_ss)

    ## Linearise
    sys = st.lin(s,sc,sf=sf,x_ss=X_ss,parameter=parameter,
        invar=invar,outvar=outvar,quiet=quiet)

    return sys,X_ss,V_ss,dX_ss

```

1.7 Extract subsystem from linear system

```

[8]: def Index(A,a):

    I = []
    for aa in a:
        i = A.index(aa)
        I.append(i)
    return np.array(I)

def zapSmall(x,tol=1e-10,quiet=True):

```

```

xx = np.zeros(len(x))
for i,val in enumerate(x):
    if abs(val)>tol:
        xx[i] = x[i]
    else:
        if not quiet:
            print(f'Setting {i}th coefficient {val:.2} to zero')
return xx

def extractSubsystem(SYS,sc,sf,inp,outp,tol=None,order=None,quiet=False):

    Sys = copy.copy(SYS)
    chemostats = sc['chemostats']
    if sf is None:
        flowstats = []
    else:
        flowstats = sf['flowstats']
    species = sc['species']
    reaction = sc['reaction']

    ## Index of input and output
    if inp[0] in chemostats:
        i_inp = Index(chemostats,inp)
        # print('Input:',i_inp,chemostats[i_inp[0]])
    else:
        i_inp = Index(flowstats,inp)+len(chemostats)
    # print(i_inp)

    if outp[0] in chemostats:
        i_outp = Index(chemostats,outp)
    elif outp[0] in species:
        i_outp = Index(species,outp)
    else:
        if outp[0] in reaction:
            i_outp = Index(reaction,outp)
        else:
            print(f'Output {outp} does not exist')

    ## Extract tf
    n_y = len(i_outp)
    n_u = len(i_inp)
    nn = Sys.A.shape
    n_x = nn[0]
    # print(n_x)

    sys = con.ss(Sys.A,
                  Sys.B[:,i_inp].reshape(n_x,n_u),
                  Sys.C[i_outp,:].reshape(n_y,n_x),
                  Sys.D[i_outp][:,i_inp].reshape(n_y,n_u))

```

```

sys = con.minreal(sys,tol=tol,verbose=False)

## Reduce order
if not (order is None):
    sys = con.balred(sys,order,method='matchdc')

return sys

```

1.8 Plotting

```

[9]: def plotSensitivity(dat,reactions=['r1','r2'],plotSim=True,name=None):

    if plotSim:
        plt.plot(t,y_step,color='black',lw=3)
    else:
        plt.plot(t,y_step,label=label,lw=3)

    for reac in reactions:
        i = s['reaction'].index(reac)
        if plotSim:
            label = reac + r' ($\tilde{\lambda}$ = ' + f'{lam-1:0.2f})'
            pc = int(round(100*(lam-1)))
            label = f'{reac} ({pc}%)'
            plt.plot(t,(dat['V'][:,i]-V_ss[i])/(lam-1),
                     lw=5,ls='dashed',label=label)

    plt.grid()
    plt.legend()
    plt.xlabel('$t$')
    plt.ylabel(r'$\Delta v / \Delta \lambda$')
    # plt.tight_layout()

```

```

[10]: def plotLines(lw=4,ls='dotted'):
    plt.hlines(g,min(t),max(t),color='black',ls=ls,lw=lw)
    plt.vlines(tau,min(y_step.flatten()),max(y_step.
    →flatten()),color='black',ls=ls,lw=lw)

```

2 Normalisation constants

```

[11]: T_human = 37 # Human body temperature
K_0 = 273.15
print(f'T_human = {T_human} degC = {T_human+K_0} K')

mu_0 = RT = st.RT(T_cent=T_human)
print(f'mu_0 = {mu_0*1e-3:0.3f} kJ/mol')

F = st.F() # Faraday's constant
print(f'F = {F*1e-3:0.2f} kC/mol')

```

```

V_0 = RT/F
print(f'V_0 = {V_0*1e3:0.2f} mV')

P_0 = 1e-3

v_0 = P_0/mu_0
print(f'v_0 = {v_0*1e6:0.4f} micro mol /s')

i_0 = F*v_0
print(f'i_0 = {i_0*1e3:0.2f} mA')

```

```

T_human = 37 degC = 310.15 K
mu_0 = 2.579 kJ/mol
F = 96.49 kC/mol
V_0 = 26.73 mV
v_0 = 0.3878 micro mol /s
i_0 = 37.42 mA

```

3 Simple example $A = B = C$


3.1 Bond Graph

```

[12]: # Simple example A = B = C
      sbg.model('ABC_abg.svg')
      import ABC_abg
      disp.SVG('ABC_abg.svg')

```

[12]:



```

[13]: ## BG generated equations
      # model = ABC_abg.model()
      # for cr in model.constitutive_relations:
      #     print(cr)
      #     #print(sp.diff(cr, 'x_0'))

```


3.2 Parameters

```
[14]: ## Parameters
parameter = {}
parameter['K_A'] = 1
parameter['K_B'] = 1
parameter['kappa_r1'] = 1
parameter['kappa_r2'] = 9
print(parameter)

## Initial states
X_A_0 = 2
```

```
{'K_A': 1, 'K_B': 1, 'kappa_r1': 1, 'kappa_r2': 9}
```

3.3 Stoichiometry & linearisation

```
[15]: ## Stoichiometry
s,sc,sf = Stoichiometry(ABC_abg.model(),chemostats=['A','C'],flowstats=[])
```

```
[16]: ## Linearise
Parameter = copy.copy(parameter)
Parameter['K_A'] = X_A_0*parameter['K_A']
Sys,X_ss,V_ss,dX_ss = □
    ↳Linear(s,sc,parameter=parameter,X0=[X_A_0,1,1],quiet=quiet)
i_A = s['species'].index('A')
X_A_ss = X_ss[i_A]

## Show transfer function
con.tf(Sys)

## Lambda for comparison
lam = 1.1
```

Steady-state finder error: 8.88e-16

```
X_ss = [2.  1.1 1. ]
```

```
V_ss = [0.9 0.9]
```

```
[17]: printLatex(s,sc=sc)
```

```
A &= \left(\begin{matrix}-10.0\end{matrix}\right)
B &= \left(\begin{matrix}1.0 & 9.0\end{matrix}\right)
C &= \left(\begin{matrix}-1.0\\9.0\end{matrix}\right)
D &= \left(\begin{matrix}1.0 & 0 & -9.0\end{matrix}\right)
\begin{align}
X&= \begin{pmatrix}
X_{\{A\}}\\
X_{\{B\}}\\
X_{\{C\}}
\end{pmatrix}
\end{align}
```

```

\begin{align}
V&= \begin{pmatrix}
V_{r1} \\
V_{r2}
\end{pmatrix} \\
\end{align}

\begin{align}
N_f &= \\
\left( \begin{matrix} 1 & 0 \\ 0 & 1 \end{matrix} \right) \\
\end{align}

\begin{align}
N_r &= \\
\left( \begin{matrix} 0 & 0 \\ 1 & 0 \end{matrix} \right) \\
\end{align}

\begin{align}
N &= \\
\left( \begin{matrix} -1 & 0 \\ 0 & -1 \end{matrix} \right) \\
\end{align}

%% Nc matrix
\begin{align}
N &= \\
\left( \begin{matrix} 0 & 0 \\ 1 & -1 \end{matrix} \right) \\
\end{align}

\begin{align}
\text{\texttt{ch}\{A \& \<> [ r1 ] B \}} \\
\text{\texttt{ch}\{B \& \<> [ r2 ] C \}} \\
\end{align}

\begin{align}
v_{r1} &= \kappa_{r1} \left( K_{\{A\}} x_{\{A\}} - K_{\{B\}} x_{\{B\}} \right) \\
v_{r2} &= \kappa_{r2} \left( K_{\{B\}} x_{\{B\}} - K_{\{C\}} x_{\{C\}} \right) \\
\end{align}

```

```

[18]: ## Show dc gain
print('DC gain: \n', con.dcgain(Sys))

```

```

DC gain:
[[ 0.9 -0.9]
 [ 0.9 -0.9]]

```

3.4 Sensitivity Bond Graph – change chemostats

```
[19]: ## Extract sensitivity system
inp = ['A']
outp = ['r1', 'r2']
sys = extractSubsystem(Sys, sc, sf, inp, outp)

## Include factor X_A_0 into the linearised system
sys.B = sys.B*X_A_0
sys.D = sys.D*X_A_0
```

```
[20]: ## Show transfer function
con.tf(sys)
```

[20]:

$$\begin{bmatrix} \frac{2s+18}{s+10} \\ \frac{18}{s+10} \end{bmatrix}$$

```
[21]: ## System matrix
sys
```

[21]:

$$\left(\begin{array}{c|c} -10 & 2 \\ -1 & 2 \\ 9 & 0 \end{array} \right)$$

```
[22]: ## Show dc gain
print('DC gain: \n', con.dcgain(sys))
```

```
DC gain:
[[1.8]
 [1.8]]
```


3.4.1 Compare sensitivity with exact simulation

```
[23]: ## Exact Simulate with changed x_A
X_ss_1 = copy.copy(X_ss)
X_ss_1[i_A] = lam*X_A_ss
print(X_ss)
t = np.linspace(0,1)
dat = st.sim(s, sc=sc, t=t, parameter=parameter, X0=X_ss_1, quiet=quiet)
print(parameter)
```

```
[2.  1.1 1. ]
{'K_A': 1, 'K_B': 1, 'kappa_r1': 1, 'kappa_r2': 9}
```


```
[24]: ## Step response to change in A
step = con.step_response(sys, T=t)
y_step = step.y[:,0,:].T
```

```
[25]: ## Plot
plotSensitivity(dat,)
```



3.5 Sensitivity Bond Graph – change K_B

```
[26]: # Simple example A = B = C: sensitivity
sbg.model('sKABC_abg.svg')
import sKABC_abg
disp.SVG('sKABC_abg.svg')
```



3.5.1 Stoichiometry & linearisation

```
[27]: ## Stoichiometry
s,sc,sf = Stoichiometry(sKABC_abg.
    ↳model(),chemostats=['A','C','sB'],flowstats=[])

## Linearise
Sys,X_ss,V_ss,dX_ss =↳
    ↳Linear(s,sc,parameter=parameter,X0=[2,1,1,1],quiet=quiet)

## Extract sensitivity system
inp = ['sB']
outp = ['r1','r2']
sys = extractSubsystem(Sys,sc,sf,inp,outp)

## Species and reactions
print(s['species'])
print(s['reaction'])
```

Steady-state finder error: 8.88e-16

X_ss = [2. 1.1 1. 1.]

V_ss = [0.9 0.9]

['A', 'B', 'C', 'sB']

['r1', 'r2']

```
[28]: ## Show transfer function
con.tf(sys)
```

[28]:

$$\begin{bmatrix} \frac{-1.1s}{s+10} \\ \frac{9.9s}{s+10} \end{bmatrix}$$

```
[29]: ## System matrix
sys
```

[29]:

$$\left(\begin{array}{c|c} -10 & -11 \\ \hline -1 & -1.1 \\ 9 & 9.9 \end{array} \right)$$

```
[30]: ## Show dc gain
print('DC gain: \n', con.dcgain(sys))
```

DC gain:

[[0.]


[0.]]

3.5.2 Compare sensitivity with exact simulation

```
[31]: ## Exact Simulate with changed K
parameter1 = copy.copy(parameter)
parameter1['K_B'] *= lam
t = np.linspace(0,1)
dat = st.sim(s,sc=sc,t=t,parameter=parameter1,X0=X_ss,quiet=quiet)
```

```
[32]: ## Step response to sB
step = con.step_response(sys,T=t)
y_step = step.y[:,0,:].T
```


```
[33]: ## Plot
plotSensitivity(dat,)
```



3.6 Sensitivity Bond Graph – change κ_1

```
[34]: # Simple example A = B = C: sensitivity
sbg.model('sKapABC_abg.svg')
import sKapABC_abg
disp.SVG('sKapABC_abg.svg')
```

```
[34]:
```



```
[35]: ## BG generated equations
model = sKapABC_abg.model()
for cr in model.constitutive_relations:
    print(cr)
    #print(sp.diff(cr, 'x_0'))
```

```

K_A*K_sr1*kappa_r1*x_0*x_3 - K_B*K_sr1*kappa_r1*x_1*x_3 + dx_0
-K_A*K_sr1*kappa_r1*x_0*x_3 + K_B*K_sr1*kappa_r1*x_1*x_3 + K_B*kappa_r2*x_1 -
K_C*kappa_r2*x_2 + dx_1
-K_B*kappa_r2*x_1 + K_C*kappa_r2*x_2 + dx_2
dx_3

```

3.6.1 Stoichiometry & linearisation

```
[36]: print(s['reaction'])
## Stoichiometry
s,sc,sf = Stoichiometry(sKapABC_abg.model(),chemostats=['A','C','sr1'])
print(sf['flowstats'])

## Linearise
Sys,X_ss,V_ss,dX_ss = _
↳Linear(s,sc,parameter=parameter,X0=[2,1,1,1],quiet=quiet)

## Extract sensitivity system
inp = ['sr1']
outp = ['r1','r2']
sys = extractSubsystem(Sys,sc,sf,inp,outp)

## Show transfer function
con.tf(sys)
```

```

['r1', 'r2']
[]
Steady-state finder error: 8.88e-16
X_ss = [2.  1.1 1.  1. ]
V_ss = [0.9 0.9]

```

[36]:

$$\left[\begin{array}{c} \frac{0.9s+8.1}{s+10} \\ \frac{8.1}{s+10} \end{array} \right]$$

```
[37]: ## System matrix
sys
```

[37]:

$$\left(\begin{array}{c|c} -10 & 9 \\ \hline -0.1 & 0.9 \\ 0.9 & 0 \end{array} \right)$$

```
[38]: ## Show dc gain
print('DC gain: \n', con.dcgain(sys))
```


```
DC gain:
[[0.81]
 [0.81]]
```

3.6.2 Compare sensitivity with exact simulation

```
[39]: ## Exact Simulate with changed K
lam = 1.1
parameter1 = copy.copy(parameter)
parameter1['kappa_r1'] *= lam
t = np.linspace(0,1)
dat = st.sim(s,sc=sc,sf=sf,t=t,parameter=parameter1,X0=X_ss,quiet=quiet)
```

```
[40]: ## Step response to sB
step = con.step_response(sys,T=t)
y_step = step.y[:,0,:].T
```

```
[41]: ## Plot
plotSensitivity(dat,)
```

[42]: sys

[42]:

$$\left(\begin{array}{c|c} -10 & 9 \\ -0.1 & 0.9 \\ 0.9 & 0 \end{array} \right)$$

[43]: disp.Latex(st.sprintvl(s))

[43]:

$$v_{r1} = K_{sr1} \kappa_{r1} x_{sr1} (K_A x_A - K_B x_B) \quad (1)$$

$$v_{r2} = \kappa_{r2} (K_B x_B - K_C x_C) \quad (2)$$

4 Sensitivity components


4.1 sCe

4.1.1 Bond Graph

[44]:

```
# sCe
sbg.model('sCe_abg.svg')
import sCe_abg
disp.SVG('sCe_abg.svg')
```

[44]:




4.2 sRe

4.2.1 Bond Graph

```
[45]: # sRe
sbg.model('sRe_abg.svg')
import sRe_abg
disp.SVG('sRe_abg.svg')
```

[45]:



4.3 Simple system revisited


```
[46]: # Simple example  $A = B = C$  with sensitivity components
sbgl.model('sABC_abg.svg')
import sABC_abg
disp.SVG('sABC_abg.svg')
```

Creating subsystem: sCe:B

Creating subsystem: sRe:r1

Creating subsystem: sRe:r2

[46]:



4.3.1 Parameters

```
[47]: ## Parameters
parameter = {}
parameter['K_A'] = 1
parameter['K_B_A'] = 1
parameter['kappa_r1'] = 0.1
parameter['kappa_r2'] = 0.9
print(parameter)

## Initial states
X_A_0 = 2
```

{'K_A': 1, 'K_B_A': 1, 'kappa_r1': 0.1, 'kappa_r2': 0.9}

```
[48]: ## Parameters
parameter = {}
parameter['K_A'] = 1
parameter['K_B_A'] = 1
parameter['kappa_r1'] = 1
parameter['kappa_r2'] = 9
print(parameter)

## Initial states
X_A_0 = 2
```

{'K_A': 1, 'K_B_A': 1, 'kappa_r1': 1, 'kappa_r2': 9}

4.3.2 Stoichiometry & linearisation

```
[49]: ## Stoichiometry
s,sc,sf = Stoichiometry(sABC_abg.
    ↳model(),chemostats=['A','C','B_sA','r1_sr','r2_sr'],flowstats=[])

## Species
print(s['species'])

## Reactions
print(s['reaction'])



## Linearise
Sys,X_ss,V_ss,dX_ss =_
    ↳Linear(s,sc,parameter=parameter,X0=[X_A_0,1,1,1,1,1],quiet=quiet)

## Lambda for comparison
lam = 1.1
```

```
['A', 'C', 'B_A', 'B_sA', 'r1_sr', 'r2_sr']
['r1', 'r2']
Steady-state finder error: 8.88e-16
X_ss = [2.  1.  1.1 1.  1.  1. ]
V_ss = [0.9 0.9]
```

```
[50]: ## Show reactions
disp.Latex(st.sprintrl(s,all=True,chemformula=True))
```

[50]:



```
[51]: ## Show system
Sys
```

[51]:

$$\left(\begin{array}{c|ccccc} -10 & 1 & 9 & -11 & 0.9 & -0.9 \\ -1 & 1 & 0 & -1.1 & 0.9 & 0 \\ 9 & 0 & -9 & 9.9 & 0 & 0.9 \end{array} \right)$$

```
[52]: ## Show transfer function
con.tf(Sys)
```

[52]:

$$\begin{bmatrix} \frac{s+9}{s+10} & \frac{-9}{s+10} & \frac{-1.1s}{s+10} & \frac{0.9s+8.1}{s+10} & \frac{0.9}{s+10} \\ \frac{9}{s+10} & \frac{s+10}{s+10} & \frac{9.9s}{s+10} & \frac{8.1}{s+10} & \frac{0.9s+0.9}{s+10} \end{bmatrix}$$

4.3.3 Stoichiometric matrix

```
[53]: disp.Latex(st.sprintl(s, 'N'))
```

[53]:

$$N = \begin{pmatrix} -1 & 0 \\ 0 & 1 \\ 1 & -1 \\ 1 & -1 \\ 0 & 0 \\ 0 & 0 \end{pmatrix} \quad (5)$$

```
[54]: disp.Latex(st.sprintl(s, 'Nf'))
```

[54]:

$$Nf = \begin{pmatrix} 1 & 0 \\ 0 & 0 \\ 0 & 1 \\ 0 & 1 \\ 1 & 0 \\ 0 & 1 \end{pmatrix} \quad (6)$$

```
[55]: disp.Latex(st.sprintl(s, 'Nr'))
```

[55]:

$$Nr = \begin{pmatrix} 0 & 0 \\ 0 & 1 \\ 1 & 0 \\ 1 & 0 \\ 1 & 0 \\ 0 & 1 \end{pmatrix} \quad (7)$$

```
[56]: ## Show dc gain
print('DC gain: \n', con.dcgain(Sys))
```

DC gain:

```
[[ 0.9 -0.9  0.    0.81 0.09]
 [ 0.9 -0.9  0.    0.81 0.09]]
```

4.4 Sensitivity Bond Graph – change B

```
[57]: ## Extract sensitivity system
inp = ['B_sA']
outp = ['r1', 'r2']
sys = extractSubsystem(Sys, sc, sf, inp, outp)
```

```
[58]: ## Show transfer function
con.tf(sys)
```

[58]:

$$\begin{bmatrix} \frac{-1.1s}{s+10} \\ \frac{9.9s}{s+10} \end{bmatrix}$$

```
[59]: ## System matrix  
sys
```

[59]:

$$\left(\begin{array}{c|c} -10 & -11 \\ \hline -1 & -1.1 \\ 9 & 9.9 \end{array} \right)$$

```
[60]: ## Show dc gain  
print('DC gain: \n', con.dcgain(sys))
```


DC gain:
[[0.]
[0.]]

4.4.1 Compare sensitivity with exact simulation

```
[61]: ## Exact Simulate with changed K  
parameter1 = copy.copy(parameter)  
parameter1['K_B_A'] *= lam  
t = np.linspace(0,1)  
dat = st.sim(s,sc=sc,t=t,parameter=parameter1,X0=X_ss,quiet=quiet)
```

```
[62]: ## Step response to sB  
step = con.step_response(sys,T=t)  
y_step = step.y[:,0,:].T
```

```
[63]: ## Plot  
plotSensitivity(dat,)
```



4.5 Sensitivity Bond Graph – change r1

```
[64]: ## Extract sensitivity system
inp = ['r1_sr']
outp = ['r1', 'r2']
sys = extractSubsystem(Sys, sc, sf, inp, outp)
```

```
[65]: ## Show transfer function
con.tf(sys)
```

```
[65]:
```

$$\begin{bmatrix} \frac{0.9s+8.1}{s+10} \\ \frac{8.1}{s+10} \end{bmatrix}$$

```
[66]: ## System matrix
sys
```

```
[66]:
```

$$\left(\begin{array}{c|c} -10 & 9 \\ \hline -0.1 & 0.9 \\ 0.9 & 0 \end{array} \right)$$

```
[67]: ## Show dc gain
print('DC gain: \n', con.dcgain(sys))
```

```
DC gain:
[[0.81]
 [0.81]]
```


4.5.1 Compare sensitivity with exact simulation

```
[68]: ## Exact Simulate with changed r1  
parameter1 = copy.copy(parameter)  
parameter1['kappa_r1'] *= lam  
t = np.linspace(0,1)  
dat = st.sim(s,sc=sc,t=t,parameter=parameter1,X0=X_ss,quiet=quiet)  
print(parameter1)
```

```
{'K_A': 1, 'K_B_A': 1, 'kappa_r1': 1.1, 'kappa_r2': 9}
```

```
[69]: ## Step response to sr1  
step = con.step_response(sys,T=t)  
y_step = step.y[:,0,:].T
```

```
[70]: ## Plot  
plotSensitivity(dat,)
```



4.6 Sensitivity Bond Graph – change r2

```
[71]: ## Extract sensitivity system  
inp = ['r2_sr']  
outp = ['r1', 'r2']  
sys = extractSubsystem(Sys,sc,sf,inp,outp)
```

```
[72]: ## Show transfer function  
con.tf(sys)
```

```
[72]:
```


$$\begin{bmatrix} \frac{0.9}{s+10} \\ \frac{0.9s+0.9}{s+10} \end{bmatrix}$$

```
[73]: ## System matrix
sys
```

[73]:

$$\left(\begin{array}{c|c} -10 & -9 \\ \hline -0.1 & 0 \\ 0.9 & 0.9 \end{array} \right)$$

```
[74]: ## Show dc gain
print('DC gain: \n', con.dcgain(sys))
```

```
DC gain:
[[0.09]
 [0.09]]
```


4.6.1 Compare sensitivity with exact simulation

```
[75]: ## Exact Simulate with changed r2
parameter1 = copy.copy(parameter)
parameter1['kappa_r2'] *= lam
t = np.linspace(0,1)
dat = st.sim(s,sc=sc,t=t,parameter=parameter1,X0=X_ss,quiet=quiet)
print(parameter1)
print(X_ss)
```

```
{'K_A': 1, 'K_B_A': 1, 'kappa_r1': 1, 'kappa_r2': 9.9}
[2.  1.  1.1 1.  1.  1. ]
```

```
[76]: ## Step response to sr2
step = con.step_response(sys,T=t)
y_step = step.y[:,0,:].T
```

```
[77]: ## Plot
plotSensitivity(dat,)
```



5 Stoichiometric approach

```
[78]: def stoichSensitivity(model, chemostats=['A', 'C'],
    ↪ parameter={}, X0=None, CommonSpecies=None):
    """Sensitivity analysis via stoichiometric approach """

    ## Stoichiometry
    s, sc, sf =
    ↪ Stoichiometry(model, chemostats=chemostats, CommonSpecies=CommonSpecies, sensitivity=True)

    ## Linearise
    if X0 is None:
        X0 = np.ones(s['n_X'])
        i_chem = s['species'].index(chemostats[0])
        X0[i_chem] = 2

    Sys, X_ss, V_ss, dX_ss = Linear(s, sc, parameter=parameter, X0=X0, quiet=quiet)

    return s, sc, sf, Sys, X_ss, V_ss, dX_ss

def simSensitivity(s, sc, sf, Sys, X_ss, V_ss, dX_ss, chemostats=['A', 'C'],
    inp=['sr1'], outp=['r1', 'r2'], t_last=2, parameter={}, lam=1.
    ↪ 2, order=None):

    ## Extract sensitivity system
    sys = extractSubsystem(Sys, sc, sf, inp=inp, outp=outp, order=order)
```

```

## Time
t = np.linspace(0,t_last,500)

## Sensitivity step response
step = con.step_response(sys,T=t)
y_step = step.y[:,0,:].T

## Exact simulation with changed parameter or state
X_ss_1 = copy.copy(X_ss)
parameter1 = copy.copy(parameter)
inComp = inp[0][1:]

if inComp in chemostats:
    ## Perturb state
    iComp = s['species'].index(inComp)
    X_ss_1[iComp] = lam*X_ss_1[iComp]
    # y_step *= X_ss_1[iComp]
else:
    ## Perturb parameter
    if inComp[0].isupper():
        parname = 'K_'+inComp
    else:
        parname = 'kappa_'+inComp

    if parname in list(parameter.keys()):
        parameter1[parname] = lam*parameter[parname]
    else:
        parameter1[parname] = lam

dat = st.sim(s,sc=sc,sf=sf,t=t,parameter=parameter1,X0=X_ss_1,quiet=quiet)

return dat,y_step,t,sys

```


5.1 Simple example $A = B = C$

```

[79]: # Simple example A = B = C
      sbg.model('ABC_abg.svg')
      import ABC_abg
      disp.SVG('ABC_abg.svg')

```

[79]:



```
[80]: ## Parameters
parameter = {}
parameter['K_A'] = 1
parameter['K_B'] = 1
parameter['kappa_r1'] = 1
parameter['kappa_r2'] = 9
print(parameter)

## Initial states
X_A_0 = 2
```

```
{'K_A': 1, 'K_B': 1, 'kappa_r1': 1, 'kappa_r2': 9}
```



```
[81]: ## ABC model
dcgain = {}
s,sc,sf,sys,X_ss,V_ss,dX_ss = stoichSensitivity(ABC_abg.
    ↳model(),parameter=parameter)
lam = 1.1
outp = ['r1','r2']
for inp in ['sA','sB','sC','sr1','sr2']:
    dat,y_step,t,sys = simSensitivity(s,sc,sf,sys,X_ss,V_ss,dX_ss,
        ↳
    ↳parameter=parameter,inp=[inp],outp=outp,lam=lam,t_last=1)
#     g = con.dcgain(sys)[0][0]



    g,tau = tfProps(sys)
    dcgain[inp] = g
    if Titles:
        plt.title(f'{inp} (g = {g:.3f})')
    plotSensitivity(dat,reactions=outp)
    plotLines()
#     plt.hlines(g,min(t),max(t),color='black',ls='dashed')
    Savefig('ABC_'+inp)
    plt.show()
```


Steady-state finder error: 8.88e-16

```
X_ss = [2.  1.1 1.  1.  1.  1.  1. ]
```

```
V_ss = [0.9 0.9]
```







[82]: `printLatex(s,sc=sc)`

```
A &= \left(\begin{matrix}-10.0\end{matrix}\right)
B &= \left(\begin{matrix}1.0 & 9.0 & 2.0 & -11.0 & 9.0 & 0.9 & \\
-0.9000000000000001\end{matrix}\right)
C &= \left(\begin{matrix}-1.0\\9.0\end{matrix}\right)
D &= \left(\begin{matrix}1.0 & 0 & 2.0 & -1.1 & 0 & 0.9 & 0\\0 & -9.0 & 0 & 9.9 \\
& -9.0 & 0 & 0.9000000000000001\end{matrix}\right)
\begin{align}
X&= \begin{pmatrix}
X_{\{A\}}\\
X_{\{B\}}\\
X_{\{C\}}\\
X_{\{sA\}}\\
X_{\{sB\}}\\
X_{\{sC\}}\\
X_{\{sr1\}}\\
X_{\{sr2\}}
\end{pmatrix}
\end{align}

\begin{align}
V&= \begin{pmatrix}
V_{\{r1\}}\\
V_{\{r2\}}
\end{pmatrix}
\end{align}

\begin{align}
```

```

Nf &=
\left(\begin{matrix}1.0 & 0\\0 & 1.0\\0 & 0\\1.0 & 0\\0 & 1.0\\0 & 0\\1.0 & 0\\0 & 1.0\end{matrix}\right)
\end{align}

\begin{align}
Nr &=
\left(\begin{matrix}0 & 0\\1.0 & 0\\0 & 1.0\\0 & 0\\1.0 & 0\\0 & 1.0\\1.0 & 0\\0 & 1.0\end{matrix}\right)
\end{align}

\begin{align}
N &=
\left(\begin{matrix}-1.0 & 0\\1.0 & -1.0\\0 & 1.0\\-1.0 & 0\\1.0 & -1.0\\0 & 1.0\\0 & 0\\0\end{matrix}\right)
\end{align}

%% Nc matrix
\begin{align}
N &=
\left(\begin{matrix}0 & 0\\1.0 & -1.0\\0 & 0\\0 & 0\\0 & 0\\0 & 0\\0 & 0\\0\end{matrix}\right)
\end{align}

\begin{align}
\text{ch}\{A + sA + sr1 \text{ \> } [ r1 ] B + sB + sr1 \}\\
\text{ch}\{B + sB + sr2 \text{ \> } [ r2 ] C + sC + sr2 \}
\end{align}

\begin{align}
v_{r1} &= \kappa_{r1} \left(K_{sr1} x_{sr1}\right)^{1.0} \left(\left(K_{A} x_{A}\right)^{1.0} \left(K_{sA} x_{sA}\right)^{1.0} - \left(K_{B} x_{B}\right)^{1.0} \left(K_{sB} x_{sB}\right)^{1.0}\right)\\
v_{r2} &= \kappa_{r2} \left(K_{sr2} x_{sr2}\right)^{1.0} \left(\left(K_{B} x_{B}\right)^{1.0} \left(K_{sB} x_{sB}\right)^{1.0} - \left(K_{C} x_{C}\right)^{1.0} \left(K_{sC} x_{sC}\right)^{1.0}\right)
\end{align}

```

5.1.1 Vary λ

```

[83]: inp = 'sr1'
      outp = ['r2']
      for lam in [1.1,2,11]:
          dat,y_step,t,sys = simSensitivity(s,sc,sf,Sys,X_ss,V_ss,dX_ss,
          ↳parameter=parameter,inp=[inp],outp=outp,lam=lam,t_last=1)
      #     print(con.dcgain(sys))
      g = con.dcgain(sys)
      if Titles:
          plt.title(f'{inp} (g = {g:.3f})')


```



```

plotSensitivity(dat,reactions=outp)
plotLines()
Savefig('ABC_lambda')

```



```

[84]: ## Show system
Sys

```

[84]:

$$\left(\begin{array}{c|ccccccc} -10 & 1 & 9 & 2 & -11 & 9 & 0.9 & -0.9 \\ \hline -1 & 1 & 0 & 2 & -1.1 & 0 & 0.9 & 0 \\ 9 & 0 & -9 & 0 & 9.9 & -9 & 0 & 0.9 \end{array} \right)$$

```

[85]: ## Show system TF
print(sc['chemostats'])
con.tf(Sys)

```

```
['A', 'C', 'sA', 'sB', 'sC', 'sr1', 'sr2']
```

[85]:

$$\begin{bmatrix} \frac{s+9}{s+10} & \frac{-9}{s+10} & \frac{2s+18}{s+10} & \frac{-1.1s}{s+10} & \frac{-9}{s+10} & \frac{0.9s+8.1}{s+10} & \frac{0.9}{s+10} \\ \frac{9}{s+10} & \frac{-9s-9}{s+10} & \frac{18}{s+10} & \frac{9.9s}{s+10} & \frac{-9s-9}{s+10} & \frac{8.1}{s+10} & \frac{0.9s+0.9}{s+10} \end{bmatrix}$$

```

[86]: ## Show DC gain
con.dcgain(Sys)

```

```

[86]: array([[ 0.9 , -0.9 ,  1.8 ,  0. , -0.9 ,  0.81,  0.09],
            [ 0.9 , -0.9 ,  1.8 ,  0. , -0.9 ,  0.81,  0.09]])

```

```
[87]: ## Show initial reponse
print(Sys.D)
```

```
[[ 1.   0.   2.  -1.1  0.   0.9  0. ]
 [ 0.  -9.   0.   9.9 -9.   0.   0.9]]
```

5.1.2 Sloppy parameters

```
[88]: imp.reload(slp)

def sloppy(Sys,inp,outh,t=None,GainOnly=False):
    sys = extractSubsystem(Sys,sc,sf,inp,outh)
    #print(sys)
    H,eig,eigv,t = slp.Sloppy(sys,t=t,GainOnly=GainOnly)
    print(H)
    slp.SloppyPlot(eig,eigv,inp)
    slp.SloppyPrint(eig,eigv,inp,min_eig=0)
    #    if not GainOnly:
    #        slp.SloppyPlotData(t,y,inp,outh)

def sloppyBoth(Sys,inp,outh,t=None):

    sys = extractSubsystem(Sys,sc,sf,inp,outh)
    SysName = sc['name']
    print(SysName)
    if (t is None):
        name = f'{SysName}_sloppy_{inp[0]}'
    else:
        name = f'{SysName}_sloppy_{inp[0]}_long'

    #print(sys)
    H,eig,eigv,t = slp.Sloppy(sys,t=t,GainOnly=False)
    print(f'\n t_f = {max(t):0.2f}')
    print('H:')
    slp.SloppyPrint(eig,eigv,inp,min_eig=0)

    H,Eig,Eigv,t = slp.Sloppy(sys,t=t,GainOnly=True)
    print('H_ss:')
    slp.SloppyPrint(Eig,Eigv,inp,min_eig=0)

    ## Direct computation
    print('Direct:')
    gain = con.dcgain(sys)[0]
    norm = np.sum(gain*gain)
    ngain = gain/np.sqrt(norm)
    slp.SloppyPrint([norm],np.array([ngain]).T,inp,min_eig=0.0,min_eigv=0.
    →05,max_eigs=2)

    ## Plot
    slp.SloppyPlot(eig,eigv,inp,Eig=Eig,Eigv=Eigv)
```

```

Savefig(name)
plt.show()

for t_last in [0,1e6]:
    if t_last==0:
        t = None
    else:
        t = np.linspace(0,t_last,100)
    sloppyBoth(Sys,['sr1','sr2'],['r1'],t=t)
    sloppyBoth(Sys,['sA','sC'],['r1'],t=t)


```

ABC

```

t_f = 0.69
H:
\sqrt{\sigma_1} \&= 0.83 \& V_1\Lambda \&= + 1.00 \lambda_{r1} + 0.09 \lambda_{r2}
\sqrt{\sigma_2} \&= 0.023 \& V_2\Lambda \&= + 1.00 \lambda_{r2} - 0.09 \lambda_{r1}
H_{ss}:
\sqrt{\sigma_1} \&= 0.81 \& V_1\Lambda \&= + 0.99 \lambda_{r1} + 0.11 \lambda_{r2}
\sqrt{\sigma_2} \&= 3.2e-05 \& V_2\Lambda \&= + 0.99 \lambda_{r2} - 0.11 \lambda_{r1}
Direct:
\sqrt{\sigma_1} \&= 0.81 \& V_1\Lambda \&= + 0.99 \lambda_{r1} + 0.11 \lambda_{r2}

```



ABC

```


t_f = 0.69
H:
\sqrt{\sigma_1} \&= 2 \& V_1\Lambda \&= + 0.92 \lambda_{A} - 0.39 \lambda_{C}

```

```

\sqrt{\sigma_2} \&= 0.21 \& V_2\Lambda \&= + 0.92 \lambda_{C} + 0.39 \lambda_{A}
H_{ss}:
\sqrt{\sigma_1} \&= 2 \& V_1\Lambda \&= + 0.89 \lambda_{A} - 0.45 \lambda_{C}
\sqrt{\sigma_2} \&= 3.2e-05 \& V_2\Lambda \&= + 0.89 \lambda_{C} + 0.45 \lambda_{A}
Direct:
\sqrt{\sigma_1} \&= 2 \& V_1\Lambda \&= + 0.89 \lambda_{A} - 0.45 \lambda_{C}

```




ABC

```

t_f = 1000000.00
H:
\sqrt{\sigma_1} \&= 0.82 \& V_1\Lambda \&= + 0.99 \lambda_{r1} + 0.11 \lambda_{r2}
\sqrt{\sigma_2} \&= 0.0099 \& V_2\Lambda \&= + 0.99 \lambda_{r2} - 0.11 \lambda_{r1}
H_{ss}:
\sqrt{\sigma_1} \&= 0.81 \& V_1\Lambda \&= + 0.99 \lambda_{r1} + 0.11 \lambda_{r2}
\sqrt{\sigma_2} \&= 3.2e-05 \& V_2\Lambda \&= + 0.99 \lambda_{r2} - 0.11 \lambda_{r1}
Direct:
\sqrt{\sigma_1} \&= 0.81 \& V_1\Lambda \&= + 0.99 \lambda_{r1} + 0.11 \lambda_{r2}

```



ABC

$t_f = 1000000.00$

H:

$\sqrt{\sigma_1} \approx 2 \& V_1 \backslash \text{Lambda} \approx + 0.90 \ \lambda_{\{A\}} - 0.44 \ \lambda_{\{C\}}$

$\sqrt{\sigma_2} \approx 0.089 \& V_2 \backslash \text{Lambda} \approx + 0.90 \ \lambda_{\{C\}} + 0.44 \ \lambda_{\{A\}}$


H_{ss}:

$\sqrt{\sigma_1} \approx 2 \& V_1 \backslash \text{Lambda} \approx + 0.89 \ \lambda_{\{A\}} - 0.45 \ \lambda_{\{C\}}$

$\sqrt{\sigma_2} \approx 3.2e-05 \& V_2 \backslash \text{Lambda} \approx + 0.89 \ \lambda_{\{C\}} + 0.45 \ \lambda_{\{A\}}$

Direct:


$\sqrt{\sigma_1} \approx 2 \& V_1 \backslash \text{Lambda} \approx + 0.89 \ \lambda_{\{A\}} - 0.45 \ \lambda_{\{C\}}$



5.2 Example: Enzyme-catalysed reaction

```
[89]: sbg.model('ECR_abg.svg')
import ECR_abg
imp.reload(ECR_abg)
disp.SVG('ECR_abg.svg')
```

[89]:



```
[90]: ## Stoichiometry
s0 = st.stoich(ECR_abg.model(),quiet=quiet)
species = s0['species']
reaction=s0['reaction']
n_X = s0['n_X']
n_V = s0['n_V']
```

```
[91]: ## Initial states (for sensitivity system)
e0 = 10 ## Total bound and unbound enzyme
XX0 = {}
# XX0['A'] = 1
XX0['E'] = e0/2
XX0['C'] = e0/2
X0 = np.ones(2*n_X+n_V)

for spec in XX0:
    X0[species.index(spec)] = XX0[spec]
```

```
[92]: ## Parameters
kappa_1 = 1
K_B = 1e-3

parameter = {}
parameter['K_A'] = 1
parameter['K_B'] = K_B
parameter['kappa_r1'] = kappa_1
parameter['kappa_r2'] = 1
print(parameter)
```

```
{'K_A': 1, 'K_B': 0.001, 'kappa_r1': 1, 'kappa_r2': 1}
```

```
[93]: ## Chemostats
chemostats = ['A','B']
```

```
[94]: dcgain = {}
syss = {}
s,sc,sf,sys,X_ss,V_ss,dX_ss = stoichSensitivity(ECR_abg.
    ↳model(),parameter=parameter,chemostats=chemostats,X0=X0)
lam = 1.01
Outp = ['r1','r2']
Inp = ['sA','sr2']
t_last = 2/kappa_1
for outp in Outp:
    for inp in Inp:
        dat,y_step,t,sys = simSensitivity(s,sc,sf,sys,X_ss,V_ss,dX_ss,
            ↳parameter=parameter,inp=[inp],outp=[outp],lam=lam,t_last=t_last)
        syss[inp] = sys
#     g = con.dcgain(sys)
    g,tau = tfProps(sys)
    dcgain[inp] = g
```

```


    #print(g)
    if Titles:
        plt.title(f'{inp} (g = {g:.3f}; tau = {tau:0.1f})')
    plotSensitivity(dat, reactions=[outp])
    plotLines()
    Savefig('ECR_'+inp+'_'+outp)
    plt.show()



```


Steady-state finder error: 1.26e-15

X_{ss} = [1. 1. 3.34 6.66 1. 1. 1. 1. 1. 1.]

V_{ss} = [3.33 3.33]








5.2.1 Vary λ

```
[95]: inp = 'sA'
      outp = ['r2']
      for lam in [1.01, 1.1, 2]:
          dat, y_step, t, sys = simSensitivity(s, sc, sf, Sys, X_ss, V_ss, dX_ss,
                                              parameter=parameter, inp=[inp], outp=outp, lam=lam, t_last=t_last)
          # print(con.dcgain(sys))
          g, tau = tfProps(sys)
          if Titles:
              plt.title(f'{inp} (g = {g:.3f})')
          plotSensitivity(dat, reactions=outp)
          plotLines()
      Savefig('ECR_lambda')
```



```
[96]: ## Show system
      #Sys
```

```
[97]: ## Show system TFs
      con.tf(syss['sA'])
```

```
[97]:
```

$$\frac{6.671}{s + 3.001}$$

```
[98]: con.tf(syss['sr2'])
```

```
[98]:
```

$$\frac{3.329s + 6.658}{s + 3.001}$$

5.2.2 Simulate over flow range - quasi steady-state

```
[99]: def QuasiSteadyState(Inp=['sAct', 'sInh'], points=10, x_max=100):
```

```
    ## Extract info
    species = s['species']
    reaction = s['reaction']

    ### Simulate over flow range.
    ## Slow ramp for x_A
    X_chemo = {}
    t_d = 1e3
    t_last = 1e6
```

```

#     points = 50
t = np.linspace(0,t_last,points)
x_0 = 0.1
X0[species.index('A')] = x_0
slope = (x_max-x_0)/(t_last-t_d)
X_chemo['A'] = f'({x_0} + {slope}*(t-{t_d})*(1*(t>{t_d})))'
print(X_chemo)

## Steady-state
X_ss,V_ss = SteadyState(s,sc,parameter=parameter,X0=X0)

## Simulate
ndat = st.
→sim(s,sc=sc,t=t,parameter=parameter,X0=X_ss,X_chemo=X_chemo,quiet=quiet)

## Plot
#     st.plot(s,ndat,species=['E0','E','C'],reaction=['r2'])

## Plot flow v X_A
ylabel = r'$\Delta f_2/\Delta \lambda$'
X_A = ndat['X'][:,species.index('A')]
V_2 = ndat['V'][:,reaction.index('r2')]
plt.plot(X_A,V_2,lw=5)
plt.grid()
plt.xlabel('$\lambda_{X_A}$')
plt.ylabel('$f$')

sysname = s['name']
plotname = f'{sysname}_flow'
Savefig(plotname)
plt.show()
plt.clf()

## Compute sensitivity gain for each steady-state
X = ndat['X']
DCgain = {}
Tau = {}

for inp in Inp:
    DCgain[inp] = []
    Tau[inp] = []
    for x in X:
        ## Linearise about this steady-state
        Sys = st.lin(s,sc,x_ss=x,parameter=parameter,
                    quiet=quiet)

        ## Extract relevant subsystems
        outp = ['r1']
        sys = extractSubsystem(Sys,sc,sf,inp=[inp],outp=outp)
#         dcgain = con.dcgain(sys)
        dcgain,tau = tfProps(sys)

```

```

#         print(dcgain)
        DCgain[inp].append(dcgain)
        Tau[inp].append(tau)

# plt.plot(X_A,V_2,lw=6,label='flow')
INP = ''
for inp in Inp:
    plt.plot(X_A,DCgain[inp],label=inp[1:],lw=5)
    INP += inp+'_'
plt.legend()
plt.grid()
plt.xlabel('$X_A$')
plt.ylabel(ylabel)
plotname = f'{sysname}_{INP}X'
Savefig(plotname)
plt.show()

# plt.plot(X_A,V_2,lw=6,label='flow')
## Plot DC gain v flow
for inp in Inp:
    plt.plot(V_2,DCgain[inp],label=inp[1:],lw=5)

plt.legend()
plt.grid()
plt.xlabel('$f$')
ylabel = '$g_{\infty}$'
plt.ylabel(ylabel)
plotname = f'{sysname}_{INP}f'
Savefig(plotname)
plt.show()

## Plot time-constant v flow
for inp in Inp:
    plt.plot(V_2,Tau[inp],label=inp[1:],lw=5)

plt.legend()
plt.grid()
plt.xlabel('$f$')
plt.ylabel(r'$\tau$')
plotname = f'{sysname}_{INP}f_tau'
Savefig(plotname)
plt.show()



```



5.2.3 Simulate over flow range - quasi steady-state

```
[100]: QuasiSteadyState(Inp=['sr1','sr2'],points=50)
```

```
{'A': '(0.1 + 0.0001*(t-1000.0)*(1*(t>1000.0)))'}
```

Steady-state finder error: 7.85e-17






5.3 Example: Modulated Enzyme-catalysed reaction

```
[101]: sbg.model('ecr_abg.svg')
import ecr_abg
imp.reload(ecr_abg)
```

```
disp.SVG('ecr_abg.svg')
```

[101] :



```
[102]: ## Stoichiometry
s0 = st.stoich(ecr_abg.model(),quiet=quiet)
species = s0['species']
n_X = s0['n_X']
n_V = s0['n_V']
```

```
[103]: ## Initial states (for sensitivity system)
# e0 = 10
XX0 = {}
# XX0['A'] = 1
XX0['E'] = e0/3
XX0['E0'] = e0/3
XX0['C'] = e0/3
XX0['Inh'] = 1
X0 = np.ones(2*n_X+n_V)

for spec in XX0:
    X0[species.index(spec)] = XX0[spec]
```

```
[104]: ## Parameters
parameter = {}
parameter['K_A'] = 1
parameter['K_B'] = K_B
# parameter['K_F'] = 1
# parameter['K_G'] = 1
parameter['kappa_r0'] = 1
parameter['kappa_r1'] = kappa_1
parameter['kappa_r2'] = 1
parameter['K_E0'] = 1
print(parameter)
```

```
{'K_A': 1, 'K_B': 0.001, 'kappa_r0': 1, 'kappa_r1': 1, 'kappa_r2': 1, 'K_E0': 1}
```



```
[105]: ## Chemostats
chemostats = ['A', 'B', 'Act', 'Inh']
```

```
[106]: dcgain = {}
syss = {}
print(s['species'])
s,sc,sf,Sys,X_ss,V_ss,dX_ss = stoichSensitivity(ecr_abg.
    ↳model(),parameter=parameter,chemostats=chemostats,X0=X0)
lam = 1.1
outp = ['r1','r2']
Inp = ['sA','sr1','sr2','sAct','sInh']
#Inp = ['sAct','sInh','sA','sB']
t_last = 4
for inp in Inp:
    dat,y_step,t,sys = simSensitivity(s,sc,sf,Sys,X_ss,V_ss,dX_ss,
        ↳
    ↳parameter=parameter,inp=[inp],outp=outp,lam=lam,t_last=t_last)
    syss[inp] = sys
    print(sys)
#    g = con.dcgain(sys)[0][0]
    g,tau = tfProps(sys)
    dcgain[inp] = g
    print(f'g = {g:0.2f}, tau = {tau:0.2f}')
    if Titles:
        plt.title(f'{inp} (g = {g:.3f})')
    plotSensitivity(dat,reactions=outp)
    plotLines()
#    plt.hlines(g,min(t),max(t),color='black',ls='dashed')
    Savefig('ecr_'+inp)
    plt.show()
```


```
['A', 'B', 'C', 'E', 'sA', 'sB', 'sC', 'sE', 'sr1', 'sr2']
Steady-state finder error: 1.66e-15
X_ss = [1. 1. 1. 2. 4. 4. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1.]
V_ss = [-8.88e-16  2.00e+00  2.00e+00]
A = [[-1.5 -0.5]
      [-0.5 -3.5]]

B = [[ 0. ]
      [-5.66]]

C = [[ 0.    1.41]
      [ 0.71 -0.71]]

D = [[4.]
      [0.]]

g = 1.60, tau = 0.32
```




```
A = [[-1.5  0.5]
      [ 0.5 -3.5]]
```

```
B = [[6.65e-16]
      [2.83e+00]]
```

```
C = [[ 0.   -1.41]
      [ 0.71  0.71]]
```

```
D = [[2.]
      [0.]]
```

```
g = 0.80, tau = 0.32
```




```
A = [[-1.5  0.5]
      [ 0.5 -3.5]]
```

```
B = [[-6.65e-16]
      [-2.83e+00]]
```

```
C = [[ 0.  -1.41]
      [ 0.71  0.71]]
```

```
D = [[0.]
      [2.]]
```

```
g = 1.20, tau = 0.32
```




$$A = \begin{bmatrix} -1.5 & 0.5 \\ 0.5 & -3.5 \end{bmatrix}$$

$$B = \begin{bmatrix} -2.83 \\ 2.83 \end{bmatrix}$$

$$C = \begin{bmatrix} 0. & 1.41 \\ -0.71 & -0.71 \end{bmatrix}$$

$$D = \begin{bmatrix} 0. \\ 0. \end{bmatrix}$$

$$g = 0.80, \tau = 0.40$$




```
A = [[-1.5  0.5]
      [ 0.5 -3.5]]
```

```
B = [[-2.83]
      [ 2.83]]
```

```
C = [[ 0.  -1.41]
      [ 0.71  0.71]]
```

```
D = [[0.]
      [0.]]
```

```
g = -0.80, tau = 0.40
```




5.3.1 Vary λ

[107]: tau

[107]: 0.39992001599680105

```
[108]: inp = 'sInh'
      outp = ['r2']
      for lam in [1.01, 1.1, 2]:
          dat, y_step, t, sys = simSensitivity(s, sc, sf, Sys, X_ss, V_ss, dX_ss,
          ↳
          ↳parameter=parameter, inp=[inp], outp=outp, lam=lam, t_last=t_last)
          # print(con.dcgain(sys))
          g = con.dcgain(sys)
          if Titles:
              plt.title(f'{inp} (g = {g:.3f})')
          plotSensitivity(dat, reactions=outp)
          plotLines()
      Savefig('ecr_lambda')
```



```
[109]: ## Show system
#Sys
```

```
[110]: ## Show system TFs
con.tf(syss['sAct'])
```

```
[110]:
```

$$\begin{bmatrix} \frac{3.999s+3.995}{s^2+5.001s+5.001} \\ \frac{-0.003999s+3.995}{s^2+5.001s+5.001} \end{bmatrix}$$

```
[111]: con.tf(syss['sInh'])
```

```
[111]:
```

$$\begin{bmatrix} \frac{-3.999s-3.995}{s^2+5.001s+5.001} \\ \frac{0.003999s-3.995}{s^2+5.001s+5.001} \end{bmatrix}$$

```
[112]: ## Test model reduction - truncate
method = 'truncate'
sys = syss['sInh']
g,tau = tfProps(sys)
print(f'g = {g:.2f}, tau = {tau:.2f}')
sys1 = con.balred(sys,orders=1,method=method)
# print(con.dcgain(sys))
# print(con.dcgain(sys1))
con.tf(sys1)
g,tau = tfProps(sys1)
print(f'g = {g:.2f}, tau = {tau:.2f}')
```

```


t = np.linspace(0,5)
step = con.step_response(sys,T=t)
step1 = con.step_response(sys1,T=t)
plt.plot(t,step.outputs[:,0,:].T,label='System')
plt.plot(t,step1.outputs[:,0,:].T,label='Reduced')
plt.legend()
plt.grid()
plotLines()

```

```

g = -0.80, tau = 0.40
g = -1.16, tau = 0.40

```



```

[113]: ## Test model reduction - matchdc
method = 'matchdc'
sys = syss['sInh']
g,tau = tfProps(sys)
print(f'g = {g:.2f}, tau = {tau:.2f}')
sys1 = con.balred(sys,orders=1,method=method)
# print(con.dcgain(sys))
# print(con.dcgain(sys1))
con.tf(sys1)
g,tau = tfProps(sys1)
print(f'g = {g:.2f}, tau = {tau:.2f}')


t = np.linspace(0,5)
step = con.step_response(sys,T=t)
step1 = con.step_response(sys1,T=t)
plt.plot(t,step.outputs[:,0,:].T,label='System')
plt.plot(t,step1.outputs[:,0,:].T,label='Reduced')

```



```
plt.legend()
plt.grid()
plotLines()
```

```
g = -0.80, tau = 0.40
g = -0.80, tau = 0.40
```







5.3.2 Simulate over flow range - quasi steady-state

```
[114]: QuasiSteadyState(Inp=['sAct', 'sInh'], points=100)
```

```
{'A': '(0.1 + 0.0001*(t-1000.0)*(1*(t>1000.0)))'}
```

Steady-state finder error: 7.85e-17









5.3.3 Simulate over flow range - quasi steady-state

```
[115]: QuasiSteadyState(Inp=['sr1', 'sr2'], points=100)
```

```
{'A': '(0.1 + 0.0001*(t-1000.0)*(1*(t>1000.0)))'}
```

Steady-state finder error: 7.85e-17









5.3.4 Simulate over flow range - quasi steady-state

```
[116]: QuasiSteadyState(Inp=['sA'],points=100)
```

```
{'A': '(0.1 + 0.0001*(t-1000.0)*(1*(t>1000.0)))'}
```

Steady-state finder error: 7.85e-17





5.3.5 Sloppy parameters

```
[117]: imp.reload(slp)
       for t_last in [0,1e2]:
```

```

if t_last==0:
    t = None
else:
    t = np.linspace(0,t_last,100)

sloppyBoth(Sys,['sr1','sr2'],['r1','r2'],t=t)
sloppyBoth(Sys,['sE','sC'],['r1','r2'],t=t)
sloppyBoth(Sys,['sA','sB'],['r1','r2'],t=t)


```

ecr

```

t_f = 5.00
H:
\sqrt{\sigma_1} \&= 2 \& V_1\Lambda \&= + 0.84 \lambda_{r2} + 0.55 \lambda_{r1}
\sqrt{\sigma_2} \&= 0.39 \& V_2\Lambda \&= + 0.84 \lambda_{r1} - 0.55 \lambda_{r2}
H_{ss}:
\sqrt{\sigma_1} \&= 2 \& V_1\Lambda \&= + 0.83 \lambda_{r2} + 0.55 \lambda_{r1}
\sqrt{\sigma_2} \&= 3.2e-05 \& V_2\Lambda \&= + 0.83 \lambda_{r1} - 0.55 \lambda_{r2}
Direct:
\sqrt{\sigma_1} \&= 1.4 \& V_1\Lambda \&= + 0.83 \lambda_{r2} + 0.55 \lambda_{r1}

```



ecr

```

t_f = 5.00
H:
\sqrt{\sigma_1} \&= 1.4 \& V_1\Lambda \&= + 0.95 \lambda_{E} + 0.30 \lambda_{C}
\sqrt{\sigma_2} \&= 0.71 \& V_2\Lambda \&= + 0.95 \lambda_{C} - 0.30 \lambda_{E}

```



H_{ss}:

$$\sqrt{\sigma_1} = 1.3 \text{ \& } V_1 \backslash \text{Lambda} = + 0.89 \lambda_E + 0.45 \lambda_C$$

$$\sqrt{\sigma_2} = 3.2\text{e-}05 \text{ \& } V_2 \backslash \text{Lambda} = + 0.89 \lambda_C - 0.45 \lambda_E$$

Direct:

$$\sqrt{\sigma_1} = 0.89 \text{ \& } V_1 \backslash \text{Lambda} = + 0.89 \lambda_E + 0.45 \lambda_C$$



ecr

$$t_f = 5.00$$

H:

$$\sqrt{\sigma_1} = 2.3 \text{ \& } V_1 \backslash \text{Lambda} = + 1.00 \lambda_A - 0.00 \lambda_B$$

$$\sqrt{\sigma_2} = 0.0014 \text{ \& } V_2 \backslash \text{Lambda} = + 1.00 \lambda_B + 0.00 \lambda_A$$


H_{ss}:

$$\sqrt{\sigma_1} = 2.3 \text{ \& } V_1 \backslash \text{Lambda} = + 1.00 \lambda_A - 0.00 \lambda_B$$

$$\sqrt{\sigma_2} = 3.2\text{e-}05 \text{ \& } V_2 \backslash \text{Lambda} = + 1.00 \lambda_B + 0.00 \lambda_A$$

Direct:

$$\sqrt{\sigma_1} = 1.6 \text{ \& } V_1 \backslash \text{Lambda} = + 1.00 \lambda_A$$



ecr

$t_f = 100.00$

H:

$\sqrt{\sigma_1} \approx 2 \& V_1 \backslash \Lambda \approx + 0.83 \backslash \lambda_{r2} + 0.55 \backslash \lambda_{r1}$

$\sqrt{\sigma_2} \approx 0.2 \& V_2 \backslash \Lambda \approx + 0.83 \backslash \lambda_{r1} - 0.55 \backslash \lambda_{r2}$


H_{ss}:

$\sqrt{\sigma_1} \approx 2 \& V_1 \backslash \Lambda \approx + 0.83 \backslash \lambda_{r2} + 0.55 \backslash \lambda_{r1}$

$\sqrt{\sigma_2} \approx 3.2e-05 \& V_2 \backslash \Lambda \approx + 0.83 \backslash \lambda_{r1} - 0.55 \backslash \lambda_{r2}$

Direct:

$\sqrt{\sigma_1} \approx 1.4 \& V_1 \backslash \Lambda \approx + 0.83 \backslash \lambda_{r2} + 0.55 \backslash \lambda_{r1}$



ecr

t_f = 100.00

H:

$\sqrt{\sigma_1} \approx 1.3 \ \& \ V_1 \backslash \Lambda \approx + 0.92 \ \lambda_{\{E\}} + 0.40 \ \lambda_{\{C\}}$

$\sqrt{\sigma_2} \approx 0.4 \ \& \ V_2 \backslash \Lambda \approx + 0.92 \ \lambda_{\{C\}} - 0.40 \ \lambda_{\{E\}}$


H_ss:

$\sqrt{\sigma_1} \approx 1.3 \ \& \ V_1 \backslash \Lambda \approx + 0.89 \ \lambda_{\{E\}} + 0.45 \ \lambda_{\{C\}}$

$\sqrt{\sigma_2} \approx 3.2\text{e-}05 \ \& \ V_2 \backslash \Lambda \approx + 0.89 \ \lambda_{\{C\}} - 0.45 \ \lambda_{\{E\}}$

Direct:

$\sqrt{\sigma_1} \approx 0.89 \ \& \ V_1 \backslash \Lambda \approx + 0.89 \ \lambda_{\{E\}} + 0.45 \ \lambda_{\{C\}}$



ecr

t_f = 100.00

H:

\sqrt{\sigma_1} \&= 2.3 \& V_1\Lambda \&= + 1.00 \lambda_{A} - 0.00 \lambda_{B}

\sqrt{\sigma_2} \&= 0.00072 \& V_2\Lambda \&= + 1.00 \lambda_{B} + 0.00 \lambda_{A}


H_ss:

\sqrt{\sigma_1} \&= 2.3 \& V_1\Lambda \&= + 1.00 \lambda_{A} - 0.00 \lambda_{B}

\sqrt{\sigma_2} \&= 3.2e-05 \& V_2\Lambda \&= + 1.00 \lambda_{B} + 0.00 \lambda_{A}

Direct:

\sqrt{\sigma_1} \&= 1.6 \& V_1\Lambda \&= + 1.00 \lambda_{A}



```
[118]: imp.reload(slp)
Outp = ['r1']
Inp_reac = ['sr1', 'sr2']
def PrintSloppy(Inp, Outp, GainOnly=True, tf=None):
    blurb = '\n*****\n'

    if tf is None:
        t = None
    else:
        t = np.linspace(0, tf)

    for outp in Outp:
        print(blurb, outp, blurb)
        sys = extractSubsystem(Sys, sc, sf, Inp, [outp])
        # print(con.dcgain(sys))
        gain = con.dcgain(sys)[0]
        norm = np.sum(gain*gain)
        ngain = gain/np.sqrt(norm)
        # print(norm, gain/np.sqrt(norm))
        H, eig, eigv, t = slp.Sloppy(sys, GainOnly=GainOnly, small=1e-10, t=tf)
        slp.SloppyPrint(eig, eigv, Inp, min_eig=0.0, min_eigv=0.05, max_eigs=2)
        if GainOnly:
            print('Direct')
            slp.SloppyPrint([norm], np.array([ngain]).T, Inp, min_eig=0.
→0, min_eigv=0.05, max_eigs=2)
        # print(eigv[:, 0])
        # print(ngain)
```

```

## Reactions
for tf in [None,1e2]:
    for GainOnly in [True,False]:
        print('\nGainOnly =',GainOnly,'; tf =',tf)
        PrintSloppy(Inp_reac,Outp,GainOnly=GainOnly,tf=tf)

```

GainOnly = True ; tf = None

r1

$\sqrt{\sigma_1} \approx 1.4 \cdot V_1 \cdot \Lambda \approx + 0.83 \lambda_{r2} + 0.55 \lambda_{r1}$
 $\sqrt{\sigma_2} \approx 1e-05 \cdot V_2 \cdot \Lambda \approx + 0.83 \lambda_{r1} - 0.55 \lambda_{r2}$
 Direct
 $\sqrt{\sigma_1} \approx 1.4 \cdot V_1 \cdot \Lambda \approx + 0.83 \lambda_{r2} + 0.55 \lambda_{r1}$

GainOnly = False ; tf = None

r1

$\sqrt{\sigma_1} \approx 1.4 \cdot V_1 \cdot \Lambda \approx + 0.79 \lambda_{r2} + 0.62 \lambda_{r1}$
 $\sqrt{\sigma_2} \approx 0.29 \cdot V_2 \cdot \Lambda \approx + 0.79 \lambda_{r1} - 0.62 \lambda_{r2}$

GainOnly = True ; tf = 100.0

r1

$\sqrt{\sigma_1} \approx 1.4 \cdot V_1 \cdot \Lambda \approx + 0.83 \lambda_{r2} + 0.55 \lambda_{r1}$
 $\sqrt{\sigma_2} \approx 1e-05 \cdot V_2 \cdot \Lambda \approx + 0.83 \lambda_{r1} - 0.55 \lambda_{r2}$
 Direct
 $\sqrt{\sigma_1} \approx 1.4 \cdot V_1 \cdot \Lambda \approx + 0.83 \lambda_{r2} + 0.55 \lambda_{r1}$

GainOnly = False ; tf = 100.0

r1

$\sqrt{\sigma_1} \approx 1.4 \cdot V_1 \cdot \Lambda \approx + 0.83 \lambda_{r2} + 0.56 \lambda_{r1}$
 $\sqrt{\sigma_2} \approx 0.069 \cdot V_2 \cdot \Lambda \approx + 0.83 \lambda_{r1} - 0.56 \lambda_{r2}$

[]:

References