



SIMATS Online Programming Lab
C PROGRAMMING

Gayathri B R
192521330RB

QUESTIONS 8 / 8 completed

Sum-Avg

SUM-AVG
Write a program that takes a list of numbers as input and computes the sum and average of the numbers.

PROGRAM EDITOR
C
Run Save

```
1 #include<stdio.h>
2 int main()
3 {
4     int a,b,c,sum=0;
5     float avg;
6     scanf ("%d%d%d",&a,&b,&c);
7     sum=a+b+c;
8     avg=sum/3.0;
9     printf("sum=%d avg=%2f",sum,avg);
10    return 0;
11 }
```

INPUT
11 22 33



SIMATS Online Programming Lab
C PROGRAMMING

Gayathri B R
192521330RB

QUESTIONS 8 / 8 completed

Max-Min

MAX-MIN
Write a program that takes three integers as input and prints the maximum and minimum of the three.

PROGRAM EDITOR
C
Run Save

```
1 #include<stdio.h>
2 int main()
3 {
4     int a,b,c;
5     scanf("%d %d %d",&a,&b,&c);
6     if(a>b && a>c)
7         printf("a is greatest");
8     else if (b>c)
9         printf("b is greatest");
10    else
11        printf("c is greatest");
12    printf("\n");
13    if(a<b && a<c)
14        printf("a is smallest");
15    else if (b<c)
16        printf("b is smallest");
```

INPUT
2 4 6



SIMATS Online Programming Lab
C PROGRAMMING

Gayathri B R
192521330RB

QUESTIONS 8 / 8 completed

Leap

LEAP
Write a program that determines whether a year is a leap year or not. A year is a leap year if it is divisible by 4, but not divisible by 100 unless it is also divisible by 400.

PROGRAM EDITOR
C
Run Save

```
1 #include<stdio.h>
2 int main()
3 {
4     int a;
5     printf("enter the value:\n");
6     scanf("%d",&a);
7     if((a%4==0 && a%100!=0)||a%400==0)
8         printf("a is leap year");
9     else
10        printf("a is not leap year");
11    return 0;
12 }
```

INPUT
2026

 **SIMATS**
ENGINEERING

SIMATS Online Programming Lab
C PROGRAMMING

Gayathri B R
192521330RB

QUESTIONS 8 / 8 completed

ODD EVEN

ODD EVEN

Write a program that checks whether a number is even or odd.

PROGRAM EDITOR

C

Run Save

```
1 #include<stdio.h>
2 int main()
3 {
4     int a;
5     printf("enter the value:");
6     scanf("%d",&a);
7     if(a%2==0)
8         printf("a is even");
9     else
10        printf("a is odd");
11    return 0;
12 }
```

INPUT

4

 **SIMATS**
ENGINEERING

SIMATS Online Programming Lab
C PROGRAMMING

Gayathri B R
192521330RB

QUESTIONS 8 / 8 completed

Convert

CONVERT

Write a program that converts Celsius to Fahrenheit. The formula is Fahrenheit = (Celsius * 1.8) + 32.

PROGRAM EDITOR

C

Run Save

```
1 #include<stdio.h>
2 int main()
3 {
4     float celsius,fahrenheit;
5     printf("enter temperature in celsius:");
6     scanf("%f",&celsius);
7     fahrenheit=(celsius*1.8)+32;
8     printf("temperature in fahrenheit = %.2f",fahrenheit);
9     return 0;
10 }
```

INPUT

25

QUESTIONS 8 / 8 completed

Arithmetic

ARITHMETIC

Write a program that takes two numbers as input and prints their sum, difference, product, and quotient.

PROGRAM EDITOR

C

Run

Save

```
1 #include<stdio.h>
2 int main()
3 {
4     int a,b;
5     printf("enter the a value:\n");
6     scanf("%d",&a);
7     printf("enter the b value:\n");
8     scanf("%d",&b);
9     printf("sum=%d\n",a+b);
10    printf("difference=%d\n",a-b);
11    printf("product=%d\n",a*b);
12    printf("quotient=%d\n",a/b);
13    return 0;
```

QUESTIONS 8 / 8 completed

Swap 2 No's

SWAP 2 NO'S

C Program to Swap Two Numbers.
Swapping two numbers in C programming means swapping the values of two variables.
For example, there are two variables m & n. Value of m is "2" & value of n is "3".

PROGRAM EDITOR

C

Run

Save

```
1 //SWAP PING 2 NUMBERS WITHOUT TEMP VAR
2 #include<stdio.h>
3 int main()
4 {
5     int a, b;
6     scanf("%d%d",&a,&b);
7     printf("before swapping a=%d b=%d\n",a,b);
8     a=a+b;
9     b=a-b;
10    a=a-b;
11    printf("after swapping a=%d b=%d",a,b);
12    return 0;
13 }
```

INPUT

10 20