



## A toolkit for DNA sequence analysis and manipulation

D. Pratas (pratas@ua.pt)

J. R. Almeida (joao.rafael.almeida@ua.pt)

A. J. Pinho (ap@ua.pt)

IEETA/DETI, University of Aveiro, Portugal

Version 1.7.17

# Contents

<b>1</b>	<b>Introduction</b>	<b>2</b>
1.1	Installation . . . . .	2
1.2	License . . . . .	2
<b>2</b>	<b>FASTQ tools</b>	<b>4</b>
2.1	Program goose-fastq2fasta . . . . .	5
<b>3</b>	<b>FASTA tools</b>	<b>7</b>
3.1	Program goose-fasta2seq . . . . .	7
3.2	Program goose-fastaextract . . . . .	8
3.3	Program goose-fastaextractbyread . . . . .	9
3.4	Program goose-fastainfo . . . . .	11
3.5	Program goose-mutatefasta . . . . .	12
3.6	Program goose-randfastaextrachars . . . . .	13
<b>4</b>	<b>Genomic sequence tools</b>	<b>16</b>
<b>5</b>	<b>Amino acid sequence tools</b>	<b>17</b>
5.1	Program goose-AminoAcidToGroup . . . . .	17
5.2	Program goose-ProteinToPseudoDNA . . . . .	18
<b>6</b>	<b>General purpose tools</b>	<b>21</b>
6.1	Program goose-reverse . . . . .	21
	<b>Bibliography</b>	<b>22</b>

# Chapter 1

## Introduction

Recent advances in DNA sequencing have revolutionized the field of genomics, making it possible for research groups to generate large amounts of sequenced data, very rapidly and at substantially lower cost. Its storage have been made using specific file formats, such as FASTQ and FASTA. Therefore, its analysis and manipulation is crucial [?]. Several frameworks for analysis and manipulation emerged, namely **GALAXY** [?], **GATK** [?], **HTSeq** [?], **MEGA** [?], among others. In the majority, these frameworks require licenses and do not provide a low level access to the information, since they are commonly approached by scripting or interfaces.

We describe **GOOSE**, a (free) novel toolkit for analyzing and manipulating FASTA-FASTQ formats and sequences (DNA, amino acids, text), with many complementary tools. The toolkit is for Linux-based systems, built for fast processing. **GOOSE** supports pipes for easy integration. It includes tools for information display, randomizing, edition, conversion, extraction, searching, calculation and visualization. **GOOSE** is prepared to deal with very large datasets, typically in the scale Gigabytes or Terabytes.

The toolkit is a command line version, using the prefix “goose-” followed by the suffix with the respective name of the program. **GOOSE** is implemented in C language and it is available, under GPLv3, at:

```
https://pratas.github.io/goose
```

### 1.1 Installation

For **GOOSE** installation, run:

```
git clone https://github.com/pratas/goose.git
cd goose/src/
make
```

### 1.2 License

The license is **GPLv3**. In resume, everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed. For details on the license, consult: <http://www.gnu.org/>

[licenses/gpl-3.0.html](#).

## Chapter 2

# FASTQ tools

Current available tools for FASTQ format analysis and manipulation include:

1. `goose-fastq2fasta`: it converts a FASTQ file format to a pseudo FASTA file.
2. `goose-fastq2mfasta`
3. `goose-fastqclustreads`
4. `goose-FastqExcludeN`
5. `goose-FastqExtractQualityScores`
6. `goose-FastqInfo`
7. `goose-FastqMaximumReadSize`
8. `goose-FastqMinimumLocalQualityScoreForward`
9. `goose-FastqMinimumLocalQualityScoreReverse`
10. `goose-FastqMinimumQualityScore`
11. `goose-FastqMinimumReadSize`
12. `goose-count`
13. `goose-extractreadbypattern`
14. `goose-fastqpack`
15. `goose-fastqsimulation`
16. `goose-FastqSplit`
17. `goose-FastqTrimm`
18. `goose-fastqunpack`

19. `goose-filter`
20. `goose-findnpos`
21. `goose-genrandomdna`
22. `goose-getunique`
23. `goose-info`
24. `goose-mfmotifcoords`
25. `goose-mutatefastq`
26. `goose-newlineonnewx`
27. `goose-period`
28. `goose-permuteseqbyblocks`
29. `goose-randfastqextrachars`
30. `goose-real2binthreshold`
31. `goose-reducematrixbythreshold`
32. `goose-renamehumanheaders`
33. `goose-searchphash`
34. `goose-seq2fasta`
35. `goose-seq2fastq`
36. `goose-SequenceToGroupSequence`
37. `goose-splitreads`
38. `goose-wsearch`

## 2.1 Program `goose-fastq2fasta`

The `goose-fastq2fasta` converts a FASTQ file format to a pseudo FASTA file. However, it does not align the sequence. Also, it extracts the sequence and adds a pseudo header.

For help type:

```
./goose-fastq2fasta -h
```

In the following subsections, we explain the input and output parameters.

## Input parameters

The `goose-fastq2fasta` program needs two streams for the computation, namely the input and output standard. The input stream is a FASTQ file.

The attribution is given according to:

```
Usage: ./goose-fastq2fasta [options] [--] args]
      or: ./goose-fastq2fasta [options]

It converts a FASTQ file format to a pseudo FASTA file.
It does NOT align the sequence.
It extracts the sequence and adds a pseudo header.

      -h, --help          show this help message and exit

Basic options
      < input.fastq      Input FASTQ file format (stdin)
      > output.fasta      Output FASTA file format (stdout)

Example: ./goose-fastq2fasta < input.fastq > output.fasta
```

An example on such an input file is:

```
@SRR001666.1 071112_SLXA-EAS1_s_7:5:1:817:345 length=72
GGGTGATGGCCGCTGCCGATGGCGTCAAATCCCACCAAGTTACCCTTAACAACCTTAAGGGTTTTCAAATAGA
+SRR001666.1 071112_SLXA-EAS1_s_7:5:1:817:345 length=72
IIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIII>IIIIII/
@SRR001666.2 071112_SLXA-EAS1_s_7:5:1:801:338 length=72
GTTTCAGGGATACGACGTTTGTATTTTAAGAATCTGAAGCAGAAGTCGATGATAATACGCGTCGTTTTATCAT
+SRR001666.2 071112_SLXA-EAS1_s_7:5:1:801:338 length=72
IIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIII>IIIII-I)8I
```

## Output

The output of the `goose-fastq2fasta` program a FASTA file.

An example, for the input, is:

```
GGGTGATGGCCGCTGCCGATGGCGTCAAATCCCACCAAGTTACCCTTAACAACCTTAAGGGTTTTCAAATAGA
GTTTCAGGGATACGACGTTTGTATTTTAAGAATCTGAAGCAGAAGTCGATGATAATACGCGTCGTTTTATCAT
```

## Chapter 3

# FASTA tools

Current available FASTA tools, for analysis and manipulation, are:

1. `goose-fasta2seq`: it converts a FASTA or Multi-FASTA file format to a seq.
2. `goose-fastaextract`: it extracts sequences from a FASTA file, which the range is defined by the user in the parameters.
3. `goose-fastaextractbyread`: it extracts sequences from each read in a Multi-FASTA file (splited by `\n`), which the range is defined by the user in the parameters.
4. `goose-fastainfo`: it shows the readed information of a FASTA or Multi-FASTA file format.
5. `goose-mutatefasta`: it reates a synthetic mutation of a fasta file given specific rates of editions, deletions and additions.
6. `goose-randfastaextrachars`: it substitutes in the DNA sequence the outside ACGT chars by random ACGT symbols.

### 3.1 Program `goose-fasta2seq`

The `goose-fasta2seq` converts a FASTA or Multi-FASTA file format to a seq.

For help type:

```
./goose-fasta2seq -h
```

In the following subsections, we explain the input and output paramters.

#### Input parameters

The `goose-fasta2seq` program needs two streams for the computation, namely the input and output standard. The input stream is a FASTA or Multi-FASTA file.

The attribution is given according to:



```
Usage: ./goose-fasta2seq [options] [[--] args]
      or: ./goose-fasta2seq [options]

It converts a FASTA or Multi-FASTA file format to a seq.

      -h, --help                show this help message and exit

Basic options
      < input.fasta             Input FASTA or Multi-FASTA file format (stdin)
      > output.seq              Output sequence file (stdout)

Example: ./goose-fasta2seq < input.fasta > output.seq
```

An example on such an input file is:

```
>AB000264 |acc=AB000264|descr=Homo sapiens mRNA
ACAAGACGGCCTCCTGCTGCTGCTGCTCTCCGGGGCCACGGCCCTGGAGGGTCCACCGCTGCCCTGCTGCCATTGTCCCC
GGCCCCACCTAAGGAAAAGCAGCCTCCTGACTTTCTCGCTTGGGCCGAGACAGCGAGCATATGCAGGAAGCGGCAGGAA
GTGGTTTGAGTGACCTCCGGGGCCCTCATAGGAGAGGAAGCTCGGGAGGTGGCCAGGCGGCAGGAAGCAGGCCAGTGCC
GCGAATCCGCGCGCCGGGACAGAATCTCCTGCAAAAGCCCTGCAGGAACCTTCTTCTGGAAGACCTTCTCCACCCCCCAGC
TAAAACCTCACCCATGAATGCTCACGCAAGTTTAATTACAGACCTGAA
>AB000263 |acc=AB000263|descr=Homo sapiens mRNA
ACAAGATGCCATTGTCCCCGGCCCTCCTGCTGCTGCTGCTCTCCGGGGCCACGGCCACCGCTGCCCTGCCCTGGAGGGT
GGCCCCACCGCGCGAGACAGCGAGCATATGCAGGAAGCGGCAGGAATAAGGAAAAGCAGCCTCTGACTTTCTCGCTTG
GTGGTTTGAGTGACCTCCCAGGCCAGTGCCGGGCCCTCATAGGAGAGGAAGCTCGGGAGGTGGCCAGGCGGCAGGAAG
GCGCACCCCCCAGCAATCCGCGCGCCGGGACAGAATGCCCTGCAGGAACCTTCTTCTGGAAGACCTTCTCCTCTGCAAA
TAAAACCTCACCCATGAATGCTCACGCAAGTTTAATTACAGACCTGAA
```

## Output

The output of the `goose-fasta2seq` program is a group sequence.

An example, for the input, is:

```
ACAAGACGGCCTCCTGCTGCTGCTGCTCTCCGGGGCCACGGCCCTGGAGGGTCCACCGCTGCCCTGCTGCCATTGTCCCC
GGCCCCACCTAAGGAAAAGCAGCCTCCTGACTTTCTCGCTTGGGCCGAGACAGCGAGCATATGCAGGAAGCGGCAGGAA
GTGGTTTGAGTGACCTCCGGGGCCCTCATAGGAGAGGAAGCTCGGGAGGTGGCCAGGCGGCAGGAAGCAGGCCAGTGCC
GCGAATCCGCGCGCCGGGACAGAATCTCCTGCAAAAGCCCTGCAGGAACCTTCTTCTGGAAGACCTTCTCCACCCCCCAGC
TAAAACCTCACCCATGAATGCTCACGCAAGTTTAATTACAGACCTGAAACAAGATGCCATTGTCCCCGGCCCTCCTGCTG
CTGCTGCTCTCCGGGGCCACGGCCACCGCTGCCCTGCCCTGGAGGGTGGCCCCACCGCGCGAGACAGCGAGCATATGCA
GGAAGCGGCAGGAATAAGGAAAAGCAGCCTCCTGACTTTCTCGCTTGGTGGTTTGAGTGACCTCCCAGGCCAGTGCCG
GGCCCCTCATAGGAGAGGAAGCTCGGGAGGTGGCCAGGCGGCAGGAAGGCGCACCCCCCAGCAATCCGCGCGCCGGGAC
AGAATGCCCTGCAGGAACCTTCTTCTGGAAGACCTTCTCCTCTGCAATAAACCTCACCCATGAATGCTCACGCAAGTT
TAATTACAGACCTGAA
```

## 3.2 Program `goose-fastaextract`

The `goose-fastaextract` extracts sequences from a FASTA file, which the range is defined by the user in the parameters.

For help type:

```
./goose-fastextract -h
```

In the following subsections, we explain the input and output parameters.

## Input parameters

The `goose-fastextract` program needs two parameters, which defines the begin and the end of the extraction, and two streams for the computation, namely the input and output standard. The input stream is a FASTA file.

The attribution is given according to:

```
Usage: ./goose-fastextract [options] [--] args]
or: ./goose-fastextract [options]

It extracts sequences from a FASTA file.

    -h, --help                show this help message and exit

Basic options
    -i, --init=<int>          The first position to start the extraction (default 0)
    -e, --end=<int>           The last extract position (default 100)
    < input.fasta             Input FASTA or Multi-FASTA file format (stdin)
    > output.seq              Output sequence file (stdout)

Example: ./goose-fastextract -i <init> -e <end> < input.fasta > output.seq
```

An example on such an input file is:

```
>AB000264 |acc=AB000264|descr=Homo sapiens mRNA
ACAAGACGGCCTCCTGCTGCTGCTGCTCTCCGGGGCCACGGCCCTGGAGGTCCACCGCTGCCCTGCTGCCATTGTCCCC
GGCCCCACCTAAGGAAAAGCAGCCTCCTGACTTTCCTCGCTTGGGCCGAGACAGCGAGCATATGCAGGAAGCGGCAGGAA
GTGGTTTGAAGTGGACCTCCGGGCCCCCTCATAGGAGAGGAAGCTCGGGAGGTGGCCAGGCGGCAGGAAGCAGGCCAGTGCC
GCCAATCCGCGCGCCGGGACAGAATCTCTGCAAAGCCCTGCAGGAACCTTCTTCTGGAAGACCTTCTCCACCCCCCAGC
TAAACCTCACCCATGAATGCTCACGCAAGTTTAATTACAGACCTGAA
```

## Output

The output of the `goose-fastextract` program is a group sequence.

An example, using the value 0 as extraction starting point and the 50 as the end, for the provided input, is:

```
ACAAGACGGCCTCCTGCTGCTGCTGCTCTCCGGGGCCACGGCCCTGGAGG
```

## 3.3 Program `goose-fastextractbyread`

The `goose-fastextractbyread` extracts sequences from a FASTA or Multi-FASTA file, which the range is defined by the user in the parameters.

For help type:

```
./goose-fastaextractbyread -h
```

In the following subsections, we explain the input and output parameters.

## Input parameters

The `goose-fastaextractbyread` program needs two parameters, which defines the begin and the end of the extraction, and two streams for the computation, namely the input and output standard. The input stream is a FASTA or Multi-FASTA file.

The attribution is given according to:

```
Usage: ./goose-fastaextractbyread [options] [--] args]
or: ./goose-fastaextractbyread [options]
```

It extracts sequences from each read in a Multi-FASTA file (splited by \n)

```
-h, --help          show this help message and exit
```

### Basic options

```
-i, --init=<int>      The first position to start the extraction (default 0)
-e, --end=<int>       The last extract position (default 100)
< input.fasta        Input FASTA or Multi-FASTA file format (stdin)
> output.fasta        Output FASTA or Multi-FASTA file format (stdout)
```

```
Example: ./goose-fastaextractbyread -i <init> -e <end> < input.fasta > output.fasta
```

An example on such an input file is:

```
>AB000264 |acc=AB000264|descr=Homo sapiens mRNA
ACAAGACGGCCTCCTGCTGCTGCTGCTCCTCGGGGCCACGGCCCTGGAGGTTCCACGCTGCCCTGCTGCCATTGTCCCC
GGCCCCACCTAAGGAAAAGCAGCCTCCTGACTTTCCTCGCTTGGGCCGAGACAGCGAGCATATGCAGGAAGCGGCAGGAA
GTGGTTTGAGTGGACCTCCGGGCCCCCTCATAGGAGAGGAAGCTCGGGAGGTGGCCAGGCGGCAGGAAGCAGGCCAGTGCC
GCGAATCCGCGCGCCGGGACAGAATCTCCTGCAAAGCCCTGCAGGAACCTTCTTCTGGAAGACCTTCTCCACCCCCCAGC
TAAACCTCACCCATGAATGCTCACGCAAGTTTAATTACAGACCTGAA
>AB000263 |acc=AB000263|descr=Homo sapiens mRNA
ACAAGATGCCATTGTCCCCGGCCTCCTGCTGCTGCTGCTCCTCGGGGCCACGGCCACCGCTGCCCTGCCCTGGAGGGT
GGCCCCACCGCGCCGAGACAGCGAGCATATGCAGGAAGCGGCAGGAATAAGGAAAAGCAGCCTCCTGACTTTCCTCGCTTG
GTGGTTTGAGTGGACCTCCAGGCCAGTGCCGGGCCCCCTCATAGGAGAGGAAGCTCGGGAGGTGGCCAGGCGGCAGGAAG
GCGCACCCCCCAGCAATCCGCGCGCCGGGACAGAATGCCCTGCAGGAACCTTCTTCTGGAAGACCTTCTCCTCTGCAAA
TAAACCTCACCCATGAATGCTCACGCAAGTTTAATTACAGACCTGAA
```

## Output

The output of the `goose-fastaextractbyread` program is FASTA or Multi-FASTA file with the extracted sequences.

An example, using the value 0 as extraction starting point and the 50 as the end, for the provided input, is:

```
>AB000264 |acc=AB000264|descr=Homo sapiens mRNA
ACAAGACGGCCTCCTGCTGCTGCTGCTCTCCGGGGCCACGGCCCTGGAGG
>AB000263 |acc=AB000263|descr=Homo sapiens mRNA
ACAAGATGCCATTGTCCCCCGGCCTCCTGCTGCTGCTGCTCTCCGGGGCC
```

### 3.4 Program goose-fastainfo

The `goose-fastainfo` shows the readed information of a FASTA or Multi-FASTA file format. For help type:

```
./goose-fastainfo -h
```

In the following subsections, we explain the input and output paramters.

#### Input parameters

The `goose-fastainfo` program needs two streams for the computation, namely the input and output standard. The input stream is a FASTA or Multi-FASTA file.

The attribution is given according to:

```
Usage: ./goose-fastainfo [options] [--] args]
or: ./goose-fastainfo [options]

It shows read information of a FASTA or Multi-FASTA file format.

-h, --help          show this help message and exit

Basic options
< input.fasta       Input FASTA or Multi-FASTA file format (stdin)
> output            Output read information (stdout)

Example: ./goose-fastainfo < input.fasta > output
```

An example on such an input file is:

```
>AB000264 |acc=AB000264|descr=Homo sapiens mRNA
ACAAGACGGCCTCCTGCTGCTGCTGCTCTCCGGGGCCACGGCCCTGGAGGTTCCACGCTGCCCTGCTGCCATTGTCCCC
GGCCCCACCTAAGGAAAAGCAGCCTCCTGACTTTCTCGCTTGGGCCGAGACAGCGAGCATATGCAGGAAGCGGCAGGAA
GTGGTTTGTAGTGGACCTCCGGGGCCCTCATAGGAGAGGAAGCTCGGGAGGTGGCCAGGCGGCAGGAAGCAGGCCAGTGCC
GCGAATCCGCGCGCCGGGACAGAATCTCCTGCAAAGCCCTGCAGGAACCTTCTTCTGGAAGACCTTCTCCACCCCCCAGC
TAAACCTCACCCATGAATGCTCACGCAAGTTTAAATTACAGACCTGAA
>AB000263 |acc=AB000263|descr=Homo sapiens mRNA
ACAAGATGCCATTGTCCCCCGGCCTCCTGCTGCTGCTGCTCTCCGGGGCCACGGCCACCGCTGCCCTGCCCCCTGGAGGGT
GGCCCCACCGGCCGAGACAGCGAGCATATGCAGGAAGCGGCAGGAATAAGGAAAAGCAGCCTCCTGACTTTCTCGCTTG
GTGGTTTGTAGTGGACCTCCAGGCCAGTGCCGGGGCCCTCATAGGAGAGGAAGCTCGGGAGGTGGCCAGGCGGCAGGAAG
GCGCACCCCCCAGCAATCCGCGCGCCGGGACAGAATGCCCTGCAGGAACCTTCTTCTGGAAGACCTTCTCCTCCTGCAAA
TAAACCTCACCCATGAATGCTCACGCAAGTTTAAATTACAGACCTGAA
```

## Output

The output of the `goose-fastainfo` program is a set of informations related with the file readed.

An example, for the input, is:

```
Number of reads      : 2
Number of bases      : 736
MIN of bases in read : 368
MAX of bases in read : 368
AVG of bases in read : 368.0000
```

## 3.5 Program `goose-mutatefasta`

The `goose-mutatefasta` creates a synthetic mutation of a fasta file given specific rates of editions, deletions and additions. All these parameters are defined by the user, and they are optional.

For help type:

```
./goose-mutatefasta -h
```

In the following subsections, we explain the input and output parameters.

### Input parameters

The `goose-mutatefasta` program needs two streams for the computation, namely the input and output standard. However, optional settings can be supplied too, such as the starting point to the random generator, and the edition, deletion and insertion rates. Also, the user can choose to use the ACGTN alphabet in the synthetic mutation. The input stream is a FASTA or Multi-FASTA File.

The attribution is given according to:

```
Usage: ./goose-mutatefasta [options] [--] args]
      or: ./goose-mutatefasta [options]

Creates a synthetic mutation of a fasta file given specific rates of editions, deletions and additions

-h, --help                show this help message and exit

Basic options
< input.fasta             Input FASTA or Multi-FASTA file format (stdin)
> output.fasta            Output FASTA or Multi-FASTA file format (stdout)

Optional
-s, --seed=<int>          Starting point to the random generator
-e, --edit-rate=<dbl>     Defines the edition rate (default 0.0)
-d, --deletion-rate=<dbl> Defines the deletion rate (default 0.0)
-i, --insertion-rate=<dbl> Defines the insertion rate (default 0.0)
-a, --ACGTN-alphabet      When active, the application uses the ACGTN alphabet
```

```
Example: ./goose-mutatefasta -s <seed> -e <edit rate> -d <deletion rate> -i <insertion rate> -a <input.fasta>
```

An example on such an input file is:

```
>AB000264 |acc=AB000264|descr=Homo sapiens mRNA
ACAAGACGGCCTCCTGCTGCTGCTGCTCCTCGGGGCCACGGCCCTGGAGGTTCCACGCTGCCCTGCTGCCATTGTCCCC
GGCCCCACCTAAGGAAAAGCAGCCTCCTGACTTTCCTCGCTTGGGCCGAGACAGCGAGCATATGCAGGAAGCGGCAGGAA
GTGGTTTGAGTGGACCTCCGGGGCCCTCATAGGAGAGGAAGCTCGGGAGGTGGCCAGGCGGCAGGAAGCAGGCCAGTGCC
GCGAATCCGCGCGCCGGGACAGAATCTCCTGCAAAGCCCTGCAGGAACCTTCTTCTGGAAGACCTTCTCCACCCCCCAGC
TAAAACCTCACCCATGAATGCTCACGCAAGTTTAATTACAGACCTGAA
>AB000263 |acc=AB000263|descr=Homo sapiens mRNA
ACAAGATGCCATTGTCCCCGGCCTCCTGCTGCTGCTGCTCCTCGGGGCCACGGCCACCGCTGCCCTGCCCTGGAGGTT
GGCCCCACCGCGCGAGACAGCGAGCATATGCAGGAAGCGGCAGGAATAAGGAAAAGCAGCCTCCTGACTTTCCTCGCTTG
GTGGTTTGAGTGGACCTCCAGGCCAGTGCCGGGCCCTCATAGGAGAGGAAGCTCGGGAGGTGGCCAGGCGGCAGGAAG
GCGCACCCCCCAGCAATCCGCGCGCCGGGACAGAATGCCTGCAGGAACCTTCTTCTGGAAGACCTTCTCCTCCTGCAAA
TAAAACCTCACCCATGAATGCTCACGCAAGTTTAATTACAGACCTGAA
```

## Output

The output of the `goose-mutatefasta` program is a FASTA or Multi-FASTA file with the synthetic mutation of input file.

Using the seed value as 1 and the edition rate as 0.5, an example for this input, is:

```
>AB000264 |acc=AB000264|descr=Homo sapiens mRNA
ACGCAACGNATTCCTGCTGATCATANTGTNCCGCNCCCCNGCGACGGGNGCTCNCNNGCACACATNGTACCATTGTCCAC
NCTTNCANGTNANCGCTAGCAGGCTACNGTTTNTCCTCNCTANCCAAANCNGGCGTNNNTACACTGGCACGTGCAGGCA
TNGGTGGCGNGNCCCTCCGGNAACGGCACCGGAGACGAAGCTCGGNGGNTATACAGGTGTCANGAAACATCCCCGCGNC
GNGTGNCNNGAANCCANAGAGTATCTCACTCACAAACCCTGCGTGACNTCTAGAGNANGACCTTACNCACCNTCCCNNT
NNGTACCACACCAATGAACGCTGCAGAAAGTCTGTTTTNAGGNGNGCA
>AB000263 |acc=AB000263|descr=Homo sapiens mRNA
ATTTGAAGGCAANCGGNCCAGNAATNCGGNGGGTGCGCTCNTGTNGGCTACGGNCATCGGGCCCTGCTNTANTAAGCN
TGAACCACCGNTCGNNGCACTTAGCAATNGCGNAANCCGTCGGCACGGCGGAGACNAANCCGCTANTNNTTCCCGCTNA
ATGGNTGTACAAGACCNACTANACCANCCCTCCGTCACCACACTGGAGCGCANGATGGNNGCTGNCAGNAGCNNTGAG
GCGCTCCNTCCTANAAANCCGTGGNCGAGCNCCCTATGGNAGNGTGGGGGTTTTACCGGAAGACCNCTCGNGCCCTATGGG
AGCAATCANAANCTAGAAAGCTTACNGATGGTGANGAANTAGACTANG
```

## 3.6 Program `goose-randfastaextrachars`

The `goose-randfastaextrachars` substitutes in the DNA sequence the outside ACGT chars by random ACGT symbols. It works both in FASTA and Multi-FASTA file formats.

For help type:

```
./goose-randfastaextrachars -h
```

In the following subsections, we explain the input and output parameters.

## Input parameters

The `goose-randfastaextrachars` program needs two streams for the computation, namely the input and output standard. The input stream is a FASTA or Multi-FASTA file.

The attribution is given according to:

```
Usage: ./goose-randfastaextrachars [options] [--] args]
       or: ./goose-randfastaextrachars [options]

It substitutes in the DNA sequence the outside ACGT chars by random ACGT symbols.
It works both in FASTA and Multi-FASTA file formats

        -h, --help                show this help message and exit

Basic options
    < input.fasta                Input FASTA or Multi-FASTA file format (stdin)
    > output.fasta               Output FASTA or Multi-FASTA file format (stdout)

Example: ./goose-randfastaextrachars < input.fasta > output.fasta
```

An example on such an input file is:

```
>AB000264 |acc=AB000264|descr=Homo sapiens mRNA
ANAAGACGGCCTCCTGCTGCTGCTGCTCTCCGGGGCCACGNCCCTGGAGGGTCCNCCGCTGCCCTGCTGCCATTGNCNCC
NGCCCCACCTAAGGAAAAGCAGCCTCCTGACTTTCTCGCTTGGGCCGAGACAGCGAGCATATGCNGGAAGCGGCAGGAA
GNGGTTTGAGTGACCTCCNGGCCCTCATAGGAGAGGAAGCNGGGAGGTGGCCAGGCGGCAGGAAGCAGGCCAGTGNC
GCGAATCCGNGCGCGGGACAGAATCTCCTGCAAAGCCCTGCAGGAACCTTCTTCTGGAAGACCTTCTCCACCCCCCENN
TAAANNNTACCCATGAATGCTCAGCAANTTTAATTACAGACCTGAA
>AB000263 |acc=AB000263|descr=Homo sapiens mRNA
GCGAATCCGNGCGCGGGACAGAATCTCCTTCTCCACCCCCCENNNTGCAAAGCCCTGCAGGAACCTTCTTCTGGAAGACC
NGCCCCACCTAAGGAAAAGCAGCCTCCAGGAACCTGACTTTCTCGCTTGGGCCGAGACAGCGAGCATATGCNGGAAGCGG
ANAAGACGGCCTCCTGCTGCTGCTGCTCTCCGGGGCCACGNCCCTGGCNCAGGGTCCNCCGCTGCCCTGCTGCCATTGN
GAGGAAGCNGGGAGGTGGCCAGGCGGCAGGAAGCAGGCCAGTGNCNGGTTTGAGTGACCTCCNGGCCCTCATAGGA
TCACGCAANTTTAATTACAGACCTGAATAAANNNTACCCATGAATGC
```

## Output

The output of the `goose-randfastaextrachars` program is a FASTA or Multi-FASTA file.

An example, for the input, is:

```
>AB000264 |acc=AB000264|descr=Homo sapiens mRNA
ATAAGACGGCCTCCTGCTGCTGCTGCTCTCCGGGGCCACGGCCCTGGAGGGTCCCCGCTGCCCTGCTGCCATTGTCCCC
TGCCCCACCTAAGGAAAAGCAGCCTCCTGACTTTCTCGCTTGGGCCGAGACAGCGAGCATATGCGGGAAGCGGCAGGAA
GAGGTTTGAGTGACCTCCCGGCCCTCATAGGAGAGGAAGCCGGGAGGTGGCCAGGCGGCAGGAAGCAGGCCAGTGTC
GCGAATCCGGGCGCGGGACAGAATCTCCTGCAAAGCCCTGCAGGAACCTTCTTCTGGAAGACCTTCTCCACCCCCCTTG
TAAAAGATCACCCATGAATGCTCAGCAAAATTTAATTACAGACCTGAA
>AB000263 |acc=AB000263|descr=Homo sapiens mRNA
GCGAATCCGTGCGCGGGACAGAATCTCCTTCTCCACCCCCCATCTGCAAAGCCCTGCAGGAACCTTCTTCTGGAAGACC
GGCCCCACCTAAGGAAAAGCAGCCTCCAGGAACCTGACTTTCTCGCTTGGGCCGAGACAGCGAGCATATGCGGGAAGCGG
AGAAGACGGCCTCCTGCTGCTGCTGCTCTCCGGGGCCACGTCCCTGGCTCCAGGGTCTCCGCTGCCCTGCTGCCATTGC
```

GAGGAAGCGGGGAGGTGGCCAGGCGGCAGGAAGCAGGCCAGTGGCGGGTTTGAGTGGACCTCCTGGCCCCCATAGGA  
TCACGCAACTTTAATTACAGACCTGAATAAAATGTCACCCATGAATGC



## Chapter 4

# Genomic sequence tools

Current available genomic sequence tools, for analysis and manipulation, are:

1. `goose-mutatedna`
2. `goose-randseqextrachars`
3. `goose-geco`
4. `goose-gede`

## Chapter 5

# Amino acid sequence tools

Current available amino acid sequence tools, for analysis and manipulation, are:

1. `goose-AminoAcidToGroup`: it converts an amino acid sequence to a group sequence.
2. `goose-ProteinToPseudoDNA`: it converts an amino acid (protein) sequence to a pseudo DNA sequence.

### 5.1 Program `goose-AminoAcidToGroup`

The `goose-AminoAcidToGroup` converts an amino acid sequence to a group sequence.

For help type:

```
./goose-AminoAcidToGroup -h
```

In the following subsections, we explain the input and output parameters.

#### Input parameters

The `goose-AminoAcidToGroup` program needs two streams for the computation, namely the input and output standard. The input stream is an amino acid sequence. The attribution is given according to:

```
Usage: ./goose-AminoAcidToGroup [options] [--] args]
or: ./goose-AminoAcidToGroup [options]

It converts a amino acid sequence to a group sequence.

    -h, --help                show this help message and exit

Basic options
    < input.prot              Input amino acid sequence file (stdin)
    > output.group             Output group sequence file (stdout)

Example: ./goose-AminoAcidToGroup < input.prot > output.group
Table:
Prot      Group
R         P
```

```

H   P   Amino acids with electric charged side chains: POSITIVE
K   P
-   -
D   N
E   N   Amino acids with electric charged side chains: NEGATIVE
-   -
S   U
T   U
N   U   Amino acids with electric UNCHARGED side chains
Q   U
-   -
C   S
U   S
G   S   Special cases
P   S
-   -
A   H
V   H
I   H
L   H
M   H   Amino acids with hydrophobic side chains
F   H
Y   H
W   H
-   -
*   *   Others
X   X   Unknown

```

It can be used to group amino acids by properties, such as electric charge (positive and negative), uncharged side chains, hydrophobic side chains and special cases. An example on such an input file is:

```

IPFLLKKQFALADKLVL SKLRQLLGGR IKMMPCGGAKLEPAIGLFFHAIGINIKLGYGMTETTATVSCWHDFQFNPN SIG
TLMPKAEVKIGENNEILVRGGMVMKGYKKPEETAQAFTEDGFLKTGDAGEFDEQGNLFITDRIKELMKTSNGKYIAPQY
IESKIGKDKFIEQIAIIADAKKYVSALIVPCFDSLEEYAKQLNIKYHDRLELLKNSDILKMFE

```

## Output

The output of the `goose-AminoAcidToGroup` program is a group sequence.

An example, for the input, is:

```

HSHHHPPUHHHHNPHHHUPHPUHHSSPHPHSSSSHPHNSHHSHHHPHHSHUHPHSHSHUNUHUHUSHPNHUHUSUHS
UHHSPhNHPhSNUUNHHHPSSHHHP SHHPPSNNUHUHHUNNSHHPPUSNHSNNHNNUSUHHHUNPHPNHHPUUUSPHHHSUH
HNUPHSPNPHHN UHHHHHHNPHPHUHHHHSSHNUNHNNHPPUHUHPHPNPHNHHPUUNHHPHHN

```

## 5.2 Program `goose-ProteinToPseudoDNA`

The `goose-ProteinToPseudoDNA` converts an amino acid (protein) sequence to a pseudo DNA sequence. For help type:

```
./goose-ProteinToPseudoDNA -h
```

In the following subsections, we explain the input and output parameters.

## Input parameters

The `goose-ProteinToPseudoDNA` program needs two streams for the computation, namely the input and output standard. The input stream is an amino acid sequence. The attribution is given according to:

```
Usage: ./goose-ProteinToPseudoDNA [options] [--] args]
       or: ./goose-ProteinToPseudoDNA [options]

It converts a protein sequence to a pseudo DNA sequence.

       -h, --help           show this help message and exit

Basic options
  < input.prot             Input amino acid sequence file (stdin)
  > output.dna             Output DNA sequence file (stdout)

Example: ./goose-ProteinToPseudoDNA < input.prot > output.dna
Table:
Prot    DNA
A      GCA
C      TGC
D      GAC
E      GAG
F      TTT
G      GGC
H      CAT
I      ATC
K      AAA
L      CTG
M      ATG
N      AAC
P      CCG
Q      CAG
R      CGT
S      TCT
T      ACG
V      GTA
W      TGG
Y      TAC
*      TAG
X      GGG
```

It can be used to generate pseudo-DNA with characteristics passed by amino acid (protein) sequences. An example on such an input file is:

```
IPFLLKKQFALADKLVLSKLRQLLGGRICKMMPCGGAKLEPAIGLFFHAIGINIKLGYGMTETTATVSCWHDFQFNPNSIG
TLM PKAEVKIGENNEILVRGGMVMKGYKKPEETAQAFTEDGFLKTGDAGEFDEQGNLFITDRIKELMKTSNGKYIAPQY
IESKIGKDKFIEQIAIIADAKKYVSALIVPCFDSLEEYAKQLNIKYHDRLELLKNSDILKMFE
```

## Output

The output of the `goose-ProteinToPseudoDNA` program is a DNA sequence.

An example, for the input, is:

```
ATCCCGTTTCTGCTGAAAAACAGTTTGC ACTGGCAGACAAACTGGTACTGTCTAAACTGCGTCAGCTGCTGGGCGGCCG
TATCAAAATGATGCCGTGCGGCGGCGCAAAACTGGAGCCGGCAATCGGCCTGTTTTTTCATGCAATCGGCATCAACATCA
AACTGGGCTACGGCATGACGGAGACGACGGCAACGGTATCTTGCTGGCATGACTTTCAGTTTAACCCGAACCTCTATCGGC
ACGCTGATGCCGAAAGCAGAGGTAAAAATCGGCGAGAACACGAGATCCTGGTACGTGGCGGCATGGTAATGAAAGGCTA
CTACAAAAAACCGGAGGAGACGGCACAGGCATTTACGGAGGACGGCTTTCTGAAACGGGCGACGCAGGCGAGTTTGACG
AGCAGGGCAACCTGTTTATCACGGACCGTATCAAAGAGCTGATGAAAACGTCTAACGGCAAATACATCGCACCGCAGTAC
ATCGAGTCTAAATCGGCAAAGACAAATTTATCGAGCAGATCGCAATCATCGCAGACGCAAAAAATACGTATCTGCACT
GATCGTACCGTGCTTTGACTCTCTGGAGGAGTACGCAAAACAGCTGAACATCAAATACCATGACCGTCTGGAGCTGCTGA
AAAACTCTGACATCCTGAAAAATGTTTGAG
```

## Chapter 6

# General purpose tools

1. `goose-comparativemap`
2. `goose-BruteForceString`
3. `goose-char2line`
4. `goose-sum`
5. `goose-min`
6. `goose-minus`
7. `goose-max`
8. `goose-extract`
9. `goose-segment`
10. `goose-reverse`: it reverses the order of a sequence.

### 6.1 Program `goose-reverse`

The `goose-reverse` reverses the order of a sequence file.

For help type:

```
./goose-reverse -h
```

In the following subsections, we explain the input and output paramters.

#### Input parameters

The `goose-reverse` program needs two streams for the computation, namely the input and output standard. The input stream is a sequence file.

The attribution is given according to:

```
Usage: ./goose-reverse [options] [--] args]
or: ./goose-reverse [options]

It reverses the order of a sequence file.

-h, --help          show this help message and exit

Basic options
  < input.seq        Input sequence file (stdin)
  > output.seq       Output sequence file (stdout)

Example: ./goose-reverse < input.seq > output.seq
```

An example on such an input file is:

```
ACAAGACGGCCTCCTGCTGCTGCTCTCCGGGGCCACGGCCCTGGAGGGTCCACCGCTGCCCTGCTGCCATTGTCCCC
GGCCCCACCTAAGGAAAAGCAGCCTCCTGACTTTCTCTCGCTTGGGCCGAGACAGCGAGCATATGCAGGAAGCGGCAGGAA
GTGGTTTGAGTGACCTCCGGGGCCCTCATAGGAGAGGAAGCTCGGGAGGTGGCCAGGCGGCAGGAAGCAGGCCAGTGCC
GCGAATCCGCGCGCCGGGACAGAATCTCCTGCAAAGCCCTGCAGGAACCTTCTTCTGGAAGACCTTCTCCACCCCCCAGC
TAAAACCTCACCCATGAATGCTCACGCAAGTTTAAATTACAGACCTGAAACAAGATGCCATTGTCCCCCGGCCCTCCTGCTG
CTGCTGCTCTCCGGGGCCACGGCCACCGCTGCCCTGCCCTGGAGGGTGGCCCCACCGCCGAGACAGCGAGCATATGCA
GGAAGCGGCAGGAATAAGGAAAAGCAGCCTCCTGACTTTCTCTCGCTTGGTGGTTTGAGTGGAACCTCCCAGGCCAGTGCCG
GGCCCCCTCATAGGAGAGGAAGCTCGGGAGGTGGCCAGGCGGCAGGAAGGCGCACCCCCCAGCAATCCGCGCGCCGGGAC
AGAATGCCCTGCAGGAACCTTCTTCTGGAAGACCTTCTCTCTGCAATAAAACCTCACCCATGAATGCTCACGCAAGTT
TAATTACAGACCTGAA
```

## Output

The output of the **goose-reverse** program is a group sequence.

An example, for the input, is:

```
AAGTCCAGACATTAATTTGAACGCACTCGTAAGTACCCACTCCAAAATAAACGTCTCTCTTCCAGAAGGTCTTCTTCA
AGGACGTCCCGTAAGACAGGGCCGCGCCCTAACGACCCCCCACGCGGAAGGACGGCGGACCGGTGGAGGGCTCGAAGG
AGAGGATACTCCCCGGGCGGTGACCGGACCTCCAGGTGAGTTTGGTGGTTTCGCTCCTTTCAGTCTCCGACGAAAAGGA
ATAAGGACGGCGAAGGACGTATACGAGCGACAGAGCCGGCCACCCCGGTGGGAGGTCCCCGTCCCGTCGCCACCGGCACC
GGGGCCTCTCGTCGTCGTCCTCCGGCCCCCTGTTACCGTAGAACAAAGTCCAGACATTAATTTGAACGCACTCGTAA
GTACCCACTCCAAAATCGACCCCCCACCTCTTCCAGAAGGTCTTCTTCAAGGACGTCCCGAAACGTCTCTAAGACAGG
GCCGCGCGCCTAAGCGCCGTGACCGGACGAAGGACGGCGGACCGGTGGAGGGCTCGAAGGAGAGGATACTCCCCGGGCCCT
CCAGGTGAGTTTGGTGAAGGACGGCGAAGGACGTATACGAGCGACAGAGCCGGGTTCGCTCCTTTTCAGTCTCCGACGAA
AAGGAATCCACCCCGGCCCTGTTACCGTCGTCCTCGTCCGACCTGGGAGGTCCCGGCACCGGGGCCTCTCGTCGTCGTC
GTCTCCGGCAGAACA
```