UK POLICE EVIDENCE ADMISSIBILITY & BS EN 62676-4 DORI SPECIFICATION

CPS Admissible Forensics, F1.0 Super-Apertures & Solid Copper Cat6 PoE Standards

Lead Engineer: Gary Pearce (25+ Years Experience • Direct: 07860 244 274)
Organisation: ADI Communications • West Yorkshire & Lancashire Field Services
Insurance & Certification: £10,000,000 Public Liability Insurance • BS EN 62676-4 Adherence
Companion Field Debrief: tvandhomesecurity.blogspot.com/cctv-forensics

1. The Crown Prosecution Service (CPS) Admissibility Failure

Over 82% of domestic and commercial CCTV footage submitted to UK police forces (West Yorkshire, South Yorkshire, Lancashire) is rejected during Crown Prosecution Service (CPS) evidential reviews. The primary failure vector is insufficient pixel density at the target acquisition plane, caused by legacy 850nm infrared 'spider-web' flare, optical blooming, and compressed 1080p sensors. Under the UK Home Office Scientific Development Branch guidelines and BS EN 62676-4, footage cannot be legally used for biometric suspect identification unless it satisfies the mandatory 250 pixels per metre (px/m) threshold.

DORI Standard	Pixel Density	Evidential Legal Purpose	Maximum Distance (2.8mm Lens)	Maximum Distance (4.0
Detection	25 px/m	General human presence awareness	42.0 Metres	64.0 Metres
Observation	63 px/m	Clothing & vehicle colour verification	17.0 Metres	25.0 Metres
Recognition	125 px/m	Familiar person identification	8.5 Metres	13.0 Metres
Identification	250 px/m	CPS Court Proof (Facial Features)	4.2 Metres	6.5 Metres

2. Optical Aperture Physics: F1.0 ColorVu vs 850nm Infrared Flare

Standard infrared security cameras switch to monochrome IR illuminators below 1.0 Lux. This strips colour data (clothing, vehicle paint, hair pigment) and causes severe face blow-out when suspects approach within 3 metres. ADI Communications specifies Hikvision ColorVu G2 systems utilizing 1/1.2-inch large-format progressive scan CMOS sensors coupled with F1.0 super-apertures that capture 4x more ambient light than conventional F2.0 lenses. Supplemental 3000K warm white LEDs ensure full 24/7 colour rendition without blinding subjects.

PHYSICAL CABLING WARNING (COPPER-CLAD ALUMINIUM CCA PROHIBITION):
Under BS 6701 and CAI benchmarking standards, Copper-Clad Aluminium (CCA) cable is strictly banned on all ADI installations. CCA cables suffer from severe DC voltage drop over 25m PoE runs, brittle galvanic corrosion, and micro-fractures in cold British weather. Gary Pearce exclusively installs solid annealed electrolytic bare copper Cat6 U/UTP (0.57mm 23AWG) with dual-shielded exterior PE jackets and drip loops.

3. Field Verification & Diagnostic Tools

To calculate storage retention (H.265+ bitrate matrices) and run police crime risk assessments across 23 regional outward postcodes, access Gary Pearce's interactive cloud tools:
• **CCTV Storage Calculator:** gary-pearce-forensic-hub.web.app/storage-calculator

- **UK Crime Risk Checker:** gary-pearce-forensic-hub.web.app/crime-checker
- **Direct Engineer Consultation:** Call Gary Pearce on **07860 244 274** for turnkey design and installation.