

**NAME****gbz80** — CPU opcode reference**DESCRIPTION**

This is the list of opcodes supported by `rgbasm(1)`, including a short description, the number of bytes needed to encode them and the number of CPU cycles at 1MHz (or 2MHz in GBC dual speed mode) needed to complete them.

Note: All arithmetic/logic operations that use register **A** as destination can omit the destination as it is assumed to be register **A** by default. The following two lines have the same effect:

```
OR A,B
OR B
```

**LEGEND**

List of abbreviations used in this document.

*r8* Any of the 8-bit registers (**A**, **B**, **C**, **D**, **E**, **H**, **L**).

*r16* Any of the general-purpose 16-bit registers (**BC**, **DE**, **HL**).

*n8* 8-bit integer constant.

*n16* 16-bit integer constant.

*e8* 8-bit offset (**-128** to **127**).

*u3* 3-bit unsigned integer constant (**0** to **7**).

*cc* Condition codes:  
**Z** Execute if Z is set.  
**NZ** Execute if Z is not set.  
**C** Execute if C is set.  
**NC** Execute if C is not set.  
**! cc** Negates a condition code.

*vec* One of the **RST** vectors (*0x00*, *0x08*, *0x10*, *0x18*, *0x20*, *0x28*, *0x30*, and *0x38*).

**INSTRUCTION OVERVIEW****8-bit Arithmetic and Logic Instructions**

```
ADC A,r8
ADC A,[HL]
ADC A,n8
ADD A,r8
ADD A,[HL]
ADD A,n8
AND A,r8
AND A,[HL]
AND A,n8
CP A,r8
CP A,[HL]
CP A,n8
DEC r8
DEC [HL]
```

**INC r8**  
**INC [HL]**  
**OR A,r8**  
**OR A,[HL]**  
**OR A,n8**  
**SBC A,r8**  
**SBC A,[HL]**  
**SBC A,n8**  
**SUB A,r8**  
**SUB A,[HL]**  
**SUB A,n8**  
**XOR A,r8**  
**XOR A,[HL]**  
**XOR A,n8**

#### **16-bit Arithmetic Instructions**

**ADD HL,r16**  
**DEC r16**  
**INC r16**

#### **Bit Operations Instructions**

**BIT u3,r8**  
**BIT u3,[HL]**  
**RES u3,r8**  
**RES u3,[HL]**  
**SET u3,r8**  
**SET u3,[HL]**  
**SWAP r8**  
**SWAP [HL]**

#### **Bit Shift Instructions**

**RL r8**  
**RL [HL]**  
**RLA**  
**RLC r8**  
**RLC [HL]**  
**RLCA**  
**RR r8**  
**RR [HL]**  
**RRA**  
**RRC r8**  
**RRC [HL]**  
**RRCA**  
**SLA r8**  
**SLA [HL]**  
**SRA r8**  
**SRA [HL]**  
**SRL r8**  
**SRL [HL]**

**Load Instructions**

**LD r8,r8**  
**LD r8,n8**  
**LD r16,n16**  
**LD [HL],r8**  
**LD [HL],n8**  
**LD r8,[HL]**  
**LD [r16],A**  
**LD [n16],A**  
**LDH [n16],A**  
**LDH [C],A**  
**LD A,[r16]**  
**LD A,[n16]**  
**LDH A,[n16]**  
**LDH A,[C]**  
**LD [HLI],A**  
**LD [HLD],A**  
**LD A,[HLI]**  
**LD A,[HLD]**

**Jumps and Subroutines**

**CALL n16**  
**CALL cc,n16**  
**JP HL**  
**JP n16**  
**JP cc,n16**  
**JR e8**  
**JR cc,e8**  
**RET cc**  
**RET**  
**RETI**  
**RST vec**

**Stack Operations Instructions**

**ADD HL,SP**  
**ADD SP,e8**  
**DEC SP**  
**INC SP**  
**LD SP,n16**  
**LD [n16],SP**  
**LD HL,SP+e8**  
**LD SP,HL**  
**POP AF**  
**POP r16**  
**PUSH AF**  
**PUSH r16**

**Miscellaneous Instructions**

**CCF**

**CPL**  
**DAA**  
**DI**  
**EI**  
**HALT**  
**NOP**  
**SCF**  
**STOP**

## INSTRUCTION REFERENCE

### **ADC A,r8**

Add the value in *r8* plus the carry flag to **A**.

Cycles: 1

Bytes: 1

Flags:

**Z** Set if result is 0.

**N** 0

**H** Set if overflow from bit 3.

**C** Set if overflow from bit 7.

### **ADC A,[HL]**

Add the byte pointed to by **HL** plus the carry flag to **A**.

Cycles: 2

Bytes: 1

Flags: See **ADC A,r8**

### **ADC A,n8**

Add the value *n8* plus the carry flag to **A**.

Cycles: 2

Bytes: 2

Flags: See **ADC A,r8**

### **ADD A,r8**

Add the value in *r8* to **A**.

Cycles: 1

Bytes: 1

Flags:

**Z** Set if result is 0.

**N** 0

**H** Set if overflow from bit 3.

**C** Set if overflow from bit 7.

### **ADD A,[HL]**

Add the byte pointed to by **HL** to **A**.

Cycles: 2

Bytes: 1

Flags: See **ADD A,r8**

#### **ADD A,n8**

Add the value *n8* to **A**.

Cycles: 2

Bytes: 2

Flags: See **ADD A,r8**

#### **ADD HL,r16**

Add the value in *r16* to **HL**.

Cycles: 2

Bytes: 1

Flags:

**N** 0

**H** Set if overflow from bit 11.

**C** Set if overflow from bit 15.

#### **ADD HL,SP**

Add the value in **SP** to **HL**.

Cycles: 2

Bytes: 1

Flags: See **ADD HL,r16**

#### **ADD SP,e8**

Add the signed value *e8* to **SP**.

Cycles: 4

Bytes: 2

Flags:

**Z** 0

**N** 0

**H** Set if overflow from bit 3.

**C** Set if overflow from bit 7.

#### **AND A,r8**

Bitwise AND between the value in *r8* and **A**.

Cycles: 1

Bytes: 1

Flags:

**Z** Set if result is 0.

<b>N</b>	0
<b>H</b>	1
<b>C</b>	0

**AND A,[HL]**

Bitwise AND between the byte pointed to by **HL** and **A**.

Cycles: 2

Bytes: 1

Flags: See **AND A,r8**

**AND A,n8**

Bitwise AND between the value in *n8* and **A**.

Cycles: 2

Bytes: 2

Flags: See **AND A,r8**

**BIT u3,r8**

Test bit *u3* in register *r8*, set the zero flag if bit not set.

Cycles: 2

Bytes: 2

Flags:

<b>Z</b>	Set if the selected bit is 0.
----------	-------------------------------

<b>N</b>	0
----------	---

<b>H</b>	1
----------	---

**BIT u3,[HL]**

Test bit *u3* in the byte pointed by **HL**, set the zero flag if bit not set.

Cycles: 3

Bytes: 2

Flags: See **BIT u3,r8**

**CALL n16**

Call address *n16*. This pushes the address of the instruction after the **CALL** on the stack, such that **RET** can pop it later; then, it executes an implicit **JP n16**.

Cycles: 6

Bytes: 3

Flags: None affected.

**CALL cc,n16**

Call address *n16* if condition *cc* is met.

Cycles: 6 taken / 3 untaken

Bytes: 3

Flags: None affected.

### CCF

Complement Carry Flag.

Cycles: 1

Bytes: 1

Flags:

**N** 0

**H** 0

**C** Inverted.

### CP A,r8

Subtract the value in *r8* from **A** and set flags accordingly, but don't store the result. This is useful for Comparing values.

Cycles: 1

Bytes: 1

Flags:

**Z** Set if result is 0.

**N** 1

**H** Set if borrow from bit 4.

**C** Set if borrow (i.e. if *r8* > **A**).

### CP A,[HL]

Subtract the byte pointed to by **HL** from **A** and set flags accordingly, but don't store the result.

Cycles: 2

Bytes: 1

Flags: See **CP A,r8**

### CP A,n8

Subtract the value *n8* from **A** and set flags accordingly, but don't store the result.

Cycles: 2

Bytes: 2

Flags: See **CP A,r8**

### CPL

ComPLement accumulator (**A** =  $\sim\mathbf{A}$ ).

Cycles: 1

Bytes: 1

Flags:

**N** 1

**H** 1

**DAA**

Decimal Adjust Accumulator to get a correct BCD representation after an arithmetic instruction.

Cycles: 1

Bytes: 1

Flags:

**Z** Set if result is 0.

**H** 0

**C** Set or reset depending on the operation.

**DEC r8**

Decrement value in register *r8* by 1.

Cycles: 1

Bytes: 1

Flags:

**Z** Set if result is 0.

**N** 1

**H** Set if borrow from bit 4.

**DEC [HL]**

Decrement the byte pointed to by **HL** by 1.

Cycles: 3

Bytes: 1

Flags: See **DEC r8**

**DEC r16**

Decrement value in register *r16* by 1.

Cycles: 2

Bytes: 1

Flags: None affected.

**DEC SP**

Decrement value in register **SP** by 1.

Cycles: 2

Bytes: 1

Flags: None affected.

**DI**

Disable Interrupts by clearing the **IME** flag.

Cycles: 1

Bytes: 1

Flags: None affected.



**EI**

Enable Interrupts by setting the **IME** flag. The flag is only set *after* the instruction following **EI**.

Cycles: 1

Bytes: 1

Flags: None affected.

**HALT**

Enter CPU low-power consumption mode until an interrupt occurs. The exact behavior of this instruction depends on the state of the **IME** flag.

**IME** set The CPU enters low-power mode until *after* an interrupt is about to be serviced. The handler is executed normally, and the CPU resumes execution after the **HALT** when that returns.

**IME** not set

The behavior depends on whether an interrupt is pending (i.e. [ IE ] & [ IF ] is non-zero).

None pending

As soon as an interrupt becomes pending, the CPU resumes execution. This is like the above, except that the handler is *not* called.

Some pending

The CPU continues execution after the **HALT**, but the byte after it is read twice in a row ( **PC** is not incremented, due to a hardware bug ).

Cycles: -

Bytes: 1

Flags: None affected.

**INC r8**

Increment value in register *r8* by 1.

Cycles: 1

Bytes: 1

Flags:

**Z** Set if result is 0.

**N** 0

**H** Set if overflow from bit 3.

**INC [HL]**

Increment the byte pointed to by **HL** by 1.

Cycles: 3

Bytes: 1

Flags: See **INC r8**

**INC r16**

Increment value in register *r16* by 1.

Cycles: 2

Bytes: 1

Flags: None affected.

### **INC SP**

Increment value in register **SP** by 1.

Cycles: 2

Bytes: 1

Flags: None affected.

### **JP n16**

Jump to address *n16*; effectively, store *n16* into **PC**.

Cycles: 4

Bytes: 3

Flags: None affected.

### **JP cc,n16**

Jump to address *n16* if condition *cc* is met.

Cycles: 4 taken / 3 untaken

Bytes: 3

Flags: None affected.

### **JP HL**

Jump to address in **HL**; effectively, load **PC** with value in register **HL**.

Cycles: 1

Bytes: 1

Flags: None affected.

### **JR e8**

Relative Jump by adding *e8* to the address of the instruction following the **JR**. To clarify, an operand of 0 is equivalent to no jumping.

Cycles: 3

Bytes: 2

Flags: None affected.

### **JR cc,e8**

Relative Jump by adding *e8* to the current address if condition *cc* is met.

Cycles: 3 taken / 2 untaken

Bytes: 2

Flags: None affected.

**LD r8,r8**

Load (copy) value in register on the right into register on the left.

Cycles: 1

Bytes: 1

Flags: None affected.

**LD r8,n8**

Load value *n8* into register *r8*.

Cycles: 2

Bytes: 2

Flags: None affected.

**LD r16,n16**

Load value *n16* into register *r16*.

Cycles: 3

Bytes: 3

Flags: None affected.

**LD [HL],r8**

Store value in register *r8* into the byte pointed to by register **HL**.

Cycles: 2

Bytes: 1

Flags: None affected.

**LD [HL],n8**

Store value *n8* into the byte pointed to by register **HL**.

Cycles: 3

Bytes: 2

Flags: None affected.

**LD r8,[HL]**

Load value into register *r8* from the byte pointed to by register **HL**.

Cycles: 2

Bytes: 1

Flags: None affected.

**LD [r16],A**

Store value in register **A** into the byte pointed to by register *r16*.

Cycles: 2

Bytes: 1

Flags: None affected.

**LD [n16],A**

Store value in register **A** into the byte at address *n16*.

Cycles: 4

Bytes: 3

Flags: None affected.

**LDH [n16],A**

Store value in register **A** into the byte at address *n16*, provided the address is between *\$FF00* and *\$FFFF*.

Cycles: 3

Bytes: 2

Flags: None affected.

This is sometimes written as `LDIO [n16],A`, or `LD [$FF00+n8],A`.

**LDH [C],A**

Store value in register **A** into the byte at address *\$FF00+C*.

Cycles: 2

Bytes: 1

Flags: None affected.

This is sometimes written as `LDIO [C],A`, or `LD [$FF00+C],A`.

**LD A,[r16]**

Load value in register **A** from the byte pointed to by register *r16*.

Cycles: 2

Bytes: 1

Flags: None affected.

**LD A,[n16]**

Load value in register **A** from the byte at address *n16*.

Cycles: 4

Bytes: 3

Flags: None affected.

**LDH A,[n16]**

Load value in register **A** from the byte at address *n16*, provided the address is between *\$FF00* and *\$FFFF*.

Cycles: 3

Bytes: 2

Flags: None affected.

This is sometimes written as `LDIO A,[n16]`, or `LD A,[$FF00+n8]`.

**LDH A,[C]**

Load value in register **A** from the byte at address  $\$FF00+c$ .

Cycles: 2

Bytes: 1

Flags: None affected.

This is sometimes written as `LDIO A, [C]`, or `LD A, [$FF00+C]`.

**LD [HL],A**

Store value in register **A** into the byte pointed by **HL** and increment **HL** afterwards.

Cycles: 2

Bytes: 1

Flags: None affected.

This is sometimes written as `LD [HL+], A`, or `LDI [HL], A`.

**LD [HLD],A**

Store value in register **A** into the byte pointed by **HL** and decrement **HL** afterwards.

Cycles: 2

Bytes: 1

Flags: None affected.

This is sometimes written as `LD [HL-], A`, or `LDD [HL], A`.

**LD A,[HLD]**

Load value into register **A** from the byte pointed by **HL** and decrement **HL** afterwards.

Cycles: 2

Bytes: 1

Flags: None affected.

This is sometimes written as `LD A, [HL-]`, or `LDD A, [HL]`.

**LD A,[HL]**

Load value into register **A** from the byte pointed by **HL** and increment **HL** afterwards.

Cycles: 2

Bytes: 1

Flags: None affected.

This is sometimes written as `LD A, [HL+]`, or `LDI A, [HL]`.

**LD SP,n16**

Load value  $n16$  into register **SP**.

Cycles: 3

Bytes: 3

Flags: None affected.

### **LD [n16],SP**

Store **SP** & **\$FF** at address *n16* and **SP** >> **8** at address *n16* + 1.

Cycles: 5

Bytes: 3

Flags: None affected.

### **LD HL,SP+e8**

Add the signed value *e8* to **SP** and store the result in **HL**.

Cycles: 3

Bytes: 2

Flags:

**Z**      0

**N**      0

**H**      Set if overflow from bit 3.

**C**      Set if overflow from bit 7.

### **LD SP,HL**

Load register **HL** into register **SP**.

Cycles: 2

Bytes: 1

Flags: None affected.

### **NOP**

No OPeration.

Cycles: 1

Bytes: 1

Flags: None affected.

### **OR A,r8**

Store into **A** the bitwise OR of the value in *r8* and **A**.

Cycles: 1

Bytes: 1

Flags:

**Z**      Set if result is 0.

**N**      0

**H**      0

**C**      0

### **OR A,[HL]**

Store into **A** the bitwise OR of the byte pointed to by **HL** and **A**.

Cycles: 2

Bytes: 1

Flags: See **OR A,r8**

### **OR A,n8**

Store into **A** the bitwise OR of *n8* and **A**.

Cycles: 2

Bytes: 2

Flags: See **OR A,r8**

### **POP AF**

Pop register **AF** from the stack. This is roughly equivalent to the following *imaginary* instructions:

```
ld f, [sp] ; See below for individual flags
inc sp
ld a, [sp]
inc sp
```

Cycles: 3

Bytes: 1

Flags:

**Z** Set from bit 7 of the popped low byte.  
**N** Set from bit 6 of the popped low byte.  
**H** Set from bit 5 of the popped low byte.  
**C** Set from bit 4 of the popped low byte.

### **POP r16**

Pop register *r16* from the stack. This is roughly equivalent to the following *imaginary* instructions:

```
ld LOW(r16), [sp] ; C, E or L
inc sp
ld HIGH(r16), [sp] ; B, D or H
inc sp
```

Cycles: 3

Bytes: 1

Flags: None affected.

### **PUSH AF**

Push register **AF** into the stack. This is roughly equivalent to the following *imaginary* instructions:

```
dec sp
ld [sp], a
dec sp
ld [sp], flag_Z << 7 | flag_N << 6 | flag_H << 5 | flag_C << 4
```

Cycles: 4

Bytes: 1

Flags: None affected.

### **PUSH r16**

Push register *r16* into the stack. This is roughly equivalent to the following *imaginary* instructions:

```
dec sp
ld [sp], HIGH(r16) ; B, D or H
dec sp
ld [sp], LOW(r16) ; C, E or L
```

Cycles: 4

Bytes: 1

Flags: None affected.

### **RES u3,r8**

Set bit *u3* in register *r8* to 0. Bit 0 is the rightmost one, bit 7 the leftmost one.

Cycles: 2

Bytes: 2

Flags: None affected.

### **RES u3,[HL]**

Set bit *u3* in the byte pointed by **HL** to 0. Bit 0 is the rightmost one, bit 7 the leftmost one.

Cycles: 4

Bytes: 2

Flags: None affected.

### **RET**

Return from subroutine. This is basically a **POP PC** (if such an instruction existed). See **POP r16** for an explanation of how **POP** works.

Cycles: 4

Bytes: 1

Flags: None affected.

### **RET cc**

Return from subroutine if condition *cc* is met.

Cycles: 5 taken / 2 untaken

Bytes: 1

Flags: None affected.

### **RETI**

Return from subroutine and enable interrupts. This is basically equivalent to executing **EI** then **RET**, meaning that **IME** is set right after this instruction.

Cycles: 4



Bytes: 1

Flags: None affected.

### **RL r8**

Rotate bits in register *r8* left through carry.

$$C \leftarrow [7 \leftarrow 0] \leftarrow C$$

Cycles: 2

Bytes: 2

Flags:

**Z**      Set if result is 0.

**N**      0

**H**      0

**C**      Set according to result.

### **RL [HL]**

Rotate the byte pointed to by **HL** left through carry.

$$C \leftarrow [7 \leftarrow 0] \leftarrow C$$

Cycles: 4

Bytes: 2

Flags: See **RL r8**

### **RLA**

Rotate register **A** left through carry.

$$C \leftarrow [7 \leftarrow 0] \leftarrow C$$

Cycles: 1

Bytes: 1

Flags:

**Z**      0

**N**      0

**H**      0

**C**      Set according to result.

### **RLC r8**

Rotate register *r8* left.

$$C \leftarrow [7 \leftarrow 0] \leftarrow [7]$$

Cycles: 2

Bytes: 2

Flags:

**Z**      Set if result is 0.

**N**      0

**H**      0

**C** Set according to result.

#### **RLC [HL]**

Rotate the byte pointed to by **HL** left.

$$C \leftarrow [7 \leftarrow 0] \leftarrow [7]$$

Cycles: 4

Bytes: 2

Flags: See **RLC r8**

#### **RLCA**

Rotate register **A** left.

$$C \leftarrow [7 \leftarrow 0] \leftarrow [7]$$

Cycles: 1

Bytes: 1

Flags:

**Z** 0

**N** 0

**H** 0

**C** Set according to result.

#### **RR r8**

Rotate register *r8* right through carry.

$$C \rightarrow [7 \rightarrow 0] \rightarrow C$$

Cycles: 2

Bytes: 2

Flags:

**Z** Set if result is 0.

**N** 0

**H** 0

**C** Set according to result.

#### **RR [HL]**

Rotate the byte pointed to by **HL** right through carry.

$$C \rightarrow [7 \rightarrow 0] \rightarrow C$$

Cycles: 4

Bytes: 2

Flags: See **RR r8**

#### **RRA**

Rotate register **A** right through carry.

$$C \rightarrow [7 \rightarrow 0] \rightarrow C$$

Cycles: 1

Bytes: 1

Flags:

**Z** 0

**N** 0

**H** 0

**C** Set according to result.

### **RRC r8**

Rotate register *r8* right.

[0] -> [7 -> 0] -> C

Cycles: 2

Bytes: 2

Flags:

**Z** Set if result is 0.

**N** 0

**H** 0

**C** Set according to result.

### **RRC [HL]**

Rotate the byte pointed to by **HL** right.

[0] -> [7 -> 0] -> C

Cycles: 4

Bytes: 2

Flags: See **RRC r8**

### **RRCA**

Rotate register **A** right.

[0] -> [7 -> 0] -> C

Cycles: 1

Bytes: 1

Flags:

**Z** 0

**N** 0

**H** 0

**C** Set according to result.

### **RST vec**

Call address *vec*. This is a shorter and faster equivalent to **CALL** for suitable values of *vec*.

Cycles: 4

Bytes: 1

Flags: None affected.

**SBC A,r8**

Subtract the value in *r8* and the carry flag from **A**.

Cycles: 1

Bytes: 1

Flags:

**Z** Set if result is 0.

**N** 1

**H** Set if borrow from bit 4.

**C** Set if borrow (i.e. if  $(r8 + \text{carry}) > \mathbf{A}$ ).

**SBC A,[HL]**

Subtract the byte pointed to by **HL** and the carry flag from **A**.

Cycles: 2

Bytes: 1

Flags: See **SBC A,r8**

**SBC A,n8**

Subtract the value *n8* and the carry flag from **A**.

Cycles: 2

Bytes: 2

Flags: See **SBC A,r8**

**SCF**

Set Carry Flag.

Cycles: 1

Bytes: 1

Flags:

**N** 0

**H** 0

**C** 1

**SET u3,r8**

Set bit *u3* in register *r8* to 1. Bit 0 is the rightmost one, bit 7 the leftmost one.

Cycles: 2

Bytes: 2

Flags: None affected.

**SET u3,[HL]**

Set bit *u3* in the byte pointed by **HL** to 1. Bit 0 is the rightmost one, bit 7 the leftmost one.

Cycles: 4

Bytes: 2

Flags: None affected.

**SLA r8**

Shift Left Arithmetically register *r8*.

$$C \leftarrow [7 \leftarrow 0] \leftarrow 0$$

Cycles: 2

Bytes: 2

Flags:

**Z** Set if result is 0.

**N** 0

**H** 0

**C** Set according to result.

**SLA [HL]**

Shift Left Arithmetically the byte pointed to by **HL**.

$$C \leftarrow [7 \leftarrow 0] \leftarrow 0$$

Cycles: 4

Bytes: 2

Flags: See **SLA r8**

**SRA r8**

Shift Right Arithmetically register *r8*.

$$[7] \rightarrow [7 \rightarrow 0] \rightarrow C$$

Cycles: 2

Bytes: 2

Flags:

**Z** Set if result is 0.

**N** 0

**H** 0

**C** Set according to result.

**SRA [HL]**

Shift Right Arithmetically the byte pointed to by **HL**.

$$[7] \rightarrow [7 \rightarrow 0] \rightarrow C$$

Cycles: 4

Bytes: 2

Flags: See **SRA r8**

**SRL r8**

Shift Right Logically register *r8*.

$$0 \rightarrow [7 \rightarrow 0] \rightarrow C$$

Cycles: 2

Bytes: 2

Flags:

**Z** Set if result is 0.

**N** 0

**H** 0

**C** Set according to result.

#### **SRL [HL]**

Shift Right Logically the byte pointed to by **HL**.

0 -> [7 -> 0] -> C

Cycles: 4

Bytes: 2

Flags: See **SRA r8**

#### **STOP**

Enter CPU very low power mode. Also used to switch between double and normal speed CPU modes in GBC.

Cycles: -

Bytes: 2

Flags: None affected.

#### **SUB A,r8**

Subtract the value in *r8* from **A**.

Cycles: 1

Bytes: 1

Flags:

**Z** Set if result is 0.

**N** 1

**H** Set if borrow from bit 4.

**C** Set if borrow (set if *r8* > **A**).

#### **SUB A,[HL]**

Subtract the byte pointed to by **HL** from **A**.

Cycles: 2

Bytes: 1

Flags: See **SUB A,r8**

#### **SUB A,n8**

Subtract the value *n8* from **A**.

Cycles: 2

Bytes: 2

Flags: See **SUB A,r8**

### **SWAP r8**

Swap the upper 4 bits in register *r8* and the lower 4 ones.

Cycles: 2

Bytes: 2

Flags:

**Z** Set if result is 0.

**N** 0

**H** 0

**C** 0

### **SWAP [HL]**

Swap the upper 4 bits in the byte pointed by **HL** and the lower 4 ones.

Cycles: 4

Bytes: 2

Flags: See **SWAP r8**

### **XOR A,r8**

Bitwise XOR between the value in *r8* and **A**.

Cycles: 1

Bytes: 1

Flags:

**Z** Set if result is 0.

**N** 0

**H** 0

**C** 0

### **XOR A,[HL]**

Bitwise XOR between the byte pointed to by **HL** and **A**.

Cycles: 2

Bytes: 1

Flags: See **XOR A,r8**

### **XOR A,n8**

Bitwise XOR between the value in *n8* and **A**.

Cycles: 2

Bytes: 2

Flags: See **XOR A,r8**

### **SEE ALSO**

rgbasm(1), rgbds(7)

**HISTORY**

**rgbds** was originally written by Carsten Sørensen as part of the ASMotor package, and was later packaged in RGBDS by Justin Lloyd. It is now maintained by a number of contributors at <https://github.com/gbdev/rgbds>