Community Admin — API Reference

Base URL (this machine): `http://localhost:5000`
Base URL (other devices on same Wi-Fi): `http://192.168.1.99:5000`

Backend listens on `HOST=0.0.0.0` (all interfaces). Replace the LAN IP if yours changes — check the `LAN access:` line when the server starts.

Example endpoints from another device

- Health: `http://192.168.1.99:5000/health`
- Login: `http://192.168.1.99:5000/api/auth/login`
- Auth header (after login): `Authorization: Bearer <token>`

Auth header (all routes except login / health):

```
Authorization: Bearer <token>
```

Common error shape

```
{ "success": false, "message": "string" }
```

Power keys

`give_signals` · `create_admins` · `manage_students` · `manage_courses` · `manage_batches` · `manage_channels` · `message_channels`

Notes

- Create/delete for students, courses, batches is CRM-only (`403`).
- Powers come from the admin's **type**, not per-admin.
- Only super admin can grant `create_admins` on a type.
- Token expires in **12 hours**.

---

1. Auth — `/api/auth`

`POST /api/auth/login`

Body

Arg	Type	Required
`adminId`	`string`	yes
`password`	`string`	yes
`client`	`"portal"` | `"app"`	no (default `"app"`)

Response `200`

```
{
  "success": true,
  "message": "string",
```

```
  "token": "string",
  "admin": {
    "id": "string",
    "name": "string",
    "email": "string?",
    "role": "super_admin | portal_admin",
    "adminType": "super | staff | signal_giver",
    "adminTypeId": "number?",
    "adminTypeName": "string?",
    "isSignalOnly": "boolean?",
    "powers": ["string"]
  }
}
```

Signal-only accounts get `403` if `client` is `"portal"`.

`GET /api/auth/me`

Headers: Bearer token

Response `200`: `{ "success": true, "admin": Admin }` — same `admin` shape as login.

---

2. Dashboard — `/api/dashboard`

Auth required.

`GET /api/dashboard/stats`

Response `200`

```
{
  "success": true,
  "stats": {
    "students": 0,
    "courses": 0,
    "enrollments": 0,
    "activeCourses": 0,
    "batches": 0,
    "studentsWithPhone": 0,
    "studentsWithTelegram": 0,
    "channels": 0,
    "activeChannels": 0,
    "channelMessages": 0,
    "channelMembers": 0,
    "portalAdmins": 0,
    "activePortalAdmins": 0,
    "signalGivers": 0,
    "staffAdmins": 0
  },
  "paymentBreakdown": [{ "label": "string", "count": 0 }],
  "enrollmentStatus": [{ "label": "string", "count": 0 }],
  "recentStudents": [],
```

```
  "recentEnrollments": [],
  "courseBreakdown": [],
  "recentChannels": [],
  "recentAdmins": [],
  "adminTypeBreakdown": [{ "label": "string", "count": 0 }]
}
```

---

3. Admin types — `/api/admin-types`

Auth + power `create_admins`.

`GET /api/admin-types/powers`

```
{
  "success": true,
  "powers": [{ "key": "string", "label": "string", "description": "string" }]
}
```

`GET /api/admin-types`

```
{
  "success": true,
  "types": [{
    "id": 1,
    "name": "string",
    "description": "string | null",
    "is_signal_only": false,
    "is_active": true,
    "created_at": "string",
    "updated_at": "string",
    "powers": ["string"],
    "admin_count": 0
  }]
}
```

`POST /api/admin-types`

Body

Arg	Type	Required
`name`	`string`	yes
`description`	`string`	no
`isSignalOnly`	`boolean`	no (default `false`)
`isActive`	`boolean`	no (default `true`)
`powers`	`string[]`	yes unless signal-only

Response `201` : `{ "success": true, "type": AdminType }`

`PUT /api/admin-types/:id`

Same body as POST. **Response** `200` : `{ "success": true, "type": AdminType }`

`DELETE /api/admin-types/:id`

Response `200` : `{ "success": true, "message": "string" }`
Fails if type has admins assigned.

---

4. Portal admins — `/api/portal-admins`

Auth + power `create_admins` .

`GET /api/portal-admins/powers`

```
{
  "success": true,
  "powers": [{ "key": "string", "label": "string", "description": "string" }]
}
```

`GET /api/portal-admins`

```
{
  "success": true,
  "admins": [{
    "id": 1,
    "admin_id": "string",
    "name": "string",
    "email": "string | null",
    "admin_type": "staff | signal_giver",
    "admin_type_id": 1,
    "is_active": true,
    "created_at": "string",
    "updated_at": "string",
    "type_name": "string | null",
    "is_signal_only": false,
    "powers": ["string"]
  }]
}
```

`POST /api/portal-admins`

Body

Arg	Type	Required
`adminId`	`string`	yes

`name`	`string`	yes
`password`	`string`	yes (min 6)
`adminTypeId`	`number`	yes
`email`	`string`	no
`isActive`	`boolean`	no (default `true`)

Response `201`: `{ "success": true, "admin": PortalAdmin }`

`PUT /api/portal-admins/:id`

Same as POST; `password` optional (omit to keep current).
Response `200`: `{ "success": true, "admin": PortalAdmin }`

`DELETE /api/portal-admins/:id`

Response `200`: `{ "success": true, "message": "string" }`

---

5. Channels — `/api/channels`

Auth + power `manage_channels`.

`GET /api/channels`

Query: `search?: string`
Response: `{ "success": true, "channels": Channel[] }`
Channel includes `message_count`, `member_count`, `admin_count`, plus DB fields (`id`, `name`, `code`, `description`, `status`, `created_by_*`, etc.).

`GET /api/channels/people-search`

Query: `search?: string`

```
{
  "success": true,
  "students": [{ "id": 1, "first_name": "", "last_name": "", "email": "", "phone": "" }],
  "admins": [{ "id": 1, "admin_id": "", "name": "", "email": "", "admin_type": "" }]
}
```

`GET /api/channels/batches`

Query: `search?: string`

```
{
  "success": true,
  "batches": [{ "id": 1, "name": "", "status": "", "course_title": "", "student_count": 0 }]
}
```

`POST /api/channels`

Body: `{ "name": "string", "code?": "string", "description?": "string", "status?": "string" }`
Response `201` : `{ "success": true, "channel": Channel }`

`PUT /api/channels/:id`

Same body. **Response:** `{ "success": true, "channel": Channel }`

`DELETE /api/channels/:id`

Response: `{ "success": true, "message": "string" }`

`GET /api/channels/:id/members`


```
{
  "success": true,
  "channel": {
    "id": 1,
    "name": "string",
    "created_by_role": "string",
    "created_by_admin_id": "string",
    "created_by_name": "string"
  },
  "admins": [{
    "membership_id": 1,
    "role": "string",
    "joined_at": "string",
    "portal_admin_id": 1,
    "admin_id": "string",
    "name": "string",
    "email": "string"
  }],
  "members": [{
    "membership_id": 1,
    "joined_at": "string",
    "student_id": 1,
    "first_name": "string",
    "last_name": "string",
    "email": "string",
    "phone": "string"
  }]
}
```


`POST /api/channels/:id/members`

Body: `{ "studentId": 1 }`
Response `201` : `{ "success": true, "member": ChannelMember }`

`POST /api/channels/:id/members/bulk`

Body: `{ "studentIds?": [1], "batchIds?": [1] }`
Response `201` : `{ "success": true, "added": 0, "skipped": 0, "total": 0 }`

`POST /api/channels/:id/admins`

Body: `{ "portalAdminId": 1 }`
Response `201` : `{ "success": true, "admin": ChannelAdmin }`

`DELETE /api/channels/:id/members/:studentId`

Response: `{ "success": true, "message": "string" }`

`DELETE /api/channels/:id/admins/:portalAdminId`

Response: `{ "success": true, "message": "string" }`

---

6. Students — `/api/students`

Auth + power `manage_students`.

Method	Path	Args	Response
GET	/	Query: search?, batchId?	{ success, students: Student[] }
PUT	/:id	Body: firstName, lastName?, email, phone?, address?, dateOfBirth?, telegramUser?	{ success, student }
POST	/	—	403 CRM only
DELETE	/:id	—	403 CRM only

Student list fields: `id`, `first_name`, `last_name`, `email`, `phone`, `address`, `date_of_birth`, `telegram_user`, `created_at`, `updated_at`, `course_count`, `batch_names`, `batch_ids`

---

7. Courses — `/api/courses`

Auth; list needs `manage_courses` **or** `manage_batches`; update needs `manage_courses`.

Method	Path	Args	Response
GET	/	Query: search?	{ success, courses: Course[] }
PUT	/:id	Body: title, description?, duration?, price?, status?	{ success, course }
POST / DELETE			403 CRM only

---

8. Batches — `/api/batches`

Auth; list needs `manage_batches` **or** `manage_students`.

Method	Path	Args	Response

GET	/	—	{ success, batches: Batch[] }
GET	/members	Query: batchId?, search? (needs manage_batches)	{ success, members: BatchMember[] }
PUT	/:id	Body: name, courseId?, startDate?, endDate?, status?, isOpen?	{ success, batch }
POST / DELETE			403 CRM only

---

9. Misc

Method	Path	Auth	Response
GET	/health	no	{ "status": "ok" }
GET	/db-check	no	{ "connected": true, "now?": "string" }