

COMS20011 – Data-Driven Computer Science




March 2024
Features

Majid Mirmehdi

Lecture MM-06

Next in DDCS



Feature Selection and Extraction

- Signal basics and Fourier Series
- 1D and 2D Fourier Transform
- **Another look at features**
- PCA for dimensionality reduction
- Convolutions

Features for recognizing a chair?



Features for recognizing good/bad apples?



Features for recognizing masculine/feminine words in French?

- le fromage (cheese)
 - le monument (monument)
 - le sentiment (feeling)
 - le couteau (knife)
 - le téléphone (telephone)
 - le microscope (microscope)
 - le romantisme (romanticism)
- la salade (salad, lettuce)
 - la fourchette (fork)
 - la télévision (television)
 - la culture (culture)
 - la situation (situation)
 - la société (society)
 - la différence (difference)

Image Features for Recognising Buildings?

Matching features (while also exploiting how they are arranged in the scene) would be much more efficient than matching all pixels



Common features between images allows us to perform tasks such as scene matching, face recognition, 3D model generation, and much more!

Examples of Features

- Primitive features, e.g.: (or Discrete/Continuous or Quantitative)
 - weight, length, width, height, volume ...
 - amplitude, frequency, phase, duration, roll-off, flux ...
 - beats per minute, temperature, pressure,...
 - edges, corners, lines, curvature, ...
 - mean RGB colour, colour histogram, ...
- Semantic features, e.g.: (or Nominal or Qualitative)
 - colour layout (red, cyan, magenta,...)
 - texture descriptors (coarse, fine, rough, smooth,...)
 - shape descriptors (rectangular, circular, elliptical,...)
 - kind of day (warm, cold, sunny, rainy, ...)
- Ordinal features, e.g.: (or Ordered)
 - Education Level (Higher, Secondary, Primary)
 - Body Mass Index (BMI): Underweight, normal weight, overweight, obese
 - Letter grades in the exam (A, B, C, D, etc.)
- Statistical features, e.g.:
 - mean, median, variance, percentiles, moments, ...
- ...


Quick Review: Features

- Features describe characteristics of our data.
- The combination of d features is represented as a d -dimensional column vector called a *feature vector*.
- The d -dimensional space defined by the feature vector is called the *feature space*.

$$\mathbf{p}_i = \begin{bmatrix} x_1 \\ x_2 \\ \vdots \\ x_d \end{bmatrix}$$


$\mathbf{p}_i \in X$ is a point in feature space X

Example:
3D feature
space X



Feature Properties – *what makes a good feature vector?*


good, linearly-separable
features




bad features




highly correlated
features



nonlinearly-separable
features






multimodal
features




The Curse of Dimensionality

- Example: one feature, no. of bins = 3, but results not good enough, so incorporate another feature.
- But, the no. of bins $\rightarrow 3^2=9$, so to maintain the density, increase the no. of examples from 9 to 27




Moving to 3 features makes it even worse...



The amount of data to sustain a given spatial density increases exponentially with the dimensionality of the input space

Dimensionality Reduction

- Strive for compact representation of the *properties* of data, such that redundancy/irrelevancy is removed.
- The choice of features is very important, as it influences:
 - accuracy of classification
 - time needed for classification
 - difficulty in performing classification
 - no. of learning examples



Feature Selection/Extraction

- **Feature selection:** Choosing $d < N$ important features, ignoring the remaining $N - d$ features

Subset selection algorithms

- **Feature extraction:** Project the original $m_i, i = 1, \dots, N$ dimensions to new $d < N$ dimensions, $x_j, j = 1, \dots, d$

Principal Components Analysis (PCA),


Linear Discriminant Analysis (LDA), & many more...

- Feature construction: create new features based on old features: $f = (\dots)$ where f is usually a non-linear function, e.g Support Vector Machines, (not within scope)


Selection or Extraction?

Two general approaches to dimensionality reduction:

- **Feature Selection:** Selecting a subset of the existing features without a transformation
- **Feature Extraction:** Transforming the existing features into a lower dimensional space



$$d \ll N$$



Exhaustive Feature Selection

- Feature Selection is necessary in a number of situations, e.g. there may be too many features or may be too expensive to obtain.
- Feature Selection involves a search strategy that may explore the space of all possible combinations of features.

Given a feature set $\{x_i\}, i = 1, \dots, N$, find a subset \mathbf{X} of size d with $d < N$, that optimizes an objective function $J(\mathbf{X})$, e.g. $P(\text{correct classification})$.

This function would have to be evaluated many times:

e.g. for 10 features out of 25 one would still have to consider 3,268,760 feature sets.



$$\frac{N!}{(N-d)!d!}$$

Exhaustive Feature Selection

- Feature Selection is necessary in a number of situations, e.g. there may be too many features or may be too expensive to obtain.
- Feature Selection involves a search strategy that may explore the space of all possible combinations of features.

Given a feature set $\{x_i\}, i = 1, \dots, N$, find a subset \mathbf{X} of size d with $d < N$, that optimizes an objective function $J(\mathbf{X})$, e.g. $P(\text{correct classification})$.

This function would have to be evaluated many times:

e.g. for 100 features out of 10000 one would have to consider K feature sets. What is K ?

$$\frac{N!}{(N-d)!d!}$$

Exhaustive Feature Selection


$$K = \underbrace{5,000,000,000,000,000,000,000,000,000,000}_{\text{Number of nodes}},$$

And continue with as many more 0s as above for 322 more slides....

i.e. $K = 5 \times 10^{35101}$



Feature Selection?



From <http://elpub.scix.net/data/works/att/02-28.content.pdf>

Sequential Feature Selection Methods

- Assume features are independent.
- Best single features can be chosen by significance tests.


Forward stepwise feature selection:
(bottom-up)

Build up d features incrementally,
starting with an empty set

The best single feature is picked first.

Then next best feature conditioned to the first, ...

Forward stepwise selection example with 5 variables:




Sequential Feature Selection Methods

- Assume features are independent.
- Best single features can be chosen by significance tests.

Backward stepwise feature selection:
(top-down)


start with full set of features and remove redundant or least significant ones one after another

Until optimal d features reached





Feature Extraction


- Linear or non-linear transformation of the original variables to a lower dimensional feature space \rightarrow also known as *feature selection in the transformed space*.
- Given a feature space R^N with feature vectors \mathbf{m} , find a mapping $\mathbf{x} = \varphi(\mathbf{m}): R^N \Rightarrow R^d, d < N$, such that the transformed feature vector $\mathbf{x} = \{x_i\} \in R^d$ preserves (most of) the information or structure in R^N .
- Principal Components Analysis (PCA) is an example of a transformed space for dimensionality reduction from which we can extract the most efficient features.



PCA



Next in DDCS



Feature Selection and Extraction

- Signal basics and Fourier Series
- 1D and 2D Fourier Transform
- Another look at features
- **PCA for dimensionality reduction**
- Convolutions