

An Hopfield Network for Digit Recognition

Artificial Intelligence Course Project

Gianluca Barbon
818453@stud.unive.it

January 4, 2015

Abstract

This report describes the artificial intelligence course project. This project consists in the implementation of a Hopfield Network using python. The weight matrix will be computed by using different algorithms, in such a way to analyse performances and thus identify the best solution.

1 Introduction

1.1 Neural Networks

They are used for recognition and classification problem, they are capable to learn and so to generalize, that is produce outputs in correspondence of inputs never met before. The training of the net take place presenting a training set (set of example) as input. The answer given by the net for each example will be compared to the desired answer, the difference (or error) between the two will be evaluated and finally the weights will be adjusted by looking at this difference. the process is repeated for the entire training set, until the produced error is minimized, so under a preset threshold.

1.1.1 Classification Problems

Classification problems consists in the classification of an object by looking at its features.

1.2 Hopfield Network [2]

Hopfield networks are neural networks that can be seen as non linear dynamic systems. They are also called recurring networks or feedback networks. We consider neural networks as non linear dynamic systems, where we consider the time variable. In order to do this, we must take into account loops, so we will use recurrent networks. recurrent networks with non linear units are difficult to analyse: they can converge to a stable state, oscillate or follow chaotic trajectories whose behaviour

is not predictable. However, the american physicist J.J. Hopfield discovered that with symmetric connections there will exist a stable global energy function. The Hopfield networks have the following properties:

- **single layer recurrent networks** in which each neuron is connected to all the others, with the exception of itself (so no cycles are admitted)
- **symmetric:** the synaptic weight matrix is symmetric, so $W = W^T$. This means that the weights is the same in both direction between two neurons.
- **not linear:** in the continuous formulation, each neuron has a non linear invertible activation function

As for the neuron update, we can use three possible approaches:

- **asynchronous update:** where neurons are updated one by one
- **synchronous update:** all neurons are updated at the same moment
- **continuous update:** all neurons are updated in a continuous way

There exists two formulation of the Hopfield model: the discrete one and the continuous one, that differ for the way in which the time flows. For this project we will use the discrete model. In this model the time flows in discrete way and neurons updates in asynchronous way. as for the neuron input, the McCulloch and Pitts model is used, with the adding of an external influence (or bias?) factor:

$$H_i = \underbrace{\sum_{j \neq i} w_{ij} V_j}_{\text{M\&P model}} + \underbrace{I_i}_{\text{external input}}$$

The activation function is the following:

$$V_i = \begin{cases} +1 & \text{se } H_i > 0 \\ -1 & \text{se } H_i < 0 \end{cases} \quad (1)$$

The update of the neurons is a random process and the selection of the unit to be updated can be done in two ways:

1. at each time instant the unit to be updated is chosen randomly (this mode is useful in simulations)
2. each unit is updated independently with constant probability at each time instant

Unlike feedforward networks, a Hopfield network is a dynamic system. It starts from an initial state

$$\vec{V}(0) = (V_1(0), \dots, V_n(0))^T$$

and evolves through a trajectory until it reach a fixed point in which $V(t+1) = V(t)$ (convergence). The Hopfield theorem supplies a sufficient condition for the convergence of the system. It uses an energy function E that govern the systems :

$$E = -\frac{1}{2} \sum_{i=1}^n \sum_{\substack{j=1 \\ j \neq i}}^n w_{ij} V_i V_j - \sum_{i=1}^n I_i V_i \quad (2)$$

Theorem 1.1 (Hopfield theorem: discrete case). *If the weights matrix in a Hopfield network is symmetric, $\text{diag}(W) = 0$, the Energy Function will be a Lyapunov function for the system, so:*

$$\Delta E = E(t+1) - E(t) \leq 0$$

with the equivalence when the system reach a stationary point.

1.3 Hebb's rule

In contrast with computer's byte-addressable memory, that adopt a precise memory address to locate information, the human brain utilize content-addressable memory, that uses the content of data to locate information. The Hebb rule has been introduced to describe such behaviour and states that the weight between two neurons increases if the two neurons activate simultaneously. In detail, the Hebb postulate says that:

Let us assume that the persistence or repetition of a reverberatory activity (or "trace") tends to induce lasting cellular changes that add to its stability. [...] When an axon of cell A is near enough to excite a cell B and repeatedly or persistently takes part in firing it, some growth process or metabolic change takes place in one or both cells such that A's efficiency, as one of the cells firing B, is increased. [1]

The memory is represented like a set of P patterns x^μ , where $\mu = 1, \dots, P$: when a new pattern x is presented,

the net typically answers producing the pattern in memory that most resembles to x . Accordingly to the Hebb postulate, proportional weights are used in the activation between a pre and a post synaptic neurons:

$$w_{ij} = \frac{1}{N} \sum_{\mu=1}^P x_i^\mu x_j^\mu$$

where N is the number of binary units with output s_1, \dots, s_N . The recall mechanism is the following:

$$s_i = \text{sgn} \left(\sum_j w_{ij} s_j \right)$$

Anyway, there are some problems in the use of Hopfield network as content-addressed memories:

- the maximum number of pattern is $0.15N$
- sometimes the net produces spurious states, that is states that do not belong to the memorized patterns
- the recalled pattern is not necessarily the most similar to the input one
- patterns are not recalled with the same emphasis

2 Conclusions

[2]

References

- [1] D. O. Hebb. *The Organization of Behavior*. Wiley, New York, 1949.
- [2] M. Pelillo. Artificial intelligence course, 2014.

A Appendix: Code

A.1 HopfieldNet.py

```
1  __author__ = 'gbarbon'
2
3  import numpy as np
4  import random as rd
5  import trainers as tr
6
7
8  class HopfieldNet:
9
10     def __init__(self, train_input, trainer_type, image_dimensions):
11
12         #number of training patterns and number of units
13         n_patterns = train_input.shape[0]
14         self.n_units = train_input.shape[1]
15
16         # crating threshold array (each unit has its own threshold)
17         self.threshold = np.zeros(self.n_units)
18
19         # setting image dimension
20         self.image_dimensions = image_dimensions
21
22         # net training
23         if trainer_type == "hebbian":
24             self.weights = tr.hebb_train(train_input, n_patterns, self.n_units)
25         elif trainer_type == "pseudoinv":
26             self.weights = tr.pseudo_inverse_train(train_input, n_patterns, self.n_units)
27         #else:
28
29     def single_unit_updater(self, unit_idx, pattern):
30
31         #temp = sum(weights[unit_idx,:] * pattern[:]) - threshold[unit_idx]
32         # we implement a powerful version that uses dotproduct with numpy
33         temp = np.dot(self.weights[unit_idx, :], pattern[:]) - self.threshold[unit_idx]
34         if temp >= 0:
35             # pattern[unit_idx] = 1
36             return 1
37         else:
38             # pattern[unit_idx] = 0
39             return -1
40
41     def energy(self, pattern):
42         e = 0
43         length = len(pattern)
44         for i in range(length):
45             for j in range(length):
46                 if i == j:
47                     continue
48                 else:
49                     e += self.weights[i][j] * pattern[i] * pattern[j]
50
51         sub_term = np.dot(self.threshold, pattern)
52         e = -1 / 2 * e - sub_term
53         return e
54
55     # function overloading in threshold
```

```

56 def test(self, pattern, threshold=0):
57
58     #setting threshold if threshold != 0
59     if threshold != 0:
60         self.threshold = threshold
61
62     pattern = pattern.flatten() # flattening pattern
63     energy = self.energy(pattern) # energy init
64
65     k = 0
66     while k < 10:
67         randomrange = range(len(pattern))
68         rd.shuffle(randomrange)
69         for i in randomrange:
70             pattern[i] = self.single_unit_updater(i, pattern)
71             #nota: l'energia deve essere calcolata ad ogni cambiamento di una singola unita' o d
72         temp_e = self.energy(pattern)
73         if temp_e == energy:
74             #break while loop
75             pattern.shape = (self.image_dimensions[0], self.image_dimensions[1])
76             return pattern
77         else:
78             energy = temp_e
79         k += 1
80
81     pattern.shape = (self.image_dimensions[0], self.image_dimensions[1])
82     return pattern

```

A.2 trainers.py

```
1  __author__ = 'gbarbon'
2
3  import numpy as np
4
5
6  # train input is in the form of a vector
7  def hebb_train(train_input, n_patterns, n_units):
8      # weights matrix init to zeros
9      weights = np.zeros((n_units, n_units))
10
11      # 1
12      for l in range(n_patterns):
13          for i in range(n_units):
14              for j in range(n_units):
15                  if i == j:
16                      continue
17                  # weights[i,j] = (1/n_units)* sum(...)
18                  else:
19                      weights[i, j] += train_input[l, i] * train_input[l, j]
20                      # print("Temp weight at this point is", weights[i,j])
21                      # uguale???: weights[i,j] = sum(train_input[:,i]*train_input[:,j])
22
23      return weights
24
25  # uses the storkey rule
26  def storkey_train(train_input, n_patterns, n_units):
27      weights = np.zeros((n_units, n_units))
28
29      #..#
30
31      return weights
32
33  def q_pseudo_inv(train_input, n_patterns, n_units):
34      q = np.zeros((n_patterns, n_patterns))
35
36      for v in range(n_patterns):
37          for u in range(n_patterns):
38              # for i in range(n_units):
39              # q[u][v] += train_input[v][i]*train_input[u][i]
40              q[u][v] = np.dot(train_input[v], train_input[u])
41
42      q *= 1 / float(n_units)
43      q = np.linalg.inv(q) # inverse of the matrix
44
45      return q
46
47  # uses the pseudo inverse training rule
48  def pseudo_inverse_train(train_input, n_patterns, n_units):
49      weights = np.zeros((n_units, n_units))
50
51      q = q_pseudo_inv(train_input, n_patterns, n_units)
52
53      for v in range(n_patterns):
54          for u in range(n_patterns):
55              for i in range(n_units):
56                  for j in range(n_units):
57                      if i == j:
```

```
58             continue
59         else:
60             weights[i, j] += train_input[v, i] * q[v][u] * train_input[u, j]
61
62
63     weights *= 1 / float(n_units)
64     return weights
```

A.3 imageManager.py

```
1  __author__ = 'gbarbon'
2
3  from PIL import Image
4  from PIL import ImageFilter
5  # from PIL import ImageEnhance
6  import os
7  import numpy as np
8
9
10 # NOTE: in images dimension are: first:= columns, second:= rows
11
12 def image_cropper(image, new_dimensions):
13     width, height = image.size # Get dimensions
14
15     left = (width - new_dimensions[1]) / 2
16     top = (height - new_dimensions[0]) / 2
17     right = (width + new_dimensions[1]) / 2
18     bottom = (height + new_dimensions[0]) / 2
19
20     return image.crop((left, top, right, bottom))
21
22
23 def image_resizer(image, new_dimensions):
24     return image.resize(new_dimensions)
25
26
27 def to_greyscale(image):
28     return image.convert("L")
29
30
31 def to_blackwhite(input_image):
32     return input_image.convert("1")
33
34
35 # convert image to a matrix of 0 and 1 and to black and white
36 def tomatrix_bew(image):
37     imarray = np.array(image.getdata(), np.uint8).reshape(image.size[1], image.size[0])
38     row = imarray.shape[0]
39     cols = imarray.shape[1]
40     newarray = np.zeros((row, cols))
41
42     for i in range(row):
43         for j in range(cols):
44             if imarray[i][j] <= 127:
45                 newarray[i][j] = 1
46             else:
47                 newarray[i][j] = 0
48     return newarray
49
50
51 # convert image to a matrix of 0 and 1
52 def tomatrix(image):
53     matrix = np.array(image.getdata(), np.uint8).reshape(image.size[1], image.size[0])
54     rows = matrix.shape[0]
55     cols = matrix.shape[1]
56     newarray = np.zeros((rows, cols))
57
```

```

58     for i in range(rows):
59         for j in range(cols):
60             if matrix[i][j] == 0:
61                 newarray[i][j] = 1
62
63     return newarray
64
65
66 def collectimages(finaldim, img_dir):
67     i = 0
68     entries = 0
69
70     # number of files checking
71     for img_file in os.listdir(img_dir):
72         if img_file.endswith(".tiff"):
73             entries += 1
74
75     dataset = np.zeros((entries, finaldim[0] * finaldim[1]))
76
77     for img_file in os.listdir(img_dir):
78         if img_file.endswith(".tiff"):
79             newdir = img_dir + "/" + img_file
80             im = Image.open(newdir)
81
82             orig_dim = im.size
83
84             # Image conversion to black and white
85             imp = to_greyscale(im)
86             imp = to_blackwhite(imp)
87
88             # Image filtering
89             imp = imp.filter(ImageFilter.MedianFilter(size=5))
90             #imp = imp.filter(ImageFilter.ModeFilter(size=5))
91
92             if orig_dim[0] > 100 and orig_dim[1] > 100:
93                 # crop if dimensions higher than 100
94                 imp = image_cropper(imp, [100, 100])
95                 imp = image_resizer(imp, finaldim)
96             else:
97                 imp = image_resizer(imp, [40, 70])
98                 imp = image_resizer(imp, finaldim)
99
100             #imp.show() # shows image in external program
101             imarray = tomatrix(imp)
102             dataset[i] = imarray.flatten()
103             i += 1
104
105     return dataset

```


A.4 utils.py

```
1  __author__ = 'gbarbon'
2
3  from matplotlib import pyplot as plt
4  import random as rnd
5  import copy as cp
6
7
8  # convert images from 0/1 to -1/1
9  def image_converter(input_image):
10     image = cp.copy(input_image)
11     image *= 2
12     image -= 1
13     return image
14
15
16 # corrupts images
17 def corrupter(input_image, corrupt_param):
18     dim_row = input_image.shape[0]
19     dim_col = input_image.shape[1]
20     corrupted_image = cp.copy(input_image).flatten()
21
22     for i in range(corrupt_param):
23         corr_idx = rnd.randint(0, (dim_row*dim_col-1))
24         corrupted_image[corr_idx] *= -1
25     corrupted_image.shape = (dim_row, dim_col)
26
27     return corrupted_image
28
29
30 # Plot the results
31 def plotter(test_set, result_set):
32     ntest = len(test_set)
33     k = 1
34     for i in range(ntest):
35         plt.subplot(ntest, 2, k)
36         plt.imshow(test_set[i], interpolation="nearest")
37         k += 1
38         plt.subplot(ntest, 2, k)
39         plt.imshow(result_set[i], interpolation="nearest")
40         k += 1
41     plt.show()
```

A.5 tests.py

```
1  __author__ = 'gbarbon'
2
3  import numpy as np
4  import HopfieldNet
5  import utils as utl
6  import imageManager as iM
7
8
9  def test1():
10     # Create the training patterns
11     a_pattern = np.array([[0, 0, 0, 1, 0, 0, 0],
12                           [0, 0, 1, 0, 1, 0, 0],
13                           [0, 1, 0, 0, 0, 1, 0],
14                           [0, 1, 1, 1, 1, 1, 0],
15                           [0, 1, 0, 0, 0, 1, 0],
16                           [0, 1, 0, 0, 0, 1, 0],
17                           [0, 1, 0, 0, 0, 1, 0]])
18
19     b_pattern = np.array([[0, 1, 1, 1, 1, 0, 0],
20                           [0, 1, 0, 0, 0, 1, 0],
21                           [0, 1, 0, 0, 0, 1, 0],
22                           [0, 1, 1, 1, 1, 0, 0],
23                           [0, 1, 0, 0, 0, 1, 0],
24                           [0, 1, 0, 0, 0, 1, 0],
25                           [0, 1, 1, 1, 1, 0, 0]])
26
27     c_pattern = np.array([[0, 1, 1, 1, 1, 1, 0],
28                           [0, 1, 0, 0, 0, 0, 0],
29                           [0, 1, 0, 0, 0, 0, 0],
30                           [0, 1, 0, 0, 0, 0, 0],
31                           [0, 1, 0, 0, 0, 0, 0],
32                           [0, 1, 0, 0, 0, 0, 0],
33                           [0, 1, 1, 1, 1, 1, 0]])
34
35     a_pattern = utl.image_converter(a_pattern)
36     b_pattern = utl.image_converter(b_pattern)
37     c_pattern = utl.image_converter(c_pattern)
38
39     train_input = np.array([a_pattern.flatten(), b_pattern.flatten(), c_pattern.flatten()])
40
41     #hebbian training
42     net = HopfieldNet.HopfieldNet(train_input, "hebbian", [7, 7])
43
44     # creating test set
45     a_test = utl.corrupter(a_pattern, 5)
46     b_test = utl.corrupter(b_pattern, 5)
47     c_test = utl.corrupter(c_pattern, 5)
48
49     # training and testing the net
50     a_result = net.test(a_test)
51     b_result = net.test(b_test)
52     c_result = net.test(c_test)
53
54     #Show the results
55     test_set = np.array([a_test, b_test, c_test])
56     result_set = np.array([a_result, b_result, c_result])
57     utl.plotter(test_set, result_set)
```

```

58
59
60 def test2():
61     images_dir = "/Users/jian/Dropbox/AI_dropbox/progetto_2014/dummy_data_set/courier_digits_data_set"
62     dim = [14, 9] # in the form rows * cols
63     testel = 8 # elements for training
64     corruption_val = 30
65
66     image_dim = [dim[1], dim[0]] # changing shape for images
67
68     # Loading images data set
69     temp_train = iM.collectimages(image_dim, images_dir)
70
71     train_input = np.zeros((testel, dim[0] * dim[1]))
72     for i in range(testel):
73         train_input[i] = temp_train[i]
74
75     # image conversion to 1 and -1 for Hopfield net
76     for i in range(train_input.shape[0]):
77         temp = utl.image_converter(train_input[i].reshape(dim))
78         train_input[i] = temp.flatten()
79
80     # training the net
81     net = HopfieldNet.HopfieldNet(train_input, "hebbian", dim)
82
83     # testing the net
84     test_set = np.zeros((testel, dim[0], dim[1]))
85     result_set = np.zeros((testel, dim[0], dim[1]))
86     for i in range(testel):
87         test_set[i] = utl.corrupter(train_input[i].reshape(dim), corruption_val)
88         result_set[i] = net.test(test_set[i])
89
90     # Plotting results
91     utl.plotter(test_set, result_set)
92
93 def test3():
94     images_dir = "/Users/jian/Dropbox/AI_dropbox/progetto_2014/dummy_data_set/digital7_digit_data_set"
95     dim = [25, 16] # in the form rows * cols
96     testel = 10 # elements for training
97     corruption_val = 10
98
99     image_dim = [dim[1], dim[0]] # changing shape for images
100
101     # Loading images data set
102     temp_train = iM.collectimages(image_dim, images_dir)
103
104     train_input = np.zeros((testel, dim[0] * dim[1]))
105     for i in range(testel):
106         train_input[i] = temp_train[i]
107
108     # image conversion to 1 and -1 for Hopfield net
109     for i in range(train_input.shape[0]):
110         temp = utl.image_converter(train_input[i].reshape(dim))
111         train_input[i] = temp.flatten()
112
113     # training the net
114     net = HopfieldNet.HopfieldNet(train_input, "pseudoinv", dim)
115
116     # testing the net

```

```

117     test_set = np.zeros((testel , dim[0], dim[1]))
118     result_set = np.zeros((testel , dim[0], dim[1]))
119     for i in range(testel):
120         test_set[i] = utl.corrupter(train_input[i].reshape(dim), corruption_val)
121         result_set[i] = net.test(test_set[i])
122
123     # Plotting results
124     utl.plotter(test_set , result_set)
125
126 test3 ()

```