

# Paths: a Powerful Graph Invariant with Interesting Limitations

Grady Ward

December 7, 2015

In searching for a polynomial time-complexity solution to the graph isomorphism problem, many researchers have focused on, *vertex invariants*, numerical properties calculated over a vertex of a graph that can be deterministically calculated, regardless of how the graph is represented or labeled. This article will aim to describe the descriptive power and information density of the  $Paths(p, v)$  function, a vertex invariant that counts the number of closed paths of length  $p$  through a vertex  $v$ . The  $Paths$  function, in order to be applied to the graph isomorphism problem, is used to construct an algebraic graph invariant, with the application of sorting to the results of individual vertex  $Paths$  results.

Though research into the descriptive power of this function has shown that it does not fully determine the graph, the lines of inquiry have proven to be fruitful in describing patterns of graph behavior that a casual observer would not anticipate. Additionally, the invariant's descriptive power can be computationally described in a way that is meaningful, and shows that for its time complexity, it is an incredibly discriminatory algorithm. Finally, this article will hope to address the various lines of inquiry that will hopefully be addressed in further research on this topic, including a systematic analysis of the classes of graphs that the  $Paths$  function is effective for, and those for which it is insufficient to prove isomorphism.

## 1 Background

To begin a discussion of this work, we must first establish a mutual understanding of the functions that we are discussing, the scope of existing research on this topic, and an appropriate category of graphs to examine.

## 1.1 Definitions

In this analysis, we will be examining *undirected* graphs that do not contain multi-edges nor loops. Any graph under these three constraints can be represented as a symmetric adjacency matrix, with zeros along the diagonal, and ones or zeroes in the remaining locations denoting an edge or disjoint vertices respectively. We will regularly reference this matrix as  $A$  with no additional annotation.

The vertex invariant we are going to examine ( $Paths(p, v)$ ) is the number of closed paths of a length  $p$  that contain the vertex  $v$ . A path is a sequence of vertices such that each vertex shares an edge with the next one. A Path can be notated by the sequence of the vertices that are visited (e.g. ABCDE or BACAB). A Path is *closed* if the first and last vertex in their traversal sequence are the same. Note that though  $ABCDE$  and  $EDCBA$  describe the same edges, they are distinct paths: even though an undirected graph doesn't have directional edges, paths maintain the order of the edges they traverse.

For this article, when we describe a path as a geometric polygon (such as a triangle, quadrilateral, pentagon, etc.), we will define to be a closed path such that the vertices of the path are non-repeating (aside from the first and last, as we assume that it is closed). Thus,  $ABABA$  does not form a quadrilateral, even though it is a closed path of length four. Note that this path could equally well be described as  $BABAB$ , as closed paths are inherently cyclic, and do not demand a starting vertex. Additionally, we will assume that unlike a path, a polygon's directionality does not matter (thus the polygon ABCA is the same as the polygon ACBA).

## 1.2 Computation of the Paths Function

The  $Paths(p, v)$  function counts the number of unique closed paths that pass through a given vertex,  $v$ . This information can be easily computed using  $A$ . Just as the entries of  $A^1$  represent the existence of paths of length 1 between two vertices (edges), the entries of  $A^p$  represent the number of paths of length  $p$  between any two vertices (by examining the row and column corresponding to two vertices). Thus, to find the number of closed paths of length  $p$  that contain a given vertex  $v$ , we simply need to calculate:


$$Paths(p, v) = A^p[v, v]$$

Where  $v$  is being used interchangeably here with its represented position within the adjacency matrix. Thus, calculating a specific value of  $Paths(p, v)$  can occur in the time it takes to exponentiate  $A$  to the power  $p$ . Though it is a

well known result that matrix multiplication can be done in faster than  $O(n^3)$  time, we will be using the naive assumption that matrix multiplication runs in  $O(n^3)$  in order to make the computational complexity calculations more accessible. Under that assumption, it is clear that calculating  $Paths(p, v)$  will occur in  $O(pv^3)$  time. This is well within polynomial time, so long as we request a polynomial number of values from  $Paths(p, v)$ . Thus we can consider this invariant one in the traditional vein of looking for polynomial invariants with the broad aim of solving GI in polynomial time, though we have already established that it does not uniquely determine isomorphism.

### 1.3 Expansion to a Paths Object

Since  $Paths(p, v)$  is a function that operates over a vertex, we will be examining a slightly modified version of the function which operates over a graph:  $Paths(P, G)$ .  $Paths(P, G)$  produces a graph invariant that is related to its vertex invariant function by a simple translation.  $Paths(p, v)$  is calculated for all  $v \in G, p \leq P$ , resulting in  $v$  vectors, each of which has  $P$  elements, representing the paths function when calculated at that node for each successive value of  $p$ . Since vectors are comparable objects, we can sort them, and return back a list of these vectors as a graph invariant, one that is computable and invariant to changes in vertex relabeling or adjacency matrix ordering. A skeptical reader should convince themselves that this holds true, even when two of the vectors to be sorted are identical, the resulting  $Paths$  object is valid and deterministically constructed from the graph.



$$A = \begin{pmatrix} 0 & 1 & 1 & 1 & 0 & 0 & 0 \\ 1 & 0 & 0 & 0 & 1 & 1 & 0 \\ 1 & 0 & 0 & 1 & 0 & 0 & 0 \\ 1 & 0 & 1 & 0 & 1 & 0 & 1 \\ 0 & 1 & 0 & 1 & 0 & 1 & 0 \\ 0 & 1 & 0 & 0 & 1 & 0 & 0 \\ 0 & 0 & 0 & 1 & 0 & 0 & 0 \end{pmatrix}$$

## 1.4 Co-Paths

Finally, two Graphs are said to be Co-Paths if they produce the same *Paths* object. Since the Paths function is invariant to labeling and positioning, all isomorphic graphs are Co-Paths. However, a broader question is implied by this implication: does the reverse hold? Does Co-Paths determine isomorphism? The answer turns out to be no, but the line of inquiry that leads to this result is worth examining, and leads us to a broader understanding and appreciation for the discriminatory power of the *Paths* function with respect to isomorphic graphs.

## 2 Cardinality Analysis

### 2.1 Brute Force - Java

### 2.2 NAUTY Package

### 2.3 GPU Calculations

### 2.4 C Calculations

## 3 Theoretical Analysis

## 4 Future Lines of Inquiry

When attempting to prove that a function is a bijection, cardinality analysis can prove empirically that it is, regardless of the internal mechanisms of the functions or its operating domain and range. We will use this type of analysis to construct proof for a bijection of our paths function on small graphs. The Paths function can be thought of as a function which operates between two sets: the set of all graphs, and the set of all possible Paths matrices.

Since I have not yet defined paths matrices I will here. Previously discussed was how the paths function is operated on an individual vertex within a graph, and returns a vertex invariant which is a  $1 \times P$  vector which reflects the state of that vertex and its surroundings. Compiling these vectors for each one of our vertices assembles us  $V$  vectors of size  $P$ . Since vectors are inherently comparable, we can sort them. Then appending them together creates a matrix of size  $V \times P$ , where the paths function for each vertex is placed in a given position regardless of its original positioning within the adjacency matrix.

Thus, we are defining our second set to be the set of all such possible paths matrices. It should be clear that the function *Paths*, mapping from a graph to such a mathematical object, is injective, as the cardinality of the domain could not be smaller than the cardinality of the range. However, the question remains: is it a bijection? Why is this important?

If we were able to prove that the relationship between the *Paths* matrices and the set of all graphs was linked by a bijective function, we could prove that if two graphs agree on their corresponding *Paths*'s matrix, then they are the same graph. This is valuable because paths matrices can be directly compared and sorted, while graphs cannot immediately be compared in polynomial time (which is what this article is attempting to redress).

So how to we go about calculating the cardinality of both sets? Luckily, the cardinality of the first set is well established. The series A000088 in the online encyclopedia of integer sequences gives us the number of non-isomorphic graphs up to  $N=28$ . Now to calculate the number of distinguishable paths matrices of a given order.