

- If I have a way of generating arbitrary members of S ...

• $\text{Amerge}(a, b)$ function

- And a law, for instance commutativity, defined as
$$\forall x \in S, y \in S : \textit{merge}(x, y) = \textit{merge}(y, x)$$

- Then I could generate a large number of inputs, and make sure the law holds of every one of them



- If I have a way of generating arbitrary members of S ...
- A $\text{merge}(a, b)$ function
- And a law, for instance commutativity, defined as
$$\forall x \in S, y \in S : \text{merge}(x, y) = \text{merge}(y, x)$$
- Then I could generate a large number of inputs, and make sure the law holds of every one of them



Introducing QuickCheck

```
-- In QuickCheck, the Arbitrary class associates a random value generator to a type
class Arbitrary t where
  arbitrary :: Gen t -- Gen t is a way of generating random values of type t

-- Let's define Arbitrary instances of our CRDTs
instance arbitraryGSet :: (Arbitrary t, Hashable t) => Arbitrary (GSet t) where
  arbitrary = GSet <<< Set.fromArray <$> arbitrary

instance gCounterArbitrary :: Arbitrary GCounter where
  arbitrary = GCounter <<< Map.fromArray <$> arrayOf kvGen
  where
    kvGen :: Gen (Tuple ReplicaId Int)
    kvGen = Tuple <$> arbitrary <*> suchThat arbitrary (\x -> greaterThanOrEq x 0)
```