

LAB 3: Centroidal floating base dynamics

This lab is to acquire confidence to some invariant properties of floating base dynamics. The base frame B of a floating base robot is usually placed at the robot waist/trunk because this choice induces a branch sparsity of the Jacobians. However, by defining a different parametrization for the floating base, it is possible to obtain a *block diagonal* joint space inertia matrix. This is achieved by defining a variable changes for the state of the system using the Center of Mass velocity \dot{x}_{com} and the *average* angular velocity $\bar{\omega}$. It can be shown that the mechanical power is invariant with respect to the change of coordinate frames used to represent the floating base.

1) *Center of mass computation*: Compute the Center of Mass of the system performing a weighted average of the Center of Masses of all the links.

2) *Kinetic energy*: Compute the kinetic energy of the system in two different ways: one by the generalized velocities and system mass matrix, another summing up the contributions from each joint. Show that the result is the same.

3) *Centroidal coordinates transform*: Build the transformation matrix ${}_G T_B$ to change coordinates from base to CoM frame.

$${}_G T_B = \begin{bmatrix} {}_G X_B & I_G^{-1} {}_G X_B^* F_B \\ 0_{n \times 6} & I_{n \times n} \end{bmatrix} \quad (1)$$

where:

$${}_G X_B = \begin{bmatrix} I_{n \times n} & -[x_{b,com}] \times \\ 0_{3 \times 3} & I_{3 \times 3} \end{bmatrix} \quad (2)$$

4) *Block-diagonal joint space inertia matrix*: Show the joint space inertia matrix is decoupled if you apply coordinate transform represented by ${}_G T_B$:

$$M_G = ({}_G T_B)^{-T} M_B ({}_G T_B)^{-1} \quad (3)$$

5) *Joint gravity vector nullifies in com coordinates*: check that the following result is true.

$$G_G = -M_G \begin{bmatrix} g_w \\ 0_{n+3} \end{bmatrix} = \begin{bmatrix} 0 \\ 0 \\ -mg \\ 0_{3 \times 1} \\ 0_{n \times 1} \end{bmatrix} \quad (4)$$