mysql 安装过程

一、环境

系统: cenos 6.5

mysql版本: mysql 5.6.37

二、安装

1、下载mysql

wget https://dev.mysql.com/get/Downloads/MySQL-5.6/mysql-5.6.37-linux-glibc2.12-x86_64.tar.gz

2、校验md5值

md5sum mysql-5.6.37-linux-glibc2.12-x86_64.tar.gz

 $16be12598f7e4dcedb91b79b133fdbfc\ mysql-5.6.37-linux-glibc2.12-x86_64.tar.gz$

与官网一致

3、创建用户&安装

groupadd mysql
useradd -r -g mysql -s /bin/false mysql
cd /usr/local
tar zxvf /root/mysql-5.6.37-linux-glibc2.12-x86_64.tar.gz
ln -s mysql-5.6.37-linux-glibc2.12-x86_64 mysql
cd mysql
chown -R mysql ./
chown -R mysql ./
scripts/mysql_install_db —user=mysql
chown -R root ./
chown -R mysql data

4、安全启动mysql

bin/mysqld_safe —user=msyql & cp -rf support-files/mysql.server /etc/init.d/msyqld

5、设置环境变量

export PATH=\$PATH:/usr/local/mysql/bin

6、配置

```
vi /etc/my.cnf
...
port=3306
```

7、启动服务

service mysqld start

```
[[root@iZ940lbk2m8Z mysql]# service mysqld start
Starting MySQL
[root@iZ940lbk2m8Z mysql]# 170803 11:04:33 mysqld_safe A mysqld process already exists
```

8、运行验证

mysql -u root

```
[[root@iZ940lbk2m8Z mysql]# mysql -u root
Welcome to the MySQL monitor. Commands end with ; or \g.
Your MySQL connection id is 3
Server version: 5.6.37 MySQL Community Server (GPL)

Copyright (c) 2000, 2013, Oracle and/or its affiliates. All rights reserved.

Oracle is a registered trademark of Oracle Corporation and/or its affiliates. Other names may be trademarks of their respective owners.

Type 'help;' or '\h' for help. Type '\c' to clear the current input statement.

mysql>
```