

Homework 2

Guilherme Albertini

October 6, 2022

Theory

Problem 1.1: Convolutional Neural Networks

1. Given an input image of dimension 21×12 , what will be output dimension after applying a convolution with 4×5 kernel, stride of 4, and no padding?

$$5 \times 2$$

2. Given an input of dimension $C \times H \times W$ what will be the dimension of the output of a convolutional layer with kernel of size $K \times K$, padding P, stride S, dilation D, and F filters. Assume that $H \geq K$, $W \geq K$.

Define Padding along height on top P_{H1}

Define Padding along height on bottom P_{H2}

Define Padding along width on left P_{W1}

Define Padding along width on right P_{W2}

Define Kernel width K_H

Define Kernel height K_W

Define Stride horizontal S_W

Define Stride vertical S_H

Define Batch Count B

Effect of adding padding and applying kernel to dimensions:

$$H_P = P_{H1} + P_{H2} + H$$

$$W_P = P_{W1} + P_{W2} + W$$

$$\begin{aligned} H_{PK} &= H_1 - [D_H(K_H - 1) + 1] \\ &= P_{H1} + P_{H2} + H - [D_H(K_H - 1) + 1] \end{aligned}$$

$$\begin{aligned} W_{PK} &= W_1 - [D_W(K_W - 1) + 1] \\ &= P_{W1} + P_{W2} + W - [D_W(K_W - 1) + 1] \end{aligned}$$

Considering stride to dimensions:

$$\begin{aligned} H_{PKS} &= \left\lfloor \frac{H_P - [D_H(K_H - 1) + 1] + S_H}{S_H} \right\rfloor \\ &= \left\lfloor \frac{P_{H1} + P_{H2} + H - [D_H(K_H - 1) + 1]}{S_H} \right\rfloor + 1 \\ W_{PKS} &= \left\lfloor \frac{W_P - [D_W(K_W - 1) + 1] + S_W}{S_W} \right\rfloor \\ &= \left\lfloor \frac{P_{W1} + P_{W2} + W - [D_W(K_W - 1) + 1]}{S_W} \right\rfloor + 1 \end{aligned}$$

We can make simplifications that I think are implied here:

$$S = S_W = S_H$$

$$D = D_W = D_H$$

$$K = K_W = K_H$$

$$B = 1$$

$$P = P_{W1} + P_{W2} = P_{H1} + P_{H2}$$

$$W = \frac{2P + W - [D(K - 1) + 1]}{S} + 1$$

$$H = \frac{2P + H - [D(K - 1) + 1]}{S} + 1$$

Thus the output dimension is:

$$F \times \left(\left\lfloor \frac{2P + H - [D(K - 1) + 1]}{S} \right\rfloor + 1 \right) \times \left(\left\lfloor \frac{2P + W - [D(K - 1) + 1]}{S} \right\rfloor + 1 \right)$$

3. Let's consider an input $x[n] \in \mathbb{R}^5$, with $1 \leq n \leq 7$, e.g. it is a length 7 sequence with 5 channels. We consider the convolutional layer f_W with one filter, with kernel size 3, stride of 2, no dilation, and no padding. The only parameters of the convolutional layer is the weight W , $W \in \mathbb{R}^{1 \times 5 \times 3}$ and there is no bias and no non-linearity.

- (a) What is the dimension of the output $f_W(x)$? Provide an expression for the value of elements of the convolutional layer output $f_W(x)$. Example answer format here and in the following sub-problems: $f_W(x) \in \mathbb{R}^{42 \times 42 \times 42}$, $f_W(x)[i, j, k] = 42$.

4. Show

Problem 1.2: Recurrent Neural Networks

$$\sigma(z) = \frac{1}{1+\exp(-z)}.$$

1. If you want
2. Now

Problem 1.3: Debugging Loss Curves

1. Why is softmax actually softargmax?