DONGGUAN NANJING ELECTRONICS .

SOT-23 Encapsulate Adjustable Reference Source

AZ431 Adjustable Accurate Reference Source



DEVICE DESCRIPSION

The AZ431 is a three-terminal a djustable shunt regulator offering excellent temperature stability . This device has a typical dynamic output impedance of 0.2Ω. The device can be used as a replacement for zener diodes in many applications.

FEATURES

- The output voltage can be adjusted to 36V
- Low dynamic output impedance, its typical value is 0.2Ω
- Trapping current capability is 1 to 100mA
- Low output noise voltage
- Fast on -state response
- The effective temperature compensation in the working range of full temperature
- The typical value of the equivalent temperature factor in the whole temperature scope is 50 ppm/℃

APPLICATION

- Shunt Regulator
- High-Current Shunt Regulator
- Precision Current Limiter

ABSOLUTE MAXIMUM RATINGS (Operating temperature range applies unless otherwise specified)

Parameter	Symbol	Value	Unit
Cathode Voltage	V_{KA}	37	V
Cathode Current Range (Continuous)	I_{KA}	-100~+150	mA
Reference Input Current Range	Iref	0.05~+10	mA
Power Dissipation	P_D	300	mW
Thermal Resistance from Junction to Ambient	$R_{\theta JA}$	417	℃/W
Operating Junction Temperature	T_j	150	℃
Operating Ambient Temperature Range	T_{opr}	0~+70	℃
Storage temperature Range	Tstg	-65~+150	℃

ELECTRICAL CHARACTERISTICS (T_a=25℃ unless otherwise specified)

Parameter	Symbol	Test conditions		Min	Typ	Max	Unit
Reference input voltage (Fig.1)	V_{ref}	$V_{KA}=V_{REF}$, I_{KA}=10mA		2.450	2.5	2.550	V
Deviation of reference input voltage over temperature (note) (Fig.1)	$\triangle V_{ref}/\triangle T$	$V_{KA}=V_{REF}$, I_{KA}=10mA $T_{min}\leq T_a\leq T_{max}$			4.5	17	mV
Ratio of change in reference input voltage to the change in cathode voltage (Fig.2)	$\triangle V_{ref}/\triangle V_{KA}$	I_{KA}=10mA	$\triangle V_{KA}$ =10V~V_{REF}		-1.0	-2.7	mV/V
			$\triangle V_{KA}$ =36V~ 10V		-0.5	-2.0	mV/V
Reference input current (Fig.2)	I_{ref}	I_{KA}= 10mA,R_1=10kΩ R_2=∞			1.5	4	μA
Deviation Of reference input current over full temperature range (Fig.2)	$\triangle I_{ref}/\triangle T$	I_{KA}=10mA, R_1=10kΩ R_2=∞ T_a=full Temperature			0.4	1.2	μA
Minimum cathode current for regulation (Fig.1)	$I_{KA(min)}$	$V_{KA}=V_{REF}$			0.45	1.0	mA
Off-state cathode Current (Fig.3)	$I_{KA(OFF)}$	V_{KA}=36V,V_{REF}=0			0.05	1.0	μA
Dynamic impedance	Z_{KA}	$V_{KA}=V_{REF}$, I_{KA}=1 to 100mA f≤1.0kHz			0.15	0.5	Ω

note: T_{MIN}=0℃ ,T_{MAX}=+70℃

CLASSIFICATION of V_{ref}

Rank	0.4**%**	**0.5%**
Range	2.49-2.51	2.487-2.513









Test Circuit for $V_{KA}=V_{ref}$





Test Circuit for $V_{KA}=V_{ref}(1+R1/R2)+R1*I_{ref}$





Test Circuit for I_{ref}





Test Circuit for I_{off}