


Deep CNNs

Matthew Engelhard

Many slides created by Tim Dunn




CNNs Take Advantage of **Repeated, Hierarchical Structure** in Images



Deep Learning for Image Analysis

Diabetic Retinopathy Classification






Healthy Retina




Unhealthy Retina












Consider a Set of “Toy” Images,
for illustration of how this structure can be extracted by an algorithm











...












High-Level Motifs/Structure













Shared Substructure Within Motifs












Shared Substructure Within Motifs



Shared Substructure Within Motifs







Shared Substructure Within Motifs



Hierarchical Representation of Images

Layer 3:
Motifs






Layer 2:
Sub-Motifs




Layer 1:
Fundamental Building Blocks




Recall the Data/Images




...




Convolutional Filter




Convolutional Filter





Convolutional Filter





Multiple Filters, One for Each Building Block






















Deep CNN Architecture




Advantage of Hierarchical Features?




- By learning and sharing statistical similarities within high-level motifs, we better leverage all training data
- If we do not use such a hierarchy, top-level motifs would be learned in isolation of each other




2D Spatial Convolution




2D Spatial Convolution




2D Spatial Convolution



2D Spatial Convolution




2D Spatial Convolution



2D Spatial Convolution

Filter (W)


0	1	0
1	-4	1
0	1	0




Input (I)




Filters Operate Over Input Volumes




Filters Operate Over Input Volumes




Filters Operate Over Input Volumes



Given Labeled Training Images, How do we Learn the Parameters of the CNN?




Training Set



$$p_i = \sigma(b_0 + b_1x_{i1} + b_2x_{i2} + \dots + b_Mx_{iM})$$


Untrained Logistic Regression Model (or "Network")



$$b = (b_0, \dots, b_M)$$

Trained Model (with learned parameters)

Given Labeled Training Images, How do we Learn the Parameters of the CNN?



CNN
Architecture



Trained
CNN




Architecture (specified) vs Parameters (learned)

Architecture:

- Number of layers
- Layer types (e.g. convolutional, pooling, fully connected)
- Number of filters in each layer
- Shape and size of filters


Use 3x3 filters
In layer 1



Parameters:

- Individual Elements of each filter
- Parameters of other layers

Learn values of
Each layer 1 filter



Summary

- Convolutional neural networks learn to recognize **high-level structure** in images by building **hierarchical representations of features**
- Features are extracted via spatial convolutions with **filters**
- Filters are learned by minimizing a loss function just like in the other models we've discussed
- Convolutional neural networks have shown capabilities beyond human performance for image analysis

