

# HW 4

May 17, 2020

```
[1]: import numpy as np
import matplotlib.pyplot as plt
from sklearn.multiclass import *
from sklearn.linear_model import *
import sklearn.metrics as metrics
from sklearn.datasets import fetch_openml
from sklearn.model_selection import *
from scipy import ndimage

import warnings
warnings.simplefilter("ignore")
```

## 1 Problem 7.2

```
[2]: data = np.loadtxt("4class_data.csv", delimiter=',')
x, y = data[:-1, :], data[-1:, :].flatten()

print(x.shape)
print(y.shape)
```

```
(2, 40)
(40,)
```

```
[3]: OvA = OneVsRestClassifier(Perceptron(max_iter=100000, early_stopping=False,\
                                         fit_intercept=True, warm_start=False,\
                                         ↪penalty='l1',\
                                         alpha=0.0005))
OvA.fit(x.T, y)
```

```
[3]: OneVsRestClassifier(estimator=Perceptron(alpha=0.0005, class_weight=None,
                                             early_stopping=False, eta0=1.0,
                                             fit_intercept=True, max_iter=100000,
                                             n_iter_no_change=5, n_jobs=None,
                                             penalty='l1', random_state=0,
                                             shuffle=True, tol=0.001,
                                             validation_fraction=0.1, verbose=0,
                                             warm_start=False),
```

```
n_jobs=None)
```

```
[4]: OvA_pred = OvA.predict(x.T)
```

```
[5]: mat = metrics.confusion_matrix(y.flatten(), OvA_pred)
```

```
[6]: mat
```

```
[6]: array([[9, 1, 0, 0],
          [1, 8, 0, 1],
          [1, 1, 5, 3],
          [0, 1, 0, 9]], dtype=int64)
```

```
[7]: print("Number of classifications: %s" % str(np.sum(mat) - np.sum(np.diag(mat))))
```

Number of classifications: 9

## 2 Problem 7.3

```
[8]: data = np.loadtxt("3class_data.csv", delimiter=',')
     x, y = data[:-1, :], data[-1, :].flatten()

     print(x.shape)
     print(y.shape)
```

```
(2, 30)
(30,)
```

```
[9]: MC = Perceptron(max_iter=100000, early_stopping=False,\
                    fit_intercept=True, warm_start=False,\
                    ↪penalty='l1',\
                    alpha=0.0005)
```

```
[10]: MC.fit(x.T, y)
```

```
[10]: Perceptron(alpha=0.0005, class_weight=None, early_stopping=False, eta0=1.0,
                fit_intercept=True, max_iter=100000, n_iter_no_change=5, n_jobs=None,
                penalty='l1', random_state=0, shuffle=True, tol=0.001,
                validation_fraction=0.1, verbose=0, warm_start=False)
```

```
[11]: pred = MC.predict(x.T)
```

```
[12]: mat = metrics.confusion_matrix(y, pred)
```

```
[13]: mat
```

```
[13]: array([[10,  0,  0],
           [ 0, 10,  0],
           [ 0,  0, 10]], dtype=int64)
```

```
[14]: print("Number of classifications: %s" % str(np.sum(mat) - np.sum(np.diag(mat))))
```

Number of classifications: 0

### 3 Problem 9.2

```
[15]: x, y = fetch_openml('mnist_784', version=1, return_X_y = True)
      y = y.astype(int)
```

```
[16]: X_train, X_test, y_train, y_test = train_test_split(x, y, train_size=50000)
```

#### 3.1 Pixel-based training

```
[17]: #Arrays to store test and training histograms
      pixel_hists_train = np.zeros((X_train.shape[0], 256))
      pixel_hists_test  = np.zeros((X_test.shape[0], 256))

      #Training
      for i in range(pixel_hists_train.shape[0]):
          count = np.histogram(X_train[i], bins=256, range=[0, 255])[0]
          pixel_hists_train[i, :] = 1.0*count

      #Test
      for i in range(pixel_hists_test.shape[0]):
          count = np.histogram(X_test[i], bins=256, range=[0, 255])[0]
          pixel_hists_test[i, :] = 1.0*count
```

```
[18]: #Arrays to store score and cost functions
      pix_score = np.array([])
      pix_cost  = np.array([])

      #Run through 1 to 20 steps
      for j in range(1, 21):
          softmax = SGDClassifier(loss = 'log', penalty='l1', alpha=0.01, max_iter=j,
          ↪
                                     early_stopping=False, warm_start=True)

          #Fit and predict
          softmax.fit(pixel_hists_train, y_train)
          y_pred = softmax.predict_proba(pixel_hists_test)

          #Calculate a score (% right) and cost function; save
```

```

    pix_score = np.append(pix_score, softmax.score(pixel_hists_test, y_test))
    pix_cost = np.append(pix_cost, metrics.log_loss(y_test, y_pred,
↪normalize=True))

```

## 3.2 Edge training

```

[19]: #Arrays to store test and training histograms
edge_hists_train = np.zeros((X_train.shape[0], 8))
edge_hists_test = np.zeros((X_test.shape[0], 8))

#Training
for i in range(edge_hists_train.shape[0]):
    reshape = X_train[i].reshape((28, 28))

    #Calculate Gaussian derivatives to find edges in x and y directions
    dIdx = ndimage.filters.gaussian_filter(reshape, [1, 1], order=[0,1],
↪mode='nearest')
    dIdy = ndimage.filters.gaussian_filter(reshape, [1, 1], order=[1,0],
↪mode='nearest')

    #Determine the angle of the edge
    angle = np.arctan(dIdy / dIdx)

    #Make histogram
    count = np.histogram(angle, bins=8, range=[-np.pi/2, np.pi/2])[0]
    edge_hists_train[i, :] = 1.0 * count

#Test
for i in range(edge_hists_test.shape[0]):
    reshape = X_test[i].reshape((28, 28))

    dIdx = ndimage.filters.gaussian_filter(reshape, [1, 1], order=[0,1],
↪mode='nearest')
    dIdy = ndimage.filters.gaussian_filter(reshape, [1, 1], order=[1,0],
↪mode='nearest')

    angle = np.arctan(dIdy / dIdx)

    count = np.histogram(angle, bins=8, range=[-np.pi/2, np.pi/2])[0]
    edge_hists_test[i, :] = 1.0 * count

```

```

[20]: edge_score = np.array([])
edge_cost = np.array([])

for j in range(1, 21):

```

```

softmax = SGDClassifier(loss = 'log', penalty='l1', alpha=0.01, max_iter=j,
↪\
                        early_stopping=False, warm_start=True)

softmax.fit(edge_hists_train, y_train)
y_pred = softmax.predict_proba(edge_hists_test)

edge_score = np.append(edge_score, softmax.score(edge_hists_test, y_test))
edge_cost = np.append(edge_cost, metrics.log_loss(y_test, y_pred,
↪normalize=True))


```

```

[21]: plt.plot(list(range(1, 21)), (1.0 - pix_score) * X_test.shape[0],
↪label="Pixel-Based")
plt.plot(list(range(1, 21)), (1.0 - edge_score) * X_test.shape[0],
↪label="Edge-Based")
plt.xlabel("Iterations")
plt.ylabel("Number of Misclassifications")
plt.legend()
plt.xlim(0, 20)

```

[21]: (0, 20)



```

[22]: plt.plot(list(range(1, 21)), pix_cost, label="Pixel-Based")
plt.plot(list(range(1, 21)), edge_cost, label="Edge-Based")

```

```
plt.xlabel("Iterations")  
plt.ylabel("Cost")  
plt.legend()
```

[22]: <matplotlib.legend.Legend at 0x25b6ae96408>

