

FAUCET HOT/COLD STOP COCK FROM INSIDE KITCHEN 4FEET(TALL)x2FEET MOTOR:GROUND-WATER-DIRECT BALCONY1 9INCH WINDOW VERTICAL SLIDING IN CASE OF 1ST TO 3RD FLOOR. (B) ON CAGE

SHAFT REAR-MAINHOLE WINDOW VERTICAL SLIDING 6FEET(TALL)x3FEET EXHAUST

BALCONY2 1FEET6INCH WINDOW MANUAL VERTICAL SLIDING 4FEET(TALL)x3FEET

FAUCET HOT/COLD

DOOR3

HANDWARE MAGRO MODEL RIMLESS ONE PIECE CLOSET ENGLISH LATERINE

1FEET 9INCH

REMAINING LENGTH 1.5INCH

BED(NOT_BOX_TYPE) 6FEET6INCHx4FEET

CHAIR

CUPBOARD HALF SLIDING DOOR 4FEETx1FEET6INCH

GEYSER

TOOTHBRUSH BASIN FAUCET HOT/COLD/DIRECT

FAUCET HOT/COLD/DIRECT

SHOWER SINK

STUDY TABLE HINGED 1INCH THICK WOOD BOARD WALL MOUNTED BREADTH 1FEET3INCH LENGTH 2.5 FEET

DOOR2: 2FEET 6INCH

SLIDING DOOR4 2FEET6INCH

SEMI-AUTO WASHING MACHINE 4FEET

FAUCET HOT/COLD/DIRECT

1FEET3INCH BREADTH CONCRETE CEMENT SLAB AT HEIGHT 2FEET9INCH

3FEET3INCH

7FEETINCHminus4.5INCH=6FEET7.5INCH

6FEETx1FEET9INCH SOFA

6FEET

FRIDGE

COMPUTER_CUM_LED_TV_RACK DESK/WALL MOUNTED

5FEET6INCH

STAIRCASE 4FEET (2ft+2ft)

STAIRCASE 11FEET

15 FEET

FRONT MAINHOLE

INTEGRATE 1ST STEP OF STAIRCASE 8INCH BREADTH WITH BALCONY 9 INCH IN CASE OF 1ST TO 3RD FLOOR.

FAUCET HOT/COLD/DIRECT

KITCHEN BASIN

ENTRY DOOR: 2FEET6INCH

5FEET6INCH

MOTOR:GROUND-WATER-DIRECT BALCONY1 9INCH WINDOW VERTICAL SLIDING 4FEET(TALL)x2FEET

THE OUTER 2_LENGTH SIDES RED SOLID BRICK WALLS THICKNESS IS=9INCH
 ALL OTHER RED SOLID BRICK WALLS THICKNESS IS=4.5INCH
 6_PILLARS:CONCRETE CEMENT TATASTEEL(IRON ORE NON SCRAP)TISCO RODS WILL BE REQUIRED. CEILING HEIGHT/FLOOR 10FEET3INCH.
 NOTE1: ALL BRICK WALLS THICKNESS MEASUREMENTS HAVE BEEN ACCOUNTED FOR BEFORE CONCLUDING THE
 INSIDE TO BETWEEN WALLS CLEARANCE DIMENSIONS. TILE SKIRTING TO BE AT SAME LEVEL AS CEMENTSAND(1:4RATIO)WALLPLASTER.
 NOTE2:FOR INDIVIDUAL PLOT [[ONLY]] FROM 1ST TO 3RD FLOOR REAR BALCONY2 BREADTH SHOULD BE [[REDUCED]] TO 9 INCH GIVIN
 G OPEN TO SKY CLEARANCE OF 9 INCH.
 REDUCED BECAUSE THERE IS A TOTAL POSSIBILITY THAT YOUR BALCONY2(REAR) WILL GET BLOCKED BY WALL(REAR) OF REAR ADJACE
 NT PLOT OWNER. YOU SHOULD RAISE YOUR REAR END BOUNDARY 4.5 INCH WALL TILL 3RD FLOOR.
 ALL INSIDE TO BETWEEN WALLS CLEARANCE DIMENSIONS(LENGTHxBREADTH):
 1. ENTRY DOOR: 2FEET6INCH NOTE1: 2_ANGULAR_STOP COCKS TO BE FITTED BEFORE EVERY SINK
 2. STAIRCASE: 11FEETx4FEET MIXER, EXCEPT AT PLACE OF SHOWER.
 3. KITCHEN: 6FEET7.5INCHx3FEET3INCH, CONCRETE CEMENT SLAB BREADTH 1FEET3INCH, AT HEIGHT 2FEET9INCH +
 1.0INCH THICKNESS MARBLE STONE ON TOP, SAME HEIGHT FOR KITCHEN BASIN 3. KUBIX PRIME KUP-35021PM PILLAR COCK
 4. SEMI_AUTO_WASHING_MACHINE: UPTO 3FEETx2FEET (WHIRLPOOL SUPERB ATOM 6.5 KG) (DIRECT) for BASIN 190MM EXTENSION BODY
 5. BATHROOM-CUM-TOILET:5FEET6INCHx4FEET9INCH, EXHAUST_FAN_CROMPTON_GREAVES: TRANSAIR/225MM/1400RPM/BIRD-SCREEN
 6. DRAWING_ROOM/HALL: 11FEETx5FEET6INCH NOTE2: FOR SHOWER-MIXER-ETERNAL KUP-35115PM 4. BIB COCK KUP-35037PM (DIRECT/GEYSER)
 7. SOFA: 6FEETx1FEET9INCH(MAXIMUM) Rupees 7100 (1 No.), SHOWER PIPE (SHA-1211N) Rupees 1700 NUMBERS= 6
 8. FRIDGE:UPTO 2FEETx2FEET NOTE3: FOR HAND-SHOWER-MIXER-EXTERNAL KUP- 5. KITCHEN LYRIC LYN-38309 SINK MIXER
 9. BEDROOM: 8FEET4.5INCHx5FEET6INCH 35149PM Rupees 6150 (1 No.) SWINGING SPOUT Rupees 4000 NUMBERS= 8
 10. SHAFT-REAR-MAINHOLE: 5FEETx1FEET6INCH (OPEN TO SKY CLEARANCE) 6. SHOWER OHS-WHM-1763 Rupees 23450
 11. BALCONY1(FRONT): 9INCH BREADTH NOTE4: ALL JAGUAR ITEMS IN CHROME FINISH 7. HAND SHOWER(BATH) HSH-1721 Rupees 3750
 12. BALCONY2(REAR): 1FEET6INCH BREADTH (IMPORTANT FOR YOUR LIFE & A MUST IN A HOUSE) 8. ANGULAR STOP COCK KUP-35053PM
 13. CUPBOARD_HALF_SLIDING_DOOR: 4FEETx1FEET6INCH(4FEETx1FEET5INCH, 1INCH MARGIN FOR SLIDING DOOR) Rupees1350 NUMBERS= 19
 14. BED(NOT_BOX_TYPE): 6FEET6INCHx4FEET, HEIGHT OF BED=12INCH+5INCH KURLONmattress 9. BEFORE ALL SINK MIXER OUTPUTS, USE 2-
 15. DOOR2: 2FEET6INCH NOTES5: ALSO, ANGULAR_STOP COCK TO BE FITTED, 1 EACH BEFORE, ANGULAR STOP COCK KUP-35053PM FOR
 16. DOOR3: 1FEET10.5INCH DIRECT_PILLAR COCK & DIRECT_WASHING_MACHINE BIB COCK & DIRECT INTAKE AND GEYSER INTAKE, THEN USE
 17. SLIDING DOOR4: 2FEET6INCH DIRECT KITCHEN BIB COCK. 1- SINK MIXER(RATIO) LYRIC LYN-38309PM
 18. USE SOMANY_TILES, TATASTEEL(IRON ORE NonSCRAP neverRustsInternally)WATER GI PIPES, WITHOUT SPOUT FOR FULL DIRECT
 UNIK GI FITTINGS(make_sure_spelling_in_products), KISAN PVC OUTPUT/FULL GEYSER OUTPUT/MIXER(RATIO)
 PIPES(FIRST_BIG DIAMETER VERTICAL PIPELINE IN SHAFT FOR LATERINE CLOSET SINK & SECOND SMALL DIAMETER VERTICAL PIPEL
 NE IN SHAFT FOR SHOWER CUM TOOTBRUSH BASIN CUM WASHING MACHINE CUM SINKS & THIRD SMALL SAME DIAMETER VE
 RTICAL PIPELINE IN SHAFT FOR KITCHEN BASIN SINK & FOURTH SMALL SAME DIAMETER VERTICAL PIPELINE IN SHAFT FOR BALC
 ONY2 SINK) & FITTINGS(KISAN NALI TRAP SIPHON SINK)SHOULD BE EXACTLY HORIZONTALLY LEVELLED SUPERVISE YOURSELF AND
 PURCHASE DOUBLE THE AMOUNT OF PVC ADHESIVE SOLUTION OF WHAT PLUMBER TELLS YOU AND TELL PLUMBER TO APPLY D
 OUBLE THE AMOUNT OF WHAT HE NORMALLY APPLIES), HINDWARE AMAZON RIMLESS SINGLE-PIECE CLOSET, HINDWARE KITCHEN
 STAINLESSSTEEL(SS)_MATT FINISH BASIN, HINDWARE TOOTHBRUSH BASIN, JAGUAR_COMPANY FAUCETS,
 KIRANSLIDOCRAFT MANUAL_VERTICAL_SLIDING WINDOW MIDDLE PICTURE.
 19. BALCONY2(REAR)_SECURELY ENCLOSED USING GRID CAGE IRON SQUARE RODS.
 20. STUDY TABLE WALL MOUNTED HINGED BOARD 4-LEG-SKELETAL-MODULAR-PLASTIC-FRAME-SUPPORT-HT.-2FEET3INCH-BREADTH1.25FT.
 21. RED SOLID BRICK DIMENSION: 9INCHx4.5INCH(DIFFICULT TO FIND EXACTLY THIS DIMENSION, MAYBE IN
 VILLAGE KILNS OR FIND AS CLOSE AS POSSIBLE, BRICK-KILN-OWNERS HAVE REDUCED THE BRICK-DIE-SIZE).
 22. SUPER BUILT-UP AREA(TOTAL PLOT_SIZE LENGTHxBREADTH): 20FEETx15FEET(FRONT)
 23. Use 1. LEGRAND_COMPANY ELECTRICAL SWITCHES, SOCKETS 2. ABB_COMPANY MCB 3. KEI_COMPANY WIRES&CABLES 4. OSRAM CFL 23W
 24. KAPSUL-AIR(DEPTH=22INCH) AIRCONDITIONER INSTALLATION AS IT APPEARS IN ADVERTISORY VIDEOS THAT ATLEAST 4 INCH DEPTH IS
 INSIDE WINDOW, THIS IMPLIES OUTSIDE WINDOW DEPTH OF 22-4=18INCH: (A) ON GROUND FLOOR THERE IS A CLEAR MARGIN OF 18INCH
 (B) ON 1ST FLOOR TO 3RD FLOOR AS BALCONY2 CLEARANCE IS 9INCH ONLY, SO MAKE A KAPSUL BODY SHAPE 7INCH HEIGHT SLOT IN IRON
 CAGE AT WINDOW-KAPSUL-INSTALL-HT. IN THE BOUNDARY-RAILING-CUM-CAGE OF BALCONY2. ALSO, KAPSUL-AIR HAS FRESH-AIR-MODE.
 →9INCH RED SOLID BRICK WALL NOTE: STANDARD EARTHING: 2inchx2inchx1inch COPPER-SOLID-BLOCK BURIED 10FEET DEEP IN GROUND
 →4.5INCH RED SOLID BRICK WALL &CONNECTED USING COPPER SOLID WIRE GAUGE-AWG4/5.18MM DIAMETER/21.15 MMSQUARE.