

THE OUTER 2\_LENGTH SIDES RED SOLID BRICK WALLS THICKNESS IS=9 INCH  
 ALL OTHER RED SOLID BRICK WALLS THICKNESS IS=4.5 INCH  
 6\_PILLARS: CONCRETE CEMENT TATASTEEL (IRON\_ORE\_NON\_SCRAP) TISCON RODS WILL BE REQUIRED. CEILING HEIGHT/FLOOR 10 FEET 3 INCH.  
 NOTE1: ALL BRICK WALLS THICKNESS MEASUREMENTS HAVE BEEN ACCOUNTED FOR BEFORE CONCLUDING THE INSIDE TO BETWEEN WALLS  
 CLEARANCE DIMENSIONS. TILE SKIRTING TO BE AT SAME LEVEL AS CEMENT: MEDIUM-GRAINSIZE-FINESAND (1:4 RATIO) WALL PLASTER.  
 NOTE2: FOR INDIVIDUAL PLOT [[ONLY]] FROM 1<sup>ST</sup> TO 3<sup>RD</sup> FLOOR REAR BALCONY2 BREADTH SHOULD BE [[REDUCED]] TO 9 INCH GIVIN  
 G OPEN TO SKY CLEARANCE OF 9 INCH.  
 REDUCED BECAUSE THERE IS A TOTAL POSSIBILITY THAT YOUR BALCONY2 (REAR) WILL GET BLOCKED BY WALL (REAR) OF REAR ADJACE  
 NT PLOT OWNER. YOU SHOULD RAISE YOUR REAR END BOUNDARY 4.5 INCH WALL TILL 3<sup>RD</sup> FLOOR.  
 ALL INSIDE TO BETWEEN WALLS CLEARANCE DIMENSIONS (LENGTHx BREADTH):

- ENTRY DOOR: 2 FEET 6 INCH NOTE1: JAGUAR 2 ANGULAR STOP COCKS TO BE FITTED
- STAIRCASE: 11 FEET x 4 FEET BEFORE EVERY SINK MIXER, EXCEPT AT PLACE OF SHOWER.
- KITCHEN: 6 FEET 7.5 INCH x 3 FEET 3 INCH, CONCRETE CEMENT SLAB BREADTH 1 FEET 3 INCH, AT HEIGHT 2 FEET 9 INCH +  
 1.0 INCH THICKNESS MARBLE STONE ON TOP, SAME HEIGHT FOR KITCHEN BASIN
- SEMI\_AUTO WASHING MACHINE: UPTO 3 FEET x 2 FEET (WHIRLPOOL SUPERB ATOM 6.5 KG)
- BATHROOM-CUM-TOILET: 5 FEET x 4 FEET 9 INCH, EXHAUST FAN CROMPTON GREAVES: TRANSAIR/225MM/1400RPM/BIRD-SCREEN
- DRAWING ROOM/HALL: 11 FEET x 5 FEET 6 INCH
- SOFA: 6 FEET x 1 FEET 9 INCH (MAXIMUM) NOTE2: JAGUAR FOR SHOWER-MIXER-ETERNAL KUP-  
 35115PM Rupees 7100 (1 No.), SHOWER PIPE (SHA-1211N)
- FRIDGE: UPTO 2 FEET x 2 FEET NOTE3: JAGUAR FOR HAND-SHOWER-MIXER-EXTERNAL  
 KUP-35149PM Rupees 6150 (1 No.)
- BEDROOM: 8 FEET 4.5 INCH x 5 FEET 6 INCH
- SHAFT-REAR-MAINHOLE: 4 FEET 9 INCH x 2 FEET (OPEN TO SKY CLEARANCE IRON CAGE AT TOP)
- BALCONY1 (FRONT): 9 INCH BREADTH NOTE4: ALL JAGUAR ITEMS IN CHROME FINISH
- BALCONY2 (REAR): 1 FEET 6 INCH BREADTH (IMPORTANT FOR YOUR LIFE & A MUST IN A HOUSE)
- CUPBOARD HALF SLIDING DOOR: 4 FEET x 1 FEET 6 INCH (4 FEET x 1 FEET 5 INCH, 1 INCH MARGIN FOR SLIDING DOOR)
- BED (NOT BOX TYPE): 6 FEET 6 INCH x 4 FEET, HEIGHT OF BED=12 INCH+5 INCH KURLON mattress
- DOOR2: 2 FEET 6 INCH NOTE5: ALSO, JAGUAR ANGULAR STOP COCK TO BE FITTED,
- DOOR3: 1 FEET 10.5 INCH 1 EACH BEFORE, DIRECT PILLAR COCK &
- SLIDING DOOR4: 2 FEET 6 INCH DIRECT WASHING MACHINE BIB COCK & DIRECT KITCHEN BIB COCK.
- USE SOMANY TILES, TATASTEEL (IRON\_ORE\_NON\_SCRAP\_neverRustsInternally) WATER GI PIPES, WITHOUT SPOUT FOR FULL DIRECT  
 UNIK GI FITTINGS (make\_sure\_spelling\_in\_products), KISAN (SWR: Soil, Waste, Rain Water) uPVC OUTPUT/FULL GEYSER OUTPUT/MIXER (RATIO)  
 PIPES (FIRST 4 INCH DIAMETER VERTICAL PIPELINE IN SHAFT FOR LATERINE CLOSET SINK & SECOND 3 INCH DIAMETER VERTICAL PIPE  
 ELINE IN SHAFT FOR SHOWER CUM TOOTBRUSH BASIN CUM WASHING MACHINE CUM SINKS & THIRD 3 INCH DIAMETER VERTICAL PIPE  
 L PIPELINE IN SHAFT FOR KITCHEN BASIN SINK & FOURTH 3 INCH DIAMETER VERTICAL PIPELINE IN SHAFT FOR BALCONY2 SINK)  
 & FITTINGS (ALL (6) KISAN NALI TRAP 3 INCH SIPHON SINKS) SHOULD BE EXACTLY HORIZONTALLY LEVELLED SUPERVISE YOURSELF AN  
 D PURCHASE DOUBLE THE AMOUNT OF PVC ADHESIVE SOLUTION OF WHAT PLUMBER TELLS YOU AND TELL PLUMBER TO APPLY  
 DOUBLE THE AMOUNT OF WHAT HE NORMALLY APPLIES), HINDWARE AMAZON RIMLESS SINGLE-PIECE CLOSET, HINDWARE KITCHEN  
 STAINLESSSTEEL (SS) MATT FINISH BASIN, HINDWARE TOOTHBRUSH BASIN, JAGUAR COMPANY FAUCETS,  
 KIRANSLIDOCRAFT MANUAL VERTICAL SLIDING WINDOW MIDDLE PICTURE.
- BALCONY2 (REAR) SECURELY ENCLOSED BY GRID CAGE IRON SQUARE RODS. CAGE BORDER ANGLE WIDTH=1.5 INCH, ROD=0.375 INCH
- STUDY TABLE WALL MOUNTED HINGED BOARD 4-LEG-SKELETAL-MODULAR-PLASTIC-FRAME-SUPPORT-HT.-2 FEET 3 INCH-BREADTH 1.25 FT.
- RED SOLID BRICK DIMENSION: 9 INCH x 4.5 INCH (DIFFICULT TO FIND EXACTLY THIS DIMENSION, MAYBE IN  
 VILLAGE KILNS OR FIND AS CLOSE AS POSSIBLE, BRICK-KILN-OWNERS HAVE REDUCED THE BRICK-DIE-SIZE).
- SUPER BUILT-UP AREA (TOTAL PLOT SIZE LENGTHx BREADTH): 20 FEET x 15 FEET (FRONT)
- Use 1. LEGRAND COMPANY ELECTRICAL SWITCHES, SOCKETS 2. ABB COMPANY MCB 3. KEI COMPANY WIRES & CABLES 4. OSRAM CFL 23W
- KAPSUL-AIR (DEPTH=22 INCH) AIRCONDITIONER INSTALLATION AS IT APPEARS IN ADVERTISORY VIDEOS THAT ATLEAST 4 INCH DEPTH IS  
 INSIDE WINDOW, THIS IMPLIES OUTSIDE WINDOW DEPTH OF 22-4=18 INCH: (A) ON GROUND FLOOR THERE IS A CLEAR MARGIN OF 18 INCH  
 (B) ON 1<sup>ST</sup> FLOOR TO 3<sup>RD</sup> FLOOR AS BALCONY2 CLEARANCE IS 9.0-1.5=7.5 INCH, SO MAKE A KAPSUL BODY SHAPE 7 INCH HEIGHT SLOT IN IRON  
 CAGE AT WINDOW-KAPSUL-INSTALL-HT. IN THE BOUNDARY-RAILING-CUM-CAGE OF BALCONY2. ALSO, KAPSUL-AIR HAS FRESH-AIR-MODE.

→ 9 INCH RED SOLID BRICK WALL NOTE: STANDARD EARTHING: 2 inch x 2 inch x 1 inch COPPER-SOLID-BLOCK BURIED 10 FEET DEEP IN GROUND  
 HAND PUMP) → 4.5 INCH RED SOLID BRICK WALL & CONNECTED USING COPPER SOLID WIRE GAUGE-AWG4/5.18MM DIAMETER/21.15 MMSQUARE.