USE JAGJEET ESTD. 1968 MANUAL VERTICAL CITRUS FRUIT PRESS THE OUTER 2 LENGTH SIDES RED SOLID BRICK WALLS THICKNESS IS=9INCH **GROUND FLOOR PLAN: SUPER BUILT-UP AREA: 300 SQUARE FEET** JUICE MACHINE CONTOURLESS BODY FINISH, CHECK SIEVE FOR CRACK ALL OTHER RED SOLID BRICK WALLS THICKNESS IS=4.5INCH 1 INCH HAS 8 1 FEET/1FOOT= 3INCH+3INCH+3INCH+3INCH, Eg. 1FEET6 INCH=1.5FEET, 1FEET3 INCH=1.25FEET AND HOLES SYMMETRY FINISH.
6_PILLARS:CONCRETE_CEMENT_TATASTEEL(IRON_ORE_NON_SCRAP)TISCON_RODS_WILL_BE_REQUIRED. CEILING HEIGHT/FLOOR 10FEET3INCH. **EQUAL PARTS** SHAFT REAR-MAINHOLE FAUCET HOT/COLD BALCONY211FEET6INCH a PART, NOTE1:ALL BRICK WALLS THICKNESS MEASUREMENTS HAVE BEEN ACCOUNTED FOR BEFORE CONCLUDING THE WINDOW MANUAL VERTICAL SLIDING WINDOW VERTICAL SLIDING SPOKEN AS □⊕ INSIDE_TO_BETWEEN_WALLS_CLEARANCE_DIMENSIONS. TILE_SKIRTING_TO_BE_AT_SAME_LEVEL_AS_CEMENTsand(1:4RATIO)WALLPLASTER. 6FEET(TALL)x3FEET EXHAUST DOOR3 4FEET(TALL)x3FEET 1by8, AND NOTE2:FOR_INDIVIDUAL_PLOT_[[ONLY]]_FROM_1ST_TO_3RD_FLOOR_REAR_BALCONY2_BREADTH_SHOULD_BE_[[REDUCED]]_TO_9_INCH_GIVIN 1FEET WRITTEN AS HINDWARE G OPEN TO SKY CLEARANCE OF 9 INCH. 9INCH MAGRO MQDEL **REMAINING LENGTH 1.5INCH** REDUCED_BECAUSE_THERE_IS_A_TOTAL_POSSIBILITY_THAT_YOUR_BALCONY2(REAR)_WILL_GET_BLOCKED_BY_WALL(REAR)_OF_REAR_ADJACE RIMLESS ONE **AOSMITH KLASSE** /75 ₹ NT PLOT OWNER. YOU SHOULD RAISE YOUR REAR END BOUNDARY 4.5 INCH WALL TILL 3RD FLOOR. PIECE CLOSE JAGUAR 1. KUBIX KUS-WHT-35935 **GEYSER 25 LITRES ENGLISH LATERINE** ALL_INSIDE_TO_BETWEEN_WALLS_CLEARANCE_DIMENSIONS(LENGTHxBREADTH): TOOTHBRUSH BASIN 565mmX420mmX140mm BED(NOT_BOX_TYPE) INPUT: USE NOTE1: 2 ANGULAR STOP COCKS TO BE FITTED BEFORE EVERY SINKRUPEES 6990, AS IN PRODUCT CATALOGUE **ENTRY DOOR: 2FEET6INCH 6FEET6INCHx4FEET** JAGUAR 2-2. HAND SHOWER(LATERINE) ALD-573 Rs. 1350 STAIRCASE: 11FEETx4FEET MIXER, EXCEPT AT PLACE OF SHOWER. ANGULAR STOP COCK KUP-KITCHEN: 6FEET7.5INCHx3FEET3INCH, CONCRETE CEMENT SLAB BREADTH 1FEET3INCH, AT HEIGHT 2FEET9INCH + 3. KUBIX PRIME KUP-35021PM PILLAR COCK 35053PM FOR 1.0INCH THICKNESS MARBLE STONE ON TOP, SAME HEIGHT FOR KITCHEN BASIN (DIRECT) for BASIN 190MM EXTENSION BODY DIRECT INTAKE SEMI_AUTO_WASHING_MACHINE: UPTO_3FEETx2FEET (WHIRLPOOL SUPERB ATOM 6.5 KG) **CUPBOARD HALF SLIDING** AND TANK INTAKE, BATHROOM-CUM-TOILET:5FEET6INCHx4FEET9INCH, EXHAUST_FAN_CROMPTON_GREAVES: TRANSAIR/225MM/1400RPM/BIRD-SCREEN 5. CHAIR THEN USE 1-DOOR 4FEETx1FEET6INCH DRAWING ROOM/HALL: 11FEETx5FEET6INCH NOTE2: FOR SHOWER-MIXER-ETERNAL KUP-35115PM 6. 4. BIB COCK KUP-35037PM (DIRECT/GEYSER) JAGUAR SINK DOOR2: SOFA: 6FEETx1FEET9INCH(MAXIMUM) Rupees 1700 NUMBERS= 6 Rupees 7100 (1 No.), SHOWER PIPE (SHA-1211N) 5 SLIDING DOOR4 MIXER(RATIO) 2FEET EMI-AUTO 8. FRIDGE:UPTO 2FEETx2FEET NOTE3: FOR HAND-SHOWER-MIXER-EXTERNAL KUP-5. KITCHEN LYRIC LYR-38309 SINK MIXER LYRIC LYR-38309PM 2FEET6INCH 6INCH SWINGING SPOUT Rupees 4000 NUMBERS= 8 9. BEDROOM: 8FEET4.5INCHx5FEET6INCH 35149PM Rupees 6150 (1 No.) WITHOUT SPOUT 6. SHOWER OHS-WHM-1763 Rupees 23450 FOR FULL DIRECT 10. SHAFT-REAR-MAINHOLE: 5FEETx1FEET6INCH (OPEN TO SKY CLEARANCE) 7. HAND SHOWER(BATH) HSH-1721 Rupees 3750 INPUT/FULL TANK NOTE4: ALL_JAGUAR_ITEMS_IN_CHROME_FINISH 8. ANGULAR STOP COCK KUP-35053PM BALCONY1(FRONT): 9INCH BREADTH SEMI-AUTO WASHING I INPUT. BALCONY2(REAR): 1FEET6INCH BREADTH (IMPORTANT FOR YOUR LIFE & A MUST IN A HO Rupees1350 NUMBERS= 19 SINK MIXER CUPBOARD_HALF_SLIDING_DOOR: 4FEETx1FEET6INCH(4FEETx1FEET5INCH, 1INCH_MARGIN_FOR_SLIDING_DOOR) **4FEET** BED(NOT_BOX_TYPE): 6FEET6INCHx4FEET, HEIGHT_OF_BED=12INCH+5INCH_KURLONmattress 9. BEFORE ALL SINK MIXER OUTPUTS, USE 2-HINDWARE KITCHEN SOFA 15. DOOR2: 2FEET6INCH NOTES: ALSO, ANGULAR STOP COCK TO BE FITTED, 1 EACH BEFORE, ANGULAR STOP COCK KUP-35053PM FOR **BASIN (SS) STAINLESS** DIRECT_PILLAR_COCK & DIRECT_WASHING_MACHINE_BIB_COCK & DOOR3: 1FEET10.5INCH DIRECT INTAKE AND GEYSER INTAKE, THEN USE STEEL CHROME FINISH 17. SLIDING DOOR4: 2FEET6INCH DIRECT_KITCHEN_BIB_COCK. 1- SINK MIXER(RATIO) LYRIC LYR-38309PM **PLATINO** WITHOUT SPOUT FOR FULL DIRECT MODEL NO .: 18. USE SOMANY TILES, TATASTEEL (IRON ORE NONSCRAP neverRustsInternally)WATER_GI_PIPE OUTPUT/FULL GEYSER OUTPUT/MIXER(RATIO) 36X20X8 UNIK GI FITTINGS(make sure spelling in products), KISAN PVC PIPES(FIRST_BIG_DIAMETER_VERTICAL_PIPELINE_IN_SHAFT_FOR_LATERINE_CLOSET_SINK_&_SECOND_SMALL_DIAMETER_VERTICAL_PIPEL 36INCH×20INCH x8INCH INE_IN_SHAFT_FOR_SHOWER_CUM_TOOTBRUSH_BASIN_CUM_WASHING_MACHINE_CUM_SINKS_&_THIRD_SMALL_SAME_DIAMETER_VE STAIRCASE 4FEET(2ft+2ft USE. VINOD RTICAL_PIPELINE_IN_SHAFT_FOR_KITCHEN_BASIN_SINK_&_FOURTH_SMALL_SAME_DIAMETER_VERTICAL_PIPELINE_IN_SHAFT_FOR_BALC INDUCTION MODENA ONY2 SINK) & FITTINGS(KISAN NALI TRAP SIPHON SINK)SHOULD BE EXACTLY HORIZONTALLY LEVELLED SUPERVISE YOURSELF AND (SS) COOKWARE, PURCHASE_DOUBLE_THE_AMOUNT_OF_PVC_ADHESIVE_SOLUTION_OF_WHAT_PLUMBER_TELLS_YOU_AND_TELL_PLUMBER_TO_APPLY_D **SUJATA 900WATT** OUBLE_THE_AMOUNT_OF_WHAT_HE_NORMALLY_APPLIES), HINDWARE AMAZON RIMLESS SINGLE-PIECE CLOSET, HINDWARE KITCHEN JUICER-CUM-GRINDER STAINLESSSTEEL(SS) MATT FINISH BASIN, HINDWARE TOOTHBRUSH BASIN, JAGUAR COMPANY FAUCETS, THIS IS LIKE 5FEET6INCH KIRANSLIDOCRAFT_MANUAL_VERTICAL_SLIDING_WINDOW_MIDDLE_PICTURE. RAIN-BALCONY2(REAR) SECURELY ENCLOSED BY GRID CAGE IRON SQUARE RODS.CAGE BORDER ANGLE WIDTH=1.5INCH, ROD=0.375INCH WATER STUDY TABLE WALL MOUNTED HINGED BOARD 4-LEG-SKELETAL-MODULAR-PLASTIC-FRAME-SUPPORT-HT.-2FEET3INCH-BREADTH1.25FT. SINK, SO RED SOLID BRICK DIMENSION: 9INCHX4.5INCH(DIFFICULT TO FIND EXACTLY THIS DIMENSION, MAYBE IN THIS GOES 15 FEET VILLAGE KILNS OR FIND AS CLOSE AS POSSIBLE, BRICK-KILN-OWNERS HAVE REDUCED THE BRICK-DIE-SIZE). TO 22. SUPER BULIT-UP AREA(TOTAL PLOT SIZE LENGTHXBREADTH): 20FEETX15FEET(FRONT) GROUND-**FAUCET** INTEGRATE 1ST STEP OF FLOOR 23. Use 1. LEGRAND COMPANY ELECTRICAL SWITCHES, SOCKETS 2. ABB COMPANY MCB 3. KEI COMPANY WIRES&CABLES 4. OSRAM CFL 23W HOT/COLD/direct STAIRCASE FRONT-24. KAPSUL-AIR(DEPTH=22INCH) AIRCONDITIONER INSTALLATION AS IT APPEARS IN ADVERTISORY VIDEOS THAT ATLEAST 4 INCH DEPTH IS 8INCH BREADTH MAINHOLE. INSIDE WINDOW. THIS IMPLIES OUTSIDE WINDOW DEPTH OF 22-4=18INCH: (A) ON GROUND FLOOR THERE IS A CLEAR MARGIN OF 18INCH MOTH BALCONY 9 INCH BASIN (B) ON 1ST FLOOR TO 3RD FLOOR AS BALCONY2 CLEARANCE IS 9.0-1.5=7.5INCH, SO MAKE A KAPSUL BODY SHAPE 7INCH HEIGHT SLOT IN IRON IN CASE OF 1ST TO 3F MOTOR:GROUND-WATER-DIRECT BALCONY1 9INCH WINDOW VERTICAL SLIDING CAGE AT WINDOW-KAPSUL-INSTALL-HT. IN THE BOUNDARY-RAILING-CUM-CAGE OF BALCONY2. ALSO, KAPSUL-AIR HAS FRESH-AIR-MODE. NOTE: STANDARD EARTHING: 2inchx2inchx1inch COPPER-SOLID-BLOCK BURIED 10FEET DEEP IN GROUND →9INCH RED SOLID BRICK WALL 4FEET(TALL)x2FEET →4.5INCH_RED_SOLID_BRICK_WALL &CONNECTED USING COPPER SOLID WIRE GAUGE-AWG4/5.18MM DIAMETER/21.15 MMSQUARE ■MOTOR:GROUND-WATER-[MANUAL_BORING]-100FEET-DEEP:DIRECT LINE(FIRST_TASK: INSTALL_CAST IRON PRESSURE HAND PUMP)