


GROUND FLOOR PLAN: SUPER BUILT-UP AREA: 300 SQUARE FEET

1 INCH HAS 8 EQUAL PARTS, a PART, SPOKEN AS 1by8, AND WRITTEN AS 1/8. AOSMITH KLASSE GEYSER 25 LITRES INPUT: USE JAGUAR 2-ANGULAR STOP COCK KUP-35053PM FOR DIRECT INTAKE AND TANK INTAKE, THEN USE 1-JAGUAR SINK MIXER(RATIO) LYRIC LVR-38309PM WITHOUT SPOUT FOR FULL DIRECT INPUT/FULL TANK INPUT.



THE OUTER_2_LENGTH_SIDES_RED_SOLID_BRICK_WALLS_THICKNESS_IS=9INCH

ALL_OTHER_RED_SOLID_BRICK_WALLS_THICKNESS_IS=4.5INCH

6_PILLARS:CONCRETE_CEMENT_TATASTEEL(IRON_ORE_NON_SCRAP)TISCON RODS WILL BE REQUIRED. CEILING HEIGHT/FLOOR 10FEET3INCH.

NOTE1:ALL BRICK WALLS THICKNESS MEASUREMENTS HAVE BEEN ACCOUNTED FOR BEFORE CONCLUDING THE

INSIDE_TO_BETWEEN_WALLS_CLEARANCE_DIMENSIONS. TILE SKIRTING TO BE AT SAME LEVEL AS CEMENTsand(1:4RATIO)WALLPLASTER.

NOTE2:FOR INDIVIDUAL PLOT [[ONLY]] FROM 1ST TO 3RD FLOOR REAR BALCONY2 BREADTH SHOULD BE [[REDUCED]] TO 9_INCH GIVIN

G_OPEN_TO_SKY_CLEARANCE_OF_9_INCH.

REDUCED BECAUSE THERE IS A TOTAL POSSIBILITY THAT YOUR BALCONY2(REAR) WILL GET BLOCKED BY WALL(REAR) OF REAR ADJACE

NT_PLOT_OWNER.

ALL_INSIDE_TO_BETWEEN_WALLS_CLEARANCE_DIMENSIONS(LENGTHxBREADTH):

- ENTRY DOOR: 2FEET6INCH
- STAIRCASE: 11FEETx4FEET
- KITCHEN: 6FEET7.5INCHx3FEET3INCH, CONCRETE CEMENT SLAB BREADTH 1FEET3INCH, AT HEIGHT 2FEET9INCH + 1.0INCH THICKNESS MARBLE STONE ON TOP, SAME HEIGHT FOR KITCHEN BASIN
- SEMI_AUTO_WASHING_MACHINE: UPTO_3FEETx2FEET (WHIRLPOOL 6.5 KG)
- BATHROOM-CUM-TOILET:5FEET6INCHx4FEET9INCH, EXHAUST_FAN_CROMPTON_GREAVES: TRANSAIR/225MM/1400RPM/BIRD-SCREEN
- DRAWING_ROOM/HALL: 11FEETx5FEET6INCH
- SOFA: 6FEETx1FEET9INCH(MAXIMUM)
- FRIDGE:UPTO 2FEETx2FEET
- BEDROOM: 8FEET4.5INCHx5FEET6INCH
- SHAFT-REAR-MAINHOLE: 5FEETx1FEET6INCH (OPEN_TO_SKY_CLEARANCE)
- BALCONY1(FRONT): 9INCH BREADTH
- BALCONY2(REAR): 1FEET6INCH BREADTH (IMPORTANT FOR YOUR LIFE & A MUST IN A HOUSE)
- CUPBOARD_HALF_SLIDING_DOOR: 4FEETx1FEET6INCH(4FEETx1FEET5INCH, 1INCH_MARGIN_FOR_SLIDING_DOOR)
- BED(NOT_BOX_TYPE): 6FEET6INCHx4FEET, HEIGHT_OF_BED=12INCH+5INCH_KURLONmattress
- DOOR2: 2FEET6INCH
- DOOR3: 1FEET10.5INCH
- SLIDING DOOR4: 2FEET6INCH
- USE SOMANY_TILES, TATASTEEL(IRON_ORE_NonSCRAP_neverRustsInternally)WATER_GI_PIPES, UNIK_GI_FITTINGS(make_sure_spelling_in_products), KISAN PVC PIPES(FIRST_BIG_DIAMETER_VERTICAL_PIPELINE_IN_SHAFT_FOR_LATERINE_CLOSET_SINK_&_SECOND_SMALL_DIAMETER_VERTICAL_PIPEL
- INE_IN_SHAFT_FOR_SHOWER_CUM_TOOTBRUSH_BASIN_CUM_WASHING_MACHINE_CUM_SINKS_&_THIRD_SMALL_SAME_DIAMETER_VE
- RTICAL_PIPELINE_IN_SHAFT_FOR_KITCHEN_BASIN_SINK_&_FOURTH_SMALL_SAME_DIAMETER_VERTICAL_PIPELINE_IN_SHAFT_FOR_BALC
- ONY2_SINK) & FITTINGS(KISAN_NALI_TRAP_SIPHON_SINK)SHOULD BE EXACTLY HORIZONTALLY LEVELLED SUPERVISE YOURSELF AND
- PURCHASE DOUBLE THE AMOUNT OF PVC ADHESIVE SOLUTION OF WHAT PLUMBER TELLS YOU AND TELL PLUMBER TO APPLY D
- DOUBLE THE AMOUNT OF WHAT HE NORMALLY APPLIES), HINDWARE AMAZON RIMLESS SINGLE-PIECE CLOSET, HINDWARE KITCHEN
- STAINLESSSTEEL(SS)_MATT_FINISH BASIN, HINDWARE TOOTHBRUSH_BASIN, JAGUAR_COMPANY_FAUCETS,
- KIRANSLIDOCRAFT MANUAL_VERTICAL_SLIDING_WINDOW_MIDDLE_PICTURE.
- BALCONY2(REAR)_SECURELY_ENCLOSED_USING_GRID_CAGE_IRON_SQUARE_RODS.
- STUDY TABLE WALL MOUNTED HINGED BOARD 4-LEG-SKELETAL-MODULAR-PLASTIC-FRAME-SUPPORT-HT.-2FEET3INCH-BREADTH1.25FT.
- RED_SOLID_BRICK_DIMENSION: 9INCHx4.5INCH(DIFFICULT TO FIND EXACTLY THIS DIMENSION, MAYBE IN VILLAGE_KILNS_OR_FIND_AS_CLOSE_AS_POSSIBLE, BRICK-KILN-OWNERS_HAVE_REDUCED_THE_BRICK-DIE-SIZE).
- SUPER BUILT-UP AREA(TOTAL_PLOT_SIZE LENGTHxBREADTH): 20FEETx15FEET(FRONT)
- Use 1. LEGRAND_COMPANY ELECTRICAL SWITCHES, SOCKETS 2. ABB_COMPANY MCB 3. KEI_COMPANY WIRES&CABLES 4. OSRAM CFL 23W
- KAPSUL-AIR(DEPTH=22INCH) AIRCONDITIONER INSTALLATION AS IT APPEARS IN ADVERTISORY VIDEOS THAT ATLEAST 4 INCH DEPTH IS
- INSIDE WINDOW, THIS IMPLIES OUTSIDE WINDOW DEPTH OF 22-4=18INCH: (A) ON GROUND FLOOR THERE IS A CLEAR MARGIN OF 18INCH
- (B) ON 1ST FLOOR TO 3RD FLOOR AS BALCONY CLEARANCE IS 9INCH ONLY, SO MAKE A KAPSUL BODY SHAPE 7INCH HEIGHT SLOT IN IRON
- CAGE OVER THE BOUNDARY RAILING (ON 4.5INCH BASE WALL) OF BALCONY2. ALSO, KAPSUL-AIR HAS FRESH-AIR-MODE.
- NOTE: STANDARD_EARTHING: 2inchx2inchx1inch COPPER-SOLID-BLOCK BURIED 10FEET DEEP IN GROUND
- &CONNECTED USING COPPER SOLID WIRE GAUGE-AWG4/5.18MM_DIAMETER/21.15 MMSQUARE.

USE JAGJEET ESTD. 1968 MANUAL VERTICAL CITRUS FRUIT PRESS

JUICE MACHINE CONTOURLESS BODY FINISH, CHECK SIEVE FOR CRACK

AND HOLES SYMMETRY FINISH.

JAGUAR 1. KUBIX KUS-WHT-35935

TOOTHBRUSH BASIN 565mmX420mmX140mm

Rupees 6990, AS IN PRODUCT CATALOGUE

2. HAND SHOWER(LATERINE) ALD-573 Rs. 1350

3. KUBIX PRIME KUP-35021PM PILLAR COCK (DIRECT) for BASIN 190MM EXTENSION BODY

Rupees 2650

4. BIB COCK KUP-35037PM (DIRECT/GEYSER)

Rupees 1700 NUMBERS= 6

5. KITCHEN LYRIC LVR-38309 SINK MIXER

SWINGING SPOUT Rupees 4000 NUMBERS= 8

6. SHOWER OHS-WHM-1763 Rupees 23450

7. HAND SHOWER(BATH) HSH-1721 Rupees 3750

8. ANGULAR STOP COCK KUP-35053PM

Rupees1350 NUMBERS= 19

9. BEFORE ALL SINK MIXER OUTPUTS, USE 2-ANGULAR STOP COCK KUP-35053PM FOR DIRECT INTAKE AND GEYSER INTAKE, THEN USE 1-SINK MIXER(RATIO) LYRIC LVR-38309PM WITHOUT SPOUT FOR FULL DIRECT OUTPUT/FULL GEYSER OUTPUT/MIXER(RATIO) OUTPUT AND THEN USE A BIBCOCK