

FAUCET HOT/COLD STOP COCK FROM INSIDE KITCHEN
MOTOR:GROUND-WATER-DIRECT BALCONY1 9INCH WINDOW VERTICAL SLIDING 4FEET(TALL)x2FEET
IN CASE OF 1ST TO 3RD FLOOR.
(B) ON CAGE C
MOTOR:GROUND-WATER-[MANUAL_BORING]-100FEET-DEEP:DIRECT LINE(FIRST_TASK: INSTALL_CAST_IRON_PRESSURE_HAND_PUMP

The diagram shows a floor plan with the following dimensions and features:

- Overall Dimensions:** 15 FEET (width) x 11 FEET (depth).
- Entrance:** DOOR: 2 FEET 6 INCH x 5 FEET 6 INCH.
- Kitchen Area:**
 - FAUCET HOT/COLD/DIRECT
 - KITCHEN BASIN
 - SEMI-AUTO WASHING MACHINE (4 FEET)
 - FAUCET HOT/COLD/DIRECT
 - SLIDING DOOR4: 2 FEET 6 INCH
 - 1 FEET 3 INCH BREADTH CONCRETE CEMENT SLAB AT HEIGHT 2 FEET 9 INCH
 - 7 FEET 1 INCH minus 4.5 INCH = 6 FEET 7.5 INCH
 - 3 FEET 3 INCH
 - 6 FEET x 1 FEET 9 INCH SOFA
- Living Area:**
 - FRIDGE
 - COMPUTER_CUM_LED_TV_RACK DESK/WALL MOUNTED
 - CHAIR
 - CUPBOARD HALF SLIDING DOOR 4 FEET x 1 FEET 6 INCH
 - BED (NOT_BOX_TYPE) 6 FEET 6 INCH x 4 FEET
 - REMAINING LENGTH 1.5 INCH
- Balcony:**
 - BALCONY2: 1 FEET 6 INCH
 - WINDOW MANUAL VERTICAL SLIDING 4 FEET (TALL) x 3 FEET
 - DOOR3: 1 FEET 9 INCH
 - STUDY TABLE HINGED 1 INCH THICK WOOD BOARD
 - WALL MOUNTED BREADTH 1 FEET 3 INCH LENGTH 2.5 FEET
 - FAUCET HOT/COLD/DIRECT
 - SHOWER
 - SINK
 - TOOTHBRUSH
 - BASIN
 - FAUCET
 - HOT/COLD/DIRECT
 - FAUCET
 - HOT/COLD/DIRECT
 - HINDWARE
 - MAGRO MODEL
 - RIMLESS ONE
 - PIECE CLOSET
 - ENGLISH LATRINE
- Staircase:** 4 FEET (2ft+2ft)
- Front Mainhole:** 8 INCH BREADTH WITH BALCONY 9 INCH
- Integrate 1st Step of Staircase:** 8 INCH BREADTH WITH BALCONY 9 INCH

THE OUTER 2_LENGTH SIDES RED SOLID BRICK WALLS THICKNESS IS=9INCH USE JAGJEET ESTD. 1968 MANUAL VERTICAL CITRUS FRUIT PRESS
 ALL_OTHER_RED_SOLID_BRICK_WALLS_THICKNESS_IS=4.5INCH JUICE MACHINE CONTOURLESS BODY FINISH, CHECK SIEVE FOR CRACK
 6_PILLARS:CONCRETE_CEMENT_TATASTEEL(IRON_ORE_NON_SCRAP)TISCON RODS WILL BE REQUIRED. CEILING HEIGHT/FLOOR 10FEET3INCH. AND HOLES SYMMETRY FINISH.
 NOTE1:ALL BRICK WALLS THICKNESS MEASUREMENTS HAVE BEEN ACCOUNTED FOR BEFORE CONCLUDING THE
 INSIDE_TO_BETWEEN_WALLS_CLEARANCE_DIMENSIONS. TILE SKIRTING TO BE AT SAME LEVEL AS CEMENTsand(1:4RATIO)WALLPLASTER.
 NOTE2:FOR INDIVIDUAL PLOT [[ONLY]] FROM 1ST TO 3RD FLOOR REAR BALCONY2 BREADTH SHOULD BE [[REDUCED]] TO 9_INCH GIVIN
 G_OPEN_TO_SKY_CLEARANCE_OF_9_INCH.
 REDUCED BECAUSE THERE IS A TOTAL POSSIBILITY THAT YOUR BALCONY2(REAR) WILL GET BLOCKED BY WALL(REAR) OF REAR ADJACE
 NT_PLOT_OWNER.
 ALL_INSIDE_TO_BETWEEN_WALLS_CLEARANCE_DIMENSIONS(LENGTHxBREADTH): JAGUAR 1. KUBIX KUS-WHT-35935
 TOOTHBRUSH BASIN 565mmX420mmX140mm
 1. ENTRY DOOR: 2FEET6INCH NOTE1: 2_ANGULAR_STOP COCKS TO BE FITTED BEFORE EVERY_SINK Rupees 6990, AS IN PRODUCT CATALOGUE
 2. STAIRCASE: 11FEETx4FEET MIXER, EXCEPT AT PLACE OF SHOWER. 2. HAND SHOWER(LATERINE) ALD-573 Rs. 1350
 3. KITCHEN: 6FEET7.5INCHx3FEET3INCH, CONCRETE CEMENT SLAB BREADTH 1FEET3INCH, AT HEIGHT 2FEET9INCH +
 1.0INCH THICKNESS MARBLE STONE ON TOP, SAME HEIGHT FOR KITCHEN BASIN 3. KUBIX PRIME KUP-35021PM PILLAR COCK
 (DIRECT) for BASIN 190MM EXTENSION BODY
 4. SEMI_AUTO_WASHING_MACHINE: UPTO_3FEETx2FEET (WHIRLPOOL 6.5 KG) Rupees 2650
 5. BATHROOM-CUM-TOILET:5FEET6INCHx4FEET9INCH, EXHAUST_FAN_CROMPTON_GREAVES: TRANSAIR/225MM/1400RPM/BIRD-SCREEN
 6. DRAWING_ROOM/HALL: 11FEETx5FEET6INCH NOTE2: FOR SHOWER-MIXER-ETERNAL KUP-35115PM 4. BIB COCK KUP-35037PM (DIRECT/GEYSER)
 7. SOFA: 6FEETx1FEET9INCH(MAXIMUM) Rupees 7100 (1 No.), SHOWER PIPE (SHA-1211N) Rupees 1700 NUMBERS= 6
 8. FRIDGE:UPTO 2FEETx2FEET NOTE3: FOR HAND-SHOWER-MIXER-EXTERNAL KUP- 5. KITCHEN LYRIC Lyr-38309 SINK MIXER
 9. BEDROOM: 8FEET4.5INCHx5FEET6INCH 35149PM Rupees 6150 (1 No.) SWINGING SPOUT Rupees 4000 NUMBERS= 8
 10. SHAFT-REAR-MAINHOLE: 5FEETx1FEET6INCH (OPEN_TO_SKY_CLEARANCE) 6. SHOWER OHS-WHM-1763 Rupees 23450
 11. BALCONY1(FRONT): 9INCH BREADTH NOTE4: ALL_JAGUAR_ITEMS_IN_CHROME_FINISH 7. HAND SHOWER(BATH) HSH-1721 Rupees 3750
 12. BALCONY2(REAR): 1FEET6INCH BREADTH (IMPORTANT_FOR_YOUR_LIFE_&_A_MUST_IN_A_HOUSE) 8. ANGULAR STOP COCK KUP-35053PM
 13. CUPBOARD_HALF_SLIDING_DOOR: 4FEETx1FEET6INCH(4FEETx1FEET5INCH, 1INCH_MARGIN_FOR_SLIDING_DOOR) Rupees1350 NUMBERS= 19
 14. BED(NOT_BOX_TYPE): 6FEET6INCHx4FEET, HEIGHT_OF_BED=12INCH+5INCH_KURLONmattress 9. BEFORE ALL SINK MIXER OUTPUTS, USE 2-
 15. DOOR2: 2FEET6INCH NOTES: ALSO, ANGULAR_STOP_COCK TO BE FITTED, 1_EACH_BEFORE, ANGULAR STOP COCK KUP-35053PM FOR
 16. DOOR3: 1FEET10.5INCH DIRECT_PILLAR_COCK & DIRECT_WASHING_MACHINE_BIB_COCK & DIRECT INTAKE AND GEYSER INTAKE, THEN USE
 17. SLIDING DOOR4: 2FEET6INCH DIRECT_KITCHEN_BIB_COCK. 1- SINK MIXER(RATIO) LYRIC Lyr-38309PM
 18. USE SOMANY_TILES, TATASTEEL(IRON_ORE_NonSCRAP_neverRustsInternally)WATER_GI_PIPES, WITHOUT SPOUT FOR FULL DIRECT
 UNIK_GI_FITTINGS(make_sure_spelling_in_products), KISAN PVC OUTPUT/FULL GEYSER OUTPUT/MIXER(RATIO)
 PIPES(FIRST_BIG_DIAMETER_VERTICAL_PIPELINE_IN_SHAFT_FOR_LATERINE_CLOSET_SINK_&_SECOND_SMALL_DIAMETER_VERTICAL_PIPEL
 NE_IN_SHAFT_FOR_SHOWER_CUM_TOOTBRUSH_BASIN_CUM_WASHING_MACHINE_CUM_SINKS_&_THIRD_SMALL_SAME_DIAMETER_VE
 RTICAL_PIPELINE_IN_SHAFT_FOR_KITCHEN_BASIN_SINK_&_FOURTH_SMALL_SAME_DIAMETER_VERTICAL_PIPELINE_IN_SHAFT_FOR_BALC
 ONY2_SINK)_&_FITTINGS(KISAN_NALI_TRAP_SIPHON_SINK)SHOULD_BE_EXACTLY_HORIZONTALLY_LEVELLED_SUPERVISE_YOURSELF_AND
 PURCHASE_DOUBLE_THE_AMOUNT_OF_PVC_ADHESIVE_SOLUTION_OF_WHAT_PLUMBER_TELLS_YOU_AND_TELL_PLUMBER_TO_APPLY_D
 OUBLE_THE_AMOUNT_OF_WHAT_HE_NORMALLY_APPLIES), HINDWARE AMAZON RIMLESS SINGLE-PIECE CLOSET, HINDWARE KITCHEN
 STAINLESSSTEEL(SS)_MATT_FINISH BASIN, HINDWARE TOOTHBRUSH_BASIN, JAGUAR_COMPANY_FAUCETS,
 KIRANSLIDOCRAFT_MANUAL_VERTICAL_SLIDING_WINDOW_MIDDLE_PICTURE.
 19. BALCONY2(REAR)_SECURELY_ENCLOSED_USING_GRID_CAGE_IRON_SQUARE_RODS.
 20. STUDY TABLE WALL MOUNTED HINGED BOARD 4-LEG-SKELETAL-MODULAR-PLASTIC-FRAME-SUPPORT-HT.-2FEET3INCH-BREADTH1.25FT.
 21. RED SOLID BRICK DIMENSION: 9INCHx4.5INCH(DIFFICULT TO FIND EXACTLY THIS DIMENSION, MAYBE IN
 VILLAGE_KILNS_OR_FIND_AS_CLOSE_AS_POSSIBLE, BRICK-KILN-OWNERS_HAVE_REDUCED_THE_BRICK-DIE-SIZE).
 22. SUPER BULIT-UP AREA(TOTAL_PLOT_SIZE LENGTHxBREADTH): 20FEETx15FEET(FRONT)
 23. Use 1. LEGRAND_COMPANY ELECTRICAL SWITCHES, SOCKETS 2. ABB_COMPANY MCB 3. KEI_COMPANY WIRES&CABLES 4. OSRAM CFL 23W
 24. KAPSUL-AIR(DEPTH=22INCH) AIRCONDITIONER INSTALLATION AS IT APPEARS IN ADVERTISORY VIDEOS THAT ATLEAST 4 INCH DEPTH IS
 INSIDE WINDOW, THIS IMPLIES OUTSIDE WINDOW DEPTH OF 22-4=18INCH: (A) ON GROUND FLOOR THERE IS A CLEAR MARGIN OF 18INCH
 (B) ON 1ST FLOOR TO 3RD FLOOR AS BALCONY CLEARANCE IS 9INCH ONLY, SO MAKE A KAPSUL BODY SHAPE 7INCH HEIGHT SLOT IN IRON
 CAGE OVER THE BOUNDARY RAILING (ON 4.5INCH BASE WALL) OF BALCONY2. ALSO, KAPSUL-AIR HAS FRESH-AIR-MODE.
 9INCH_RED_SOLID_BRICK_WALL NOTE: STANDARD_EARTHING: 2inchx2inchx1inch COPPER-SOLID-BLOCK BURIED 10FEET DEEP IN GROUND
 4.5INCH_RED_SOLID_BRICK_WALL &CONNECTED USING COPPER SOLID WIRE GAUGE-AWG4/5.18MM DIAMETER/21.15 MMSQUARE