GROUND FLOOR PLAN: SUPER BUILT-UP AREA: 300 SQUARE FEET=27.87 SQUARE METER USE, JAGJEET ESTD. 1968 MANUAL VERTICAL CITRUS FRUIT PRESS THE OUTER 2 LENGTH SIDES RED SOLID BRICK WALLS THICKNESS IS=9INCH SINK MIXER 1 FEET/1FOOT= 3INCH+3INCH+3INCH+1.5INCH+1.5INCH, Eg. 1FEET 6INCH=1.5FEET, 1FEET 3IN=1.25FEET JUICE MACHINE PLAIN STEEL FINISH, CHECK SIEVE FOR CRACK AND ALL OTHER RED SOLID BRICK WALLS THICKNESS IS=4.5INCH IRON-CAGE-BOTTOM-BASE-SLAB-CEMENT, JEERA-GITTI, SANDSTONE, TISCON-6MM-RODS-INSIDE-SLAB=8FEET9INCHx1.5INx3IN 6 PILLARS 18INCHx10.5INCH:CEMENT,GITTI,SANDSTONE,TATASTEEL(IRON_ORE_NOnSCRAP)TISCON_ROD. CEILING HEIGHT/FLOOR 10FEET3INCH FAUCET HOT/COLD 1 INCH HAS 8 BALCONY211FEET6INCH SHAFT REAR-MAINHOLE NOTE1:ALL BRICK WALLS THICKNESS MEASUREMENTS HAVE BEEN ACCOUNTED FOR BEFORE CONCLUDING THE INSIDE TO BETWEEN WALLS WINDOW MANUAL VERTICAL SLIDING **EQUAL PARTS** WINDOW VERTICAL SLIDING $\blacksquare \oplus$ CLEARANCE_DIMENSIONS. TILE_SKIRTING_TO_BE_AT_SAME_LEVEL_AS_CEMENT: MEDIUM-GRAINSIZE-FINESAND (1:4 RATIO) WALLPLASTER. 4FEET(TALL)x3FEET a PART, SPOKEN **6FEET(TALL)x3FEET EXHAUS** NOTE2:FOR_INDIVIDUAL_PLOT_[[ONLY]]_FROM_1ST_TO_3RD_FLOOR_REAR_BALCONY2_BREADTH_SHOULD_BE_[[REDUCED]]_TO_9_INCH_GIVIN AS 1by8, AND DOOR3 1FEET REMAINING ROOM LENGTH 1.5INCH G OPEN TO SKY CLEARANCE OF 9 INCH. WRITTEN AS 1/8. 9INCH TRAP MAGRO MODEL REDUCED_BECAUSE_THERE_IS_A_TOTAL_POSSIBILITY_THAT_YOUR_BALCONY2(REAR)_WILL_GET_BLOCKED_BY_WALL(REAR)_OF_REAR_ADJACE AOSMITH KLASSE (RIMLESS ONE **GEYSER 25 LITRES** NT PLOT OWNER. YOU SHOULD RAISE YOUR REAR END BOUNDARY 4.5 INCH WALL TILL 3RD FLOOR. **JAGUAR 1. KUBIX KUS-WHT-35935** PIECE CLOSET INPUT: USE ALL_INSIDE_TO_BETWEEN_WALLS_CLEARANCE_DIMENSIONS(LENGTHxBREADTH): TOOTHBRUSH BASIN 565mmX420mmX140mm BED(NOT BOX TYPE) ENGLISH LATERINE JAGUAR 2-**ENTRY DOOR: 2FEET6INCH** NOTE1: JAGUAR 2 ANGULAR STOP COCKS TO BE FITTED Rupees 6990, AS IN PRODUCT CATALOGUE 6FEET6INCHx4FEET. ANGULAR STOP 2. HAND SHOWER(LATERINE) ALD-573 Rs. 1350 STAIRCASE: 11FEETx4FEET BEFORE_EVERY_SINK MIXER, EXCEPT AT PLACE OF SHOWER. TAKE BED MEASUREMENT COCK KUP-KITCHEN: 6FEET7.5INCHx3FEET3INCH. CONCRETE CEMENT SLAB BREADTH 1FEET3INCH, AT HEIGHT 2FEET9INCH + AFTER CEMENT PLASTER. 35053PM FOR 3. KUBIX PRIME KUP-35021PM PILLAR COCK 1.0INCH THICKNESS MARBLE STONE ON TOP, SAME HEIGHT FOR KITCHEN BASIN **DIRECT INTAKE** (DIRECT) for BASIN 190MM EXTENSION BODY SEMI_AUTO_WASHING_MACHINE: UPTO_3FEETx2FEET (WHIRLPOOL SUPERB ATOM 6.5 KG) AND TANK INTAKE, **CUPBOARD HALF SLIDING** BATHROOM-CUM-TOILET:5FEETx4FEET9INCH, EXHAUST_FAN_CROMPTON_GREAVES: TRANSAIR/225MM/1400RPM/BIRD-SCREEN THEN USE 1-CHAIR DOOR 4FEETx1FEET6INCH JAGUAR SINK 6. DRAWING ROOM/HALL: 11FEETx5FEET6INCH 4. BIB COCK KUP-35037PM (DIRECT/GEYSER) NOTE2: JAGUAR FOR SHOWER-MIXER-ETERNAL KUP-MIXER(RATIO) MIXER(RATIO) DOOR2: SOFA: 6FEETx1FEET9INCH(MAXIMUM) Rupees 1700 NUMBERS=7 5 SLIDING DOOR4 35115PM Rupees 7100 (1 No.), SHOWER PIPE (SHA-1211N) 5. KITCHEN LYRIC LYR-38309 SINK MIXER 8. FRIDGE:UPTO 2FEETx2FEET 2FEET3INCH NOTE3: JAGUAR FOR HAND-SHOWER-MIXER-EXTERNAL WITHOUT SPOUT 6INCH SWINGING SPOUT Rupees 4000 NUMBERS= 8 BEDROOM: 8FEET4.5INCHx5FEET6INCH KUP-35149PM Rupees 6150 (1 No.) FOR FULL DIRECT SHAFT-REAR-MAINHOLE: 4FEET9INCHx2FEET (OPEN_TO_SKY_CLEARANCE_IRON_CAGE_AT_TOP) 6. SHOWER OHS-WHM-1763 Rupees 23450 10. INPUT/FULL TANK 7. HAND SHOWER(BATH) HSH-1721 Rupees 3750 BALCONY1(FRONT): 9INCH BREADTH NOTE4: ALL JAGUAR ITEMS IN CHROME FINISH 8. ANGULAR STOP COCK KUP-35053PM BALCONY2(REAR): 1FEET6INCH BREADTH (IMPORTANT FOR YOUR LIFE & A MUST IN A HO <u>JAGUAR</u> USE 1-BIBCOCK Rupees1350 NUMBERS= 19 BEFORE GEYSER-STOP-CUPBOARD HALF SLIDING DOOR: 4FEETx1FEET6INCH(4FEETx1FEET5INCH, 1INCH MARGIN FOR SLIDING DOOR) COCK TO EMPTY-CLEAN S 4FEET BED(NOT_BOX_TYPE): 6FEET6INCHx4FEET, HEIGHT_OF_BED=12INCH+5INCH_KURLONmattress 9. BEFORE ALL SINK MIXER OUTPUTS, USE 2-SOFA 15. DOOR2: 2FEET6INCH NOTES: ALSO, JAGUAR ANGULAR STOP COCK TO BE FITTED, ANGULAR STOP COCK KUP-35053PM FOR HINDWARE KITCHEN DOOR3: 1FEET9INCH 1 EACH BEFORE, DIRECT PILLAR COCK & DIRECT INTAKE AND GEYSER INTAKE, THEN USE BASIN (SS) STAINLESS 17. SLIDING DOOR4: 2FEET3INCH DIRECT_WASHING_MACHINE_BIB_COCK & DIRECT KITCHEN BIB COCK. 1- SINK MIXER(RATIO) LYRIC LYR-38309PM 3FEET3INCH STEEL CHROME FINISH WITHOUT SPOUT FOR FULL DIRECT 18. USE SOMANY TILES, TATASTEEL (IRON ORE NonSCRAP neverRustsInternally) WATER GI PIPES PLATINO OUTPUT/FULL GEYSER OUTPUT/MIXER(RATIO) UNIK_GI_FITTINGS(make_sure_spelling_in_products), KISAN (SWR:Soil,Waste,RainWater) uPVC MODEL NO .: PIPES(FIRST 4INCH DIAMETER VERTICAL PIPELINE IN SHAFT FOR LATERINE CLOSET SINK & SECON 36X20X8 ELINE IN SHAFT FOR SHOWER CUM TOOTBRUSH_BASIN_CUM_WASHING_MACHINE_CUM_SINKS_&_THIRD_3INCH_DIAMETER_VERTICA 36INCHx20INCH STAIRCASE 4FEET(2ft+2ft K8INCH L_PIPELINE_IN_SHAFT_FOR_KITCHEN_BASIN_SINK_&_FOURTH_3INCH_DIAMETER_VERTICAL_PIPELINE_IN_SHAFT_FOR_BALCONY2_SINK)_ USE, VINOD & FITTINGS(ALL(6) KISAN NALI TRAP 3INCH SIPHON SINKS)SHOULD BE EXACTLY HORIZONTALLY LEVELLED SUPERVISE YOURSELF AN INDUCTION MODENA D_PURCHASE_DOUBLE_THE_AMOUNT_OF_PVC_ADHESIVE_SOLUTION_OF_WHAT_PLUMBER_TELLS_YOU_AND_TELL_PLUMBER_TO_APPLY (SS) COOKWARE, DOUBLE THE AMOUNT OF WHAT HE NORMALLY APPLIES), HINDWARE AMAZON RIMLESS SINGLE-PIECE CLOSET, HINDWARE KITCHEN SUJATA 900WATT STAINLESSSTEEL(SS) MATT FINISH BASIN, HINDWARE TOOTHBRUSH BASIN, JAGUAR COMPANY FAUCETS, UICER-CUM-GRINDER 5FEET6INCH KIRANSLIDOCRAFT_MANUAL_VERTICAL_SLIDING_WINDOW_MIDDLE_PICTURE. NOTE: KISAN SWR uPVC TYPE-B, HIGH PRESSURE CAPACITY. THIS IS LIKE BALCONY2(REAR) SECURELY ENCLOSED BY GRID CAGE IRON SQUARE RODS.CAGE BORDER ANGLE WIDTH=1.5INCH, ROD=0.375INCH RAIN-STUDY TABLE WALL MOUNTED HINGED BOARD 4-LEG-SKELETAL-MODULAR-PLASTIC-FRAME-SUPPORT-HT.-2FEET3INCH-BREADTH1.25FT. WATER NOTE: USE 46MM, SINK, SO RED SOLID BRICK DIMENSION: 9INCHX4.5INCH(DIFFICULT TO FIND EXACTLY THIS DIMENSION, MAYBE IN TATA-PRAVESH STEEL THIS GOES 15 FEET VILLAGE KILNS OR FIND AS CLOSE AS POSSIBLE, BRICK-KILN-OWNERS HAVE REDUCED THE BRICK-DIE-SIZE). **ENTRY DOOR (CORAL)** TO 22. SUPER BULIT-UP AREA(TOTAL PLOT SIZE LENGTHXBREADTH): 20FEETX15FEET(FRONT) NOTE: USE, ULTRATECH WEATHER PLUS CEMENT FAUCET INTEGRATE 1ST STEP OF GROUND-23. Use 1. LEGRAND COMPANY ELECTRICAL SWITCHES, SOCKETS 2. ABB COMPANY MCB 3. KEI COMPANY WIRES&CABLES 4. OSRAM CFL 23W HOT/COLD/DIRECT STAIRCASE **FLOOR** 24. KAPSUL-AIR(DEPTH=22INCH) AIRCONDITIONER INSTALLATION AS IT APPEARS IN ADVERTISORY VIDEOS THAT ATLEAST 4 INCH DEPTH IS 8INCH BREADTH FRONT-INSIDE WINDOW. THIS IMPLIES OUTSIDE WINDOW DEPTH OF 22-4=18INCH: (A) ON GROUND FLOOR THERE IS A CLEAR MARGIN OF 18INCH WITH BALCONY 9 INCH BASIN MAINHOLE. IN CASE OF 1ST TO 3 (B) ON 1ST FLOOR TO 3RD FLOOR AS BALCONY2 CLEARANCE IS 9.0-1.5=7.5INCH, SO MAKE A KAPSUL BODY SHAPE 7INCH HEIGHT SLOT IN IRON CAGE AT WINDOW-KAPSUL-INSTALL-HT. IN THE BOUNDARY-RAILING-CUM-CAGE OF BALCONY2, ALSO, KAPSUL-AIR HAS FRESH-AIR-MODE. →9INCH RED SOLID BRICK WALL ■ NOTE: STANDARD EARTHING: 2inchx2inchx1inch COPPER-SOLID-BLOCK BURIED 10FEET DEEP IN GROUND 4FEET(TALL)x2FEET ◆4.5INCH RED SOLID BRICK WALL &CONNECTED USING COPPER SOLID WIRE GAUGE-AWG4/5.18MM DIAMETER/21.15 MMSQUARE MOTOR:GROUND-WATER-[MANUAL_BORING]-100FEET-DEEP:DIRECT LINE(FIRST_TASK: INSTALL_CAST IRON PRESSURE HAND PUMP)