

PILLARS&ROOF(LINTER)-TISCON-RODS-SPECIFICATION:

1. 10MM LONG-LENGTH, with CROSS-Concealed-BEAM every 10 feet.
2. CROSS-CONCEALED-BEAM will not be needed in case of HOME28.
3. CONCEALED-BEAM 12MM(6MM-Rectangular-RINGS).
4. CROSS-CONCEALED-BEAM 12MM(6MM-Rectangular-RINGS)
5. 12MM SHORT-LENGTH
6. PILLARS 16MM(8MM-Rectangular-RINGS).
7. Though PILLARS are 18Inchesx10.5Inches, for-concrete-mixture-margin, PILLARS are [17Inchesx9.5Inches::RING-To-RING]. This will give 0.5Inch-concrete-mixture-margin-on-all-sides.
8. BALCONY1 & BALCONY2, PROJECTION, 20FEET-16MM(on-two-9Inch-Walls) and 12FEET6INCHES-16MM(on-middle-4.5Inch-Wall)
9. BALCONY1 & BALCONY2 Outermost-Edge-15feet-CONCEALED-BEAM-12MM.
10. REAR-END-WALL CONCEALED-BEAM-12MM-AT-EveryFLOOR.
11. ROOF(LINTER)-THICKNESS-5INCH
12. For PILLARS,  
Tiscon-Rods-Iron-Grid-BaseStand-Lifted-Gap-2Inch-From-PRESSED-LEVELLED-HammeredBrick. GapLift-by-using-small-sufficient-brick-peices.
13. For ROOF(LINTER), Tiscon-Rods-Iron-Grid-Lifted-Gap-1Inch-From-Shattering.  
GapLift-by-using-small-sufficient-brick-peices.
14. For ROOF(LINTER), TISCON-RODS-GRID-SPACING-5Inches.
15. 2.5FEET-LENGTH-CANTILEVER-RODS-GRID-on(from)-all-4.5Inch-aswellas-9Inch-WALLS.
16. CANTILEVER-THICKNESS-3Inches-WHICH-IS-SAME-AS-CONCEALED-BEAM-THICKNESS
17. CONCEALED-BEAM-WIDTH-IS-WALL-WIDTH(4.5Inches or 9Inches), as-per-Wall.
18. CROSS-CONCEALED-BEAM-WIDTH-9Inches.
19. Though DRAWING-ROOM front-4.5Inch-Wall-has-a-slanted-corner, but CONCEALED-BEAM-12MM-is-Straight-15FEET. Also, BEDROOM Wall has 15FEET-CONCEALED-BEAM- 12MM
20. KITCHEN-SLAB-there-wiil-one-middle-supporting-wall.  
SLAB-THICKNESS-3Inches[At-Height-(2feet6Inches+3InchesSlab)].
21. Bathroom-cum-Toilet-EXHAUST\_FAN  
is-installedOVER-Vertical-SlidingWindow-on-one-side-opposite-to-Cistern(not-at-center).