JAQUAR(CORECT- SPELLING):

REDONE-ITEMS-LIST: [All-but-1-Item-From-KUBIX PRIME, Only-1-Item-From-LYRIC]

- 1. GEYSER-OUTPUT is TANK-HOTTED or DIRECT- HOTTED.
- [SINK-MIXER]-SWINGING-SPOUT LYRIC LYR-38309, the SWINGING-SPOUT-OF-SINK-MIXER-is-removed-and-attached-at GEYSER-INPUT.
- 3. DIRECT(Non-GEYSER) is STANDALONE-DIRECT-MOTOR-LINE
- 4. SINK-MIXER is (not-needed/to-be-used) at place of SHOWER. At place of SHOWER, there is also a STANDALONE-BIBCOCK(Faucet)-is-STANDALONE-DIRECT-MOTOR-LINE.
- 5. For CLOSET(English Laterine) use KUBIX PRIME KUP-CHR 35115PM instead of SINK-MIXER.
- 6. For-TOOTHBRUSH-BASIN, instead of SINK-MIXER, use KUP-CHR 35149PM along-with-BIBCOCK-KUP-35037PM.
 - PILLAR-COCK KUP-35021PM is for STANDALONE-DIRECT-MOTOR-LINE
- 7. For Washing Machine use KUP-CHR 35149PM instead of SINK-MIXER. There is also a STANDALONE-DIRECT-MOTOR-LINE-BIBCOCK(Faucet).
- 8. For BALCONY2, instead of SINK- MIXER, use KUP-CHR 35119PM along-with-BIBCOCK-KUP-35037PM.
- 9. For BALCONY1, instead of SINK- MIXER, use KUP-CHR 35149PM-inside-kitchen-along-with-BIBCOCK-outside-KUP-35037PM
- 10. At KITCHEN, there is also a STANDALONE-BIBCOCK(Faucet)-DIRECT-MOTOR-LINE.
- 11. ITEMS & QUANTITY(Alongwith-SEE map_plan_inventory.pdf for further explanations):
 - A) [SINK-MIXER]-SWINGING-SPOUT LYRIC LYR-38309: 2QTY
 - B) KUP-CHR 35115PM: 2QTY
 - C) SHA-1211N: 1QTY
 - D) KUP-CHR 35119PM: 1QTY
 - E) KUP-CHR 35149PM: 3QTY
 - F) KUP-35037PM: 6QTY
 - G) ANGULAR-STOP-COCK KUP-35053PM: 20QTY
 - H) KUP-35021PM: 1QTY (190mm Extension Body)
 - I) ALD-573: 1QTY J) HSH-1721: 1QTY
 - K) OHS-WHM-1763: 1QTY
 - L) KUS-WHT-35935: 1QTY (565mmx420mmx140mm)

<u>HOME28-MAKE-ENTRY-DOOR-SLANT</u>-TO-BE-5feet10Inch-INSTEAD-OF-5feet6Inch(This will provide 2feet-setback on your-right-side of the entry-door-start in map_plan_inventory.pdf)

HOME28BED-[MAKE-DOOR3-1feet7.5InchWide-InsteadOf-1feet9InchWide,So-RemainingRoomLengthB ecomesZero-In:map_plan_inventory.pdf]VerticalStraightWoodBoardHeadRest1InchThick&3Feet5InchesB readth-Horizontal1SlitAtBottom1InchWideForTyingPassThrough-1SideSlantedOtherSideStraight3FeetBre adthThermocolHeadRest.FOURinNumber-VerticalBackSpinalChords2InchWide0.5InchThickAtEvery1Fee tSpacing-ForVerticalStraightWoodBoardHeadRestSupports(FOURinNumber-includesSameBackSpinalChords-At-LeftSideEdge-&-RightSideEdge).So,BEDMATTRESS-LENGTH-Becomes6Feet7.5InchesMINUS1.5Inch=6Feet6Inches.Use-KITPLY25mm(1Inch)KITBOARDGOLD-BWP-BoilingWaterProof-(BLOCKBOARD)-8feet×4feet.And-KITPLY-GOLD-12mm(0.5Inch)-(PLYWOOD)-7feetx4feet

<u>For-INTERNAL-DOORS</u>-Use-KITPLY-FLUSHDOOR35MM-84inchx48inch-(7feetx4feet)-1Piece-ForDoor2 &Door3.

<u>For-CUPBOARD-SLIDING-DOOR</u>-Use-KITPLY-GOLD-(PLYWOOD)-12mm-7feetx4feet,1Piece <u>For-BATHROOMcumTOILET-SLIDING-DOOR</u>-Use-KITPLY-GOLD-(PLYWOOD)-19mm-7feet×3feet,1Piece

For-CUPBOARD&TV&KITCHEN-RACKS-Use-KITPLY-KITBOARD-GOLD-BWP-BoilingWaterProof-(BLO CKBOARD)-25mm-8feetx4feet.