



THE OUTER 2\_LENGTH\_SIDES\_RED\_SOLID\_BRICK\_WALLS\_THICKNESS\_IS=9INCH

ALL\_OTHER\_RED\_SOLID\_BRICK\_WALLS\_THICKNESS\_IS=4.5INCH

6\_PILLARS\_18INCHx10.5INCH:CEMENT,GITTI,STONEDUST,TATASTEEL(IRON\_ORE\_NonSCRAP),TISCO-ROD. CEILING HEIGHT/FLOOR 10FEET3INCH

NOTE1:ALL BRICK WALLS THICKNESS MEASUREMENTS HAVE BEEN ACCOUNTED FOR BEFORE CONCLUDING THE INSIDE\_TO\_BETWEEN\_WALLS CLEARANCE\_DIMENSIONS. TILE\_SKIRTING\_[CLOSE\_TO/AT\_SAME\_LEVEL\_AS] CEMENT:MEDIUM-GRAINSIZE-FINESAND(1:4 RATIO)WALLPLASTER.

NOTE2:FOR INDIVIDUAL\_PLOT\_[[ONLY]] FROM 1ST TO 3RD FLOOR REAR BALCONY2 BREADTH SHOULD BE [[REDUCED]] TO 9\_INCH GIVING OPEN\_TO\_SKY\_CLEARANCE\_OF\_9\_INCH. REDUCED BECAUSE THERE IS A TOTAL POSSIBILITY THAT YOUR BALCONY2(REAR) WILL GET BLOCKED BY\_WALL(REAR)\_OF\_REAR\_ADJACENT\_PLOT\_OWNER. YOU SHOULD RAISE YOUR REAR END BOUNDARY 4.5 INCH WALL TILL 3RD FLOOR.

NOTE3:TILE SKIRTING THICKNESS IS < WALL PLASTER THICKNESS, TOP GETS PRESSED BY WALLPLASTER. JAGUAR 1. KUBIX KUS-WHT-35935 TOOTHBRUSH BASIN 565mmX420mmX140mm Rupees 6990, AS IN PRODUCT CATALOGUE

2. HAND SHOWER(LATERINE) ALD-573 Rs. 1350

ALL\_INSIDE\_TO\_BETWEEN\_WALLS\_CLEARANCE\_DIMENSIONS(LENGTHxBREADTH):

- ENTRY\_DOOR: 2FEET6INCH NOTE1: JAGUAR 2-ANGULAR\_STOP\_COCKS TO BE FITTED BEFORE EVERY [SINK-MIXER], EXCEPT AT PLACE OF SHOWER.
- STAIRCASE: 11FEETx4FEET
- KITCHEN: 6FEET7.5INCHx3FEET3INCH, CONCRETE CEMENT SLAB BREADTH 1FEET3INCH, AT HEIGHT 2FEET9INCH + 1.0INCH\_THICKNESS\_MARBLE\_STONE\_ON\_TOP, SAME\_HEIGHT\_FOR\_KITCHEN\_BASIN
- SEMI\_AUTO\_WASHING\_MACHINE: UPTO\_3FEETx2FEET (WHIRLPOOL SUPERB ATOM 6.5 KG)
- BATHROOM-CUM-TOILET:5FEETx4FEET9INCH, EXHAUST\_FAN\_CROMPTON\_GREAVES: TRANSAIR/225MM/1400RPM/BIRD-SCREEN Rupees 2650
- DRAWING\_ROOM/HALL: 11FEETx5FEET6INCH
- SOFA: 6FEETx1FEET9INCH(MAXIMUM) NOTE2: JAGUAR FOR SHOWER-MIXER-ETERNAL KUP-35115PM Rupees 7100 (1 No.), SHOWER PIPE (SHA-1211N) Rupees 1700 NUMBERS= 7
- FRIDGE:UPTO 2FEETx2FEET NOTE3: JAGUAR FOR HAND-SHOWER-MIXER-EXTERNAL KUP-35149PM Rupees 6150 (1 No.)
- BEDROOM: 8FEET4.5INCHx5FEET6INCH
- SHAFT-REAR-MAINHOLE: 4FEET9INCHx2FEET (OPEN\_TO\_SKY\_CLEARANCE\_IRON\_CAGE\_AT\_TOP) NOTE4: ALL\_JAGUAR\_ITEMS\_IN\_CHROME\_FINISH
- BALCONY1(FRONT): 9INCH BREADTH
- BALCONY2(REAR): 1FEET6INCH BREADTH (IMPORTANT\_FOR\_YOUR\_LIFE\_&\_A\_MUST\_IN\_A\_HOUSE) Rupees1350 NUMBERS= 20
- CUPBOARD\_HALF\_SLIDING\_DOOR: 4FEETx1FEET6INCH(4FEETx1FEET5INCH, 1INCH\_MARGIN\_FOR\_SLIDING\_DOOR)
- BED(NOT\_BOX\_TYPE): 6FEET6INCHx4FEET, HEIGHT\_OF\_BED=12INCH+5INCH\_KURLONmattress
- DOOR2: 2FEET3INCH NOTES: ALSO, JAGUAR ANGULAR\_STOP\_COCK TO BE FITTED, 1\_EACH\_BEFORE\_DIRECT\_PILLAR\_COCK\_&
- DOOR3: 1FEET9INCH
- SLIDING DOOR4: 2FEET3INCH DIRECT\_WASHING\_MACHINE\_BIB\_COCK\_& DIRECT\_KITCHEN\_BIB\_COCK.
- USE SOMANY\_TILES, TATASTEEL(IRON\_ORE\_NonSCRAP\_neverRustsInternally)WATER\_GI\_PIPES, UNIK\_GI\_FITTINGS(make\_sure\_spelling\_in\_products), KISAN (SWR:Soil,Waste,RainWater) uPVC PIPES(FIRST\_4INCH\_DIAMETER\_VERTICAL\_PIPELINE\_IN\_SHAFT\_FOR\_LATERINE\_CLOSET\_SINK\_& SECOND\_3INCH\_DIAMETER\_VERTICAL\_PIPELINE\_IN\_SHAFT\_FOR\_SHOWER\_CUM\_TOOTHBRUSH\_BASIN\_CUM\_WASHING\_MACHINE\_CUM\_SINKS\_& THIRD\_3INCH\_DIAMETER\_VERTICAL\_PIPELINE\_IN\_SHAFT\_FOR\_KITCHEN\_BASIN\_SINK\_& FOURTH\_3INCH\_DIAMETER\_VERTICAL\_PIPELINE\_IN\_SHAFT\_FOR\_BALCONY2\_SINK)\_& FITTINGS(ALL(6)\_KISAN\_NALI\_TRAP\_3INCH\_SIPHON\_SINKS)SHOULD\_BE\_EXACTLY\_HORIZONTALLY\_LEVELLED\_SUPERVISE\_YOURSELF\_AND\_PURCHASE\_DOUBLE\_THE\_AMOUNT\_OF\_PVC\_ADHESIVE\_SOLUTION\_OF\_WHAT\_PLUMBER\_TELLS\_YOU\_AND\_TELL\_PLUMBER\_TO\_APPLY\_DOUBLE\_THE\_AMOUNT\_OF\_WHAT\_HE\_NORMALLY\_APPLIES), HINDWARE\_MAGRO\_RIMLESS\_ONE-PIECE\_CLOSET\_ENGLISH\_LATRINE, HINDWARE\_KITCHEN\_BASIN\_STAINLESSSTEEL(SS)\_MATT\_FINISH, JAGUAR\_TOOTHBRUSH\_BASIN, JAGUAR\_COMPANY\_FAUCETS, KIRANSOLIDOCRAFT MANUAL\_VERTICAL\_SLIDING\_WINDOW\_MIDDLE\_PICTURE. NOTE: KISAN SWR uPVC TYPE-B, HIGH PRESSURE CAPACITY.
- BALCONY2(REAR)\_SECURELY\_ENCLOSED\_BY\_GRID\_CAGE\_IRON\_SQUARE\_RODS.CAGE\_BORDER\_ANGLE\_WIDTH=1.5INCH, ROD=0.375INCH
- STUDY TABLE WALL MOUNTED HINGED BOARD 4-LEG-SKELETAL-MODULAR-PLASTIC-FRAME-SUPPORT-HT.-2FEET3INCH-BREADTH1.25FT. NOTE: USE 46MM, TATA-PRAVESH STEEL ENTRY DOOR (CORAL)
- DARK\_RED\_RIPE\_SOLID\_BRICK\_DIMENSION: 9INCHx4.5INCH(DIFFICULT TO FIND EXACTLY THIS DIMENSION, MAYBE IN VILLAGE\_KILNS\_OR\_FIND\_AS\_CLOSE\_AS\_POSSIBLE, BRICK-KILN-OWNERS\_HAVE\_REDUCED\_THE\_BRICK-DIE-SIZE).
- SUPER BUILT-UP AREA(TOTAL\_PLOT\_SIZE LENGTHxBREADTH): 20FEETx15FEET(FRONT) NOTE: USE, ULTRATECH WEATHER PLUS CEMENT
- Use 1. LEGRAND\_COMPANY ELECTRICAL SWITCHES, SOCKETS 2. ABB\_COMPANY MCB 3. KEI\_COMPANY WIRES&CABLES 4. OSRAM CFL 23W
- KAPSUL-AIR(DEPTH=22INCH) AIRCONDITIONER INSTALLATION AS IT APPEARS IN ADVERTISORY VIDEOS THAT ATLEAST 4 INCH DEPTH IS INSIDE WINDOW, THIS IMPLIES OUTSIDE WINDOW DEPTH OF 22-4=18INCH: (A) ON GROUND FLOOR THERE IS A CLEAR MARGIN OF 18INCH (B) ON 1ST FLOOR TO 3RD FLOOR AS BALCONY2 CLEARANCE IS 9.0-1.5=7.5INCH, SO MAKE A KAPSUL BODY SHAPE 7INCH HEIGHT SLOT IN IRON CAGE AT WINDOW-KAPSUL-INSTALL-HT. IN THE BOUNDARY-RAILING-CUM-CAGE OF BALCONY2. ALSO, KAPSUL-AIR HAS FRESH-AIR-MODE.

NOTE: STANDARD\_EARTHING: 2inchx2inchx1inch COPPER-SOLID-BLOCK BURIED 10FEET DEEP IN GROUND &CONNECTED USING COPPER SOLID WIRE GAUGE-AWG4/5.18MM\_DIAMETER/21.15 MMSQUARE.