THE OUTER 2 LENGTH SIDES RED SOLID BRICK WALLS THICKNESS IS=9INCH **GROUND FLOOR PLAN: SUPER BUILT-UP AREA: 300 SQUARE FEET** ALL OTHER RED SOLID BRICK WALLS THICKNESS IS=4.5INCH 1 FEET/1FOOT= 3INCH+3INCH+3INCH+3INCH, Eg. 1FEET6 INCH=1.5FEET, 1FEET3 INCH=1.25FEET 6_PILLARS:CONCRETE_CEMENT_TATASTEEL(IRON_ORE_NON_SCRAP)TISCON_RODS_WILL_BE_REQUIRED. CEILING HEIGHT/FLOOR 10FEET3INCH SHAFT REAR-MAINHOLE FAUCET HOT/COLD BALCONY211FEET6INCH NOTE1:ALL BRICK WALLS THICKNESS MEASUREMENTS HAVE BEEN ACCOUNTED FOR BEFORE CONCLUDING THE WINDOW VERTICAL SLIDING WINDOW VERTICAL SLIDING 4FEETx3FEET INSIDE_TO_BETWEEN_WALLS_CLEARANCE_DIMENSIONS. TILE_SKIRTING_TO_BE_AT_SAME_LEVEL_AS_CEMENTsand(1:4RATIO)WALLPLASTER. 6FEET(TALL)x3FEET EXHAUST DOOR3 NOTE2:FOR INDIVIDUAL PLOT [[ONLY]] FROM 1ST TO 3RD FLOOR REAR BALCONY2 BREADTH SHOULD BE [[REDUCED]] TO 9 INCH GIVI 1FEET **HINDWARE** NG OPEN TO SKY CLEARANCE OF 9 INCH. 9INCH MAGRO MODEL **REMAINING LENGTH 1.5INCH** REDUCED_BECAUSE_THERE_IS_A_TOTAL_POSSIBILITY_THAT_YOUR_BALCONY2(REAR)_WILL_GET_BLOCKED_BY_WALL(REAR)_OF_REAR_ADJAC D BOARD EADTH 2.5 FEE1 AOSMITH KLASSE MIMLESS ONE ENT PLOT OWNER. JAGUAR 1. KUBIX KUS-WHT-35935 **GEYSER 25 LITRES** PIECE CLOSET ALL INSIDE TO BETWEEN WALLS CLEARANCE DIMENSIONS(LENGTHXBREADTH): TOOTHBRUSH BASIN 565mmX420mmX140mm INPUT: USE BED(NOT BOX TYPE) NOTE1: 2_ANGULAR_STOP_COCKS TO BE FITTED BEFORE EVERY SINK Rupees 6990, AS IN PRODUCT CATALOGUE ENTRY DOOR: 2FEET6INCH 6FEET6INCHx4FEET JAGUAR 2-STAIRCASE: 11FEETx4FEET MIXER, EXCEPT AT PLACE OF SHOWER. ANGULAR STOP OOTHBRUSH KITCHEN: 6FEET7.5INCHx3FEET3INCH, CONCRETE CEMENT SLAB BREADTH 1FEET3INCH, AT HEIGHT 2FEET9INCH +

2. KUBIX PRIME KUP-35021PM PILLAR COCK COCK KUP-35053PM FOR 1.0INCH_THICKNESS_MARBLE_STONE_ON_TOP, SAME_ HEIGHT_FOR_KITCHEN_BASIN (DIRECT) for BASIN 190MM EXTENSION BODY **DIRECT INTAKE** SEMI AUTO WASHING MACHINE: UPTO 3FEETx2FEET Rupees 2650 AND TANK INTAKE, **CUPBOARD HALF SLIDING** BATHROOM-CUM-TOILET:5FEET6INCHx4FEET9INCH, EXHAUST FAN CROMPTON GREAVES: TRANSAIR/225MM/1400RPM/BIRD-SCREEN CHAIR DOOR 4FEETx1FEET6INCH THEN USE 1-DRAWING ROOM/HALL: 11FEETx5FEET6INCH 3. BIB COCK KUP-35037PM (DIRECT/GEYSER) NOTE2: FOR SHOWER-MIXER-ETERNAL JAGUAR SINK DOOR2: SOFA: 6FEETx1FEET9INCH(MAXIMUM) Rupees 1700 NUMBERS= 6 KUP-35115PM Rupees 7100 (1 No.) 5 SLIDING DOOR4 MIXER(RATIO) 2FEET 4. KITCHEN LYRIC LYR-38309 SINK MIXER 8. FRIDGE:UPTO 2FEETx2FEET NOTE3: FOR HAND-SHOWER-MIXER-EXTERNAL LYRIC LYR-38309PM 2FEET6INCH SEMI-AUTO

WASHING MACHINE 6INCH **SWINGING SPOUT Rupees 4000 NUMBERS= 8** WITHOUT SPOUT BEDROOM: 8FEET4.5INCHx5FEET6INCH KUP-35149PM Rupees 6150 (1 No.) 5. SHOWER OHS-WHM-1763 Rupees 23450 FOR FULL DIRECT SHAFT-REAR-MAINHOLE: 5FEETx1FEET6INCH (OPEN TO SKY CLEARANCE) 6. HAND SHOWER HSH-1721 Rupees 3750 INPUT/FULL TANK 7. ANGULAR STOP COCK KUP-35053PM 11. BALCONY1(FRONT): 9INCH BREADTH NOTE4: ALL JAGUAR ITEMS IN CHROME FINISH INPUT. 12. BALCONY2(REAR): 1FEET6INCH BREADTH (IMPORTANT FOR YOUR LIFE & A MUST IN A HO Rupees1350 NUMBERS= 19 13. CUPBOARD HALF SLIDING DOOR: 4FEETx1FEET6INCH(4FEETx1FEET5INCH, 1INCH_MARGIN_FOR_SLIDING_DOOR) SINK MIXER **4FEET** BED(NOT_BOX_TYPE): 6FEET6INCHx4FEET, HEIGHT_OF_BED=12INCH+5INCH_KURLONmattress
DOOR2: 2FFFT6INCH NOTE5: ALSO, ANGULAR_STOP_COCK TO BE FITTED 1_BEFORE 5. BEFORE ALL SINK MIXER OUTPUTS, USE 2-SOFA 15. DOOR2: 2FEET6INCH ANGULAR STOP COCK KUP-35053PM FOR **HINDWARE** DIRECT PILLAR COCK, DIRECT INTAKE AND GEYSER INTAKE. THEN USE 16. DOOR3: 1FEET10.5INCH **KITCHEN** TV_RACK DIRECT WASHING MACHINE BIB COCK & DIRECT 1- SINK MIXER(RATIO) LYRIC LYR-38309PM BASIN 17. SLIDING DOOR4: 2FEET6INCH KITCHEN BIB COCK. WITHOUT SPOUT FOR FULL DIRECT **PLATINO** 18. USE SOMANY COMPANY TILES, TATA STEEL(IRON ORE NON SCRAP)GI_PIPES(WATER), FEETINCHminus4.5INCH=6FEET7.5INCH 1FEET3INCH BREADTH CONCRETE CEMENT SLAB AT HEIGHT 2FEET9INCH OUTPUT/FULL GEYSER OUTPUT/MIXER(RATIO) MODEL UNIK GI FITTINGS(make sure spelling in products), KISAN PVC PIPES(FIRST_BIG_DIAMETER_VERTICAL_PIPELINE_IN_SHAFT_FOR_LATERINE_CLOSET_SINK_&_SECOND_SMALL_DIAMETER_VERTICAL_PIPE NO.:36X20X8 36INCHby20IN LINE IN SHAFT FOR SHOWER CUM TOOTBRUSH BASIN CUM WASHING MACHINE CUM SINKS & THIRD SMALL SAME DIAMETER V STAIRCASE 4FEET(2ft+2ft CHby8INCH ERTICAL_PIPELINE_IN_SHAFT_FOR_KITCHEN_BASIN_SINK_&_FOURTH_SMALL_SAME_DIAMETER_VERTICAL_PIPELINE_IN_SHAFT_FOR_BAL CONY2 SINK) & FITTINGS(KISAN_NALI_TRAP_SIPHON_SINK)SHOULD BE EXACTLY HORIZONTALLY LEVELLED SUPERVISE YOURSELF AN D_PURCHASE_DOUBLE_THE_AMOUNT_OF_PVC_ADHESIVE_SOLUTION_OF_WHAT_PLUMBER_TELLS_YOU_AND_TELL_PLUMBER_TO_APPLY DOUBLE THE AMOUNT OF WHAT HE NORMALLY APPLIES), HINDWARE AMAZON RIMLESS SINGLE-PIECE CLOSET, HINDWARE KITCHEN STAINLESSSTEEL(SS) MATT FINISH BASIN, HINDWARE TOOTHBRUSH BASIN, JAGUAR COMPANY FAUCETS, THIS IS LIKE 5FEET6INCH RAIN-KIRANSLIDOCRAFT_MANUAL_VERTICAL_SLIDING_WINDOW_MIDDLE_PICTURE. WATER BALCONY2(REAR) SECURELY ENCLOSED USING GRID CAGE IRON SQUARE RODS. SINK. SO 20. STUDY TABLE WALL MOUNTED HINGED BOARD 4-LEG-SKELETAL-MODULAR-PLASTIC-FRAME-SUPPORT-HT.-2FEET3INCH-BREADTH1.25FT. THIS GOES 21. RED SOLID BRICK DIMENSION: 9INCHX4.5INCH(DIFFICULT TO FIND EXACTLY THIS DIMENSION, MAYBE IN TO 15 FEET VILLAGE KILNS OR FIND AS CLOSE AS POSSIBLE, BRICK-KILN-OWNERS HAVE REDUCED THE BRICK-DIE-SIZE). **GROUND** 22. SUPER BULIT-UP AREA(TOTAL_PLOT_SIZE LENGTHxBREADTH): 20FEETx15FEET(FRONT) FLOOR **FAUCET** INTEGRATE 1ST STEP OF 23. Use 1. LEGRAND COMPANY ELECTRICAL SWITCHES, SOCKETS, 2. ABB COMPANY MCB, 3. KEI COMPANY WIRES & CABLES, 4. OSRAM CFL HOT/COLD/direct FRONT-STAIRCASE 24. KAPSUL-AIR(DEPTH=22INCH) AIRCONDITIONER INSTALLATION AS IT APPEARS IN ADVERTISORY VIDEOS THAT ATLEAST 4 INCH DEPTH IS MAINHOLE. 8INCH BREADTH MITH BALCONY 9 INCH INSIDE WINDOW, THIS IMPLIES OUTSIDE WINDOW DEPTH OF 22-4=18INCH: (A) ON GROUND FLOOR THERE IS A CLEAR MARGIN OF 18INCH BASIN IN CASE OF 1ST TO 3RI (B) ON 1ST FLOOR TO 3RD FLOOR AS BALCONY CLEARANCE IS 9INCH ONLY, SO MAKE A KAPSUL BODY SHAPE 7INCH HEIGHT SLOT IN IRON MOTOR:GROUND-WATER-DIRECT BALCONY1 9INCH FAUCET HOT/COLD FLOOR. CAGE OVER THE BOUNDARY RAILING (ON 4.5INCH BASE WALL) OF BALCONY2. ALSO, KAPSUL-AIR HAS FRESH-AIR-MODE. BALL VALVE FROM →9INCH RED SOLID BRICK WALL 4FEET(TALL)x2FEET **INSIDE KITCHEN** → 4.5INCH RED SOLID BRICK WALL MOTOR:GROUND-WATER-BORING-100FEET:DIRECT LINE