THE OUTER 2 LENGTH SIDES RED SOLID BRICK WALLS THICKNESS IS=9INCH **GROUND FLOOR PLAN: SUPER BUILT-UP AREA: 300 SQUARE FEET** ALL OTHER RED SOLID BRICK WALLS THICKNESS IS=4.5INCH 1 FEET/1FOOT= 3INCH+3INCH+3INCH+3INCH, Eg. 1FEET6 INCH=1.5FEET, 1FEET3 INCH=1.25FEET 6_PILLARS:CONCRETE_CEMENT_TATASTEEL(IRON_ORE_NON_SCRAP)TISCON_RODS_WILL_BE_REQUIRED. CEILING HEIGHT/FLOOR 10FEET3INCH. SHAFT REAR-MAINHOLE BALCONY211FEET6INCH FAUCET HOT/COLD NOTE1:ALL BRICK WALLS THICKNESS MEASUREMENTS HAVE BEEN ACCOUNTED FOR BEFORE CONCLUDING THE WINDOW VERTICAL SLIDING | WINDOW VERTICAL SLIDING 4FEETx3FEET INSIDE_TO_BETWEEN_WALLS_CLEARANCE_DIMENSIONS. TILE_SKIRTING_TO_BE_AT_SAME_LEVEL_AS_CEMENTsand(1:4RATIO)WALLPLASTER. 6FEET(TALL)x3FEET EXHAUST DOOR3 NOTE2:FOR_INDIVIDUAL_PLOT_[[ONLY]]_FROM_1ST_TO_3RD_FLOOR_REAR_BALCONY2_BREADTH_SHOULD_BE_[[REDUCED]]_TO_9_INCH_GIVIN нот/согр 1FEET G OPEN TO SKY CLEARANCE OF 9 INCH. 9INCH MAGRO-MODEL **REMAINING LENGTH 1.5INCH** REDUCED_BECAUSE_THERE_IS_A_TOTAL_POSSIBILITY_THAT_YOUR_BALCONY2(REAR)_WILL_GET_BLOCKED_BY_WALL(REAR)_OF_REAR_ADJACE RIMLESS ONE BOARD EADTH AOSMITH KLASSE NT PLOT OWNER. PIECE CLOSE JAGUAR 1. KUBIX KUS-WHT-35935 **GEYSER 25 LITRES ENGLISH LATERINE** ALL_INSIDE_TO_BETWEEN_WALLS_CLEARANCE_DIMENSIONS(LENGTHxBREADTH): TOOTHBRUSH BASIN 565mmX420mmX140mm INPUT: USE BED(NOT BOX TYPE) NOTE1: 2_ANGULAR_STOP_COCKS TO BE FITTED BEFORE EVERY SINKRupees 6990, AS IN PRODUCT CATALOGUE **ENTRY DOOR: 2FEET6INCH** 6FEET6INCHx4FEET JAGUAR 2-2. HAND SHOWER(LATERINE) ALD-573 Rs. 1350 STAIRCASE: 11FEETx4FEET MIXER, EXCEPT AT PLACE OF SHOWER. ANGULAR STOP COCK KUP-KITCHEN: 6FEET7.5INCHx3FEET3INCH, CONCRETE CEMENT SLAB BREADTH 1FEET3INCH, AT HEIGHT 2FEET9INCH + 3. KUBIX PRIME KUP-35021PM PILLAR COCK 35053PM FOR 1.0INCH THICKNESS MARBLE STONE ON TOP, SAME HEIGHT FOR KITCHEN BASIN (DIRECT) for BASIN 190MM EXTENSION BODY **DIRECT INTAKE** SEMI AUTO WASHING_MACHINE: UPTO_3FEETx2FEET Rupees 2650
BATHROOM-CUM-TOILET:5FEET6INCHx4FEET9INCH, EXHAUST_FAN_CROMPTON_GREAVES: TRANSAIR/225MM/1400RPM/BIRD-SCREEN AND TANK INTAKE, **CUPBOARD HALF SLIDING** 5. CHAIR DOOR 4FEETx1FEET6INCH THEN USE 1-DRAWING ROOM/HALL: 11FEETx5FEET6INCH NOTE2: FOR SHOWER-MIXER-ETERNAL KUP-35115PM 6. 4. BIB COCK KUP-35037PM (DIRECT/GEYSER) JAGUAR SINK DOOR2: SOFA: 6FEETx1FEET9INCH(MAXIMUM) Rupees 1700 NUMBERS= 6 Rupees 7100 (1 No.), SHOWER PIPE (SHA-1211N) 5 SLIDING DOOR4 MIXER(RATIO) 2FEET 8. FRIDGE:UPTO 2FEETx2FEET NOTE3: FOR HAND-SHOWER-MIXER-EXTERNAL KUP-5. KITCHEN LYRIC LYR-38309 SINK MIXER LYRIC LYR-38309PM 2FEET6INCH SEMI-AUTO

WASHING MACHINE 6INCH SWINGING SPOUT Rupees 4000 NUMBERS= 8 BEDROOM: 8FEET4.5INCHx5FEET6INCH 35149PM Rupees 6150 (1 No.) WITHOUT SPOUT 6. SHOWER OHS-WHM-1763 Rupees 23450 FOR FULL DIRECT 10. SHAFT-REAR-MAINHOLE: 5FEETx1FEET6INCH (OPEN TO SKY CLEARANCE) 7. HAND SHOWER(BATH) HSH-1721 Rupees 3750 INPUT/FULL TANK NOTE4: ALL_JAGUAR_ITEMS_IN_CHROME_FINISH 8. ANGULAR STOP COCK KUP-35053PM BALCONY1(FRONT): 9INCH BREADTH INPUT. BALCONY2(REAR): 1FEET6INCH BREADTH (IMPORTANT FOR YOUR LIFE & A MUST IN A HC Rupees1350 NUMBERS= 19 CUPBOARD_HALF_SLIDING_DOOR: 4FEETx1FEET6INCH(4FEETx1FEET5INCH, 1INCH_MARGIN_FOR_SLIDING_DOOR) SINK MIXER **4FEET** BED(NOT_BOX_TYPE): 6FEET6INCHx4FEET, HEIGHT_OF_BED=12INCH+5INCH_KURLONmattress 9. BEFORE ALL SINK MIXER OUTPUTS, USE 2-SOFA 15. DOOR2: 2FEET6INCH NOTES: ALSO, ANGULAR STOP COCK TO BE FITTED, 1 EACH BEFORE, ANGULAR STOP COCK KUP-35053PM FOR **HINDWARE** DIRECT_PILLAR_COCK & DIRECT_WASHING_MACHINE_BIB_COCK & DOOR3: 1FEET10.5INCH DIRECT INTAKE AND GEYSER INTAKE, THEN USE **KITCHEN** 17. SLIDING DOOR4: 2FEET6INCH DIRECT_KITCHEN_BIB_COCK. 1- SINK MIXER(RATIO) LYRIC LYR-38309PM BASIN WITHOUT SPOUT FOR FULL DIRECT **PLATINO** 18. USE SOMANY TILES, TATASTEEL (IRON ORE NONSCRAP neverRustsInternally)WATER_GI_PIPE OUTPUT/FULL GEYSER OUTPUT/MIXER(RATIO) MODEL UNIK GI FITTINGS(make sure spelling in products), KISAN PVC PIPES(FIRST_BIG_DIAMETER_VERTICAL_PIPELINE_IN_SHAFT_FOR_LATERINE_CLOSET_SINK_&_SECOND_SMALL_DIAMETER_VERTICAL_PIPEL NO.:36X20X8 36INCHby20IN INE_IN_SHAFT_FOR_SHOWER_CUM_TOOTBRUSH_BASIN_CUM_WASHING_MACHINE_CUM_SINKS_&_THIRD_SMALL_SAME_DIAMETER_VE STAIRCASE 4FEET(2ft+2ft) CHby8INCH RTICAL_PIPELINE_IN_SHAFT_FOR_KITCHEN_BASIN_SINK_&_FOURTH_SMALL_SAME_DIAMETER_VERTICAL_PIPELINE_IN_SHAFT_FOR_BALC ONY2_SINK)_&_FITTINGS(KISAN_NALI_TRAP_SIPHON_SINK)SHOULD_BE_EXACTLY_HORIZONTALLY LEVELLED SUPERVISE YOURSELF AND PURCHASE_DOUBLE_THE_AMOUNT_OF_PVC_ADHESIVE_SOLUTION_OF_WHAT_PLUMBER_TELLS_YOU_AND_TELL_PLUMBER_TO_APPLY_D OUBLE_THE_AMOUNT_OF_WHAT_HE_NORMALLY_APPLIES), HINDWARE AMAZON RIMLESS SINGLE-PIECE CLOSET, HINDWARE KITCHEN STAINLESSSTEEL(SS) MATT FINISH BASIN, HINDWARE TOOTHBRUSH BASIN, JAGUAR COMPANY FAUCETS, THIS IS LIKE 5FEET6INCH RAIN-KIRANSLIDOCRAFT_MANUAL_VERTICAL_SLIDING_WINDOW_MIDDLE_PICTURE. WATER BALCONY2(REAR) SECURELY ENCLOSED USING GRID CAGE IRON SQUARE RODS. SINK. SO STUDY TABLE WALL MOUNTED HINGED BOARD 4-LEG-SKELETAL-MODULAR-PLASTIC-FRAME-SUPPORT-HT.-2FEET3INCH-BREADTH1.25FT. THIS GOES RED SOLID BRICK DIMENSION: 9INCHX4.5INCH(DIFFICULT TO FIND EXACTLY THIS DIMENSION, MAYBE IN TO 15 FEET VILLAGE KILNS OR FIND AS CLOSE AS POSSIBLE, BRICK-KILN-OWNERS HAVE REDUCED THE BRICK-DIE-SIZE). **GROUND** 22. SUPER BULIT-UP AREA(TOTAL PLOT SIZE LENGTHXBREADTH): 20FEETX15FEET(FRONT) FLOOR **FAUCET** INTEGRATE 1ST STEP OF 23. Use 1. LEGRAND COMPANY ELECTRICAL SWITCHES, SOCKETS 2. ABB COMPANY MCB 3. KEI COMPANY WIRES&CABLES 4. OSRAM CFL 23W HOT/COLD/direct FRONT-STAIRCASE 24. KAPSUL-AIR(DEPTH=22INCH) AIRCONDITIONER INSTALLATION AS IT APPEARS IN ADVERTISORY VIDEOS THAT ATLEAST 4 INCH DEPTH IS MAINHOLE. 8INCH BREADTH MITH BALCONY 9 INCH INSIDE WINDOW, THIS IMPLIES OUTSIDE WINDOW DEPTH OF 22-4=18INCH: (A) ON GROUND FLOOR THERE IS A CLEAR MARGIN OF 18INCH BASIN IN CASE OF 1ST TO 3RI (B) ON 1ST FLOOR TO 3RD FLOOR AS BALCONY CLEARANCE IS 9INCH ONLY, SO MAKE A KAPSUL BODY SHAPE 7INCH HEIGHT SLOT IN IRON MOTOR:GROUND-WATER-DIRECT BALCONY1 9INCH WINDOW MANUAL VERTICAL SLIDING FAUCET HOT/COLD FLOOR. CAGE OVER THE BOUNDARY RAILING (ON 4.5INCH BASE WALL) OF BALCONY2. ALSO, KAPSUL-AIR HAS FRESH-AIR-MODE. BALL VALVE FROM →9INCH RED SOLID BRICK WALL NOTE: STANDARD EARTHING: 2inchx2inchx1inch COPPER-SOLID-BLOCK BURIED 10FEET DEEP IN GROUND 4FEET(TALL)x2FEET **INSIDE KITCHEN** → 4.5INCH_RED_SOLID_BRICK_WALL & CONNECTED USING COPPER SOLID WIRE GAUGE-AWG4/5.18MM DIAMETER/21.15 MMSQUARE. MOTOR:GROUND-WATER-BORING-100FEET:DIRECT LINE