



THE OUTER 2\_LENGTH SIDES RED SOLID BRICK WALLS THICKNESS IS=9INCH

ALL OTHER RED SOLID BRICK WALLS THICKNESS IS=4.5INCH

6\_PILLARS:CONCRETE\_CEMENT\_TATASTEEL(IRON\_ORE\_NON\_SCRAP)TISCOON RODS WILL BE REQUIRED. CEILING HEIGHT/FLOOR 10FEET3INCH.

NOTE1:ALL BRICK WALLS THICKNESS MEASUREMENTS HAVE BEEN ACCOUNTED FOR BEFORE CONCLUDING THE

INSIDE TO BETWEEN WALLS CLEARANCE DIMENSIONS. TILE SKIRTING TO BE AT SAME LEVEL AS CEMENTsand(1:4RATIO)WALLPLASTER.

NOTE2:FOR INDIVIDUAL PLOT [[ONLY]] FROM 1<sup>ST</sup> TO 3<sup>RD</sup> FLOOR REAR BALCONY2 BREADTH SHOULD BE [[REDUCED]] TO 9 INCH GIVIN G\_OPEN TO SKY CLEARANCE OF 9 INCH.

REDUCED BECAUSE THERE IS A TOTAL POSSIBILITY THAT YOUR BALCONY2(REAR) WILL GET BLOCKED BY WALL(REAR) OF REAR ADJACE NT\_PLOT\_OWNER. YOU SHOULD RAISE YOUR REAR END BOUNDARY 4.5 INCH WALL TILL 3<sup>RD</sup> FLOOR.

ALL INSIDE TO BETWEEN WALLS CLEARANCE DIMENSIONS(LENGTHxBREADTH):

1. ENTRY DOOR: 2FEET6INCH NOTE1: 2\_ANGULAR\_STOP\_COCKS TO BE FITTED BEFORE EVERY\_SINK

2. STAIRCASE: 11FEETx4FEET MIXER, EXCEPT AT PLACE OF SHOWER.

3. KITCHEN: 6FEET7.5INCHx3FEET3INCH, CONCRETE CEMENT SLAB BREADTH 1FEET3INCH, AT HEIGHT 2FEET9INCH + 1.0INCH THICKNESS MARBLE STONE ON TOP, SAME HEIGHT FOR KITCHEN BASIN

4. SEMI\_AUTO\_WASHING\_MACHINE: UPTO\_3FEETx2FEET (WHIRLPOOL SUPERB ATOM 6.5 KG)

5. BATHROOM-CUM-TOILET:5FEET6INCHx4FEET9INCH, EXHAUST\_FAN\_CROMPTON\_GREAVES: TRANSAIR/225MM/1400RPM/BIRD-SCREEN

6. DRAWING\_ROOM/HALL: 11FEETx5FEET6INCH

7. SOFA: 6FEETx1FEET9INCH(MAXIMUM)

8. FRIDGE:UPTO 2FEETx2FEET

9. BEDROOM: 8FEET4.5INCHx5FEET6INCH

10. SHAFT-REAR-MAINHOLE: 5FEETx1FEET6INCH (OPEN TO SKY CLEARANCE)

11. BALCONY1(FRONT): 9INCH BREADTH

12. BALCONY2(REAR): 1FEET6INCH BREADTH (IMPORTANT FOR YOUR LIFE & A MUST IN A HOUSE)

13. CUPBOARD\_HALF\_SLIDING\_DOOR: 4FEETx1FEET6INCH(4FEETx1FEET5INCH, 1INCH MARGIN FOR SLIDING DOOR)

14. BED(NOT\_BOX\_TYPE): 6FEET6INCHx4FEET, HEIGHT\_OF\_BED=12INCH+5INCH\_KURLONmattress

15. DOOR2: 2FEET6INCH

16. DOOR3: 1FEET10.5INCH

17. SLIDING DOOR4: 2FEET6INCH

18. USE SOMANY\_TILES, TATASTEEL(IRON\_ORE\_NonSCRAP\_neverRustsInternally)WATER\_GI\_PIPES, UNIK\_GI\_FITTINGS(make\_sure\_spelling\_in\_products), KISAN PVC PIPES(FIRST\_BIG\_DIAMETER\_VERTICAL\_PIPELINE\_IN\_SHAFT\_FOR\_LATERINE\_CLOSET\_SINK\_&\_SECOND\_SMALL\_DIAMETER\_VERTICAL\_PIPEL IN\_SHAFT\_FOR\_SHOWER\_CUM\_TOOTBRUSH\_BASIN\_CUM\_WASHING\_MACHINE\_CUM\_SINKS\_&\_THIRD\_SMALL\_SAME\_DIAMETER\_VE RTICAL\_PIPELINE\_IN\_SHAFT\_FOR\_KITCHEN\_BASIN\_SINK\_&\_FOURTH\_SMALL\_SAME\_DIAMETER\_VERTICAL\_PIPELINE\_IN\_SHAFT\_FOR\_BALC ONY2\_SINK) & FITTINGS(KISAN\_NALI\_TRAP\_SIPHON\_SINK)SHOULD BE EXACTLY HORIZONTALLY LEVELLED SUPERVISE YOURSELF AND PURCHASE DOUBLE THE AMOUNT OF PVC ADHESIVE SOLUTION OF WHAT PLUMBER TELLS YOU AND TELL PLUMBER TO APPLY D OUBLE THE AMOUNT OF WHAT HE NORMALLY APPLIES), HINDWARE AMAZON RIMLESS SINGLE-PIECE CLOSET, HINDWARE KITCHEN STAINLESSSTEEL(SS)\_MATT\_FINISH BASIN, HINDWARE TOOTHBRUSH\_BASIN, JAGUAR\_COMPANY\_FAUCETS, KIRANSLIDOCRAFT MANUAL\_VERTICAL\_SLIDING\_WINDOW\_MIDDLE\_PICTURE.

19. BALCONY2(REAR)\_SECURELY\_ENCLOSED\_BY\_GRID\_CAGE\_IRON\_SQUARE\_RODS.CAGE\_BORDER\_ANGLE\_WIDTH=1.5INCH, ROD=0.375INCH

20. STUDY TABLE WALL MOUNTED HINGED BOARD 4-LEG-SKELETAL-MODULAR-PLASTIC-FRAME-SUPPORT-HT.-2FEET3INCH-BREADTH1.25FT.

21. RED\_SOLID\_BRICK\_DIMENSION: 9INCHx4.5INCH(DIFFICULT TO FIND EXACTLY THIS DIMENSION, MAYBE IN VILLAGE\_KILNS\_OR\_FIND\_AS\_CLOSE\_AS\_POSSIBLE, BRICK-KILN-OWNERS\_HAVE\_REDUCED\_THE\_BRICK-DIE-SIZE).

22. SUPER BUILT-UP AREA(TOTAL\_PLOT\_SIZE LENGTHxBREADTH): 20FEETx15FEET(FRONT)

23. Use 1. LEGRAND\_COMPANY ELECTRICAL SWITCHES, SOCKETS 2. ABB\_COMPANY MCB 3. KEI\_COMPANY WIRES&CABLES 4. OSRAM CFL 23W

24. KAPSUL-AIR(DEPTH=22INCH) AIRCONDITIONER INSTALLATION AS IT APPEARS IN ADVERTISORY VIDEOS THAT ATLEAST 4 INCH DEPTH IS INSIDE WINDOW, THIS IMPLIES OUTSIDE WINDOW DEPTH OF 22-4=18INCH: (A) ON GROUND FLOOR THERE IS A CLEAR MARGIN OF 18INCH (B) ON 1<sup>ST</sup> FLOOR TO 3<sup>RD</sup> FLOOR AS BALCONY2 CLEARANCE IS 9.0-1.5=7.5INCH, SO MAKE A KAPSUL BODY SHAPE 7INCH HEIGHT SLOT IN IRON CAGE AT WINDOW-KAPSUL-INSTALL-HT. IN THE BOUNDARY-RAILING-CUM-CAGE OF BALCONY2. ALSO, KAPSUL-AIR HAS FRESH-AIR-MODE.

NOTE: STANDARD\_EARTHING: 2inchx2inchx1inch COPPER-SOLID-BLOCK BURIED 10FEET DEEP IN GROUND &CONNECTED USING COPPER SOLID WIRE GAUGE-AWG4/5.18MM DIAMETER/21.15 MMSQUARE.

JAGUAR 1. KUBIX KUS-WHT-35935

TOOTHBRUSH BASIN 565mmX420mmX140mm

Rupees 6990, AS IN PRODUCT CATALOGUE

2. HAND SHOWER(LATERINE) ALD-573 Rs. 1350

3. KUBIX PRIME KUP-35021PM PILLAR COCK (DIRECT) for BASIN 190MM EXTENSION BODY

Rupees 2650

4. BIB COCK KUP-35037PM (DIRECT/GEYSER)

Rupees 1700 NUMBERS= 6

5. KITCHEN LYRIC LVR-38309 SINK MIXER

SWINGING SPOUT Rupees 4000 NUMBERS= 8

6. SHOWER OHS-WHM-1763 Rupees 23450

7. HAND SHOWER(BATH) HSH-1721 Rupees 3750

8. ANGULAR STOP COCK KUP-35053PM

Rupees1350 NUMBERS= 19

9. BEFORE ALL SINK MIXER OUTPUTS, USE 2- ANGULAR STOP COCK KUP-35053PM FOR DIRECT INTAKE AND GEYSER INTAKE, THEN USE 1- SINK MIXER(RATIO) LYRIC LVR-38309PM WITHOUT SPOUT FOR FULL DIRECT OUTPUT/FULL GEYSER OUTPUT/MIXER(RATIO) OUTPUT AND THEN USE A BIBCOCK