GROUND FLOOR PLAN: SUPER BUILT-UP AREA: 300 SQUARE FEET=27.87 SQUARE METER=HOME28 USE, JAGJEET ESTD. 1968 MANUAL VERTICAL CITRUS FRUIT PRESS THE OUTER 2 LENGTH SIDES RED SOLID BRICK WALLS THICKNESS IS=9INCH [SINK-MIXER] 1FEET/1FOOT=3INCH+3INCH+3INCH+1.5INCH+1.5INCH=12INCH Eg.1FEET6INCH=1.5FEET, 1FEET3IN=1.25FEETALL_OTHER_RED_SOLID_BRICK_WALLS_THICKNESS_IS=4.5INCH JUICE MACHINE PLAIN STEEL FINISH, CHECK SIEVE FOR CRACK AND IRON-CAGE-BOTTOM-BASE-SLAB-CEMENT, JEERA-GITTI, STONEDUST, TISCON-6MM-RODS-INSIDE-SLAB=8FEET9INCHx1.5INx3IN 6_PILLARS_18INCHx10.5INCH:CEMENT, GITTI, STONEDUST, TATASTEEL (IRON_ORE_NonSCRAP) TISCON_ROD. CEILING HEIGHT/FLOOR 10FEET3INCH 1 INCH HAS 8 BALCONY211FEET6INCH FAUCET HOT-COLD SHAFT REAR-MAINHOLE NOTE1:ALL BRICK WALLS THICKNESS MEASUREMENTS HAVE BEEN ACCOUNTED FOR BEFORE CONCLUDING THE INSIDE TO BETWEEN WALLS WINDOW MANUAL VERTICAL SLIDING **EQUAL PARTS** WINDOW VERTICAL SLIDING CLEARANCE_DIMENSIONS. TILE_SKIRTING_[CLOSE_TO/AT_SAME_LEVEL_AS]_CEMENT: MEDIUM-GRAINSIZE-FINESAND(1:4 RATIO) WALLPLASTER. 4FEET(TALL)x3FEET a PART. SPOKEN 6FEET(TALL)x3FEET EXHAUS NOTE2:FOR INDIVIDUAL PLOT [[ONLY]] FROM 1ST TO 3RD FLOOR REAR BALCONY2 BREADTH SHOULD BE [[REDUCED]] TO 9 INCH GIVIN AS 1by8, AND DOOR3 1FEET REMAINING SINCH G OPEN TO SKY CLEARANCE OF 9 INCH. REDUCED BECAUSE THERE IS A TOTAL POSSIBILITY THAT YOUR BALCONY2(REAR) WILL GET BLOCKED WRITTEN AS 1/8. \9INCHROOM LENGTH 1.5INCH BY WALL(REAR) OF REAR ADJACENT PLOT OWNER. YOU SHOULD RAISE YOUR REAR END BOUNDARY 4.5 INCH WALL TILL 3RD FLOOR. AOSMITH KLASSE RIMLESS ONE **GEYSER 25 LITRES** NOTE3:TILE SKIRTING THICKNESS IS < WALL PLASTER THICKNESS, TOP GETS PRESSED BY WALLPLASTER. JAGUAR 1. KUBIX KUS-WHT-35935 PHECE-CLOSET INPUT: USE ALL_INSIDE_TO_BETWEEN_WALLS_CLEARANCE_DIMENSIONS(LENGTHxBREADTH): TOOTHBRUSH BASIN 565mmX420mmX140mm BED(NOT BOX TYPE) ENGLISH LATERINE JAGUAR: 2-Rupees 6990, AS IN PRODUCT CATALOGUE **ENTRY DOOR: 2FEET6INCH** NOTE1: JAGUAR 2 ANGULAR STOP COCKS TO BE FITTED 6FEET6INCHx4FEET. ANGULAR STOP 2. HAND SHOWER(LATERINE) ALD-573 Rs. 1350 STAIRCASE: 11FEETx4FEET BEFORE_EVERY_[SINK-MIXER], EXCEPT AT PLACE OF SHOWER. TAKE BED MEASUREMENT KITCHEN: 6FEET7.5INCHx3FEET3INCH, CONCRETE CEMENT SLAB BREADTH 1FEET3INCH, AT HEIGHT 2FEET9INCH +
3. KUBIX PRIME KUP-35021PM PILLAR COCK COCK KUP-AFTER CEMENT PLASTER. 35053PM FOR 1.0INCH THICKNESS MARBLE STONE ON TOP, SAME HEIGHT FOR KITCHEN BASIN **DIRECT-INTAKE** (DIRECT) for BASIN 190MM EXTENSION BODY SEMI_AUTO_WASHING_MACHINE: UPTO_3FEETx2FEET (WHIRLPOOL SUPERB ATOM 6.5 KG) AND TANK-INTAKE Rupees 2650 **CUPBOARD HALF SLIDING** 5. BATHROOM-CUM-TOILET:5FEETx4FEET9INCH, EXHAUST FAN CROMPTON GREAVES: TRANSAIR/225MM/1400RPM/BIRD-SCREEN THEN USE 1-CHAIR DOOR 4FEETx1FEET6INCH JAGUAR: [SINK-6. DRAWING ROOM/HALL: 11FEETx5FEET6INCH 4. BIB COCK KUP-35037PM (DIRECT/GEYSER) NOTE2: JAGUAR FOR SHOWER-MIXER-ETERNAL KUP-MIXER](RATIO) DOOR2: SOFA: 6FEETx1FEET9INCH(MAXIMUM) Rupees 1700 NUMBERS=7 **≒** SLIDING DOOR4 35115PM Rupees 7100 (1 No.), SHOWER PIPE (SHA-1211N) LYRIC LYR-38309PM 2FEET 5. KITCHEN LYRIC LYR-38309 [SINK-MIXER] CONSTRUCTION TIP: 8. FRIDGE:UPTO 2FEETx2FEET 2FEET3INCH NOTE3: JAGUAR FOR HAND-SHOWER-MIXER-EXTERNAL WITHOUT SPOUT 3INCH CONSTRUCT HOUSE **SWINGING SPOUT Rupees 4000 NUMBERS= 8** 9. BEDROOM: 8FEET4.5INCHx5FEET6INCH KUP-35149PM Rupees 6150 (1 No.) FOR FULL-DIRECT-CORRECTLY WHILE WORKING 6. SHOWER OHS-WHM-1763 Rupees 23450 10. SHAFT-REAR-MAINHOLE: 4FEET9INCHx2FEET (OPEN_TO_SKY_CLEARANCE_IRON_CAGE_AT_TOP INPUT/FULL-TANK-7. HAND SHOWER(BATH) HSH-1721 Rupees 3750 WITH SMALLEST DIMENSION BALCONY1(FRONT): 9INCH BREADTH NOTE4: ALL JAGUAR ITEMS IN CHROME FINISH INPUT. 8. ANGULAR STOP COCK KUP-35053PM UNIT AT 1.5 INCH BALCONY2(REAR): 1FEET6INCH BREADTH (IMPORTANT FOR YOUR LIFE & A MUST IN A HOUSE) JAGUAR: USE (IMPLICITLY 0.5INCH). Rupees1350 NUMBERS= 20 1-BIBCOCK CUPBOARD HALF SLIDING DOOR: 4FEETx1FEET6INCH(4FEETx1FEET5INCH, 1INCH MARGIN FOR SLIDING DOOR) TAKING STRAIGHT, SAGLESS, BEFORE BED(NOT BOX TYPE): 6FEET6INCHx4FEET, HEIGHT OF BED=12INCH+5INCH KURLONmattress 9. BEFORE ALL [SINK-MIXER] OUTPUTS, USE 2-SAME-LEVEL-AT-BOTH-ENDS GEYSER-STOP-MEASUREMENTS. 15. DOOR2: 2FEET3INCH ANGULAR STOP COCK KUP-35053PM FOR NOTES: ALSO, JAGUAR ANGULAR STOP COCK TO BE FITTED, соск то AUTOMATIC SUPERVISION. 16. DOOR3: 1FEET9INCH 1 EACH BEFORE, DIRECT PILLAR COCK & DIRECT-INTAKE AND GEYSER-INTAKE. THEN USE EMPTY-CLEAN TANK≓ 17. SLIDING DOOR4: 2FEET3INCH DIRECT_WASHING_MACHINE_BIB_COCK & DIRECT_KITCHEN BIB COCK. 1- [SINK-MIXER](RATIO) LYRIC LYR-38309PM **USE, FREEMANS METAL-STRIP** HINDWARE KITCHEN 3FEET3INCH TAPE(5METER, 50METER). WITHOUT SPOUT FOR FULL-DIRECT-18. USE SOMANY TILES, TATASTEEL (IRON ORE NonSCRAP neverRustsInternally) WATER GI PIPES BASIN (SS) STAINLE\$S UNIK GI FITTINGS(make sure spelling in products), KISAN (SWR:Soil,Waste,RainWater) uPVC STEEL CHROME FINISH Z STAIRCASE 4FEET(2ft+2ft) **OUTPUT AND THEN USE A BIBCOCK** PIPES(FIRST 4INCH DIAMETER VERTICAL PIPELINE IN SHAFT FOR LATERINE CLOSET SINK & SECOND 3INCH DIAMETER VERTICAL PIP PLATINO NOTE: USE AQUATECH MODEL NO.: ELINE IN SHAFT FOR SHOWER CUM TOOTBRUSH BASIN CUM WASHING MACHINE CUM SINKS & THIRD 3INCH DIAMETER VERTICA TRIPLE-LAYER-36X20X8 L_PIPELINE_IN_SHAFT_FOR_KITCHEN_BASIN_SINK_&_FOURTH_3INCH_DIAMETER_VERTICAL_PIPELINE_IN_SHAFT_FOR_BALCONY2_SINK)_ (white-black-white) 36INCH×20INCH & FITTINGS(ALL(6) KISAN NALI TRAP 3INCH SIPHON SINKS)SHOULD BE EXACTLY HORIZONTALLY LEVELLED SUPERVISE YOURSELF AN WATER-TANK-500-LITRE. x8INCH D_PURCHASE_DOUBLE_THE_AMOUNT_OF_PVC_ADHESIVE_SOLUTION_OF_WHAT_PLUMBER_TELLS_YOU_AND_TELL_PLUMBER_TO_APPLY NOTE: HOT-COAL-USE, VINOD DOUBLE THE AMOUNT OF WHAT HE NORMALLY APPLIES), HINDWARE MAGRO RIMLESS ONE-PIECE CLOSET ENGLISH LATRINE, TAR-COATED-ON-INDUCTION MODENA [DPC-2INCH-THICK]-HINDWARE KITCHEN BASIN STAINLESSSTEEL(SS) MATT FINISH, JAGUAR TOOTHBRUSH BASIN, JAGUAR COMPANY FAUCETS, (SS) COOKWARE, 5FEET6INCH DPC-PLACED-ON-KIRANSLIDOCRAFT MANUAL VERTICAL SLIDING WINDOW MIDDLE PICTURE. NOTE: KISAN SWR uPVC TYPE-B, HIGH PRESSURE CAPACITY. SUJATA 900WATT JUICER-CUM-GRINDER TOP-OF-ALL-WALLS BALCONY2(REAR) SECURELY ENCLOSED BY GRID CAGE IRON SQUARE RODS.CAGE BORDER ANGLE WIDTH=1.5INCH, ROD=0.375INCH -AT-2FEET-FROM-STUDY TABLE WALL MOUNTED HINGED BOARD 4-LEG-SKELETAL-MODULAR-PLASTIC-FRAME-SUPPORT-HT.-2FEET3INCH-BREADTH1.25FT. THIS IS LIKE ROAD-LEVEL. DARK RED RIPE SOLID BRICK DIMENSION: 9INCHX4.5INCH(DIFFICULT TO FIND EXACTLY THIS DIMENSION, MAYBE IN **RAIN-WATER** 15 FEET VILLAGE KILNS OR FIND AS CLOSE AS POSSIBLE, BRICK-KILN-OWNERS HAVE REDUCED THE BRICK-DIE-SIZE). SINK, SO THIS **GOES TO** 22. SUPER BULIT-UP AREA(TOTAL PLOT SIZE LENGTHXBREADTH): 20FEETX15FEET(FRONT) **FAUCET** NOTE: USE, ULTRATECH WEATHER PLUS CEMENT INTEGRATE 1ST STEP OF GROUND-23. Use 1. LEGRAND COMPANY ELECTRICAL SWITCHES, SOCKETS 2. ABB COMPANY MCB 3. KEI COMPANY WIRES&CABLES 4. OSRAM CFL 23W HOT-COLD/DIRECT STAIRCASE FLOOR 24. KAPSUL-AIR(DEPTH=22INCH) AIRCONDITIONER INSTALLATION AS IT APPEARS IN ADVERTISORY VIDEOS THAT ATLEAST 4 INCH DEPTH IS **҈∿7.5INCH BREADT**⊦ FRONT-INSIDE WINDOW. THIS IMPLIES OUTSIDE WINDOW DEPTH OF 22-4=18INCH: (A) ON GROUND FLOOR THERE IS A CLEAR MARGIN OF 18INCH MITH BALCONY 9 INCH BASIN (B) ON 1ST FLOOR TO 3RD FLOOR AS BALCONY2 CLEARANCE IS 9.0-1.5=7.5INCH, SO MAKE A KAPSUL BODY SHAPE 7INCH HEIGHT SLOT IN IRON 到 IN CASE OF 1ST TO 3R MOTOR:GROUND-WATER-DIRECT BALCONY1-9INCH WINDOW VERTICAL SLIDING CAGE AT WINDOW-KAPSUL-INSTALL-HT. IN THE BOUNDARY-RAILING-CUM-CAGE OF BALCONY2. ALSO, KAPSUL-AIR HAS FRESH-AIR-MODE. →9INCH RED SOLID BRICK WALL ■ NOTE: STANDARD EARTHING: 2inchx2inchx1inch COPPER-SOLID-BLOCK BURIED 10FEET DEEP IN GROUND 4FEET(TALL)x2FEET NOTE: TATA WATER_0.5INCH_DIAMETER_GI_PIPES ◆4.5INCH RED SOLID BRICK WALL &CONNECTED USING COPPER SOLID WIRE GAUGE-AWG4/5.18MM DIAMETER/21.15 MMSQUARE MOTOR:GROUND-WATER[MANUAL BORING]-100FEET-DEEP:DIRECT-LINE:FIRST TASK:INSTALL CAST IRON PRESSURE HAND PUMP