GROUND FLOOR PLAN: SUPER BUILT-UP AREA: 300 SQUARE FEET **USE JAGJEET ESTD. 1968 MANUAL VERTICAL CITRUS FRUIT PRESS** THE OUTER 2 LENGTH SIDES RED SOLID BRICK WALLS THICKNESS IS=9INCH 1 FEET/1FOOT= 3INCH+3INCH+3INCH+3INCH, Eg. 1FEET6 INCH=1.5FEET, 1FEET3 INCH=1.25FEET JUICE MACHINE PLAIN STEEL FINISH, CHECK SIEVE FOR CRACK AND ALL OTHER RED SOLID BRICK WALLS THICKNESS IS=4.5INCH IRON-CAGE-BOTTOM-BASE-CONCRETE-CEMENT-IRON-THIN-RODS-INSIDE-SLAB=8FEET11INCHx1.5INCHx3INCH HOLES SYMMETRY.
6\_PILLARS:CONCRETE\_CEMENT\_<mark>TATASTEEL</mark>(IRON\_ORE\_NON\_SCRAP)<mark>TISCON</mark>\_RODS\_WILL\_BE\_REQUIRED. CEILING HEIGHT/FLOOR 10FEET3INCH. FAUCET HOT/COLD BALCONY211FEET6INCH SHAFT REAR-MAINHOLE , a PART, NOTE1:ALL BRICK WALLS THICKNESS MEASUREMENTS HAVE BEEN ACCOUNTED FOR BEFORE CONCLUDING THE WINDOW MANUAL VERTICAL SLIDING **SPOKEN AS** WINDOW VERTICAL SLIDING  $\blacksquare \oplus$ INSIDE\_TO\_BETWEEN\_WALLS\_CLEARANCE\_DIMENSIONS. TILE\_SKIRTING\_TO\_BE\_AT\_SAME\_LEVEL\_AS\_CEMENTsand(1:4RATIO)WALLPLASTER. 4FEET(TALL)x3FEET 1by8, AND 6FEET(TALL)x3FEET EXHAUS NOTE2:FOR\_INDIVIDUAL\_PLOT\_[[ONLY]]\_FROM\_1<sup>ST</sup>\_TO\_3<sup>RD</sup>\_FLOOR\_REAR\_BALCONY2\_BREADTH\_SHOULD\_BE\_[[REDUCED]]\_TO\_9\_INCH\_GIVIN DOOR3 WRITTEN AS 1FEET REMAINING ROOM LENGTH 1.5INCH G OPEN TO SKY CLEARANCE OF 9 INCH. 9INCH MAGRO MODEL REDUCED\_BECAUSE\_THERE\_IS\_A\_TOTAL\_POSSIBILITY\_THAT\_YOUR\_BALCONY2(REAR)\_WILL\_GET\_BLOCKED\_BY\_WALL(REAR)\_OF\_REAR\_ADJACE **AOSMITH KLASSE** RIMLESS ONE NT PLOT OWNER, YOU SHOULD RAISE YOUR REAR END BOUNDARY 4.5 INCH WALL TILL 3RD FLOOR. JAGUAR 1. KUBIX KUS-WHT-35935 **GEYSER 25 LITRES** PIECE CLOSET ALL\_INSIDE\_TO\_BETWEEN\_WALLS\_CLEARANCE\_DIMENSIONS(LENGTHxBREADTH): TOOTHBRUSH BASIN 565mmX420mmX140mm INPUT: USE BED(NOT BOX TYPE) ENGLISH LATERIN NOTE1: 2 ANGULAR STOP COCKS TO BE FITTED BEFORE EVERY SINKRUPEES 6990, AS IN PRODUCT CATALOGUE **ENTRY DOOR: 2FEET6INCH** JAGUAR 2-6FEET6INCHx4FEET. 2. HAND SHOWER(LATERINE) ALD-573 Rs. 1350 STAIRCASE: 11FEETx4FEET MIXER, EXCEPT AT PLACE OF SHOWER. ANGULAR STOP TAKE BED MEASUREMENT KITCHEN: 6FEET7.5INCHx3FEET3INCH. CONCRETE CEMENT SLAB BREADTH 1FEET3INCH. AT HEIGHT 2FEET9INCH + COCK KUP-AFTER CEMENT PLASTER. 3. 3. KUBIX PRIME KUP-35021PM PILLAR COCK 35053PM FOR 1.0INCH\_THICKNESS\_MARBLE\_STONE\_ON\_TOP, SAME\_ HEIGHT\_FOR\_KITCHEN\_BASIN (DIRECT) for BASIN 190MM EXTENSION BODY DIRECT INTAKE SEMI AUTO WASHING MACHINE: UPTO 3FEETx2FEET (WHIRLPOOL SUPERB ATOM 6.5 KG) AND TANK INTAKE, **CUPBOARD HALF SLIDING** BATHROOM-CUM-TOILET:5FEETx4FEET9INCH, EXHAUST FAN CROMPTON GREAVES: TRANSAIR/225MM/1400RPM/BIRD-SCREEN 5. CHAIR DOOR 4FEETx1FEET6INCH THEN USE 1-DRAWING ROOM/HALL: 11FEETx5FEET6INCH NOTE2: FOR SHOWER-MIXER-ETERNAL KUP-35115PM 6. 4. BIB COCK KUP-35037PM (DIRECT/GEYSER) JAGUAR SINK DOOR2: SOFA: 6FEETx1FEET9INCH(MAXIMUM) Rupees 1700 NUMBERS= 6 Rupees 7100 (1 No.), SHOWER PIPE (SHA-1211N) 5 SLIDING DOOR4 MIXER(RATIO) 2FEET 8. FRIDGE:UPTO 2FEETx2FEET NOTE3: FOR HAND-SHOWER-MIXER-EXTERNAL KUP-5. KITCHEN LYRIC LYR-38309 SINK MIXER LYRIC LYR-38309PM EMI-AUTO 2FEET4.5INCH 6INCH SWINGING SPOUT Rupees 4000 NUMBERS= 8 9. 35149PM Rupees 6150 (1 No.) WITHOUT SPOUT BEDROOM: 8FEET4.5INCHx5FEET6INCH SHAFT-REAR-MAINHOLE: 4FEET9INCHx2FEET (OPEN\_TO\_SKY\_CLEARANCE\_IRON\_CAGE\_AT\_TOP) 6. SHOWER OHS-WHM-1763 Rupees 23450 FOR FULL DIRECT 10. 7. HAND SHOWER(BATH) HSH-1721 Rupees 3750 INPUT/FULL TANK BALCONY1(FRONT): 9INCH BREADTH NOTE4: ALL JAGUAR ITEMS IN CHROME FINISH 8. ANGULAR STOP COCK KUP-35053PM SEMI-AUTC WASHING I INPUT. BALCONY2(REAR): 1FEET6INCH BREADTH (IMPORTANT FOR YOUR LIFE & A MUST IN A HO Rupees1350 NUMBERS= 19 SINK MIXER CUPBOARD HALF SLIDING DOOR: 4FEETx1FEET6INCH(4FEETx1FEET5INCH, 1INCH\_MARGIN\_FOR\_SLIDING\_DOOR) **4FEET** BED(NOT BOX TYPE): 6FEET6INCHx4FEET, HEIGHT OF BED=12INCH+5INCH KURLONmattress 9. BEFORE ALL SINK MIXER OUTPUTS, USE 2-HINDWARE KITCHEN SOFA 15. DOOR2: 2FEET6INCH NOTES: ALSO, ANGULAR STOP COCK TO BE FITTED, 1 EACH BEFORE, ANGULAR STOP COCK KUP-35053PM FOR BASIN (SS) STAINLESS DIRECT\_PILLAR\_COCK & DIRECT\_WASHING\_MACHINE\_BIB\_COCK & DOOR3: 1FEET10.5INCH DIRECT INTAKE AND GEYSER INTAKE, THEN USE STEEL CHROME FINISH 17. SLIDING DOOR4: 2FEET6INCH DIRECT\_KITCHEN\_BIB\_COCK. 1- SINK MIXER(RATIO) LYRIC LYR-38309PM PLATINO 3FEET3INCH WITHOUT SPOUT FOR FULL DIRECT MODEL NO.: 18. USE SOMANY TILES, TATASTEEL (IRON ORE NONSCRAP neverRustsInternally)WATER\_GI\_PIPE OUTPUT/FULL GEYSER OUTPUT/MIXER(RATIO) 36X20X8 UNIK GI FITTINGS(make sure spelling in products), KISAN PVC PIPES(FIRST\_BIG\_DIAMETER\_VERTICAL\_PIPELINE\_IN\_SHAFT\_FOR\_LATERINE\_CLOSET\_SINK\_&\_SECOND\_SMALL\_DIAMETER\_VERTICAL\_PIPEL 36INCHx20INCH x8INCH INE IN SHAFT FOR SHOWER CUM TOOTBRUSH BASIN CUM WASHING MACHINE CUM SINKS & THIRD SMALL SAME DIAMETER VE STAIRCASE 4FEET(2ft+2ft USE. VINOD RTICAL\_PIPELINE\_IN\_SHAFT\_FOR\_KITCHEN\_BASIN\_SINK\_&\_FOURTH\_SMALL\_SAME\_DIAMETER\_VERTICAL\_PIPELINE\_IN\_SHAFT\_FOR\_BALC INDUCTION MODENA ONY2 SINK) & FITTINGS(KISAN NALI TRAP SIPHON SINK)SHOULD BE EXACTLY HORIZONTALLY LEVELLED SUPERVISE YOURSELF AND (SS) COOKWARE, PURCHASE\_DOUBLE\_THE\_AMOUNT\_OF\_PVC\_ADHESIVE\_SOLUTION\_OF\_WHAT\_PLUMBER\_TELLS\_YOU\_AND\_TELL\_PLUMBER\_TO\_APPLY\_D SUJATA 900WATT OUBLE\_THE\_AMOUNT\_OF\_WHAT\_HE\_NORMALLY\_APPLIES), HINDWARE AMAZON RIMLESS SINGLE-PIECE CLOSET, HINDWARE KITCHEN JUICER-CUM-GRINDER STAINLESSSTEEL(SS) MATT FINISH BASIN, HINDWARE TOOTHBRUSH BASIN, JAGUAR COMPANY FAUCETS, THIS IS LIKE 5FEET6INCH KIRANSLIDOCRAFT\_MANUAL\_VERTICAL\_SLIDING\_WINDOW\_MIDDLE\_PICTURE. RAIN-BALCONY2(REAR) SECURELY ENCLOSED BY GRID CAGE IRON SQUARE RODS.CAGE BORDER ANGLE WIDTH=1.5INCH, ROD=0.375INCH WATER STUDY TABLE WALL MOUNTED HINGED BOARD 4-LEG-SKELETAL-MODULAR-PLASTIC-FRAME-SUPPORT-HT.-2FEET3INCH-BREADTH1.25FT. SINK, SO RED SOLID BRICK DIMENSION: 9INCHX4.5INCH(DIFFICULT TO FIND EXACTLY THIS DIMENSION, MAYBE IN THIS GOES 15 FEET VILLAGE KILNS OR FIND AS CLOSE AS POSSIBLE, BRICK-KILN-OWNERS HAVE REDUCED THE BRICK-DIE-SIZE). TO 22. SUPER BULIT-UP AREA(TOTAL PLOT SIZE LENGTHXBREADTH): 20FEETX15FEET(FRONT) GROUND-**FAUCET** INTEGRATE 1ST STEP OF FLOOR 23. Use 1. LEGRAND COMPANY ELECTRICAL SWITCHES, SOCKETS 2. ABB COMPANY MCB 3. KEI COMPANY WIRES&CABLES 4. OSRAM CFL 23W HOT/COLD/direct STAIRCASE FRONT-24. KAPSUL-AIR(DEPTH=22INCH) AIRCONDITIONER INSTALLATION AS IT APPEARS IN ADVERTISORY VIDEOS THAT ATLEAST 4 INCH DEPTH IS 8INCH BREADTH MAINHOLE. INSIDE WINDOW. THIS IMPLIES OUTSIDE WINDOW DEPTH OF 22-4=18INCH: (A) ON GROUND FLOOR THERE IS A CLEAR MARGIN OF 18INCH MOTH BALCONY 9 INCH BASIN (B) ON 1ST FLOOR TO 3RD FLOOR AS BALCONY2 CLEARANCE IS 9.0-1.5=7.5INCH, SO MAKE A KAPSUL BODY SHAPE 7INCH HEIGHT SLOT IN IRON IN CASE OF 1ST TO 3F MOTOR:GROUND-WATER-DIRECT BALCONY1 9INCH WINDOW VERTICAL SLIDING CAGE AT WINDOW-KAPSUL-INSTALL-HT. IN THE BOUNDARY-RAILING-CUM-CAGE OF BALCONY2, ALSO, KAPSUL-AIR HAS FRESH-AIR-MODE. ■ NOTE: STANDARD EARTHING: 2inchx2inchx1inch COPPER-SOLID-BLOCK BURIED 10FEET DEEP IN GROUND →9INCH RED SOLID BRICK WALL 4FEET(TALL)x2FEET →4.5INCH\_RED\_SOLID\_BRICK\_WALL &CONNECTED USING COPPER SOLID WIRE GAUGE-AWG4/5.18MM DIAMETER/21.15 MMSQUARE ■MOTOR:GROUND-WATER-[MANUAL\_BORING]-100FEET-DEEP:DIRECT LINE(FIRST\_TASK: INSTALL\_CAST IRON PRESSURE HAND PUMP)