

PILLARS&ROOF(LINTER)-TISCON-RODS-SPECIFICATION:

1. 10 MM LONG-LENGTH with CROSS-Concealed-BEAM every 10 feet.
2. CONCEALED-BEAM 12MM(6MM-Rectangular-RINGS).
3. 12MM SHORT-LENGTH
4. PILLARS 16MM(8MM-Rectangular-RINGS).
5. (NONE-IN-OUR-CASE-OF-HOME28) For Eg. 22feetx5feet-BALCONY-PROJECTION, 20MM-THREE-Concealed-Beams-On-9InchWallsAtleast5feetLength.
6. BALCONY1 & BALCONY2, PROJECTION, 16MM(on-two-9Inch-Walls) and 16MM(on-middle-4.5Inch-Wall)
7. ROOF(LINTER)-THICKNESS-5INCH
8. For PILLARS,
Tiscon-Rods-Iron-Grid-BaseStand-Lifted-Gap-2Inch-From-PRESSED-LEVELLED-HammeredBrick. GapLift-by-uding-small-sufficient-brick-peices.
9. For ROOF(LINTER), Tiscon-Rods-Iron-Grid-Lifted-Gap-1Inch-From-Shattering.
GapLift-by-using-small-sufficient-brick-peices.
10. For ROOF(LINTER), TISCON-RODS-GRID-SPACING-5Inches.
11. 2.5FEET-LENGTH-CANTILEVER-RODS-GRID-on(from)-all-4.5Inch-aswellas-9InchWalls.