

# Deep learning for character-level text processing

Grzegorz Chrupała

Tilburg University

ATILA 2013

# Small steps towards fully autonomous learning

Until recently **feature engineering** was a major bottleneck.

Until recently **feature engineering** was a major bottleneck.

Manually design, select and tune high-level, informative features.

Until recently **feature engineering** was a major bottleneck.


Manually design, select and tune high-level, informative features.

Feed these together with labels to shallow learners

Recent focus on automatic learning of features

Neural networks in vision and speech

# Machine vision: from pixels to labels via learned features



# NLP: from characters to labels via learned features



sex http://t.co/# انحراف #ممحونات #كس #نهود #طيز #مكوه #نيك #سكس  
giYHeL5j3

Buenos dias lindisimo @Gorrita0mar que tal estas? Espero que bien  
feliz miercoles abrazos y besazos para ti y para tu rica trompita  
gorrita

@nachovinerta Ahora salgo dame 10 min jajajajaja

Photo: Challenges and solutions from the voices of the future.

@worldwaterweek #WWWeek #gen2050 #youth... http://t.co/Gpw1iIoNx8

うちわオナニーだいすき☆

Only those who dare to fail greatly can ever achieve greatly.

~Robert Francis Kennedy~]

関西の学生主催イベント情報局SPCです！ここで紹介しておりますイベントは学生主催ではありませんが、どなたでもご参加いただけます。毎日家と学校、あるいは家と勤務場所の往復だけではつまらない！そんな皆さんに新たな一歩を踏み出せるよう情報を提供しております。

風呂！！

RT @naopics\_bot: くぐたす(古畑奈和) より https://t.co/ZBVliphayc http://  
t.co/kGPM20hg4Q #古畑奈和

眠い。だめだこれは。眠いぞ。でも少しでもフラ語終わらせなきゃ。土日稼ぎたい！！！！！！！！

istediğim bgyi buldum çok şükür

Курским автомобилистам предлагают принять участие в акции по  
улучшению организации дорожного движения

# Java - Convert String to enum

Say I have an enum which is just

```
public enum Blah {  
    A, B , C, D  
}
```

319  
60

and I would like to find the enum value of a string of for example "A" which would be `Blah.A`. How would it be possible to do this?

Is the `Enum.valueOf()` the method I need? If so, how would I use this?

`java enums`

# Common approaches to representation learning for language

# Common approaches to representation learning for language

- Word classes

# Common approaches to representation learning for language

- Word classes
- Topics

# Common approaches to representation learning for language

- Word classes
- Topics
- Word embeddings

# Alternative

## Alternative

Learn text representations from raw character streams.




- Train a simple recurrent network to predict the next symbol in a sequence of characters (or bytes).

- Train a simple recurrent network to predict the next symbol in a sequence of characters (or bytes).
- Run trained network on new text.

- Train a simple recurrent network to predict the next symbol in a sequence of characters (or bytes).
- Run trained network on new text.
- Text representation: Activation of hidden layer at each position.

# Finding Structure in Time, Elman 1990




# Hidden units

# Hidden units


- Encode history

# Hidden units


- Encode history
- Hopefully, generalize



$t-1$



$t$



$t+1$



- Train SRN on unlabeled text

- Train SRN on unlabeled text
- Learn labels:

- Train SRN on unlabeled text
- Learn labels:
  - ▶ Extract simple **baseline** features from examples

- Train SRN on unlabeled text
- Learn labels:
  - ▶ Extract simple **baseline** features from examples
  - ▶ Run trained SRN on examples to get **learned** representations

- Train SRN on unlabeled text
- Learn labels:
  - ▶ Extract simple **baseline** features from examples
  - ▶ Run trained SRN on examples to get **learned** representations
  - ▶ Use a supervised shallow learner (e.g. CRF) with the union of **baseline** features and **learned** features

# Segmenting STACKOVERFLOW posts

## Java - Convert String to enum


Say I have an enum which is just

```
public enum Blah {  
    A, B , C, D  
}
```

319 and I would like to find the enum value of a string  
60 of for example "A" which would be Blah.A. How  
would it be possible to do this?

Is the Enum.ValueOf() the method I need? If  
so, how would I use this?

java enums



# Elephant: Sequence Labeling for Word and Sentence Segmentation

**Kilian Evang<sup>\*</sup>, Valerio Basile<sup>\*</sup>, Grzegorz Chrupała<sup>†</sup> and Johan Bos<sup>\*</sup>**

<sup>\*</sup>University of Groningen, Oude Kijk in 't Jatstraat 26, 9712 EK Groningen, The Netherlands

<sup>†</sup>Tilburg University, PO Box 90153, 5000 LE Tilburg, The Netherlands

<sup>\*</sup>{k.evang, v.basile, johan.bos}@rug.nl <sup>†</sup>g.chrupala@uvt.nl



It didn't matter if the faces were male,  
SIOTIITIIOTIIIIIIOTIOTIIOTIIIIOTIIIIOTIIITO  
female or those of children. Eighty-  
TIIIIIIOTIOTIIIIOTIOTIIIIIIITOSIIIIIIIO  
three percent of people in the 30-to-34  
IIIIIIOTIIIIIIOTIOTIIIIIIOTIOTIIOTIIIIIIIO  
year old age range gave correct responses.  
TIIIOOTIIOTIIOTIIIIOTIIIOOTIIIIIIOTIIIIIIIIIT


- Character-wise sequence labeler (CRF)

- Character-wise sequence labeler (CRF)
- Baseline features: characters and their Unicode categories in a window around current position

- Character-wise sequence labeler (CRF)
- Baseline features: characters and their Unicode categories in a window around current position
- SRN features: discretized activations of hidden layer

- Character-wise sequence labeler (CRF)
- Baseline features: characters and their Unicode categories in a window around current position
- SRN features: discretized activations of hidden layer
- English, Dutch and Italian

# Errors per thousand characters



+SRN	Ms. Hughes will joi SIIOSIIIIIIOTIIIIOTII SIIOTIIIIIIOTIIIIOTII
+SRN	\$ 3.9 trillion by t TOTTIOTIIIIIIIIOTIOT TOTIIOTIIIIIIIIOTIOT
+SRN	prof. Teulings het TIIITOSIIIIIIIIOTIIIO TIIIIOTIIIIIIIIOTIIIO
+SRN	bleek 0,4 procent OTIIIIOTTIOTIIIIIIIO OTIIIIOTIIOTIIIIIIIO
+SRN	per costringerlo al TIIOTIIIIIIIIIIIIOTI TIIOTIIIIIIIIIIITIOTI

# Work in progress: labeling tweets

Add / suggest hashtags to tweets or other user generated content



sex http://t.co/# انحراف #ممحونات #كس #نهود #طيز #مكوه #نيك #سكس  
giYHeL5j3

Buenos dias lindisimo @Gorrita0mar que tal estas? Espero que bien  
feliz miercoles abrazos y besazos para ti y para tu rica trompita  
gorrita

@nachovinerta Ahora salgo dame 10 min jajajajaja

Photo: Challenges and solutions from the voices of the future.

@worldwaterweek #WWWeek #gen2050 #youth... http://t.co/Gpw1iIoNx8

うちわオナニーだいすき☆

Only those who dare to fail greatly can ever achieve greatly.

~Robert Francis Kennedy~]

関西の学生主催イベント情報局SPCです！ここで紹介しておりますイベントは学生主催ではありませんが、どなたでもご参加いただけます。毎日家と学校、あるいは家と勤務場所の往復だけではつまらない！そんな皆さんに新たな一歩を踏み出せるよう情報を提供しております。

風呂！！

RT @naopics\_bot: ぐぐたす(古畑奈和)より https://t.co/ZBVliphayc http://  
t.co/kGPM20hg4Q #古畑奈和

眠い。だめだこれは。眠いぞ。でも少しでもフラ語終わらせなきゃ。土日稼ぎたい！！！！！！！！！！

istediğim bgyi buldum çok şükür

Курским автомобилистам предлагают принять участие в акции по  
улучшению организации дорожного движения

Tweets notoriously hard to deal with using traditional NLP pipelines

Tweets notoriously hard to deal with using traditional NLP pipelines

- Multitude of languages and scripts

Tweets notoriously hard to deal with using traditional NLP pipelines

- Multitude of languages and scripts
- Nonstandard spelling and punctuation

Tweets notoriously hard to deal with using traditional NLP pipelines

- Multitude of languages and scripts
- Nonstandard spelling and punctuation
- Abbreviations, slang etc.

Can features learned from raw bytes strings help?

Train SRN on a stream of tweets.

# Train SRN on a stream of tweets.

- Use common hashtags to learn to label



# Train SRN on a stream of tweets.

- Use common hashtags to learn to label
- Single-pass online learner

# Train SRN on a stream of tweets.

- Use common hashtags to learn to label
- Single-pass online learner
- Baseline character n-gram features + SRN features

# Train SRN on a stream of tweets.

- Use common hashtags to learn to label
- Single-pass online learner
- Baseline character n-gram features + SRN features
- Activation vectors recorded at valleys in entropy profile, and averaged together

# Very preliminary results

on 5000 items

Features	Mean Average Precision
char. n-grams	31.1
char. n-grams +SRN	<b>34.8</b>

# Thank you

## Sample of nearest neighbors according to cosine of the hidden layer activation in a span of 10.000 characters

```
n-laptop": {"last_share": 130738  
ierre-pc": {"last_share": 130744  
d-laptop": {"last_share": 130744  
laptop": {"last_share": 13074434  
erre-pc": {"last_share": 1307441
```

data table has integer values a  
,2,3,4,5. For all these values I  
ere i can add more connections s  
eating lots of private methods a  
or more different data sources c

e given URL.I'd like to change t  
e = SqlPersist¶¶¶When I remove t  
sources explaining how to save f  
basic knowledge doesn't enable m  
eDirectory, but I need to save t

# Generated random text

I·only·make·event·glds.

so,·on·the·cell·proceedclicks·like·completed,·with·color?

....st·potention,  
'column']HeaderException=ID·=·new·Put="True"·MetadataTemplate,  
·grwTrowerRow="SELECTEMBRow"·on?

All·clearBeanLockCollection="#7293df3335b-E9"·/&gt;  
.....&lt;Image:DataKey="BackgroundCollectionC2UTID"·  
onclick="Nore".

# Labels

## Block

w	r	o	n	g	?	¶	t	r	y
0	0	0	0	0	0	0	B-BL	I-BL	I-BL

## Inline

e	r	.	.	.	/	i	m	g
0	0	0	B-IN	I-IN	I-IN	I-IN	I-IN	I-IN



# Baseline feature set

...wrong? try {...

Unigram	n g ? ¶ t
Bigram	g? ?¶
Trigram	g?¶
Fourgram	ng?¶ g?¶t
Fivegram	ng?¶t

# Augmented feature set

- Baseline features
- 400-unit hidden layer activation
  - ▶ For each of 10 most active units
    - ★ Is the activation  $> 0.5$ ?

