


Screenshot of a decomposed aws ec2 describe-instances command with each part labeled (service/operation/parameters).

```
aws ec2 describe-instances --region us-east-2 --output table
```

ec2	<-- Service
describe-instances	<-- Operation
--region us-east-2	<-- Parameter
--output table	<-- Parameter

Screenshot of the “Hello from...” web page from Example 2 (Part C5).



Hello from ip-172-31-44-129.us-east-2.compute.internal

Screenshot of git status showing .env is not tracked, alongside your .gitignore file contents.

```
root@aa80cd592e15:/CloudClass# git check-ignore -v .env
.gitignore:1:.env      .env

root@aa80cd592e15:/CloudClass# git status
On branch main
Your branch is up to date with 'origin/main'.

Untracked files:
  (use "git add <file>..." to include in what will be committed)
  .gitignore

nothing added to commit but untracked files present (use "git add" to track)
root@aa80cd592e15:/CloudClass# git check-ignore -v .env
.gitignore:1:.env      .env
```

Screenshot of create_instances.sh output showing 2 instance IDs.

```
root@aa80cd592e15:/CloudClass# ./create_instances.sh
Launching 2 instance(s) in us-east-2...
Launched instance IDs:
i-0ae415e11eec119f2      i-0b9fb9b0a2229efcc
Instance IDs saved to instance_ids.txt
```

Screenshot of delete_instances.sh output confirming termination.

```
root@aa80cd592e15:/CloudClass# ./delete_instances.sh
Terminating instances: i-0ae415e11eec119f2 i-0b9fb9b0a2229efcc
{
  "TerminatingInstances": [
    {
      "InstanceId": "i-0b9fb9b0a2229efcc",
      "CurrentState": {
        "Code": 32,
        "Name": "shutting-down"
      },
      "PreviousState": {
        "Code": 16,
        "Name": "running"
      }
    },
    {
      "InstanceId": "i-0ae415e11eec119f2",
      "CurrentState": {
        "Code": 32,
        "Name": "shutting-down"
      },
      "PreviousState": {
        "Code": 16,
        "Name": "running"
      }
    }
  ]
}
Waiting for instances to terminate...
All instances terminated successfully.
```

Link to your GitHub repo showing create_instances.sh ,
delete_instances.sh , .env.example , and .gitignore (but not .env).

<https://github.com/gcm131/CloudClass>

One paragraph explaining why environment files are excluded from Git, even in a “private” repository.

.env or environment files contain keys, credentials, passwords, and secrets that aren't hardcoded for security and privacy reasons. They are excluded from git because as mentioned earlier they contain very sensitive data that should be secured to ensure that they are not misused or abused. Another issue that comes up is git storing snapshots of everything that is uploaded so if you do upload a .env file by accident you are going to have a very hard time wiping the record of it.