
GCVE-BCP-04 - Recommendations and Best Practices for ID Allocation

GCVE.eu



Contents

1	Recommendations and Best Practices for ID Allocation	1
1.1	Introduction	1
1.2	GCVE Identifier Format	1
1.2.1	Format Breakdown	2
1.2.1.1	Examples of valid identifiers	2
1.2.2	Identifier Length	3
1.3	Allocation of GCVE Identifiers	3

1 Recommendations and Best Practices for ID Allocation



GCVE.eu

- **Version:** 1.3
- **Status:** Published
- **Date:** 2025-12-09
- **Authors:** GCVE Working Group
- **BCP ID:** BCP-04

This guide is distributed and available under [CC-BY-4.0](#).

Copyright (C) 2025 GCVE Initiative.

1.1 Introduction

This document describes the best practices and recommendations for ID allocation and GCVE identifier format.

1.2 GCVE Identifier Format

The GCVE identifier typically follows a traditional four-part format:

`GCVE-<GNA-ID>-<YEAR>-<UNIQUE-ID>`

- [GCVE-65535-2021-XX-\[222\]_XX{1}/1/1/1](#)
- [GCVE-65535-2021-XX-\[222\]_XX{1}\1/1\1](#)
- [GCVE-65535-GHSA-jc7w-c686-c4v9](#)
- [GCVE-65535-jc7w-c686-c4v9](#)
- [GCVE-65535-ababcbbe.onion-1](#)
- [GCVE-65535-Ivanti/Avalanche-1](#)

The GNA ID 65535 is reserved as a test GNA ID, as defined in the [GCVE directory](#).

1.2.2 Identifier Length

The maximum length for a GCVE identifier is **255 characters**. This ensures compatibility and reliable handling across different software systems.

The reference implementation, [Vulnerability-Lookup](#), supports longer identifiers, but keeping identifiers within 255 characters facilitates integration across diverse toolsets. Nevertheless, it is recommended to keep identifiers within **255 characters (including the prefix)**. - If your regular expression engine supports positive lookahead assertions (most do), `^(?=.{8,255}$)GCVE-[0-9]+-[\x22-\x7E]+$` also accounts for a maximum length of 255 characters. For strict POSIX compliance (no lookahead assertions), `^GCVE-[0-9]+-[\x22-\x7E]{1,247}$` will be mostly accurate with reasonable performance and readability.

1.3 Allocation of GCVE Identifiers

A GCVE Identifier must uniquely identify a vulnerability within the scope of a GNA.

GCVE Identifiers are **not limited** to newly discovered vulnerabilities. They may also be used to:

- extend the description of an existing vulnerability (e.g., adding metadata),
- reference a patch or remediation,
- establish a parent/child relationship with another vulnerability (e.g., a fork or variant).

The GCVE model is designed to support **multiple identifiers for the same vulnerability**, providing complementary information or alternative perspectives.

For example, this may occur when:

- vendors disagree on a vulnerability classification,

- independent discoveries are made in parallel,
- additional context is provided by different GNAs.

There is **no single authoritative identifier** for a given vulnerability. Instead, GCVE enables multiple viewpoints, fostering a more decentralized and transparent ecosystem.

We recommend that GNAs include cross-references whenever possible. This applies both to:

- other GCVE identifiers (from the same or different GNAs),
- identifiers from other vulnerability systems.

This cross-referencing supports stronger interoperability and helps build a richer, interconnected knowledge base covering scenarios such as parallel or independent vulnerability discoveries.