

# Chapter 2: Literature Review

2d Lt Gannon Gebauer

CSCE 823

AFIT

WPAFB

gannon.gebauer.1@au.af.edu

**LEO** Low Earth Orbit  
**TLE** Two Line Elements  
**JSPOC** Joint Space Operations Center  
**RMS** Root Mean Square  
**EKF** Extended Kalman Filter  
**UKF** Unscented Kalman Filter  
**UPF** Unscented Particle Filter  
**SRIF** Square Root Information Filter  
**GNSS** Global Navigation Satellite System  
**MAGSAT** Magnetic Field Satellite  
**LACE** Low-Power Atmospheric Compensation Experiment  
**DE-2** Dynamics Explorer-2  
**BLS** Batch Least Squares Filter  
**ILS** Iterated Least Squares Filter  
**ULS** Unscented Least Squares Filter  
**HLS** Hybrid Least Squares Filter  
**GAN** Generative Adversarial Network  
**ML** Machine Learning  
**CNN** Convolutional Neural Network

## I. INTRODUCTION

Space has been at the forefront of research and exploration for decades and much of modern technology has come to rely on the innovations and architecture that have been built to maintain it. The largest growing component of space innovation involves the deployment of Low Earth Orbit (LEO) satellites [1]. This greatly expanding front of new technology and ideas brings along its own challenges that range from security to new ways to track orbits [2, 3].

## II. CUBESATS

The use of CubeSats has continued to grow in the LEO environment and has become a major component of the space industry [1]. CubeSats are small satellites that are typically built in a standard size and form factor, which allows for easy deployment and integration into existing satellite constellations. This standardization has led to the rapid growth of CubeSat technology including the development of new communication systems [4, 5] and onboard processing capabilities [6]. These developments have enabled CubeSats to perform a wide range of missions, from Earth observation, scientific research, and commercial applications.

### A. Security

With the rapid growth of CubeSat technology, there has been an increased focus on the vulnerabilities and security

risks associated with these small satellites. Much of these now deployed CubeSats are built with a focus on cost and size much like IoT devices, which has led to a lack of security features and protocols [7]. This makes CubeSats a prime target for research into security and resiliency of these systems.

Ahmad et al. [8] pursue the one tactic of utilizing a Generative Adversarial Network (GAN), a type of neural network, to generate synthetic data to train a Machine Learning (ML) model to detect and mitigate cyber attacks on CubeSats. It utilized the Edge-IIoTset to train the GAN to generate the synthetic data and then used the generated data to train a Convolutional Neural Network (CNN) plus an autoencoder to detect cyber attacks on IoT devices specifically aimed at CubeSats. The results displayed a validation accuracy of 96.56% for the CNN in the first epoch showing that the GAN was able to generate realistic data that could be used to train a ML model to detect cyber attacks on CubeSats. This demonstrates the potential of using GANs to enhance the security of CubeSats and other small satellites.

In the offensive space security domain Calabrese et al. [9] explores the use of a hosted payload to perform a cyber attack against a CubeSat in a simulated environment. The study provides a full demonstrable attack chain, inspired by the SPARTA Matrix [10], the only uses open source tools and software to demonstrate the vulnerabilities of CubeSats and the potential for cyber attacks against them.

## III. NAVIGATION

LEO satellite use a variety of methods to assist in their own navigation and an organization's ability to track them from the ground. The most common methods used to track a satellite from the ground is through Two Line Elements (TLE)s. TLEs describe the orbital parameters, as seen in Table III, that are required for the tracking and locating of specific satellites during orbit [11]. They provide the specific time and location that each LEO satellite occupies to facilitate communication and to ensure that no satellite impacts another. The recordings of a satellite's orbit are taken through observation at Joint Space Operations Center (JSPOC) and provide consistent snapshot updates of currently recorded TLE's every 8 hours [11]. A majority of these satellites have a mean motion of 90 minutes with an altitude (Circular) of 281.49 km [12]. This provides only a few minutes in which the satellite can be contacted before it is out of range and continues until its next orbit. These minimal contact intervals make it vitally important

TABLE I  
TWO-LINE ELEMENT SET FIELD DEFINITIONS

| Line  | Field | Content                                                  |
|-------|-------|----------------------------------------------------------|
| Title | –     | Satellite Name                                           |
| 1     | 1     | Line Number                                              |
| 1     | 2     | Satellite Catalog Number                                 |
| 1     | 3     | Classification (U/C/S)                                   |
| 1     | 4     | International Designator (Launch Year)                   |
| 1     | 5     | International Designator (Launch Number)                 |
| 1     | 6     | International Designator (Launch Piece)                  |
| 1     | 7     | Epoch Year                                               |
| 1     | 8     | Epoch (Day and Fractional Day)                           |
| 1     | 9     | First Derivative of Mean Motion (rev/day <sup>2</sup> )  |
| 1     | 10    | Second Derivative of Mean Motion (rev/day <sup>3</sup> ) |
| 1     | 11    | B* Drag Term (Earth radii <sup>-1</sup> )                |
| 1     | 12    | Ephemeris Type                                           |
| 1     | 13    | Element Set Number                                       |
| 1     | 14    | Checksum (modulo 10)                                     |
| 2     | 1     | Line Number                                              |
| 2     | 2     | Satellite Catalog Number                                 |
| 2     | 3     | Inclination (deg)                                        |
| 2     | 4     | Right Ascension of Ascending Node (deg)                  |
| 2     | 5     | Eccentricity                                             |
| 2     | 6     | Argument of Perigee (deg)                                |
| 2     | 7     | Mean Anomaly (deg)                                       |
| 2     | 8     | Mean Motion (rev/day)                                    |
| 2     | 9     | Revolution Number at Epoch                               |
| 2     | 10    | Checksum (modulo 10)                                     |

to accurately predict when contact can be made and what communications are of import to send during this window. This creates a need for accurate truly autonomous navigation and orbit determination that does not rely on outside systems to provide accurate information [13].

#### IV. ALTERNATIVE NAVIAGTION

Alternative methods of navigation and orbit determination continue to be explored to provide more robust and accurate systems. A newly explored source of navigation is the use of satellite sensors, like magnetomoeter and gravitometer, in conjunction with accurate modeling to derive orbit parameters without specefic ground station interference [14–16]. These alternative methods provide an independent system of determination without reliance on outside systems [16].

TABLE II  
POSITION ERROR RESULTS FOR THE SRIF AND BATCH LS FILTERS [13]

| S/C    | Filter   | RMS/Total | Peak   | Along/Cross-Track     |
|--------|----------|-----------|--------|-----------------------|
| MAGSAT | SRIF     | –         | <8 km  | slow drift / periodic |
| MAGSAT | Batch LS | 4 km RMS  | <8 km  | 3.4 / 1.8 km RMS      |
| DE-2   | SRIF     | –         | –      | not tested            |
| DE-2   | Batch LS | –         | 18 km  | 8–15 km / steady osc. |
| LACE   | SRIF     | –         | –      | not tested            |
| LACE   | Batch LS | 88 km RMS | 125 km | – / dominant          |

##### A. Magnetometer

It has been proven by Psiaki and Martel [17] that 5 of the 6 keplerian elements can be determined using only the magnetic field with the missing element being the longitude

TABLE III  
FILTER CONVERGENCE AND ORBIT DETERMINATION ACCURACY

| Metric                                | Adaptive HLS<br>(before drift est.) | Adaptive HLS<br>(with drift est.) |
|---------------------------------------|-------------------------------------|-----------------------------------|
| Radial position error, RMS (m)        | 10.8                                | 10.4                              |
| Along-track position error, RMS (m)   | 1208.3                              | 677.0                             |
| Cross-track position error, RMS (m)   | 37.9                                | 22.8                              |
| Radial velocity error, RMS (m/s)      | 1.2                                 | 0.80                              |
| Along-track velocity error, RMS (m/s) | 0.013                               | 0.012                             |
| Cross-track velocity error, RMS (m/s) | 0.044                               | 0.026                             |

of the ascending node. Utilizing the magnetometer, known variables like start postion and time of flight along with a series of kalman filters the orbit/position of a satellite can be determined [18, 19].

Pisaki and Martel [13] utilize a Square Root Information Filter (SRIF) and Batch Least Squares Filter (BLS) to determine the position of the satellite using only the magnetometer and adjusted based on the truth data. The SRIF was tested on the Magnetic Field Satellite (MAGSAT) launched in October 1979 equipped with a vector magnetometer, the Dynamics Explorer-2 (DE-2) launched in August 1981 equipped with vector magnetometer, and the Low-Power Atmospheric Compensation Experiment (LACE) launched in February 1990 equipped with a scalar magnetometer. The results form the tests can be seen in Table II where the SRIF was able to provide a position estimate with a peak error of less than 8 km for the MAGSAT and the BLS was able to provide a position estimate with a Root Mean Square (RMS) error of 4 km for the MAGSAT, 18 km for the DE-2, and 88 km for the LACE [13]. This demonstrates that the magnetometer can be used to provide a position estimate with a reasonable accuracy, but it is not as accurate as Global Navigation Satellite System (GNSS) and is dependent on the type of magnetometer used.

A series of kalman filters have been explored by Ning and Ma [18] to determine the method and accuracy of differing strategies, this included Unscented Kalman Filter (UKF), Extended Kalman Filter (EKF), and Unscented Particle Filter (UPF). A best case RMS accuracy of 203.32 meters for an EKF, a RMS accuracy of 161.3 meters for an UKF, and a RMS accuracy of 159.7 meters for an UPF when considering a known orbit and 3 second sample rate to filter to a position [18]. The EKF introduces a larger error due to the neglected non-linearities in the system, while the UPF provides a more accurate result at the cost of increased computational complexity [18]. While this method does not provide the same accuracy of GNSS it does provide an independent method of orbit determination that if given the compute power and time can provide a redundant system of orbit determination without reliance on outside systems.

##### B. Gravitometer

A further exploration of alternative navigation methods has been explored by Sun et al [15]. This study explores the use of an Iterated Least Squares Filter (ILS), an Unscented

TABLE IV  
RMS ORBIT DIFFERENCES WITH RESPECT TO EGM2008

| Gravity Model | Radial<br>diff. (m) | Along-track<br>diff. (m) | Cross-track<br>diff. (m) |
|---------------|---------------------|--------------------------|--------------------------|
| EGM96         | 1.51                | 3.47                     | 2.32                     |
| JGM3          | 1.66                | 56.6                     | 6.92                     |
| EIGEN-6C4     | 0.043               | 13.05                    | 0.57                     |
| GGM05G        | 0.052               | 12.15                    | 0.55                     |

Least Squares Filter (ULS), and the proposed Hybrid Least Squares Filter (HLS) utilizing gravity gradient measurements to determine specific orbital elements of a satellite. These filters were implemented on the Gravity Field and Steady-State Ocean Circulation Explorers 12 hour arc starting from 8 September 2013, 00:00:00 GPS time. This study also makes the assumption that the gravity gradient measurements are optimal and available. A baseline gravity model EGM2008 is used to provide reference and as a comparison to the EGM96, JGM3, EIGEN-6C4, and GGM05G models IV. The result of the study shows the HLS model provides the best results with a RMS error of 10.4 meters in the radial position, 677 meters in the along-track position, and 22.8 meters in the cross-track position III.

#### C. ML Models

#### D. Machine Learning

#### E. Neural Networks

#### REFERENCES

- [1] J. Zhang, Y. Cai, C. Xue, Z. Xue, and H. Cai, "LEO Mega Constellations: Review of Development, Impact, Surveillance, and Governance," vol. 2022, p. 2022/9865174. [Online]. Available: <https://spj.science.org/doi/10.34133/2022/9865174>
- [2] R. Idan, R. Peled, A. Ben Siman Tov, E. Markus, B. Zadov, O. Chodeda, Y. Fadida, O. Holschke, J. Plachy, Y. Elovici, and A. Shabtai, "AegisSat: A Satellite Cybersecurity Testbed," in *Proceedings 2025 Workshop on Security of Space and Satellite Systems*. Internet Society. [Online]. Available: <https://www.ndss-symposium.org/wp-content/uploads/spacesec25-final69.pdf>
- [3] S. Kazemi, N. L. Azad, K. A. Scott, H. B. Oqab, and G. B. Dietrich, "Orbit determination for space situational awareness: A survey," vol. 222, pp. 272–295. [Online]. Available: <https://www.sciencedirect.com/science/article/pii/S0094576524003308>
- [4] N. Saeed, A. Elzanaty, H. Almorad, H. Dahrouj, T. Y. Al-Naffouri, and M.-S. Alouini, "CubeSat Communications: Recent Advances and Future Challenges." [Online]. Available: <http://arxiv.org/abs/1908.09501>
- [5] V. Rastinasab and H. Weidong, "Implementation and Design of RF-Front-End Telemetry Tracking and Command Subsystem of a CubeSat With 500-km Altitude," vol. 2, no. 1, pp. 43–47. [Online]. Available: <https://ieeexplore.ieee.org/document/9205829/>
- [6] W. Sajjad, A. Shafique, and R. Mahmood, "Designing of Reliable, Low-Power, and Performance-Efficient Onboard Computer Architecture for CubeSats," vol. 5, no. 2, pp. 59–72. [Online]. Available: <https://ieeexplore.ieee.org/document/10356635/>
- [7] G. Marra, U. Planta, P. Wüstenberg, and A. Abbasi, "On the Feasibility of CubeSats Application Sandboxing for Space Missions," in *Proceedings 2024 Workshop on Security of Space and Satellite Systems*. [Online]. Available: <http://arxiv.org/abs/2404.04127>
- [8] S. Z. Ahmad, F. Qamar, H. Alshehri, F. Jeribi, A. Tahir, S. T. Siddiqui, and J. Ramakrishnan, "A GAN-Based Approach for enhancing security in satellite based IoT networks using MPI enabled HPC," vol. 20, no. 9, p. e0331019. [Online]. Available: <https://dx.plos.org/10.1371/journal.pone.0331019>
- [9] M. Calabrese, G. Kavallieratos, and G. Falco, "A Hosted Payload Cyber Attack Against Satellites," in *AIAA SCITECH 2024 Forum*. American Institute of Aeronautics and Astronautics. [Online]. Available: <https://arc.aiaa.org/doi/10.2514/6.2024-0270>
- [10] The Aerospace Corporation, "SPARTA: Space Attack Research and Tactic Analysis," <https://sparta.aerospace.org/>, accessed: August 3, 2026.
- [11] Two-line element sets - Practice and use. ResearchGate. [Online]. Available: [https://www.researchgate.net/publication/289774073\\_Two-line\\_element\\_sets\\_-\\_Practice\\_and\\_use](https://www.researchgate.net/publication/289774073_Two-line_element_sets_-_Practice_and_use)
- [12] 18th Space Defense Squadron, "Space-track.org," <https://www.space-track.org>, United States Space Force, 2026, accessed: 2026-05-19. [Online]. Available: <https://www.space-track.org>
- [13] M. L. Psiaki, L. Huang, and S. M. Fox, "Ground tests of magnetometer-based autonomous navigation (MAGNAV) for low-earth-orbiting spacecraft," vol. 16, no. 1, pp. 206–214. [Online]. Available: <https://research.ebsco.com/linkprocessor/plink?id=62aac5b3-a27c-3b7e-8f8c-1fb340c3143c>
- [14] C. C. Finlay, C. Kloss, N. Olsen, M. D. Hammer, L. Tøffner-Clausen, A. Grayver, and A. Kuvshinov, "The CHAOS-7 geomagnetic field model and observed changes in the South Atlantic Anomaly," vol. 72, no. 1, p. 156. [Online]. Available: <https://doi.org/10.1186/s40623-020-01252-9>
- [15] X. Sun, P. Chen, C. Macabiau, and C. Han, "Low-Earth Orbit Determination from Gravity Gradient Measurements," vol. 123, pp. 350–362. [Online]. Available: <https://www.sciencedirect.com/science/article/pii/S0094576515301193>
- [16] E. A. Butcher, J. Wang, and T. A. Lovell, "On Kalman Filtering and Observability in Nonlinear Sequential Relative Orbit Estimation," vol. 40, no. 9, pp. 2167–2182. [Online]. Available: <https://doi.org/10.2514/1.G002702>
- [17] M. Psiaki and F. Martel, "Autonomous Magnetic Navigation for Earth Orbiting Spacecraft."
- [18] X. Ning, X. Ma, C. Peng, W. Quan, and J. Fang, "Analysis of Filtering Methods for Satellite Autonomous Orbit Determination Using Celestial and Geomagnetic Measurement," vol. 2012, no. 1, p. 267875. [Online]. Available: <https://onlinelibrary.wiley.com/doi/abs/10.1155/2012/267875>
- [19] J. K. Deutschmann and I. Y. Bar-Itzhack, "Evaluation of attitude and orbit estimation using actual earth magnetic field data," vol. 24, no. 3, pp. 616–623.