

What is an array, really?

An array is a special class in Java.

It's still a class.

The array, like all other classes, ultimately inherits from `java.lang.Object`.

Array initialization and default element values

When you don't use an array initializer statement, all array elements get initialized to the default value for that type.

For primitive types, this is **zero** for any kind of **numeric primitive**, like `int`, `double` or `short`.

For **booleans**, the default value will be **false**.

And for any **class** type, the elements will be initialized to **null**.

The Enhanced For Loop, the For Each Loop

This loop was designed to walk through elements in an array, or some other type of collection.

It processes **one element at a time**, from the **first** element to the **last**.

Here I show you the syntax for the two types of for loop statements, side by side.

Enhanced For Loop	Basic For Loop
<pre>for (declaration : collection) { // block of statements }</pre>	<pre>for (init; expression; increment) { // block of statements }</pre>

The enhanced for loop only has two components, vs. 3, defined in the parentheses after the for keyword.

The Enhanced For Loop, the For Each Loop

Enhanced For Loop	Basic For Loop
<pre>for (declaration : collection) { // block of statements }</pre>	<pre>for (init; expression; increment) { // block of statements }</pre>

It's important to notice, that the separator character between components, is a **colon**, and not a semi-colon, for the Enhanced For Loop.

The **first** part is a **declaration expression**, which includes the type and a variable name. This is usually a local variable with the same type as an element in the array.

And the **second** component is the **array**, or some other collection variable.

java.util.Arrays

Java's array type is very basic, it comes with very little built-in functionality.

It has a single property or field, named length.

And it inherits java.util.Object's functionality.

Java provides a helper class named java.util.Arrays, providing common functionality, you'd want for many array operations.

These are static methods on Arrays, so are class methods, not instance methods.

Printing elements in an array using Arrays.toString()

The toString method on this helper class, prints out all the array elements, comma delimited, and contained in square brackets.

```
String arrayElementsInAString = Arrays.toString(newArray);
```

The output from this method is shown here, conceptually.

It prints the element at index 0 first, followed by a comma, then element at index 1 next, comma, and so on, until all elements are printed.

```
[ e[0], e[1], e[2], e[3], ... ]
```